

Maximum Permissible Exposure Evaluation

FCC ID: 2AE6WRP-R1

1. Client Information

Applicant : Shenzhen omimo Technology Co.,Ltd.
Address : Room1212, Chuangjian Building, No.6023, Shennan Boulevard,
Futian District, Shenzhen, China
Manufacturer : Shenzhen omimo Technology Co.,Ltd.
Address : Room1212, Chuangjian Building, No.6023, Shennan Boulevard,
Futian District, Shenzhen, China

2. General Description of EUT

EUT Name	:	omimo WIFI Repeater	
Models No.	:	RP-R1	
Model Difference	:	N/A	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
		Number of Channel:	802.11b/g/n(HT20):11 channels 802.11n(HT40): 7 channels
		RF Output Power:	802.11b: 14.54 dBm 802.11g: 14.64 dBm 802.11n (HT20): 14.33 dBm 802.11n (HT40): 14.41 dBm
		Antenna Gain:	1 dBi PCB Antenna
		Modulation Type:	802.11b: DSSS(BPSK, QPSK, CCK) 802.11g/n:OFDM(BPSK,QPSK,16QAM, 64QAM)
		Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n(HT20):14.44/28.88/43.34/57.78/86.66/115.56 /130/144.44Mbps 802.11n(HT40):30/60/90/120/180/240/270/300Mbps

TB-RF-075-1.0

Power Supply	:	DC 5V supplied by AC/DC Adapter.
Power Rating	:	Input: AC 100~240V, 50/60Hz Output: DC 5V
Connecting I/O Port(S)	:	Please refer to the User's Manual

MPE Calculations for WIFI

1. Antenna Gain:

PCB Antenna: 1 dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Worst Maximum MPE Result																	
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm) [P]		ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]			Power Density Limit (mW/ cm ²)	Result						
			Ant a	Ant b			Ant 1	Ant 2	Sum								
802.11b	1	2412	14.28	14.34	1	20	0.0067	0.0068	---	1.000	PASS						
		2437	14.52	14.48	1	20	0.0071	0.0070	---								
		2462	14.54	14.41	1	20	0.0071	0.0069	---								
802.11g	1	2412	14.14	14.34	1	20	0.0065	0.0068	---			1.000	PASS				
		2437	14.49	14.14	1	20	0.0070	0.0065	---								
		2462	14.64	14.16	1	20	0.0073	0.0065	---								
802.11n (HT20)	2	2412	11.14	11.07	1	20	0.0033	0.0032	0.0064					1.000	PASS		
		2437	11.57	10.91	1	20	0.0036	0.0031	0.0067								
		2462	11.17	11.46	1	20	0.0033	0.0035	0.0068								
802.11n (HT40)	2	2422	11.71	10.90	1	20	0.0037	0.0031	0.0068							1.000	PASS
		2437	11.35	11.45	1	20	0.0032	0.0035	0.0067								
		2452	11.05	11.28	1	20	0.0034	0.0034	0.0068								
Note: (1) N _{TX} = Number of Transmit Antennas (2) RF Output power specifies that Maximum Conducted Peak Output Power.																	

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n (2412~2462 MHz)

MPE limit S: 1 mW/ cm²

The MPE is calculated as ***0.0073mW / cm² < limit 1 mW / cm²***. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----