



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 Fax: +86-755-26636041

## FCC PART 15 SUBPART C TEST REPORT

### FCC PART 15.249

Report Reference No.: CTL1506251750-WF

Compiled by:  
( position+printed name+signature)

Jacky Chen  
(File administrators)

*Jacky Chen*

Tested by:  
( position+printed name+signature)

Allen Wang  
(Test Engineer)

*Allen Wang*

Approved by:  
( position+printed name+signature)

Tracy Qi  
(Manager)

*Tracy Qi*

Product Name.....: Bluetooth Speaker

Model/Type reference.....: HY-BOOM-BT-BLK

List Model(s).....: /

Trade Mark.....: /

FCC ID.....: 2AE7BHY-BOOM

Applicant's name.....: Hype Wireless LPD LTD

Address of applicant.....: 195 Raritan Center Parkway Edison, NJ 08837

Test Firm.....: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm.....: Floor 1-A, Baisha Technology Park, No.3011, Shahe Xi Road, Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: FCC Part 15.249: Operation within the bands 920-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of Receipt.....: Jun., 25, 2015

Date of Test Date.....: Jun., 26, 2015 – July, 02, 2015

Data of Issue.....: July, 03, 2015

Result.....: Positive

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

<b>Test Report No. :</b> CTL1506251750-WF	July, 03, 2015 Date of issue
---	---------------------------------

Equipment under Test : Bluetooth Speaker

Model /Type : HY-BOOM-BT-BLK

Listed Models : /

**Applicant** : **Hype Wireless LPD LTD**

Address : 195 Raritan Center Parkway Edison, NJ 08837

**Manufacturer** : **SHENZHEN TEKSUN TECHNOLOGY CO.,LTD**

Address : 3F, bldg F7, F518 Idea Land, Baoyuan Road, Xixiang Avenue, Bao'an District, Shenzhen, CN

<b>Test result</b>	<b>Pass *</b>
--------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**\*\* Modified History \*\***


Revision	Description	Issued Data	Report No.	Remark
Revsion 1.0	Initial Test Report Release	2015-07-03	CTL1506251750-WF	Tracy Qi



## Table of Contents

## Page

<b>1. SUMMARY.....</b>	<b>5</b>
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY .....	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
<b>2. GENERAL INFORMATION.....</b>	<b>7</b>
2.1. ENVIRONMENTAL CONDITIONS .....	7
2.2. GENERAL DESCRIPTION OF EUT .....	7
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	7
2.4. EQUIPMENTS USED DURING THE TEST .....	8
2.5. RELATED SUBMITTAL(S) / GRANT (S).....	8
2.6. MODIFICATIONS.....	8
<b>3. TEST CONDITIONS AND RESULTS .....</b>	<b>9</b>
3.1. CONDUCTED EMISSIONS TEST .....	9
3.2. RADIATED EMISSIONS AND BAND EDGE .....	12
3.3. OCCUPIED BANDWIDTH MEASUREMENT.....	18
3.4. ANTENNA REQUIREMENT.....	19
<b>4. TEST SETUP PHOTOS OF THE EUT .....</b>	<b>23</b>
<b>5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</b>	<b>25</b>



# 1. SUMMARY

## 1.1. TEST STANDARDS

The tests were performed according to following standards:

**FCC Rules Part 15.249:** Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

**ANSI C63.4:2014** American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

## 1.2. Test Description

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	PASS
FCC Part 15.203	Antenna Requirement	PASS





### 1.3. Test Facility

#### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

#### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

##### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

##### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

### 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2. General Description of EUT

Product Name:	Bluetooth Speaker
Model/Type reference:	HY-BOOM-BT-BLK
Power supply:	DC 3.7V from battery
<b>Bluetooth 3.0</b>	
Version:	Supported BT3.0
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	1.0dBi

Note: For more details, please refer to the user's manual of the EUT.

### 2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

#### Operation Frequency :

Channel	Frequency (MHz)
<b>00</b>	<b>2402</b>
2	2403
:	:
38	2440
<b>39</b>	<b>2441</b>
40	2442
:	:
77	2479
<b>78</b>	<b>2480</b>

All test performed at GFSK,  $\pi/4$  DQPSK and 8DPSK mode of each test frequency and recorded worst case at GFSK DH5 mode.

## 2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2015/05/19	2016/05/18
LISN	R&S	ENV216	3560.6550.12	2015/06/02	2016/06/01
LISN	R&S	ESH2-Z5	860014/010	2015/06/02	2016/06/01
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Transient Limiter	SCHWARZCECK	VTSD 9561F	9666	2015/06/02	2016/06/01
Temperature/Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19

The calibration interval was one year

## 2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID:2AE7BHY-BOOM filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.



### 3. TEST CONDITIONS AND RESULTS

#### 3.1. Conducted Emissions Test


##### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION




##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

SCAN TABLE: "Voltage (9K-30M)FIN"  
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL150702215\_fin"

7/2/2015 10:02AM							
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
0.902000	42.40	10.1	56	13.6	QP	L1	GND
0.938000	42.10	10.1	56	13.9	QP	L1	GND
25.004000	44.70	11.0	60	15.3	QP	L1	GND


MEASUREMENT RESULT: "CTL150702215\_fin2"

7/2/2015 10:02AM							
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
24.146000	34.70	10.9	50	15.3	AV	L1	GND
24.674000	34.90	11.0	50	15.1	AV	L1	GND
24.722000	34.90	11.0	50	15.1	AV	L1	GND



**SCAN TABLE: "Voltage (9K-30M)FIN"**

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL150702216\_fin"**

7/2/2015 10:05AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
2.348000	48.50	10.4	56	7.5	QP	N	GND
2.738000	47.40	10.5	56	8.6	QP	N	GND
3.098000	46.70	10.5	56	9.3	QP	N	GND

**MEASUREMENT RESULT: "CTL150702216\_fin2"**

7/2/2015 10:05AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.362000	45.40	9.9	49	3.3	AV	N	GND
0.512000	41.40	9.9	46	4.6	AV	N	GND

### 3.2. Radiated Emissions and Band Edge

#### Limit

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5Mhz shall not exceed 94dB $\mu$ V/m(50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/m)	Radiated ( $\mu$ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

#### TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



## (C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**

1. The EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency (MHz)	FS (dBμV/m)	RA (dBμV/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
150.00	40	58.1	12.2	1.6	31.90	-18.1

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

**TEST RESULTS**

Remark:

1. We measured Radiated Emission at GFSK, π/4 DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.

**For 9 KHz-30MHz**

Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.18	49.56	102.50	52.94	PK	PASS
1.52	56.80	63.97	7.17	QP	PASS
15.35	55.55	69.54	13.99	QP	PASS
25.30	48.75	69.54	20.79	QP	PASS




## For 30MHz-1GHz

## Horizontal

**SWEEP TABLE: "test (30M-1G)"**

Short Description:		Field Strength			Transducer
Start	Stop	Detector	Meas. Time	IF Bandw.	
Frequency	Frequency				
30.0 MHz	1.1 GHz	MaxPeak	Coupled	100 kHz	JB1

**MEASUREMENT RESULT: "CTL150702137\_red"**


7/2/2015 4:37PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
549.920000	35.80	-9.5	46.0	10.2	---	100.0	196.00	HORIZONTAL
677.960000	36.20	-7.4	46.0	9.8	---	100.0	139.00	HORIZONTAL
734.220000	35.90	-6.3	46.0	10.1	---	100.0	175.00	HORIZONTAL
749.740000	40.10	-6.1	46.0	5.9	---	100.0	45.00	HORIZONTAL
790.480000	38.70	-5.8	46.0	7.3	---	100.0	175.00	HORIZONTAL
850.620000	37.10	-5.1	46.0	8.9	---	100.0	358.00	HORIZONTAL

## Vertical

**SWEEP TABLE: "test (30M-1G)"**

Short Description:		Field Strength			Transducer
Start	Stop	Detector	Meas. Time	IF Bandw.	
Frequency	Frequency				
30.0 MHz	1.1 GHz	MaxPeak	Coupled	100 kHz	JB1

**MEASUREMENT RESULT: "CTL150702136\_red"**

7/2/2015 4:34PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
499.480000	32.10	-10.2	46.0	13.9	---	100.0	359.00	VERTICAL
549.920000	35.80	-9.5	46.0	10.2	---	100.0	57.00	VERTICAL
577.080000	32.70	-8.8	46.0	13.3	---	100.0	139.00	VERTICAL
749.740000	36.40	-6.1	46.0	9.6	---	100.0	0.00	VERTICAL
802.120000	31.60	-5.8	46.0	14.4	---	100.0	177.00	VERTICAL
850.620000	35.40	-5.1	46.0	10.6	---	100.0	0.00	VERTICAL

**For 1GHz to 25GHz****GFSK Mode (above 1GHz)**

Frequency(MHz):				2402		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	97.54	PK	114	16.46	99.50	28.78	4.61	35.36	-1.96
1	2402.00	88.69	AV	94	5.31	90.65	28.78	4.61	35.36	-1.96
2	2390.00	36.54	PK	74	37.46	38.58	28.72	4.60	35.36	-2.04
2	2390.00	--	AV	54	--	--	--	--	--	--
3	4520.25	57.44	PK	74	16.56	53.64	32.89	6.73	35.82	3.80
3	4520.25	43.26	AV	54	10.74	39.46	32.89	6.73	35.82	3.80
4	4804.00	63.87	PK	74	10.13	57.81	33.49	6.91	34.34	6.06
4	4804.00	47.81	AV	54	6.19	41.75	33.49	6.91	34.34	6.06
5	5205.50	55.69	PK	74	18.31	48.31	34.55	7.14	34.30	7.38
5	5205.50	43.57	AV	54	10.43	36.19	34.55	7.14	34.30	7.38
6	7206.00	47.69	PK	74	26.31	36.58	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2402		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	98.89	PK	114	15.11	100.85	28.78	4.61	35.36	-1.96
1	2402.00	87.56	AV	94	6.44	89.52	28.78	4.61	35.36	-1.96
2	2390.00	37.65	PK	74	36.35	39.69	28.72	4.60	35.36	-2.04
2	2390.00	--	AV	54	--	--	--	--	--	--
3	4322.55	55.47	PK	74	18.53	51.81	32.83	6.60	35.78	3.66
3	4322.55	42.69	AV	54	11.31	39.03	32.83	6.60	35.78	3.66
4	4804.00	67.87	PK	74	6.13	61.81	33.49	6.91	34.34	6.06
4	4804.00	49.89	AV	54	4.11	43.83	33.49	6.91	34.34	6.06
5	4949.50	55.55	PK	74	18.45	49.01	33.80	6.99	34.26	6.54
5	4949.50	44.98	AV	54	9.02	38.44	33.80	6.99	34.26	6.54
6	7206.00	47.85	PK	74	26.15	36.74	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

**REMARKS:**

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW 1MHz VBW 3MHz Peak detector for PK value RMS detector for AV value.

Frequency(MHz):				2441		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2441.00	98.59	PK	114	15.41	100.45	28.85	4.66	35.37	-1.86
1	2441.00	89.65	AV	94	4.35	91.51	28.85	4.66	35.37	-1.86
2	3385.50	55.87	PK	74	18.13	53.87	31.53	5.69	35.22	2.00
2	3385.50	43.45	AV	54	10.55	41.45	31.53	5.69	35.22	2.00
3	4882.00	64.69	PK	74	9.31	58.33	33.60	6.95	34.19	6.36
3	4882.00	45.58	AV	54	8.42	39.22	33.60	6.95	34.19	6.36
4	5255.25	55.87	PK	74	18.13	48.19	34.60	7.17	34.08	7.68
4	5255.25	43.69	AV	54	10.31	36.01	34.60	7.17	34.08	7.68
5	7323.00	48.95	PK	74	25.05	37.25	37.46	9.23	35.00	11.70
5	7323.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2441		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2441.00	99.87	PK	114	14.13	101.73	28.85	4.66	35.37	-1.86
1	2441.00	90.25	AV	94	3.75	92.11	28.85	4.66	35.37	-1.86
2	3398.05	55.59	PK	74	18.41	53.57	31.53	5.71	35.22	2.02
2	3398.05	43.54	AV	54	10.46	41.52	31.53	5.71	35.22	2.02
3	4882.00	64.58	PK	74	9.42	58.22	33.60	6.95	34.19	6.36
3	4882.00	48.89	AV	54	5.11	42.53	33.60	6.95	34.19	6.36
4	5250.23	58.36	PK	74	15.64	50.69	34.59	7.17	34.09	7.67
4	5250.23	43.98	AV	54	10.02	36.31	34.59	7.17	34.09	7.67
5	7323.00	48.52	PK	74	25.48	36.82	37.46	9.23	35.00	11.70
5	7323.00	--	AV	54	--	--	--	--	--	--

## REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector for PK value RMS detector for AV value.

Frequency(MHz):				2480		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	97.58	PK	114	16.42	99.33	28.92	4.70	35.38	-1.75
1	2480.00	87.26	AV	94	6.74	89.01	28.92	4.70	35.38	-1.75
2	2483.50	57.48	PK	74	16.52	59.22	28.93	4.70	35.38	-1.74
2	2483.50	41.26	AV	54	12.74	43.00	28.93	4.70	35.38	-1.74
3	4335.20	56.95	PK	74	17.05	53.29	32.84	6.61	35.78	3.66
3	4335.20	43.54	AV	54	10.46	39.88	32.84	6.61	35.78	3.66
4	4960.00	57.55	PK	74	16.45	50.96	33.84	7.00	34.25	6.59
4	4960.00	47.98	AV	54	6.02	41.39	33.84	7.00	34.25	6.59
5	5210.55	56.56	PK	74	17.44	49.17	34.55	7.15	34.31	7.39
5	5210.55	45.54	AV	54	8.46	38.15	34.55	7.15	34.31	7.39
6	7440.00	48.96	PK	74	25.04	37.01	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2480		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	98.35	PK	114	15.65	100.10	28.92	4.70	35.38	-1.75
1	2480.00	89.41	AV	94	4.59	91.16	28.92	4.70	35.38	-1.75
2	2483.50	59.2	PK	74	14.8	60.94	28.93	4.70	35.38	-1.74
2	2483.50	43.26	AV	54	10.74	45.00	28.93	4.70	35.38	-1.74
3	4525.40	55.74	PK	74	18.26	51.93	32.90	6.74	35.83	3.81
3	4525.40	43.69	AV	54	10.31	39.88	32.90	6.74	35.83	3.81
4	4960.00	60.87	PK	74	13.13	54.28	33.84	7.00	34.25	6.59
4	4960.00	48.96	AV	54	5.04	42.37	33.84	7.00	34.25	6.59
5	6232.54	56.87	PK	74	17.13	48.44	35.19	7.95	34.70	8.43
5	6232.54	43.26	AV	54	10.74	34.83	35.19	7.95	34.70	8.43
6	7440.00	48.41	PK	74	25.59	36.46	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

## REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector for PK value RMS detector for AV value.




### 3.3. Occupied Bandwidth Measurement

#### Limit

N/A

#### Test Configuration



#### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### Test Results

Modulation	Channel	99% OBW (MHz)	20dB bandwidth (MHz)	Result
GFSK	CH00	0.878	0.948	Pass
	CH39	0.862	0.941	
	CH78	0.894	0.975	
$\pi/4$ DQPSK	CH00	1.151	1.256	
	CH39	1.171	1.266	
	CH78	1.159	1.203	
8DPSK	CH00	1.176	1.267	
	CH39	1.157	1.264	
	CH78	1.176	1.281	

Test plot as follows:





CH39

Agilent

R

T

Ch Freq2.48 GHz

TrigFree

Occupied Bandwidth

Ref 21 dBm

#Atten 30 dB

Mkr1 2.4799550 GHz

-1.774 dBm

#Peak

Log

10

dB/

Offset

1

dB

Center 2.48 GHz

#Res BW 30 kHz

#VBW 100 kHz

Span 3 MHz

Sweep 5 ms

Occupied Bandwidth

893.7564 kHz

Occ BW % Pwr99.00 %

x dB-20.00 dB

Transmit Freq Error-27.726 kHz

x dB Bandwidth975.259 kHz

Peak Search

Meas Tools

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

More1 of 2

CH78

Agilent

Ch Freq 2.402 GHz

Trig Free

Occupied Bandwidth

Ref 21 dBm

#Atten 30 dB

Mkr1 2.4021350 GHz

-3.645 dBm

#Peak

Log

10

dB/

Ofst

1

dB

Center 2.402 GHz

#Res BW 30 kHz

#VBW 100 kHz

Span 3 MHz

Sweep 5 ms

Occupied Bandwidth

1.1511 MHz

Occ BW % Pwr

99.00 %

x dB

-20.00 dB

Transmit Freq Error

-27.956 kHz

x dB Bandwidth

1.256 MHz

Peak Search

Meas Tools

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

More

1 of 2

The screen displays the Occupied Bandwidth measurement results. At the top, the Channel Frequency (Ch Freq) is 2.441 GHz. The measurement is triggered (Trig) and free (Free). The main display shows a spectral plot with a peak marker (Mkr 1) at 2.4408275 GHz with a level of -2.866 dBm. The plot shows a signal with a peak at the center frequency. The Y-axis is labeled #Peak, Log, 10, dB/Ofst, 1, dB. The X-axis represents frequency. Below the plot, the Center frequency is 2.441 GHz, the Resolution Bandwidth (Res BW) is 30 kHz, the Span is 3 MHz, and the Sweep time is 5 ms. The Occupied Bandwidth is 1.1707 MHz. The Transmit Frequency Error is -27.318 kHz, and the dB Bandwidth is 1.266 MHz. The Occupied Bandwidth percentage power (Occ BW % Pwr) is 99.00%, and the power level is -20.00 dB.

Agilent R T

Ch Freq 2.48 GHz Trig Free

Occupied Bandwidth

Ref 21 dBm #Atten 30 dB Mkr1 2.4799700 GHz 2.262 dBm

#Peak Log 10 dB/dB 1 dB

Center 2.48 GHz Span 3 MHz

#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms

Occupied Bandwidth 1.1592 MHz

Occ BW % Pwr 99.00 %


x dB -20.00 dB

Transmit Freq Error -27.448 kHz

x dB Bandwidth 1.203 MHz

Peak Search Meas Tools Next Peak Next Pk Right Next Pk Left Min Search Pk-Pk Search More 1 of 2

## CH78



### 3.4. Antenna Requirement

#### Standard Applicable


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### **Refer to statement below for compliance.**



The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

#### Antenna Connected Construction

The antenna used in this product is an internal Antenna, The directional gains of antenna used for transmitting is 1 dBi.



## 4. Test Setup Photos of the EUT








## 5. External and Internal Photos of the EUT



### External Photos of EUT









Internal Photos of EUT





\*\*\*\*\* End of Report \*\*\*\*\*

