



Report No: FCC 1703233-01 File reference No: 2017-04-10

Applicant: AOC

Product: Tablet PC

Model No: A832, A832-E

Trademark: AOC

Test Standards: FCC Part 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for the

evaluation of electromagnetic compatibility

Approved By

# Jack Chung

Jack Chung

Manager

Dated: April 10, 2017

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: FCC1703233-01 Page 2 of 94

Date: 2017-04-10



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

### **CNAL-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

### FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

Page 3 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



### **Test Report Conclusion**

### Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	8
3.1	Summary of Test Results	8
3.2	Test Standards.	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure	9
5.3	Configuration of the EUT	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test	13
6.1	Test Method and Test Procedure	13
6.2	Configuration of the EUT	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	14
7.0	6dB Bandwidth Measurement	38
8.0	Maximum Output Power	55
9.0	Power Spectral Density Measurement.	58
10.0	Out of Band Measurement.	73
11.0	Antenna Requirement.	82
12.0	FCC ID Label.	83
13.0	Photo of Test Setup and EUT View.	84

Report No.: FCC1703233-01 Page 4 of 94

Date: 2017-04-10



### 1.0 General Details

### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen,

Guangdong China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

### 1.2 Applicant Details

Applicant: AOC

Address: 14F-5, No. 258, Liancheng Rd., Zhonghe Dist., New Taipei City, Taiwan

Telephone: -Fax: --

1.3 Description of EUT

Product: Tablet PC
Manufacturer: AOC

Address: 14F-5, No. 258, Liancheng Rd., Zhonghe Dist., New Taipei City, Taiwan

Brand Name: AOC
Model Number: A832
Additional Model Number: A832-E

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20/HT40): OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20): 2412-2462MHz; IEEE 802.11n (HT40): 2422-2452MHz;

Channel Spacing 5MHz for IEEE 802.11b/g/n(HT20/HT40)

Air Data Rate IEEE 802.11b: 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20/HT40: msc0-msc7

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20) : 11 Channels; IEEE 802.11n (HT40) : 7 Channels

Antenna: Integral Antenna and the maximum Gain of this antenna is 1.28dBi;

Power Adapter Model No.: JHD-AP013U-050150BB-A

Input: 100-240V, 50/60Hz, 0.35A; Output: 5V, 1500mA

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703233-01 Page 5 of 94

Date: 2017-04-10



Submitted Sample: 2 Samples

Test Duration 1.5 2017-03-30 to 2017-04-08

1.6 Test Uncertainty Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Page 6 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



2.0 Test Equipment  Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2016-08-22	2017-08-21
TWO	R&S	ESPI 3	1003/9	2010-08-22	2017-08-21
	R&S	EZH3-Z5	100294	2016-08-22	2017-08-21
Line-V-NETW	D o C				
TWO	R&S	EZH3-Z5	100253	2016-08-22	2017-08-21
Line-V-NETW	D o G				
III. D. 11. 1	R&S	III 572	100157	2016 00 22	2017 00 22
Ultra Broadband		HL562	100157	2016-08-23	2017-08-22
ANT	D o G				
EGDVÆ (D	R&S	ESDV	100008	2016-08-22	2017-08-21
ESDV Test Receiver	D o C	EGI12 72	100201	2016 00 22	2017 00 21
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2016-08-22	2017-08-21
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXLO*	-	-
Loop Antenna	EMCO	6502	00042960	2016-08-23	2017-08-22
ESPI Test Receiver	R&S	ESI26	838786/013	2016-08-22	2017-08-21
3m OATS			N/A	2016-08-24	2017-08-23
Horn Antenna	R&S	BBHA 9170	BBHA9170265	2016-08-24	2017-08-23
Horn Antenna	R&S	BBHA 9120D	9120D-631	2016-08-24	2017-08-23
Power meter	Anritsu	ML2487A	6K00003613	2016-08-22	2017-08-21
Power sensor	Anritsu	MA2491A	32263	2016-08-22	2017-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2016-08-23	2017-08-21
LISN	AFJ	LS16C	10010947251	2016-08-22	2017-08-21
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2016-08-23	2017-08-22
9*6*6 Anechoic			N/A	2016-08-24	2017-08-23
EMI Test Receiver	RS	ESCS30	100139	2016-08-22	2017-08-21
DE C 11	SCHWARZBEC			2016 00 25	2017 00 55
RF Cable	K			2016-08-23	2017-08-22
Pre-Amplifier	НР	8447D	2727A05017	2016-08-05	2017-08-04
Pre-Amplifier	EM	EM30265		2016-08-05	2017-08-04

### 2.1 **Auxiliary Equipment**

Name	Model No.	Rating	Manufacturer	FCC ID/DOC
Passive				
Earphone				

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 7 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



### 3. DESCRIPTION OF TEST MODES

### IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 1Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 6Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: msc0 data rate (worst case) were chosen for full testing

Note:dutycycle>98%

### IEEE 802.11n (HT40) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Middle	2437
High	2452

IEEE 802.11n (HT40) mode: msc0 data rate (worst case) were chosen for full testing Note:dutycycle>98%

Page 8 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



### 3.0 **Technical Details**

### 3.1 **Summary of test results**

Standard	Test Type	Result	Notes
ECC Part 15, Paragraph 15.107 & 15.207	<b>Conducted Emission Test</b>	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	bandwidth>500kHz  Maximum peak output  power  Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit:30dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

### 3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

### **EUT Modification** 4.0

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.


Report No.: FCC1703233-01

Date: 2017-04-10



### 5.0 Power Line Conducted Emission Test


### 5.1 Schematics of the test



### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the Appropriate peripherals. All peripherals and cables are listed below.

### A. EUT

Device	Manufacturer	Model	FCC ID	
Tablet PC	AOC	A832, A832-E	2AEB5-A832	

### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

### C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
				-

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703233-01 Page 10 of 94

Date: 2017-04-10



### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

0 0 1								
Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB $\mu$ V)					
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level				
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*				
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0				
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0				

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No.: FCC1703233-01 Page 11 of 94

Date: 2017-04-10



### Conducted Emission on Live Terminal (150kHz to 30MHz) A:

**EUT Operating Environment** 

Humidity: 65%RH Atmospheric Pressure: 101 KPa Temperature: 26℃


**EUT set Condition: Keep WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual

### 80.0 dBuV



No. Mk	c. Freq.			Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBu∀	dB	Detector	Comment
1	0.6672	26.90	10.48	37.38	56.00	-18.62	QP	
2 *	0.6672	17.90	10.48	28.38	46.00	-17.62	AVG	

Page 12 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



### B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Humidity: 65%RH Atmospheric Pressure: 101 KPa Temperature: 26°C

**EUT set Condition: Keep WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



No. Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBu∀	dB	Detector	Comment
1	0.6684	35.00	10.49	45.49	56.00	-10.51	QP	
2 *	0.6684	25.20	10.49	35.69	46.00	-10.31	AVG	
3	1.3276	30.30	10.89	41.19	56.00	-14.81	QP	
4	1.3276	16.40	10.89	27.29	46.00	-18.71	AVG	
5	2.3800	28.50	10.87	39.37	56.00	-16.63	QP	
6	2.3800	14.00	10.87	24.87	46.00	-21.13	AVG	

Report No.: FCC1703233-01 Page 13 of 94

Date: 2017-04-10



### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 8999988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=1MHz VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

# Block diagram of Test setup Distance = 3m Computer Pre -Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1703233-01 Page 14 of 94

Date: 2017-04-10



### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

### Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB $\mu$ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No.: FCC1703233-01 Page 15 of 94

Date: 2017-04-10



### Test result

# General Radiated Emission Data and Harmonics Radiated Emission Data

### Radiated Emission In Horizontal/Vertical (30MHz----1000MHz)

**EUT set Condition: Keep Transmitting** 

**Results: Pass** 

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
270.080	29.83	Н	46.00
180.400	38.49	Н	43.50
82.560	36.51	Н	40.00
390.040	39.96	Н	46.00
272.120	35.17	V	46.00
182.400	40.42	V	43.50
84.560	35.51	V	40.00
390.040	38.32	V	46.00


Page 16 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



### Test Figure:




Date: 30.MAR.2017 13:53:56 Report No.: FCC1703233-01 Page 17 of 94

Date: 2017-04-10



### Test Figure:



Date: 30.MAR.2017 13:52:02 Report No.: FCC1703233-01 Page 18 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH01 for 11b at 1Mbps

	8		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4824.00	50.80 (PK)	Н	74(Peak)/ 54(AV)
4824.00	50.56 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 1Mbps

### Operation Mode: Transmitting under CH06 for 11b at 1Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4874.00	51.12 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.81 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 1Mbps

Page 19 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### Operation Mode: Transmitting under CH11 for 11b at 1Mbps

		_	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4924	52.29 (PK)	Н	74(Peak)/ 54(AV)
4924	52.12 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

<sup>3.</sup> For 802.11b mode at 1Mbps


Report No.: FCC1703233-01

Date: 2017-04-10




Please refer to the following test plots for details:

# CH01 for 11b at 1Mbps: Horizontal



# CH01 for 11b at 1Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 21 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH06 for 11b at 1Mbps: Vertical



### CH06 for 11b at 1Mbps: Horizontal




Report No.: FCC1703233-01


Date: 2017-04-10



### CH11 for 11b at 1Mbps: Vertical



### CH11 for 11b at 1Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703233-01 Page 23 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH01 for 11g at 6Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \text{V/m} \)
4824.00	50.78 (PK)	Н	74(Peak)/ 54(AV)
4824.00	52.32 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

<sup>3.</sup> For 802.11g mode 6Mbps

Report No.: FCC1703233-01 Page 24 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH06 for 11g at 6Mbps

	8	9 1	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4874.00	52.32 (PK)	V	74(Peak)/ 54(AV)
4874.00	52.47 (PK)	Н	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

3. For 802.11g mode 6Mbps

# Operation Mode: Transmitting under CH11 for 11g at 6Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \( \mu \text{V/m} \)
4924	50.08 (PK)	Н	74(Peak)/ 54(AV)
4924	51.64 (PK)	V	74(Peak)/ 54(AV)
7368	1	H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310	1	H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 6Mbps


Report No.: FCC1703233-01

Date: 2017-04-10




Please refer to the following test plots for details:

# CH01 for 11g at 6Mbps: Horizontal



# CH01 for 11g at 6Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to


Page 26 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH06 for 11g at 6Mbps: Vertical



### CH06 for 11g at 6Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to


Page 27 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH11 for 11g at 6Mbps: Vertical



### CH11 for 11g at 6Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Report No.: FCC1703233-01 Page 28 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH01 for 11n HT20 at msc0

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4824.00	52.35 (PK)	Н	74(Peak)/ 54(AV)
4824.00	52.10 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode msc0

### Operation Mode: Transmitting under CH06 for 11n HT20 at msc0

		·	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4874.00	51.04 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.19 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode msc0

Report No.: FCC1703233-01 Page 29 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH11 for 11n HT20 at msc0

	-		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4924	50.19 (PK)	Н	74(Peak)/ 54(AV)
4924	50.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)

<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

<sup>3.</sup> For 802.11n (HT20) mode msc0


Report No.: FCC1703233-01

Date: 2017-04-10




Please refer to the following test plots for details:

# CH01 for 11n HT20 at msc0: Horizontal



### CH01 for 11n HT20 at msc0: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to


Page 31 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH06 for 11n HT20 at msc0: Vertical



### CH06 for 11n HT20 at msc0: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to


Page 32 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH11 for 11n HT20 at msc0: Vertical



### CH11 for 11n HT20 at msc0: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Report No.: FCC1703233-01 Page 33 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH01 for 11n HT40 at msc0

1	8		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4844.00	49.51 (PK)	Н	74(Peak)/ 54(AV)
4844.00	50.27 (PK)	V	74(Peak)/ 54(AV)
7266.00		H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376		H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 6.5Mbps

# Operation Mode: Transmitting under CH04 for 11n HT40 at msc0

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \( \mu \text{V/m} \)
4874.00	48.66 (PK)	Н	74(Peak)/ 54(AV)
4874.00	48.03 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185	1	H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 6.5Mbps

Report No.: FCC1703233-01 Page 34 of 94

Date: 2017-04-10



### Operation Mode: Transmitting under CH07 for 11n HT40 at msc0

		ī	7
Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4904	49.73 (PK)	Н	74(Peak)/ 54(AV)
4904	49.58 (PK)	V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 6.5Mbps


Report No.: FCC1703233-01

Date: 2017-04-10




Please refer to the following test plots for details:

# CH01 for 11n HT40 at msc0: Horizontal



### CH01 for 11n HT40 at msc0: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 36 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH04 for 11n HT40 at msc0: Vertical



### CH04 for 11n HT40 at msc0: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to


Page 37 of 94

Report No.: FCC1703233-01


Date: 2017-04-10



### CH07 for 11n HT40 at msc0: Vertical



### CH07 for 11n HT40 at msc0: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Report No.: FCC1703233-01 Page 38 of 94

Date: 2017-04-10



# 7.0 6dB Bandwidth Measurement

# 7.1 Test Setup



### 7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

## 7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode =  $\max$  hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 7.4 Test Result

Page 39 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



## 6dB Occupied Bandwidth


EUT		Ta	ablet PC		Model		A	832
Mode		8	302.11b		Input Vol	tage	DC	3.7V
Temperat	ure	24	4 deg. C,		Humidity		56%	% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	-	ndwidth Hz)		mum Limit MHz)	Pass/ Fail
1		2412	1	9.	08		0.5	Pass
6		2437	1	9.	08		0.5	Pass
11		2462	1	9.	08		0.5	Pass

Page 40 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



## 1. 802.11b at 1Mbps of CH01




1.APR.2017 Date: 18:48:17 Report No.: FCC1703233-01 Page 41 of 94

Date: 2017-04-10



## 2. 802.11b at 1Mbps of CH06




5.APR.2017 Date: 10:53:11 Report No.: FCC1703233-01 Page 42 of 94

Date: 2017-04-10



## 3. 802.11b at 1Mbps of CH11



5.APR.2017 Date: 11:11:19

Page 43 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



# 6dB Occupied Bandwidth

EUT		Ta	ablet PC		Model			A832
Mode		8	302.11g		Input Vol	tage	Γ	DC3.7V
Temperat	ure	24	4 deg. C,		Humidity	r	5	6% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		andwidth [Hz]		num Limit MHz)	Pass/ Fail
1		2412	6	16	5.53		0.5	Pass
6		2437	6	16	5.59	0.5		Pass
11		2462	6	16	5.53	0.5		Pass


Page 44 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### **Test Plots:**

## 1. 802.11g at 6Mbps of CH01




Date: 5.APR.2017 10:45:57 Report No.: FCC1703233-01 Page 45 of 94

Date: 2017-04-10



## 2. 802.11g at 6Mbps of CH06




5.APR.2017 Date: 10:58:21 Report No.: FCC1703233-01 Page 46 of 94

Date: 2017-04-10



## 3. 802.11g at 6Mbps of CH11



5.APR.2017 11:05:33 Date:

Page 47 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



## 6dB Occupied Bandwidth

EUT	_	T	ablet PC		Model		A	832
Mode		802	.11n HT20		Input Vol	tage	DC	3.7V
Temperat	ure	24	4 deg. C,		Humidity		56%	% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	-	ndwidth Hz)		num Limit MHz)	Pass/ Fail
1		2412	mcs0	17	.80		0.5	Pass
6		2437	mcs0	17	.80	0.5		Pass
11		2462	mcs0	17	.80		0.5	Pass

Page 48 of 94


Report No.: FCC1703233-01

Date: 2017-04-10



### **Test Plots:**

## 1. 802.11n at HT20 of CH01




Date: 5.APR.2017 12:01:34 Report No.: FCC1703233-01 Page 49 of 94

Date: 2017-04-10



### 2. 802.11n at HT20 of CH06




5.APR.2017 Date: 11:59:40

Page 50 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 3. 802.11n at HT20 of CH11



5.APR.2017 Date: 11:56:58

Page 51 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



## 6dB Occupied Bandwidth

EUT		Т	ablet PC		Model		A	832
Mode		802	.11n HT40		Input Vol	tage	DC	3.7V
Temperat	ure	24	4 deg. C,		Humidity		56%	6 RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	-	ndwidth Hz)		num Limit MHz)	Pass/ Fail
1		2422	mcs0	36	.47		0.5	Pass
4		2437	mcs0	36	.48	0.5		Pass
7		2452	mcs0	36	.48		0.5	Pass


Report No.: FCC1703233-01 Page 52 of 94

Date: 2017-04-10



### **Test Plots:**

## 1. 802.11n at HT40 of CH01




Date: 5.APR.2017 12:04:09

Page 53 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 2. 802.11n at HT40 of CH04




5.APR.2017 Date: 12:06:16

Page 54 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 3. 802.11n at HT40 of CH07



5.APR.2017 12:10:45 Date:

Report No.: FCC1703233-01


Date: 2017-04-10



Page 55 of 94

# 8. Maximum Output Power

# 8.1 Test Setup



### 8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

### **8.3 Test Procedure**

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: AV power was measured

Page 56 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



### **8.4Test Results**

EUT		Tablet	PC	M	odel		A832
Mode	Mode 802.		1b	Input Voltage		DC3.7V	
Temperature		24 deg	24 deg. C,		Humidity		56% RH
Channel	Cha	annel Frequency (MHz)	Max. Power Output (dBm)		Power Limit (dBm)		Pass/ Fail
		(WITZ)	Average		(uD	111)	
1	2412		7.93		30		Pass
6	6 2437		8.29		30	)	Pass
11		2462	8.50		30	)	Pass

Note: 1. At finial test to get the worst-case emission at 1Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		Tablet	PC	M	odel		A832	
Mode	Mode 802.1		1g	Input Voltage		DC3.7V		
Temperat	Temperature 24 de		g. C, Hum		midity		56% RH	
Channel	Cha	annel Frequency (MHz)	Max. Power Output (dBm)		Power Limit (dBm)		Pass/ Fail	
		(1/11/2)	Average	:	(GD	,		
1		2412	6.11		30		Pass	
6	6 2437		6.60		30	)	Pass	
11		2462	6.88		30	)	Pass	

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Page 57 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



EUT		Tablet	PC	M	odel		A832
Mode		802.11n (	802.11n (HT20)		Input Voltage		DC3.7V
Temperature		24 deg	24 deg. C,		Humidity		56% RH
Channel	Cha	annel Frequency (MHz)	Max. Power Output (dBm)		Power (dB		Pass/ Fail
		(WITIZ)	Average		(uD	111)	
1	2412		6.22		30		Pass
6	6 2437		6.61		30	)	Pass
11		2462	6.85	•	30	)	Pass

Note: 1. At finial test to get the worst-case emission at msc0 of 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow: Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		Tablet	PC	M	odel		A832
Mode		802.11n (HT40)		Input Voltage			DC3.7V
Temperature		24 deg	24 deg. C,		Humidity		56% RH
Channel	Cha	annel Frequency (MHz)	Max. Power Output (dBm)		Power (dB		Pass/ Fail
		(WITIZ)	Average		(ub	111)	
1		2422	5.77		30		Pass
4	4 2437		5.98		30	)	Pass
7		2452	6.38		30	)	Pass

Note: 1. At finial test to get the worst-case emission at msc0 of 11n HT40 for CH01, CH04 and CH07

2. The result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded


Report No.: FCC1703233-01 Page 58 of 94

Date: 2017-04-10



# 9. Power Spectral Density Measurement

# 9.1 Test Setup



### 9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

### 9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW  $\geq$  30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be  $\leq 8$  dBm.

Page 59 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 9.4Test Result

EUT		Tablet	PC	M	odel		A832
Mode		802.11b 1Mbps		Input Voltage		DC3.7V	
Temperature		24 deg	g. C,	Humidity			56% RH
Channel	Cha	annel Frequency (MHz)	Final RF Po Level in (dF		Maximur (dB		Pass/ Fail
			1Mbps	l			
1	2412		-18.18		8		Pass
6 2437		-17.77		8		Pass	
11		2462	-17.64		8		Pass

EUT		Tablet	PC	M	odel		A832
Mode	Mode 802.1		6Mbps	Input Voltage		DC3.7V	
Temperature		24 deg	g. C,	Hur	Humidity		56% RH
Channel	Cha	annel Frequency	Final RF Power		Maximum Limit		Pass/ Fail
Chamiei		(MHz)	Level in (dI	Bm)	(dB	m)	
			6Mbps				
1		2412	-23.30		8		Pass
6	6 2437		-22.59		8		Pass
11		2462	-22.13		8		Pass

Page 60 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



EUT		Tablet	PC	M	odel		A832
Mode		802.11n H7	802.11n HT20 msc0		Input Voltage		DC3.7V
Temperature		24 deg	g. C,	Humidity		56% RH	
Channel	Channel Frequency		Final RF Power		Maximum Limit		Pass/ Fail
Chamie		(MHz)	Level (dBm)		(dB	m)	
			HT20				
1		2412	-23.40		8		Pass
6	2437		-23.00		8		Pass
11		2462	-22.80		8		Pass

EUT		Tablet	Tablet PC		Model		A832
Mode 802		802.11n H7	802.11n HT40 msc0		Input Voltage		DC3.7V
Temperature		24 deg	g. C,	Humidity		56% RH	
Channel	Cha	annel Frequency	Final RF Power		Maximum Limit		Pass/ Fail
Channel		(MHz)	Level (dB	m)	(dB	m)	
			HT40				
1	2422		-27.25		8		Pass
4	4 2437		-27.21		8		Pass
7		2452	-27.53		8		Pass


Page 61 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



## 9.5 Photo of Power Spectral Density Measurement

1. 802.11b at 1Mbps of CH1




Date: 5.APR.2017 15:07:16

Page 62 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



# 2. 802.11b at 1Mbps of CH6




5.APR.2017 Date: 15:09:21

Page 63 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



# 3. 802.11b at 1Mbps of CH11




5.APR.2017 Date: 15:11:38 Report No.: FCC1703233-01 Page 64 of 94

Date: 2017-04-10



# 4. 802.11g at 6Mbps of CH1



Date: 5.APR.2017 15:06:26


Page 65 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



## 5. 802.11g at 6Mbps of CH6




Date: 5.APR.2017 15:03:41 Page 66 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



## 6. 802.11g at 6Mbps of CH11




Date: 5.APR.2017 15:00:57

Page 67 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 7. 802.11n at HT20 of CH01




5.APR.2017 Date: 15:19:54

Page 68 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 8. 802.11n at HT20 of CH06




Date: 5.APR.2017 15:17:42

Page 69 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 9. 802.11n at HT20 of CH11




Date: 5.APR.2017 15:15:44 Report No.: FCC1703233-01 Page 70 of 94

Date: 2017-04-10



### 10. 802.11n at HT40 of CH01




5.APR.2017 Date: 15:23:59

Page 71 of 94 Report No.: FCC1703233-01

Date: 2017-04-10



### 11. 802.11n at HT40 of CH04




5.APR.2017 Date: 15:27:12 Report No.: FCC1703233-01 Page 72 of 94

Date: 2017-04-10



### 12. 802.11n at HT40 of CH07



5.APR.2017 Date: 15:29:30 Report No.: FCC1703233-01


Date: 2017-04-10



Page 73 of 94

## 10 Out of Band Measurement

## 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

#### 10.2 Limits of Out of Band Emissions Measurement

- 1. Below -30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### **10.3 Test Procedure**

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. (Peak values with RBW=1MHz, VBW=3MHzPK detector. AV value with RMS detector)

For bandage test, the spectrum set as follows: RBW=100kHz, VBW=300 kHz peak detector. A conducted measurement used

#### 10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position. the worse case was recorded

2. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Page 74 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




### For 802.11b mode

CH01 at 1Mbps

#### Band-edge and Restricted band Measurement 10.4

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBμV/m)	55.2	T ' '4	$74(dB\mu V/m)$
	AV (dBμV/m)	35.3	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	40.9	Limit	74(dBµV/m)
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 75 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




### CH11 at 1Mbps

#### 10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	42.8	т,	74(dBμV/m)
	AV (dBμV/m)		Limit	54(dBμV/m)

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Page 76 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




### For 802.11g mode

CH01 at 6Mbps

#### Band-edge and Restricted band Measurement 10.4

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBµV/m)	60.4	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)	40.1	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	46.9	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Lillit	$54(dB\mu V/m)$

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 77 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




### CH11 at 6Mbps

### 10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Mod	lel	A832
Mode	Keeping Transmitting		Input V	oltage	DC3.7V
Temperature	24 deg. C,		Humi	dity	56% RH
Test Result:	Pass		Detec	ctor	PK
2483.5	PK (dBµV/m)	50.3	T,	74(dBμV/m) 54(dBμV/m)	
	AV (dBμV/m)	31.8	Limit		

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Page 78 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




### For 802.11n (HT20) mode

CH01 at msc0

#### 10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBµV/m)	61.2	T 114	$74(dB\mu V/m)$
	AV (dBμV/m)	40.8	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	47.5	Limit	74(dBμV/m)
	AV (dBμV/m)		Limit	54(dBμV/m)

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 79 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




#### CH11 at msc0

#### 10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	50.6	T,	$74(dB\mu V/m)$
	AV (dBμV/m)	31.9	Limit	54(dBµV/m)

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Page 80 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




### For 802.11n (HT40) mode

CH01 at msc0

#### Band-edge and Restricted band Measurement 10.4

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBµV/m)	63.8	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)	44.3	Limit	$54(dB\mu V/m)$
2390	PK (dBµV/m)	44.9	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Liillit	$54(dB\mu V/m)$

## **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 81 of 94

Report No.: FCC1703233-01

Date: 2017-04-10




#### CH7 at msc0

#### 10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC		Model	A832
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	46.2	T ' '4	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBµV/m)

## **Test Figure:**



5.APR.2017 15:30:20

Note: The Max. FS in Restrict Band are measured in conventional method.

Report No.: FCC1703233-01

Date: 2017-04-10



# Page 82 of 94

## 11.0 Antenna Requirement

## 11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

### 11.2 Antenna Connected construction

Integral antenna used. The maximum Gain of the antennas is 1.28dBi.

Report No.: FCC1703233-01 Page 83 of 94

Date: 2017-04-10




#### 12.0 FCC ID Label

### **FCC ID: 2AEB5-A832**

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### Mark Location:




Report No.: FCC1703233-01 Page 84 of 94

Date: 2017-04-10



#### 13.0 **Photo of testing**

Conducted Emission Test Setup:




Page 85 of 94


Report No.: FCC1703233-01

Date: 2017-04-10



### Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1703233-01

Date: 2017-04-10



## Photographs - EUT

## Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 87 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 88 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 89 of 94


Report No.: FCC1703233-01

Date: 2017-04-10



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 90 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 91 of 94


Report No.: FCC1703233-01

Date: 2017-04-10



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 92 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 93 of 94


Report No.: FCC1703233-01

Date: 2017-04-10



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 94 of 94

Report No.: FCC1703233-01

Date: 2017-04-10



Inside view



## **End of the report**

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.