

FCC PART 22H, PART 24E TEST REPORT

For

elco

1 Rue Galilée 56270 Ploemeur France

FCC ID: 2AEBFS5160Q4G

Report Type: Original Report	Product Type: Smart Phone
Test Engineer: <u>Mike Hu</u> <i>Mike Hu</i>	
Report Number: <u>RSZ150304004-00D</u>	
Report Date: <u>2015-03-19</u>	
Reviewed By: <u>RF Engineer</u> <i>Jimmy Xiao</i>	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST DATA	11
FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH	18
APPLICABLE STANDARD	18
TEST PROCEDURE	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST DATA	18
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA	26
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	32
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	34
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY.....	47
APPLICABLE STANDARD	47

TEST PROCEDURE47

TEST EQUIPMENT LIST AND DETAILS.....48

TEST DATA48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *elco*'s product, model number: *S5160Q 4G (FCC ID: 2AEBFS5160Q4G)* or the "EUT" in this report was a *Smart Phone*, which was measured approximately: 14.5 cm (L) x 7.3 cm (W) x 0.9 cm (H), rated input voltage: DC 3.7 V battery or DC 5.0V from adapter.

Adapter Information:

Model: S5160Q 4G

Input: AC100-240V, 50/60Hz, 0.2A

Output: DC 5.0V, 1000mA

**All measurement and test data in this report was gathered from production sample serial number: 1503019 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2015-03-04*

Objective

This test report is prepared on behalf of *elco* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS&DSS, Part 27 PCE and Part 15B JBP submissions with FCC ID: 2AEBFS5160Q4G.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ150304004-20.

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ150304004-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2014-12-01	2015-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-8-22	2015-08-22
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2014-11-12	2015-11-12
Sunol Sciences	Broadband Antenna	JB3	A111513	2014-6-18	2017-6-17
HP	Signal Generator	8341B	2624A00116	2014-06-03	2015-06-03
COM POWER	Dipole Antenna	AD-100	041000	NCR	NCR
A.H. System	Horn Antenna	SAS-200/571	135	2013-02-11	2016-02-10
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2014-11-23	2015-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Hu on 2015-03-12

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.32	38.45
	190	836.6	32.65	38.45
	251	848.8	32.81	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	32.32	32.24	32.07	31.94	38.45
	190	836.6	32.69	32.56	32.44	32.28	38.45
	251	848.8	32.75	32.69	32.58	32.37	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	826.4	25.63	25.63	25.57	25.43	38.45
	190	836.6	25.86	25.74	25.73	25.61	38.45
	251	846.6	26.06	25.96	25.92	25.83	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.48	22.56	22.46
		Rel 6 HSDPA	1	21.36	21.23	21.30
			2	21.25	21.10	21.22
			3	21.41	21.30	21.34
			4	21.26	21.19	21.21
		Rel 6 HSUPA	1	20.73	20.83	20.78
			2	20.62	20.75	20.75
			3	20.84	20.91	20.88
			4	20.62	20.78	20.71
			5	20.82	20.94	20.84

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	28.64	33
	661	1880.0	28.63	33
	810	1909.8	28.66	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	28.56	28.44	28.51	28.27	33
	661	1880.0	28.61	28.52	28.23	27.98	33
	810	1909.8	28.59	28.50	28.25	28.08	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1852.4	24.44	24.32	24.30	24.06	33
	661	1880.0	24.38	24.31	24.22	24.03	33
	810	1907.6	24.50	24.38	24.29	24.13	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		22.35	22.28	22.26
		Rel 6 HSDPA	1	21.25	21.17	21.32
			2	21.14	21.05	21.24
			3	21.36	21.25	21.43
			4	21.21	21.11	21.22
		Rel 6 HSUPA	1	20.75	20.58	20.56
			2	20.72	20.47	20.49
			3	20.81	20.61	20.60
			4	20.64	20.55	20.51
			5	20.85	20.64	20.63

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.19	13
	Middle	0.18	13
	High	0.20	13

Mode	Channel	PAR (dB)	Limit (dB)
EDGE	Low	0.17	13
	Middle	0.22	13
	High	0.19	13

Mode	Channel	PAR (dB)	Limit (dB)
WCDMA (BPSK)	Low	2.75	13
	Middle	2.72	13
	High	2.75	13
HSDPA (16QAM)	Low	2.79	13
	Middle	2.81	13
	High	2.69	13
HSUPA (BPSK)	Low	2.66	13
	Middle	2.82	13
	High	2.71	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.20	13
	Middle	0.23	13
	High	0.23	13

Mode	Channel	PAR (dB)	Limit (dB)
EDGE	Low	0.28	13
	Middle	0.24	13
	High	0.25	13

Mode	Channel	PAR (dB)	Limit (dB)
WCDMA (BPSK)	Low	2.75	13
	Middle	2.86	13
	High	2.78	13
HSDPA (16QAM)	Low	2.75	13
	Middle	2.74	13
	High	2.68	13
HSUPA (BPSK)	Low	2.67	13
	Middle	2.54	13
	High	2.53	13

Radiated Power (Measured at Max. conducted power channel)**ERP & EIRP****GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), High Channel										
848.8	93.28	88	1.2	H	26.3	0.69	0.0	25.61	38.45	12.84
848.8	98.36	225	1.3	V	30.6	0.69	0.0	29.91	38.45	8.54
EIRP for PCS Band (Part 24E), High Channel										
1909.8	86.72	77	1.2	H	19.2	1.40	7.30	25.10	33	7.90
1909.8	89.68	152	1.5	V	21.3	1.40	7.30	27.20	33	5.80

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), High Channel										
848.8	87.62	250	1.4	H	16.1	0.69	0.0	15.41	38.45	23.04
848.8	91.32	160	2.1	V	23.5	0.69	0.0	22.81	38.45	15.64
EIRP for PCS Band (Part 24E), High Channel										
1909.8	82.37	160	1.9	H	14.8	1.40	7.30	20.70	33	12.30
1909.8	84.98	27	1.2	V	16.4	1.40	7.30	22.30	33	10.70

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	85.36	85	1.4	H	14.3	0.69	0.0	13.61	38.45	24.84
836.6	88.67	160	1.3	V	20.8	0.69	0.0	20.11	38.45	18.34
EIRP for WCDMA Band II (Part 24E), Low Channel										
1852.4	79.32	25	1.5	H	11.2	1.03	9.40	19.57	33	13.43
1852.4	80.36	157	1.4	V	12.1	1.03	9.40	20.47	33	12.53

Note:

All above data were tested with no amplifier.

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 5 kHz (Cellular /PCS) & 100 kHz (WCDMA) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-08-22	2015-08-22
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2014-11-23	2015-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Hu on 2015-03-12.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	244.5	316.6
EGPRS(8PSK)	836.6	244.5	316.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA (BPSK)	836.6	4.17	4.69
HSUPA (BPSK)	836.6	4.17	4.73
HSDPA (16QAM)	836.6	4.17	4.71


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	242.5	318.6
EGPRS(8PSK)	1880.0	244.5	316.6


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA (BPSK)	1880.0	4.17	4.71
HSUPA (BPSK)	1880.0	4.17	4.72
HSDPA (16QAM)	1880.0	4.15	4.71

Cellular Band (Part 22H)


99% Occupied & 26 dB Emissions Bandwidth for GSM (GMSK) Mode




99% Occupied & 26 dB Emissions Bandwidth for EDGE Mode




99% Occupied & 26 dB Emissions Bandwidth for WCDMA (BPSK) Mode



99% Occupied & 26 dB Emissions Bandwidth for HSUPA (BPSK) Mode




99% Occupied & 26 dB Emissions Bandwidth for HSDPA (16QAM) Mode




PCS Band (Part 24E)


99% Occupied & 26 dB Emissions Bandwidth for GSM (GMSK) Mode




99% Occupied & 26 dB Emissions Bandwidth for EGPRS Mode




99% Occupied & 26 dB Emissions Bandwidth for WCDMA (BPSK) Mode



99% Occupied & 26 dB Emissions Bandwidth for HSUPA (BPSK) Mode



99% Occupied & 26 dB Emissions Bandwidth for HSDPA (16QAM) Mode



FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-08-22	2015-08-22
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2014-11-23	2015-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Hu on 2015-03-12


Test result: Compliance, please refer to the following plots. (The Worst Case)

Cellular Band (Part 22H)


30 MHz – 1 GHz (GSM Mode)




1 GHz – 10 GHz (GSM Mode)



30 MHz – 1 GHz (WCDMA Mode)




1 GHz – 10 GHz (WCDMA Mode)




PCS Band (Part 24E)


30 MHz – 1 GHz (GSM Mode)




1 GHz – 20 GHz (GSM Mode)



30 MHz – 1 GHz (WCDMA Mode)



1 GHz – 20 GHz (WCDMA Mode)



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg(\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2014-12-01	2015-11-30
Sunol Sciences	Broadband Antenna	JB3	A111513	2014-06-18	2017-06-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-08-22	2015-08-22
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2014-11-03	2015-11-03
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2014-04-23	2015-04-23
HP	Amplifier	8447E	1937A01046	2014-05-06	2015-05-06
HP	Signal Generator	8341B	2624A00116	2014-06-03	2015-06-03
COM POWER	Dipole Antenna	AD-100	041000	NCR	NCR
A.H. System	Horn Antenna	SAS-200/571	135	2013-02-11	2016-02-10
Electro-Mechanics	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2014-11-23	2015-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	58 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Hu on 2015-02-28

EUT operation mode: Transmitting (The Worst Case)

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
GSM Mode, High channel										
263.2	27.67	12	2.0	H	-69.3	0.32	0	-69.62	-13	56.62
263.2	28.34	200	1.7	V	-68.7	0.32	0	-69.02	-13	56.02
1697.6	61.29	72	1.1	H	-34.9	1.6	6.90	-29.60	-13	16.60
1697.6	62.97	51	1.9	V	-35.3	1.60	6.90	-30.00	-13	17.00
WCDMA Mode, Middle channel										
131.6	27.88	310	1.3	H	-69.1	0.26	0	-69.36	-13	56.36
131.6	28.21	117	2.2	V	-68.8	0.26	0	-69.06	-13	56.06
1673.2	56.63	55	1.8	H	-39.5	1.6	6.90	-34.20	-13	21.20
1673.2	55.91	156	1.9	V	-42.3	1.60	6.90	-37.00	-13	24.00
2509.8	40.34	65	1.2	H	-54.2	1.70	8.60	-47.30	-13	34.30
2509.8	42.23	306	1.4	V	-52.4	1.70	8.60	-45.50	-13	32.50
3346.4	36.34	223	1.2	H	-52.8	1.90	9.80	-44.90	-13	31.90
3346.4	38.52	150	1.9	V	-52.1	1.90	9.80	-44.20	-13	31.20

30 MHz ~ 20 GHz:**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
GSM Mode, High channel										
263.2	28.25	136	2.2	H	-68.7	0.32	0	-69.02	-13	56.02
263.2	28.71	95	1.0	V	-68.3	0.32	0	-68.62	-13	55.62
3819.6	51.96	270	1.4	H	-39.9	1.8	10.00	-31.70	-13	18.70
3819.6	52.48	54	1.1	V	-39.7	1.80	10.00	-31.50	-13	18.50
WCDMA Mode, Low channel										
131.6	27.54	139	1.7	H	-69.5	0.26	0	-69.76	-13	56.76
131.6	28.27	55	1.9	V	-68.7	0.26	0	-68.96	-13	55.96
3704.8	35.96	49	2.4	H	-54.6	1.8	10.00	-46.40	-13	33.40
3704.8	36.74	272	2.0	V	-54.2	1.80	10.00	-46.00	-13	33.00

Note:

1) Absolute Level = SG Level - Cable loss + Antenna Gain

2) Margin = Limit- Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Signal Analyzer	FSIQ26	837405/023	2014-08-22	2015-08-22
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2014-11-23	2015-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Hu on 2015-03-12

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Band Edge	Emission(dBm)	Limit(dBm)
GSM (GMSK)	Left Band	-17.48	-13
	Right Band	-21.79	-13

Mode	Band Edge	Emission(dBm)	Limit(dBm)
EGPRS(8PSK)	Left Band	-21.79	-13
	Right Band	-21.76	-13

Mode	Band Edge	Emission(dBm)	Limit(dBm)
WCDMA (BPSK)	Left Band	-18.85	-13
	Right Band	-19.12	-13

Mode	Band Edge	Emission(dBm)	Limit(dBm)
HSDPA (16QAM)	Left Band	-17.65	-13
	Right Band	-19.13	-13

Mode	Band Edge	Emission(dBm)	Limit(dBm)
HSUPA (BPSK)	Left Band	-18.85	-13
	Right Band	-20.05	-13

PCS Band (Part 24E)



Mode	Band Edge	Emission(dBm)	Limit(dBm)
GSM(GMSK)	Left Band	-16.73	-13
	Right Band	-20.06	-13



Mode	Band Edge	Emission(dBm)	Limit(dBm)
EGPRS(8PSK)	Left Band	-21.56	-13
	Right Band	-21.94	-13

Mode	Band Edge	Emission(dBm)	Limit(dBm)
WCDMA (BPSK)	Left Band	-14.37	-13
	Right Band	-17.13	-13


Mode	Band Edge	Emission(dBm)	Limit(dBm)
HSDPA (16QAM)	Left Band	-17.05	-13
	Right Band	-18.84	-13

Mode	Band Edge	Emission(dBm)	Limit(dBm)
HSUPA (BPSK)	Left Band	-17.34	-13
	Right Band	-19.86	-13


Cellular Band, Left Band Edge for GSM (GMSK) Mode**Cellular Band, Right Band Edge for GSM (GMSK) Mode**



Cellular Band, Left Band Edge for EGPRS Mode**Cellular Band, Right Band Edge for EGPRS Mode**

Cellular Band, Left Band Edge for WCDMA (BPSK) Mode




Cellular Band, Right Band Edge for WCDMA (BPSK) Mode




Cellular Band, Left Band Edge for HSDPA (16QAM) Mode**Cellular Band, Right Band Edge for HSDPA (16QAM) Mode**


Cellular Band, Left Band Edge for HSUPA (BPSK) Mode



Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




PCS Band, Left Band Edge for GSM (GMSK) Mode




Date: 12.MAR.2015 17:10:26

PCS Band, Right Band Edge for GSM (GMSK) Mode




Date: 12.MAR.2015 17:11:47

PCS Band, Left Band Edge for EGPRS Mode




Date: 12.MAR.2015 17:23:01

PCS Band, Right Band Edge for EGPRS Mode




Date: 12.MAR.2015 17:23:58


PCS Band, Left Band Edge for WCDMA (BPSK) Mode




PCS Band, Right Band Edge for WCDMA (BPSK) Mode




PCS Band, Left Band Edge for HSDPA (16QAM) Mode




PCS Band, Right Band Edge for HSDPA (16QAM) Mode



PCS Band, Left Band Edge for HSUPA (BPSK) Mode



PCS Band, Right Band Edge for HSUPA (BPSK) Mode



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY**Applicable Standard**

FCC § 2.1055, §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2014-11-01	2015-11-01
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2014-11-23	2015-11-23

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	20 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Mike Hu on 2015-03-12

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error(ppm)	Limit (ppm)
-30	3.7	12	0.01434	2.5
-20		12	0.01434	2.5
-10		13	0.01554	2.5
0		15	0.01793	2.5
10		9	0.01076	2.5
20		10	0.01195	2.5
30		8	0.00956	2.5
40		9	0.01076	2.5
50		14	0.01673	2.5
25	V min.= 3.5	11	0.01315	2.5
25	V max.= 4.2	13	0.01554	2.5

EDGE Mode

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error(ppm)	Limit (ppm)
-30	3.7	12	0.01434	2.5
-20		12	0.01434	2.5
-10		10	0.01195	2.5
0		10	0.01195	2.5
10		10	0.01195	2.5
20		12	0.01434	2.5
30		10	0.01195	2.5
40		10	0.01195	2.5
50		12	0.01434	2.5
25	V min.= 3.5	12	0.01434	2.5
25	V max.= 4.2	12	0.01434	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied(V _{DC})	Frequency Error(Hz)	Frequency Error(ppm)	Limit (ppm)
-30	3.7	8	0.00956	2.5
-20		7	0.00837	2.5
-10		6	0.00717	2.5
0		5	0.00598	2.5
10		9	0.01076	2.5
20		8	0.00956	2.5
30		7	0.00837	2.5
40		9	0.01076	2.5
50		6	0.00717	2.5
25	V min.= 3.5	7	0.00837	2.5
25	V max.= 4.2	5	0.00598	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0=1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error(ppm)	Limit (ppm)
-30	3.7	5	0.00266	PASS
-20		7	0.00372	PASS
-10		6	0.00319	PASS
0		8	0.00426	PASS
10		9	0.00479	PASS
20		7	0.00372	PASS
30		12	0.00638	PASS
40		9	0.00479	PASS
50		11	0.00585	PASS
25	$V_{min}=3.5$	9	0.00479	PASS
25	$V_{max}=4.2$	6	0.00319	PASS

EDGE Mode

Middle Channel, $f_0=1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error(ppm)	Limit (ppm)
-30	3.7	20	0.01064	PASS
-20		28	0.01489	PASS
-10		17	0.00904	PASS
0		17	0.00904	PASS
10		16	0.00851	PASS
20		17	0.00904	PASS
30		17	0.00904	PASS
40		20	0.01064	PASS
50		24	0.01277	PASS
25	$V_{min}=3.5$	20	0.01064	PASS
25	$V_{max}=4.2$	20	0.01064	PASS

WCDMA Mode

Middle Channel, $f_0=1880.0$ MHz				
Temperature (°C)	Power Supplied(V_{DC})	Frequency Error(ppm)	Frequency Error(ppm)	Limit (ppm)
-30	3.7	12	0.00638	PASS
-20		11	0.00585	PASS
-10		14	0.00745	PASS
0		12	0.00638	PASS
10		10	0.00532	PASS
20		11	0.00585	PASS
30		12	0.00638	PASS
40		9	0.00479	PASS
50		11	0.00585	PASS
25	$V_{min.}=3.5$	14	0.00745	PASS
25	$V_{max.}=4.2$	12	0.00638	PASS

******* END OF REPORT *******