







ISO/IEC17025Accredited Lab.

Report No.: FCC 1502048
File reference No.: 2015-02-27

Applicant: Ningbo WinHi Electronics&Technology Co.,Ltd

Product: Bluetooth Audio Transmitter

Model No.: EYE-BT

Trademark: Eyezone

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: February 27, 2015

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timewaytech.com

Report No: FCC1502048 Page 2 of 79

Date: 2015-02-27



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.:899988.

IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration No.: IC 5205A-02.

Date: 2015-02-27



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	7
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT	12
6.3	EUT Operation Condition.	12
5.4	Radiated Emission Limit.	13
7.0	20dB Bandwidth Measurement.	22
8.0	Maximum Peak Output Power.	34
9.0	Carrier Frequency Separation.	37
10.0	Number of Hopping Channel	41
11.0	Time of Occupancy (Dwell Time)	45
12.0	Out of Band Measurement.	58
13.0	Antenna Requirement.	71
14.0	FCC Label.	72
15.0	Photo of Test Setup and EUT View	73

Report No: FCC1502048 Page 4 of 79

Date: 2015-02-27



1.0 General Details

Test Lab Details 1.1

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen,

Guangdong China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Ningbo WinHi Electronics&Technology Co.,Ltd

Address: 529# West Mingzhou Rd, Beilun District, Ningbo, China

Telephone: 0574-86818895 Fax: 0574-86818895

1.3 Description of EUT

Product: Bluetooth Audio Transmitter

Manufacturer: Ningbo WinHi Electronics&Technology Co.,Ltd

Address: 529# West Mingzhou Rd, Beilun District, Ningbo, China

Model Number: EYE-BT Additional Model Number: N/A Brand Name: Eyezone

Additional Brand Name: N/A

Type of Modulation GFSK, Л/4DQPSK, 8DPSK

2402-2480MHz Frequency range

Number of Channel 79

Frequency Selection By software

Antenna type PCB Antenna used, the antenna gain is 0dBi

1.4 Submitted Sample: 1 Sample

The report refers only to the sample tested and does not apply to the bulk.

Report No: FCC1502048 Page 5 of 79

Date: 2015-02-27



1.5 Test Duration:

2015-02-10 to 2015-02-27

1.6 Test Uncertainty

> Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer Terry (ang

The sample tested by

Print Name: Terry Tang

Page 6 of 79 Report No: FCC1502048

Date: 2015-02-27



2.0 Test Equipments					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2014-08-21	2015-08-20
TWO Line-V-NETW	R&S	EZH3-Z5	100294	2014-08-22	2015-08-21
TWO Line-V-NETW	R&S	EZH3-Z5	100253	2014-08-22	2015-08-21
Ultra Broadband ANT	R&S	HL562	100157	2014-08-23	2015-08-22
ESDV Test Receiver	R&S	ESDV	100008	2014-08-22	2015-08-21
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2014-08-21	2015-08-20
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXLO*	-	-
Loop Antenna	EMCO	6502	00042960	2014-08-22	2015-08-21
ESPI Test Receiver	R&S	ESI26	838786/013	2014-08-22	2015-08-21
3m OATS			N/A	2014-08-21	2015-08-20
Horn Antenna	R&S	BBHA 9170	BBHA9170265	2014-08-23	2015-08-22
Horn Antenna	R&S	BBHA 9120D	9120D-631	2014-08-23	2015-08-22
Power meter	Anritsu	ML2487A	6K00003613	2014-08-22	2015-08-21
Power sensor	Anritsu	MA2491A	32263	2014-08-22	2015-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2014-08-23	2015-08-22
LISN	AFJ	LS16C	10010947251	2014-08-21	2015-08-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2014-08-22	2015-08-21
9*6*6 Anechoic			N/A	2014-08-21	2015-08-20
EMI Test Receiver	RS	ESCS30	100139	2014-08-22	2015-08-21

Report No: FCC1502048 Page 7 of 79

Date: 2015-02-27



3.0 **Technical Details**

3.1 **Summary of test results**

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies
Spurious Emission, Band Edge, and	15.247(d),15.205(a),	PASS	Complies
Restricted bands	15.209 (a),15.109		
Conducted Emissions	15.207(a), 15.107	PASS	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 **EUT Modification**

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Report No: FCC1502048 Page 8 of 79

Date: 2015-02-27



5. **Power Line Conducted Emission Test**

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 -2009.

Test Voltage: 120V~60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

79 channels are provided to the EUT

Date: 2015-02-27



EUT

Device	Manufacturer	Model	FCC ID
Bluetooth Audio Transmitter	Ningbo WinHi Electronics&Technology Co.,Ltd	EYE-BT	2AECVEYE-BT-00001

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
Power	GME	GFP101U-050200-Q	VOC	
Supply				
Mobile	NOKIA	610	QTLRM-835	

5.4 **EUT Operating Condition**

Operating condition is according to ANSI C63.10 -2013.

- Α Setup the EUT and simulators as shown on follow
- В Enable AF signal and confirm EUT active to normal condition

Power line conducted Emission Limit according to Paragraph 15.107,15.207 5.5

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

The report refers only to the sample tested and does not apply to the bulk.

Date: 2015-02-27



Conducted Emission on Live Terminal (150kHz to 30MHz) A:

EUT Operating Environment


Humidity: 65%RH Temperature: 26°C Atmospheric Pressure: 101 kPa

EUT set Condition: Charging and Keep Bluetooth Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level		Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBu∀	dBuV	dB	Detector	Comment
1 *	0.8900	21.30	11.78	33.08	56.00	-22.92	QP	
2	0.8900	1.20	11.78	12.98	46.00	-33.02	AVG	

Date: 2015-02-27



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging and Keep Bluetooth Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No. Mk.	Freq.			Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.8768	21.40	11.77	33.17	56.00	-22.83	QP	
2	0.8768	-2.60	11.77	9.17	46.00	-36.83	AVG	

Report No: FCC1502048 Page 12 of 79

Date: 2015-02-27



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10 –2013. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre -Amplifier Furn-table Receiver

- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No: FCC1502048 Page 13 of 79

Date: 2015-02-27



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.109. 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. After pre-scanning, GFSK was the worse case. The test data of this mode was recorded.

Page 14 of 79 Report No: FCC1502048

Date: 2015-02-27



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/ In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Bluetooth Transmitting

Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
878.040	36.43	Н	46.00
30.120	29.15	Н	40.00
873.680	34.01	V	46.00
30.080	29.46	V	40.00


Page 15 of 79

Report No: FCC1502048

Date: 2015-02-27



Test Figure:



10.FEB.2015 17:03:51 Date:


Page 16 of 79

Report No: FCC1502048

Date: 2015-02-27



Test Figure:



10.FEB.2015 17:06:18 Date:

Report No: FCC1502048 Page 17 of 79

Date: 2015-02-27



Operation Mode: Transmitting under Low Channel (2402MHz)

	ů.		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4804		Н	74(Peak)/ 54(AV)
4804		V	74(Peak)/ 54(AV)
7206		H/V	74(Peak)/ 54(AV)
9608		H/V	74(Peak)/ 54(AV)
12010		H/V	74(Peak)/ 54(AV)
14412		H/V	74(Peak)/ 54(AV)
16814		H/V	74(Peak)/ 54(AV)
19216		H/V	74(Peak)/ 54(AV)
21618		H/V	74(Peak)/ 54(AV)
24020		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Operation Mode: Transmitting g under Middle Channel (2441MHz)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)	
4882		Н	74(Peak)/ 54(AV)	
4882		V	74(Peak)/ 54(AV)	
7323		H/V	74(Peak)/ 54(AV)	
9764		H/V	74(Peak)/ 54(AV)	
12205		H/V	74(Peak)/ 54(AV)	
14646		H/V	74(Peak)/ 54(AV)	
17087		H/V	74(Peak)/ 54(AV)	
19528		H/V	74(Peak)/ 54(AV)	
21969		H/V	74(Peak)/ 54(AV)	
24410		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Report No: FCC1502048 Page 18 of 79

Date: 2015-02-27



Operation Mode: Transmitting under High Channel (2480MHz)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
4960	-	Н	74(Peak)/ 54(AV)
4960	-	V	74(Peak)/ 54(AV)
7440		H/V	74(Peak)/ 54(AV)
9920		H/V	74(Peak)/ 54(AV)
12400		H/V	74(Peak)/ 54(AV)
14880		H/V	74(Peak)/ 54(AV)
17360		H/V	74(Peak)/ 54(AV)
19840		H/V	74(Peak)/ 54(AV)
22320		H/V	74(Peak)/ 54(AV)
24800		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


^{2.} Remark "---" means that the emissions level is too low to be measured

Date: 2015-02-27




Please refer to the following test plots for details:

Low Channel: Horizontal



Low Channel: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Date: 2015-02-27



Middle Channel: Horizontal



Middle Channel: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Date: 2015-02-27



High Channel: Horizontal



High Channel: Vertical



Note: for the radiated emissions above 18G, it is the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No: FCC1502048 Page 22 of 79

Date: 2015-02-27



7.0 20dB Bandwidth Measurement

7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.2 Limits of 20dB Bandwidth Measurement

N/A

7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =3MHz, RBW =30 kHz, VBW=100 kHz, Sweep = auto Detector function = peak, Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

7.4 Test Result

Type of Modulation: GFSK

Type of Modulation. Of Six								
EUT	Bluetooth Audio		dio Transmitter Model			EYE-BT		
Mode	;	Keep Tra	nsmitting	Input Volta	put Voltage		120V~	
Tempera	ture	24 de	eg. C,	Humidity	7		56% RH	
Channel	Cha	Channel Frequency (MHz) 20 dB Bandwidth (kHz)		Ma	Maximum Limit (kHz) Pass/ Fail			
Low		2402	871.7	74			Pass	
Middle		2441	853.7	71			Pass	
High		2480	853.7	71			Pass	


Report No: FCC1502048 Page 23 of 79

Date: 2015-02-27



Test Figure:

1. Condition: Low Channel




12.FEB.2015 14:15:37 Date:

Report No: FCC1502048 Page 24 of 79

Date: 2015-02-27



2. Condition: Middle Channel




12.FEB.2015 14:14:03 Date:

Report No: FCC1502048 Page 25 of 79

Date: 2015-02-27



3. High Channel



12.FEB.2015 14:12:21 Date:

Report No: FCC1502048 Page 26 of 79

Date: 2015-02-27



Test Result

Type of Modulation: Л/4DQPSK

EUT	Π Bluetooth Audio Transmitter Model		EYE-BT						
Mode	;	Keep Tran	nsmitting	Input Voltage	ge		Itage 120V~		120V~
Temperat	ture	24 de	g. C,	Humidity		4	66% RH		
Channel	Cha	nnel Frequency (MHz)		dB Bandwidth (kHz)		Maximum Limit (kHz)	Pass/ Fail		
Low		2402	121	214.43			Pass		
Middle		2441	121	4.43			Pass		
High		2480	122	0.44	4		Pass		


Report No: FCC1502048 Page 27 of 79

Date: 2015-02-27



Test Figure:

1. Condition: Low Channel




12.FEB.2015 14:16:36 Date:

Report No: FCC1502048 Page 28 of 79

Date: 2015-02-27



2. Condition: Middle Channel




12.FEB.2015 14:18:10 Date:

Report No: FCC1502048 Page 29 of 79

Date: 2015-02-27



3. High Channel



12.FEB.2015 14:20:05 Date:

Page 30 of 79 Report No: FCC1502048

Date: 2015-02-27



Test Result

Type of Modulation: 8DPSK

EUT		Bluetooth Audio Transmitter		Model		EYE-BT	
Mode	ode Keep Transmitting Input Voltage		nge 120V~		120V~		
Temperar	ture	24 deş	24 deg. C, Humidity		56% RH		
Channel	Cha	nnel Frequency (MHz)	20 dB Bandwidth (kHz)		Ma	aximum Limit (kHz)	Pass/ Fail
Low		2402	02 121		4.43		Pass
Middle		2441	121	4.43			Pass
High		2480	121	1214.43			Pass


Report No: FCC1502048 Page 31 of 79

Date: 2015-02-27



Test Figure:

1. Condition: Low Channel




12.FEB.2015 14:26:17 Date:

Report No: FCC1502048 Page 32 of 79

Date: 2015-02-27



2. Condition: Middle Channel




12.FEB.2015 14:23:55 Date:

Report No: FCC1502048 Page 33 of 79

Date: 2015-02-27



3. High Channel



12.FEB.2015 14:27:57 Date:

Date: 2015-02-27



Page 34 of 79

8. Maximum Peak Output Power

8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW =10MHz, RBW=3MHz; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 35 of 79

Report No: FCC1502048

Date: 2015-02-27



8.4Test Results

Type of Modulation: GFSK

EUT		Bluetooth Audio Transmitter		Model		EYE-BT		
Mode		Keep Transmitting Input Voltage		Input Voltage		smitting Input Voltage 120		120V~
Temperatu	re	24 deg	. C,	Humidity			56% RH	
Channel	Ch	annel Frequency (MHz)	Peak Power	Output (dBm)	Peak Power Limit (dBm)		Pass/ Fail	
Low		2402	0.11			30	Pass	
Middle		2441	0.52		30		Pass	
High		2480	0.81			30	Pass	

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Type of Modulation: √1/4DQPSK

EUT	UT Bluetooth Audio Transmitter Mode.		Model		EYE-BT				
Mode		Keep Trans	Keep Transmitting Input Voltage		ansmitting Input Voltage 120V		smitting Input Voltage		120V~
Temperatu	ıre	24 deg	. C,	Humidity	56% RH		56% RH		
Channel	Channel Frequency (MHz) Peak Power		Output (dBm)	Peak Power Limit (dBm)		Pass/ Fail			
Low		2402 -		1.05		Pass			
Middle		2441	2441		30		Pass		
High		2480	-(-0.27		30	Pass		

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Report No: FCC1502048 Page 36 of 79

Date: 2015-02-27



Type of Modulation: 8DPSK

EUT		Bluetooth Audio Transmitter		Model		EYE-BT	
Mode	Mode Keep Transmitting Input Vo		Input Vol	age 120V~		120V~	
Temperatur	re	24 deg	. C,	Humidi	ty	56% RH	
Channel	Channel Frequency (MHz) Peak Power Output		Output (dBm)	Peak Power Limit (dBm)		Pass/ Fail	
Low		2402	-0.79		30		Pass
Middle		2441	-0.39		30		Pass
High		2480	-0.10			30	Pass

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Date: 2015-02-27



Page 37 of 79

9. Carrier Frequency Separation

9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.2 Limits of Carrier Frequency Separation

The Maximum Power Spectral Density Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) \geq 1% of the span; Video (or Average) Bandwidth (VBW) \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Date: 2015-02-27




9.4Test Result

Type of Modulation: GFSK

EUT	Bluetooth Audio Transmitter		Model		EYE-BT
Mode	Hopping On		Input Voltage	120V~	
Temperature	24 deg. C,		Humidity		56% RH
Carrier I	Frequency Separation	Limit			Pass/ Fail
	1000kHz	≥ 25	kHz or 2/3 of 20 dB b	andwidth	Pass

Test Plots



12.FEB.2015 11:41:34

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 39 of 79

Report No: FCC1502048


Date: 2015-02-27



Type of Modulation: Л/4DQPSK

EUT	Bluetooth Audio Transmitter		Model	EYE-BT	
Mode	Hopping On		Input Voltage	120V~	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation			Limit		Pass/ Fail
1000 kHz			5 kHz or 2/3 of 20 dB	bandwidth	Pass

Test Plots



Date: 12.FEB.2015 11:23:01

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No: FCC1502048 Page 40 of 79


Date: 2015-02-27



Type of Modulation: 8DPSK

EUT	Bluetooth Audio Transmitter		Model	Е	YE-BT
Mode	Hopping On		Input Voltage	120V~	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation			Limit		Pass/ Fail
1000 kHz		≥	25 kHz or 2/3 of 20	Pass	

Test Plots



Date: 12.FEB.2015 11:14:27

Date: 2015-02-27



Page 41 of 79

10. Number of Hopping Channels

10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

10.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=100 kHz, VBW= 300 kHz;

Sweep = auto; Detector function = peak; Trace = max hold

3. Record the number of hopping channels.

Date: 2015-02-27




10.4Test Result

Type of Modulation: GFSK

EUT	Bluetooth Audio Transmitter			Model		EYE-BT	
Mode		Hopping On		Input Voltage		120V~	
Temperature		24 deg. C,		Humidity		56% RH	
Operating Frequency		Number of hopping channels		Limit		Pass/ Fail	
2402-2480MHz		79		≥ 15		Pass	

Test Plot



12.FEB.2015 10:54:59

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No: FCC1502048 Page 43 of 79


Date: 2015-02-27



Type of Modulation: Л/4DQPSK

EUT	Bluetooth Audio Transmitter		ooth Audio Transmitter Model		EYE-BT
Mode	Hopping On		Input Voltage		120V~
Temperature	24 deg. C,		Humidity		56% RH
Operating Frequency		Number of hopping channels		Limit	Pass/ Fail
2402-2480MHz		79		≥ 15	Pass

Test Plot



12.FEB.2015 Date: 10:59:48

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-02-27



Page 45 of 79

11. Time of Occupancy (Dwell Time)

11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Report No: FCC1502048 Page 46 of 79

Date: 2015-02-27



11.4 Test Result

Type of Modulation: GFSK

EUT	Bluetooth Audio	Transmitter	Model		EYE-BT
Mode	Keep Trans	smitting	Input V	oltage	120V~
Temperature	e 24 deg	. C,	Humid	ity	56% RH
Channel	Reading	Hoping Rate		Actual	Limit
Low	2.95ms	266.667 hc	p/s	0.315s	0.4s
Middle	2.99ms	266.667 hc	266.667 hop/s		0.4s
High	2.99ms	266.667 hc	p/s	0.319s	0.4s

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 was the worse case


Page 47 of 79

Report No: FCC1502048

Date: 2015-02-27



Test Plots: Low Channel:




Date: 12.FEB.2015 14:37:05 Report No: FCC1502048 Page 48 of 79

Date: 2015-02-27



Middle Channel:




12.FEB.2015 14:37:46 Date:

Page 49 of 79 Report No: FCC1502048

Date: 2015-02-27



High Channel



12.FEB.2015 14:38:37 Date:

Report No: FCC1502048 Page 50 of 79

Date: 2015-02-27



Test Result

Type of Modulation: Л/4DQPSK

EUT	Bluetooth Audio	Transmitter Model		odel	EYE-BT		
Mode	Keep Trans	smitting	Input Voltage		120V~		
Temperature	e 24 deg	. C,	Humidity		Humidity 56% RH		56% RH
Channel	Reading	Hoping Rate		Actual	Limit		
Low	2.97ms	266.667 ho	p/s	0.317s	0.4s		
Middle	2.99ms	266.667 hc	266.667 hop/s		0.4s		
High	2.97ms	266.667 hc	p/s	0.317s	0.4s		

Actual = Reading \times (Hopping rate / Number of channels) \times Test period, Test period = 0.4 [seconds / channel] \times 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 was the worse case


Page 51 of 79

Report No: FCC1502048

Date: 2015-02-27



Test Plots: Low Channel:




12.FEB.2015 14:41:02 Date:

Report No: FCC1502048 Page 52 of 79

Date: 2015-02-27



Middle Channel:




12.FEB.2015 14:39:59 Date:

Page 53 of 79 Report No: FCC1502048

Date: 2015-02-27



High Channel



12.FEB.2015 14:39:16 Date:

Report No: FCC1502048 Page 54 of 79

Date: 2015-02-27



Type of Modulation: 8DPSK

EUT		Bluetooth Audio	Transmitter Model		odel	EYE-BT
Mode		Keep Trans	mitting	Input Voltage		120V~
Temperature	e	24 deg.	C,	Humid	ity	56% RH
Channel		Reading	Hoping Rate		Actual	Limit
Low		2.97ms	266.667 ho	p/s	0.317s	0.4s
Middle		3.01ms	266.667 hop/s		0.321s	0.4s
High		3.01ms	266.667 ho	p/s	0.321s	0.4s

Actual = Reading × (Hopping rate / Number of channels) × Test period, Test period = 0.4 [seconds / channel] × 79 [channel] = 31.6 [seconds] NOTE: The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. Then the EUT makes worst case 266.667 hops per second with 79 channels.

Note: DH5 was the worse case


Page 55 of 79

Report No: FCC1502048

Date: 2015-02-27



Test Plots: Low Channel:




12.FEB.2015 14:41:44 Date:

Report No: FCC1502048 Page 56 of 79

Date: 2015-02-27



Middle Channel:




12.FEB.2015 14:42:52 Date:

Page 57 of 79 Report No: FCC1502048

Date: 2015-02-27



High Channel



12.FEB.2015 14:43:28 Date:


Report No: FCC1502048 Page 58 of 79

Date: 2015-02-27



12 Out of Band Measurement

12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Page 59 of 79

Report No: FCC1502048

Date: 2015-02-27




Type of Modulation: GFSK

Out of Band Test Result

Product:	Bluetoot	h Audio Transmitter	Test Mode:	Low Channel
Mode	Keep	ing Transmitting	Input Voltage	120V~
Temperature	24 deg. C		Humidity	56% RH
Test Result:		Pass		PK
The Max. FS in	PK (dBμV/m)	35.5		74(dBμV/m)
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2390MHz				

Test Figure:



12.FEB.2015 11:56:46 Date:

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-02-27




Type of Modulation: GFSK

Out of Band Test Result

Product:	Bluetoo	th Audio Transmitter	Test Mode:	High Channel
Mode	Kee	ping Transmitting	Input Voltage	120V~
Temperature		24 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	37.1		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

Test Figure:



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-02-27




Type of Modulation: GFSK

Out of Band Test Result

Product:	Bluetoo	th Audio Transmitter	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	120V~
Temperature		24 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	36.1		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

Test Figure:



12.FEB.2015 11:43:31 Date:

Date: 2015-02-27




Type of Modulation: GFSK

Out of Band Test Result

Product:	Bluetoo	th Audio Transmitter	Test Mode:	Hopping mode
Mode		Hopping On	Input Voltage	120V~
Temperature		24 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	38.2		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

Test Figure:



Date: 12.FEB.2015 12:01:05

Date: 2015-02-27




Type of Modulation: Л/4DQPSK

Out of Band Test Result 12.4

Product:	Bluetooth Audio Transmitter		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	120V~
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 36.2			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz		(

Test Figure:



12.FEB.2015 11:54:17

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-02-27




Type of Modulation: Л/4DQPSK

Out of Band Test Result

Product:	Bluetooth Audio Transmitter		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 37.7			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

Test Figure:



12.FEB.2015 14:06:47

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-02-27




Type of Modulation: Л/4DQPSK

Out of Band Test Result

Product:	Bluetooth Audio Transmitter		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 36.0			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

Test Figure:



12.FEB.2015 11:48:00 Date:

Date: 2015-02-27




Type of Modulation: Л/4DQPSK

Out of Band Test Result

Product:	Bluetooth Audio Transmitter		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	38.5		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2483.5MHz				

Test Figure:



Date: 12.FEB.2015 13:53:55

Date: 2015-02-27




Type of Modulation: 8DPSK

Out of Band Test Result 12.4

Product:	Bluetooth Audio Transmitter		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	120V~
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 35.9			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBµV/m)
2390MHz				

Test Figure:



Date: 12.FEB.2015 11:53:15

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-02-27




Type of Modulation: 8DPSK

Out of Band Test Result 12.4

Product:	Bluetooth Audio Transmitter		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 37.6			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

Test Figure:



Date: 12.FEB.2015 14:05:45

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-02-27




Type of Modulation: 8DPSK

Out of Band Test Result

Product:	Bluetooth Audio Transmitter		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 35.8			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2390MHz				

Test Figure:



12.FEB.2015 11:51:55 Date:

Date: 2015-02-27




Type of Modulation: 8DPSK

Out of Band Test Result

Product:	Bluetooth Audio Transmitter		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m) 38.2			$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	$54(dB\mu V/m)$
2483.5MHz				

Test Figure:



Date: 12.FEB.2015 14:04:46

Date: 2015-02-27



Page 71 of 79

13.0 Antenna Requirement

13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

13.2 Antenna Connected constructions

PCB Antenna used. The maximum Gain of this antenna is 0dBi

Report No: FCC1502048 Page 72 of 79

Date: 2015-02-27




14.0 FCC ID Label

FCC ID: 2AECVEYE-BT-00001

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 73 of 79 Report No: FCC1502048

Date: 2015-02-27



15.0 **Photo of testing**

Conducted Emission Test Setup:




Date: 2015-02-27



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduct event of the report.

Date: 2015-02-27



Photographs - EUT

Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-02-27



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-02-27



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduct event of the report.

Date: 2015-02-27



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduct event of the report.

Report No: FCC1502048 Page 79 of 79

Date: 2015-02-27



Inside view



End of the report