

# FCC RADIO TEST REPORT-BT FCC ID: 2AECY-S-32

Product: Bluetooth HandsFree car kit

Trade Name: N/A

Model Name: S-32

Serial Model: N/A

Report No.: NTEK-2015NT02071226F1

# **Prepared for**

SHENZHEN SOAIY TECHNOLOGY CO.,LTD.

4F, Bldg. D, Fuxinlin Industrial Park, Hangcheng Industrial Zone, Xixiang Street, Bao'an District, Shenzhen, China

# Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn



#### TEST RESULT CERTIFICATION

Applicant's name .....: SHENZHEN SOAIY TECHNOLOGY CO.,LTD.

Address ...... 4F, Bldg. D, Fuxinlin Industrial Park, Hangcheng Industrial Zone,

Xixiang Street, Bao'an District, Shenzhen, China

Manufacture's Name.....: SHENZHEN SOAIY TECHNOLOGY CO.,LTD.

Xixiang Street, Bao'an District, Shenzhen, China

**Product description** 

Serial Model:

Product name ...... Bluetooth HandsFree car kit

Model and/or type reference : S-32

Standards ...... FCC Part15.247: 01 Oct. 2014

N/A

Test procedure ...... ANSI C63.4-2009

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date of Issue ...... 11 Mar. 2015

Test Result..... Pass

Testing Engineer: Eileen Wu.

(Eileen Liu)

Technical Manager :

(Brown Lu)

Authorized Signatory:

(Bill Yao)



# **Table of Contents**

	Page
1 . SUMMARY OF TEST RESULTS 1.1 TEST FACILITY	5 6
1.2 MEASUREMENT UNCERTAINTY	6
	7
2 . GENERAL INFORMATION	_
2.1 GENERAL DESCRIPTION OF EUT 2.2 DESCRIPTION OF TEST MODES	7
2.2 DESCRIPTION OF TEST MODES  2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9 9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING  2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	_
	_
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 3.1.2 TEST PROCEDURE	13 14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14 15
3.1.6 TEST RESULTS	15 17
3.2 RADIATED EMISSION MEASUREMENT 3.2.1 RADIATED EMISSION LIMITS	17 17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP 3.2.5 EUT OPERATING CONDITIONS	19 20
3.2.6 TEST RESULTS (BELOW 30 MHZ)	20 21
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	22
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	24
4 . NUMBER OF HOPPING CHANNEL	25
4.1 APPLIED PROCEDURES / LIMIT	25
4.1.1 TEST PROCEDURE	25
4.1.2 DEVIATION FROM STANDARD 4.1.3 TEST SETUP	25 25
4.1.4 EUT OPERATION CONDITIONS	25 25
4.1.5 TEST RESULTS	26
5 . AVERAGE TIME OF OCCUPANCY	27
5.1 APPLIED PROCEDURES / LIMIT	27



#### **Table of Contents**

	Page
5.1.1 TEST PROCEDURE 5.1.2 DEVIATION FROM STANDARD 5.1.3 TEST SETUP 5.1.4 EUT OPERATION CONDITIONS 5.1.5 TEST RESULTS	27 27 28 28 29
6 . HOPPING CHANNEL SEPARATION MEASUREMENT 6.1 APPLIED PROCEDURES / LIMIT 6.1.1 TEST PROCEDURE 6.1.2 DEVIATION FROM STANDARD 6.1.3 TEST SETUP 6.1.4 EUT OPERATION CONDITIONS 6.1.5 TEST RESULTS	35 35 35 35 35 35 36
7 . BANDWIDTH TEST  7.1 APPLIED PROCEDURES / LIMIT  7.1.1 TEST PROCEDURE  7.1.2 DEVIATION FROM STANDARD  7.1.3 TEST SETUP  7.1.4 EUT OPERATION CONDITIONS  7.1.5 TEST RESULTS	42 42 42 42 42 42 43
8 . PEAK OUTPUT POWER TEST  8.1 APPLIED PROCEDURES / LIMIT  8.1.1 TEST PROCEDURE  8.1.2 DEVIATION FROM STANDARD  8.1.3 TEST SETUP  8.1.4 EUT OPERATION CONDITIONS  8.1.5 TEST RESULTS	49 49 49 49 49 50
9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 9.1 DEVIATION FROM STANDARD 9.2 TEST SETUP 9.3 EUT OPERATION CONDITIONS 9.4 TEST RESULTS	56 56 56 56 57
10 . ANTENNA REQUIREMENT 10.1 STANDARD REQUIREMENT 10.2 EUT ANTENNA 11 . EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	65 65 65 66



# 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C				
Standard Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	PASS		
15.247(a)(1)	Hopping Channel Separation	PASS		
15.247(b)(1)	Peak Output Power	PASS		
15.247(c)	Radiated Spurious Emission	PASS		
15.247(a)(iii)	Number of Hopping Frequency	PASS		
15.247(a)(iii)	Dwell Time	PASS		
15.247(a)(1)	Bandwidth	PASS		
15.205	Band Edge Emission	PASS		
15.203	Antenna Requirement	PASS		

# NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



#### 1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

# 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $\mathbf{y} \pm \mathbf{U}$ , where expended uncertainty  $\mathbf{U}$  is based on a standard uncertainty multiplied by a coverage factor of  $\mathbf{k=2}$ , providing a level of confidence of approximately 95 %  $^{\circ}$ 

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



# 2. GENERAL INFORMATION

# 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth HandsFree car kit				
Trade Name	N/A				
Model Name	S-32	S-32			
Serial Model	N/A				
Model Difference	N/A				
	The EUT is a Bluetooth H	andsFree car kit			
	Operation Frequency:	2402~2480 MHz			
	Modulation Type:	BT(1Mbps): GFSK			
		BT EDR(2Mbps): π/4-DQPSK			
		BT EDR(3Mbps): 8-DPSK			
Product Description	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps			
	Number Of Channel	79 CH			
	Antenna Designation:	Please see Note 3.			
Channel List	Please refer to the Note 2				
Adapter	N/A				
Battery	DC 3.7V				
Connecting I/O Port(s)	Please refer to the User's	Manual			

#### Note

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

	Channel List				
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	0.5	BT Antenna



#### 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	normal link

For Conducted Emission		
Final Test Mode	Description	
Mode 4	normal link	

For Radiated Emission			
Final Test Mode	Description		
Mode 1	CH00		
Mode 2	CH39		
Mode 3	CH78		

#### Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3)The data rate was set in 3Mbps for radiated emission due to the highest RF output power.

#### 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom			
Frequency	2402 MHz 2441 MHz 2480 MHz			
Parameters(1/2/3Mbps)	DEF DEF DEF			




# 2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test

E-1 EUT

**Conducted Emission Test** 





# 2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Bluetooth HandsFree car kit	N/A	S-32	N/A	EUT
E-2	Adapter	N/A	AD1	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	120cm	

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length\_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



# 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of	Manufacturer	Type No.	Serial No.	Last	Calibrated	Calibratio
	Equipment				calibration	until	n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-101 80	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2014.07.06	2015.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2014.07.06	2015.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufactu rer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year
7	Test Cable	N/A	C01	N/A	2014.06.08	2015.06.07	1 year
8	Test Cable	N/A	C02	N/A	2014.06.08	2015.06.07	1 year
9	Test Cable	N/A	C03	N/A	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------



# 3. EMC EMISSION TEST

# 3.1 CONDUCTED EMISSION MEASUREMENT

# 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

	Class A	Class A (dBuV)		Class B (dBuV)		
FREQUENCY (MHz)	Quasi-peak	Average	Quasi-peak	Average	Standard	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR	
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR	
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR	

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

#### Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting		
Attenuation	10 dB		
Start Frequency	0.15 MHz		
Stop Frequency	30 MHz		
IF Bandwidth	9 kHz		



#### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

# 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




# 3.1.6 TEST RESULTS

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>26</b> ℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1539	48.14	9.63	57.77	65.78	-8.01	QP
0.1539	21.50	9.63	31.13	55.78	-24.65	AVG
0.1780	44.08	9.62	53.70	64.57	-10.87	QP
0.1780	20.36	9.62	29.98	54.57	-24.59	AVG
0.5060	32.78	9.77	42.55	56.00	-13.45	QP
0.5060	16.90	9.77	26.67	46.00	-19.33	AVG
1.6780	28.35	9.67	38.02	56.00	-17.98	QP
1.6780	9.81	9.67	19.48	46.00	-26.52	AVG
3.8860	27.52	9.70	37.22	56.00	-18.78	QP
3.8860	10.32	9.70	20.02	46.00	-25.98	AVG
6.8980	30.40	9.70	40.10	60.00	-19.90	QP
6.8980	15.34	9.70	25.04	50.00	-24.96	AVG

#### Remark

<sup>2.</sup> Factor = Insertion Loss + Cable Loss.



<sup>1.</sup> All readings are Quasi-Peak and Average values.




EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L1
Test Voltage :	DC 5.0V from adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1700	43.11	9.62	52.73	64.96	-12.23	QP
0.1700	19.20	9.62	28.82	54.96	-26.14	AVG
0.2140	37.13	9.63	46.76	63.04	-16.28	QP
0.2140	16.54	9.63	26.17	53.04	-26.87	AVG
0.4980	35.92	9.76	45.68	56.03	-10.35	QP
0.4980	19.79	9.76	29.55	46.03	-16.48	AVG
1.4660	29.72	9.70	39.42	56.00	-16.58	QP
1.4660	14.19	9.70	23.89	46.00	-22.11	AVG
4.9220	31.34	9.70	41.04	56.00	-14.96	QP
4.9220	15.25	9.70	24.95	46.00	-21.05	AVG
6.6779	31.94	9.70	41.64	60.00	-18.36	QP
6.6779	17.44	9.70	27.14	50.00	-22.86	AVG

## Remark:

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.





#### 3.2 RADIATED EMISSION MEASUREMENT

## 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

# LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)		
	PEAK	AVERAGE	
Above 1000	74	54	

# Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

# FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting	
Attenuation	Auto	
Start Frequency	1000 MHz	
Stop Frequency	10th carrier harmonic	
RB / VB (emission in restricted	1 MHz / 1 MHz for Dook, 1 MHz / 10Hz for Average	
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average	

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth	
30 to 1000	QP	120 kHz	300 kHz	
	Peak	1 MHz	1 MHz	
Above 1000	Peak	1 MHz	10 Hz	


## 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




# 3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





# (C) Radiated Emission Test-Up Frequency Above 1GHz



# 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



# 3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature:	<b>20</b> ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	

Freq.	Reading	Limit	Limit Margin	
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				Pass
				Pass

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =20 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.




# 3.2.7 TEST RESULTS (BETWEEN 30M - 1000 MHZ)

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	20 ℃	Relative Humidity:	48%
Pressure :	1010hPa	Test Mode:	TX
Test Voltage :	DC 3.7V		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Roman
V	47.6586	10.93	11.27	22.20	40.00	-17.80	QP
V	66.4989	17.89	6.37	24.26	40.00	-15.74	QP
V	109.0286	26.34	9.86	36.20	43.50	-7.30	QP
V	122.404	16.72	12.05	28.77	43.50	-14.73	QP
V	308.9126	20.23	14.53	34.76	46.00	-11.24	QP
V	614.2142	7.85	22.70	30.55	46.00	-15.45	QP

# Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit






Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Roman
Н	30.1053	5.24	19.37	24.61	40.00	-15.39	QP
Н	44.1200	5.72	12.21	17.93	40.00	-22.07	QP
Н	66.4989	7.22	6.37	13.59	40.00	-26.41	QP
Н	132.2205	5.93	11.78	17.71	43.50	-25.79	QP
Н	324.456	14.75	15.18	29.93	46.00	-16.07	QP
Н	779.6068	6.72	26.88	33.60	46.00	-12.40	QP

# Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit





# 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>20</b> ℃	Relative Humidity:	48%
Pressure :	1010hPa	Test Mode:	TX
Test Mode :	DC 3.7V		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remar	Commont
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	k	Comment
		Low Ch	annel (2402 MHz)-A	Above 1G			
4803.842	62.35	-3.64	58.71	74.00	-15.29	Pk	Vertical
4803.842	48.11	-3.64	44.47	54.00	-9.53	AV	Vertical
7206.183	57.84	-0.95	56.89	74.00	-17.11	Pk	Vertical
7206.183	42.56	-0.95	41.61	54.00	-12.39	AV	Vertical
4804.247	65.49	-3.64	61.85	74.00	-12.15	Pk	Horizontal
4804.247	48.77	-3.64	45.13	54.00	-8.87	AV	Horizontal
7206.502	60.06	-0.96	59.10	74.00	-14.90	Pk	Horizontal
7206.502	46.44	-0.96	45.48	54.00	-8.52	AV	Horizontal
		Mid Ch	annel (2441 MHz)-A	Above 1G		1 1	
4882.199	66.28	-3.67	62.61	74.00	-11.39	Pk	Vertical
4882.199	46.51	-3.67	42.84	54.00	-11.16	AV	Vertical
7323.401	57.46	-0.82	56.64	74.00	-17.36	Pk	Vertical
7323.401	43.61	-0.82	42.79	54.00	-11.21	AV	Vertical
4882.586	61.97	-3.67	58.30	74.00	-15.70	Pk	Horizontal
4882.586	46.10	-3.67	42.43	54.00	-11.57	AV	Horizontal
7323.317	60.07	-0.82	59.25	74.00	-14.75	Pk	Horizontal
7323.317	45.55	-0.82	44.73	54.00	-9.27	AV	Horizontal
		High Ch	annel (2480 MHz)-	Above 1G	<u> </u>	1 1	
4960.291	61.67	-3.59	58.08	74.00	-15.92	Pk	Vertical
4960.291	44.71	-3.59	41.12	54.00	-12.88	AV	Vertical
7440.376	56.34	-0.68	55.66	74.00	-18.34	Pk	Vertical
7440.376	42.10	-0.68	41.42	54.00	-12.58	AV	Vertical
4960.816	59.62	-3.59	56.03	74.00	-17.97	Pk	Horizontal
4960.816	46.58	-3.59	42.99	54.00	-11.01	AV	Horizontal
7440.508	58.73	-0.68	58.05	74.00	-15.95	Pk	Horizontal
7440.508	44.15	-0.68	43.47	54.00	-10.53	AV	Horizontal

Note: Mode 1Mbps is the worst mode.



## 4. NUMBER OF HOPPING CHANNEL

#### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting	
Attenuation	Auto	
Span Frequency	= the frequency band of operation	
RB	RBW=100kHz	
VB	VBW ≥ RBW	
Detector	Peak	
Trace	Max Hold	
Sweep Time	Auto	

#### **4.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100kHz, VBW=300kHz, Sweep time = Auto.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### **4.1.4 EUT OPERATION CONDITIONS**


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



# 4.1.5 TEST RESULTS

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode-GFSK		

Number of Hopping Channel 79





#### 5. AVERAGE TIME OF OCCUPANCY

#### 5.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS	

#### **5.1.1 TEST PROCEDURE**

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. A Period Time = (channel number)\*0.4

  - DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)
    DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)
    DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

#### **5.1.2 DEVIATION FROM STANDARD**

No deviation.


NTEK	Page 28 of 67	Report No.:NTEK-2015NT02071226F1
5.1.3 TEST SETUR	•	
EUT		SPECTRUM ANALYZER
5.1.4 EUT OPERA	TION CONDITIONS	
The EUT tested sys	stem was configured as the statements of is specified in the follows during the test	of 2.4 Unless otherwise a special ting.




#### **5.1.5 TEST RESULTS**

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH5 ,2DH5,3DH5		


Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH5	2441 MHz	2.96	0.32	0.4
2DH5	2441 MHz	2.97	0.32	0.4
3DH5	2441 MHz	2.96	0.32	0.4
















EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH3,2DH3,3DH3		

Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH3	2441 MHz	1.73	0.28	0.4
2DH3	2441 MHz	1.73	0.28	0.4
3DH3	2441 MHz	1.72	0.28	0.4














EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration	Dwell Time	Limits
		(ms)	(s)	(s)
DH1	2441 MHz	0.45	0.14	0.4
2DH1	2441 MHz	0.49	0.16	0.4
3DH1	2441 MHz	0.47	0.15	0.4











#### 6. HOPPING CHANNEL SEPARATION MEASUREMENT

#### **6.1 APPLIED PROCEDURES / LIMIT**

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	er Setting	
Attenuation	Auto	
Span Frequency	> Measurement Bandwidth or Channel Separation	
RB	30 kHz (Channel Separation)	
VB	100 kHz (Channel Separation)	
Detector Peak		
Trace Max Hold		
Sweep Time	Auto	


#### **6.1.1 TEST PROCEDURE**

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

#### **6.1.2 DEVIATION FROM STANDARD**

No deviation.

#### 6.1.3 TEST SETUP



# **6.1.4 EUT OPERATION CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.



# **6.1.5 TEST RESULTS**


EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.003	Complies
2441 MHz	1.007	Complies
2480 MHz	1.003	Complies

# Ch. Separation Limits: > 20dB bandwidth










EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		


Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.004	Complies
2441 MHz	1.000	Complies
2480 MHz	1.004	Complies

# Ch. Separation Limits: >2/3 of 20dB bandwidth





#Res BW 30 kHz



#VBW 100 kHz

Copyright 2000-2004 Agilent Technologies

Span 2.5 MHz

Sweep 2.64 ms (601 pts)


1 of 2




EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.004	Complies
2441 MHz	1.000	Complies
2480 MHz	1.004	Complies

# Ch. Separation Limits: >2/3 of 20dB bandwidth







#VBW 100 kHz

Copyright 2000-2004 Agilent Technologies



#### 7. BANDWIDTH TEST

## 7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting	
Attenuation	Auto	
Span Frequency	> Measurement Bandwidth or Channel Separation	
RB	30 kHz	
VB	100 kHz	
Detector	Peak	
Trace	Max Hold	
Sweep Time Auto		

#### 7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

## 7.1.2 DEVIATION FROM STANDARD

No deviation.

# 7.1.3 TEST SETUP



#### 7.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




## 7.1.5 TEST RESULTS

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(1Mbps)		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	875.490	PASS
2441 MHz	855.563	PASS
2480 MHz	865.785	PASS











EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78 <b>(2Mbps)</b>		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.203	PASS
2441 MHz	1.225	PASS
2480 MHz	1.223	PASS











EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(3Mbps)		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.208	PASS
2441 MHz	1.212	PASS
2480 MHz	1.213	PASS









#### 8. PEAK OUTPUT POWER TEST

## 8.1 APPLIED PROCEDURES / LIMIT

	FCC	Part15 (15.247) , Sub	part C	
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 20.96dBm	2400-2483.5	PASS

## 8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

 $VBW \geq RBW$ 

Sweep = auto

Detector function = peak

Trace = max hold

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

## 8.1.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

## **8.1.4 EUT OPERATION CONDITIONS**


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# 8.1.5 TEST RESULTS


EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3N	/lbps Mode)	

		1Mbps	
Test Channel	Frequency	Peak Output Power	LIMIT
rest orialine	(MHz)	(dBm)	(dBm)
CH00	2402	3.60	30
CH39	2441	3.51	30
CH78	2480	3.81	30
		2Mbps	
CH00	2402	2.36	20.96
CH39	2441	3.05	20.96
CH78	2480	2.94	20.96
		3Mbps	
CH00	2402	2.63	20.96
CH39	2441	3.41	20.96
CH78	2480	3.40	20.96





































# 9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **TEST PROCEDURE**

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

#### 9.1 DEVIATION FROM STANDARD

No deviation.

#### 9.2 TEST SETUP

EUT	SPECTRUM
	ANALYZER

#### 9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



# 9.4 TEST RESULTS

EUT:	Bluetooth HandsFree car kit	Model Name :	S-32
Temperature :	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH78 (1M/2M/3Mbps Mode)		

Frequency Band	Delta Peak to band emission (dBc)  > Limit (dBc)		Result		
	1Mbps Non-hopp	oing			
2400	49.11 20 Pass				
2483.5	68.63	20	Pass		
	2Mbps Non-hopp	oing			
2400	48.80	20	Pass		
2483.5	62.28	20	Pass		
3Mbps Non-hopping					
2400	48.83 20 Pass				
2483.5	60.91 20 Pass		Pass		
	1Mbps hopping				
2400	54.76	20	Pass		
2483.5	68.32 20 Pass		Pass		
	2Mbps hopping				
2400	52.13	20	Pass		
2483.5	58.95	20	Pass		
	3Mbps hopping	g			
2400	55.72	20	Pass		
2483.5	58.29	20	Pass		





# Radiated band edge:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Commont
(MHz)	(dBμV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре	Comment
		1N	/lbps Non-hopp	oing			
2390	64.88	-13.06	51.82	74	-22.18	peak	Vertical
2390	65.12	-13.06	52.06	74	-21.94	peak	Horizontal
2483.5	64.36	-12.78	51.58	74	-22.42	peak	Vertical
2483.5	61.78	-12.78	49.00	74	-25.00	peak	Horizontal
			1Mbps hoppin	g			
2390	66.13	-13.06	53.07	74	-20.93	peak	Vertical
2390	63.45	-13.06	50.39	74	-23.61	peak	Horizontal
2483.5	60.58	-12.78	47.8	74	-26.2	peak	Vertical
2483.5	59.78	-12.78	47.0	74	-27.00	peak	Horizontal
		21	Mbps Non-hopp	ing	1	1	
2390	63.00	-13.06	49.94	74	-24.06	peak	Vertical
2390	62.34	-13.06	49.28	74	-24.72	peak	Horizontal
2483.5	64.51	-12.78	51.73	74	-22.27	peak	Vertical
2483.5	60.19	-12.78	47.41	74	-26.59	peak	Horizontal
	T	ı	2Mbps hopping	)	ı	1	1
2390	61.28	-13.06	48.22	74	-25.78	peak	Vertical
2390	64.17	-13.06	51.11	74	-22.89	peak	Horizontal
2483.5	65.59	-12.78	52.81	74	-21.19	peak	Vertical
2483.5	57.08	-12.78	44.30	74	-29.70	peak	Horizontal
	Γ	31	Mbps Non-hopp	ing	ı	T	1
2390	61.41	-13.06	48.35	74	-25.65	peak	Vertical
2390	59.87	-13.06	46.81	74	-27.19	peak	Horizontal
2483.5	64.05	-12.78	51.27	74	-22.73	peak	Vertical
2483.5	66.34	-12.78	53.56	74	-20.44	peak	Horizontal
	Γ	т	3Mbps hopping	9	T	T	1
2390	62.03	-13.06	48.97	74	-25.03	peak	Vertical
2390	61.41	-13.06	48.35	74	-25.65	peak	Horizontal
2483.5	61.88	-12.78	49.10	74	-24.90	peak	Vertical
2483.5	65.74	-12.78	52.96	74	-21.04	peak	Horizontal


Note: Refer to chapter 3.2 test method, When PK value is lower than the Average value limit, average didn't record.














































NOTE: Hopping enabled and disabled have evaluated, and the wortest data was reported



# **10. ANTENNA REQUIREMENT**

## **10.1 STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

# **10.2 EUT ANTENNA**

The EUT antenna is permanent attached antenna. It comply with the standard requirer
---



# 11. EUT TEST PHOTO



