

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : Gill Electronics

Applicant Address : 725 Bond Ave. NW Grand Rapids, MI 49503

Kind of Product : Sidewinder

FCC ID : 2AEFM-WPT170AT

RF power : 1.042 dBm Peak Conducted

Antenna type : PCB antenna

Antenna Gain : 3.0 dBi

Frequency Range : 2402 MHz - 2480 MHz

Number of channels : 40 CH



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

** MPE Calculations **

No Evaluation Required if power is below this threshold. (60/f(GHz) mW)

Frequency (GHz)		mW	
Lowest	2.402	24.98	
Highest	2.480	24.19	

The MPE calculation for this exposure is shown below.

	Where, P = Conducted output power (dBm) G = Power gain of the antenna (dBi)
--	---

Measured Transmitter Output Power(Maximum: GFSK, CH 0)

Output Power(dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP (mW)
1.042	3.0	4.042	2.536

Conclusion: No SAR evaluation required since Transmitter EIRP is below FCC threshold.