



# RF EXPOSURE EVALUATION REPORT

**FCC ID** : 2AEIM-1472547  
**Equipment** : TPMS sensor  
**Brand Name** : TESLA, Inc  
**Model Name** : 1472547  
**Marketing Name** : TESLA  
**Applicant** : Tesla, Inc  
3500 Deer Creek Road, Palo Alto, California US 94304  
United States Of America  
**Manufacturer** : TESLA, Inc  
3500 Deer Creek Road, Palo Alto, California US 94304  
United States Of America  
**Standard** : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 2.1091 and it complies with applicable limit.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Ken Chen

***Sporton International (USA) Inc.***  
1175 Montague Expressway, Milpitas, CA 95035



## **Table of Contents**

<b>1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>4</b>
<b>2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS .....</b>	<b>5</b>
<b>3. RF EXPOSURE LIMIT INTRODUCTION .....</b>	<b>5</b>
<b>4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION .....</b>	<b>6</b>
4.1. Standalone Power Density Calculation .....	6



## History of this test report

Report No.	Version	Description	Issued Date
FA190911001	Rev. 01	Initial issue of report	Oct. 14, 2019

**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	TPMS sensor
Brand Name	TESLA, Inc
Model Name	1472547
Marketing Name	TESLA
FCC ID	2AEIM-1472547
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth LE
HW Version	Rev-02
SW Version	n/a
EUT Stage	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

**Reviewed by: Jason Wang**

**Report Producer: Daisy Peng**

## 2. Maximum RF average output power among production units

Band / Mode	Average Power (dBm)
	LE
	GFSK
Bluetooth	5

## 3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



## **4. Radio Frequency Radiation Exposure Evaluation**

### **4.1. Standalone Power Density Calculation**

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
Bluetooth	2402.0	3.39	5.00	8.390	0.007	6.902	0.001	1.000

**Note:** For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band

### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.