FCC 47 CFR MPE REPORT

HUIZHOU FORYOU GENERAL ELECTRONICS CO.,LTD.

RADIO ENTERTAINMENT

Model Number: 4154493C1

Additional Model: 4154492C1, 4154490C1

FCC ID: 2AEIN-4154493C1

Prepared for:	North Shangxia Road, Dongjiang Hi tech,Industry Park,Huizhou,China
	HUIZHOU FORYOU GENERAL ELECTRONICS CO.,LTD.
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1908137
Date of Test:	Aug. 13~21, 2019
Date of Report:	Aug. 24, 2019

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2，｜H｜2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm2)	Averaging Times｜E｜2，｜H｜2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.o	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

E (V/m) = $(30*P*G)^{0.5}/d$ Power Density: Pd (W/m2) = $E^2/377$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$Pd = (30*P*G) / (377*d^2)$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、**Conducted Power Result**

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power（dBm）	Antenna gain	
					(dBi)	(Linear)
GFSK	2402	2.43	1.7498	2±1	0	1
	2441	4.67	2.9309	4±1	0	1
	2480	5.42	3.4834	5±1	0	1
8-DPSK	2402	0.48	1.1169	0±1	0	1
	2441	3.03	2.0091	3±1	0	1
	2480	3.83	2.4155	3±1	0	1
BLE	2402	4.23	2.6485	4±1	0	1
	2440	5.85	3.8459	5±1	0	1
	2480	6.38	4.3451	6±1	0	1

4、**Calculated Result and Limit**

Mode	Target power（dBm）	Antenna gain		Power Density (S) (mW/cm2)	Limited of Power Density (S) (mW/cm2)	Test Result
		(dBi)	(Linear)			
GFSK	6	0	1	0.00079	1	Compiles
8-DPSK	4	0	1	0.00050	1	Compiles
BLE	7	0	1	0.00100	1	Compiles