


Rear of Unit



	Connector A				Connector B				
ı	PIN NO	Description	PIN NO	Description	PIN NO	Description	PIN NO	Description	
ı	1	BATT	6	GND	1	SPK RL+	4	NC	
ı	2	ACC	7	P.ANT	2	SPK RR+	5	NC	
ı	3	SPK FL+	8	GND	3	SPK RL-	6	SPK RR-	
	4	SPK FR+	9	SPK FL-					
ı	5	ILLUMI	10	SPK FR-					

					Connector D					
	Conne	set or (-		PIN NO	Description	PIN NO	Description		
_			-		1	CAMERA_PWR	11	NC		
IN NO	Description	PIN NO	Description		2	CAMER_GND	12	NC		
1	NC	15	NC		3	CAMERA_CVBS	13	NC		
2	NC	16	WHEEL_KEY1		4	GND	14	NC		
3	NC	17	NC		5	WHEEL_KEY2	15	NC		
4	NC	18	NC		6	NC	16	NC		
5	NC	19	NC		7	WHEEL_KEY1	17	REVERSE		
6	NC	20	NC		8	NC	18	NC		
7	NC	21	NC		9	GND	19	NC		
8	NC	22	NC		10	NC	20	NC		
9	NC	23	NC							
10	NC		CDEED							

This device complies with Part 15 of the FCC Rules. Operation

is subject to the following two conditions:

(1) This device may not cause harmful interference, and

(2) This device must accept any interference received, including interference that may cause undesired operation.

FCC ID: 2AEIN-HM4Z05A

Model: Adayo HM4Z05A

	Conne	ctor E			
PIN NO	Description	PIN NO	Description		
1	NC	22	AUX_CVBS		
2	AGND/MIC-	23	NC		
3	MIC+	24	AGND		
4	AGND	25	NC		
5	SPEED	26	NC		
6	NC	27	NC		
7	CAMERA CVBS IN	28	GND		
8	GND	29	NC		
9	AGND	30	NC		
10	LINE OUT FL	31	NC		
11	LINE OUT FR	32	GND		
12	AGND	33	USB_5V		
13	LINE OUT RL	34	USB_DM		
14	LINE OUT RR	35	GND		
15	AGND	36	USB_DP		
16	SUB OUT	37	NC		
17	CVBS_OUT	38	NC		
18	AGND	39	NC		
19	AUX_LIN	40	NC		
20	AUX_RIN	41	NC		
21	GND	42	GND		

Warnings: Warranty void if this unit is damaged due to misuse or unauthorized service attempting.

Before making any electical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Owner's Manual.

Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 45-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle. Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

This product was produced using lead free technology. Help keep the world clean! Dispose properly!

12V ⊖ GROUND === 15A max

P/N:1270720108900/A0

100.00 mm