



Software 6 User Manual

Release 6.4.5



Neratec Solutions AG

April 8, 2015

Version control

| | |
|-------------------------|--|
| Document identification | 5100.20.105 |
| Authors | schwand, gujaarm, maymatt |
| Owner | Andreas Schwarz |
| Revision hash | e75686bbc7035c50a9d285ff223786363e91bbec |

Notice

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

©2012 - 2014 by Neratec Solutions AG

Contents

| | | |
|---------------------------------------|-----------------------------|----------|
| 0.1 | Firewall | 4 |
| 0.1.1 | Port forward | 4 |
| 0.1.2 | Outbound NAT | 6 |
| MIB Reference: NERATEC-SW6-MIB | | 7 |
| 1 | Device configuration | 7 |
| 1.1 | configuration | 7 |
| 1.1.1 | cfgSystem | 7 |
| 1.1.2 | cfgSsh | 7 |
| 1.1.3 | cfgLogging | 8 |
| 1.1.4 | cfgSnmp | 10 |
| 1.1.5 | cfgDhcp | 13 |
| 1.1.6 | cfgNtp | 16 |
| 1.1.7 | cfgHttp | 17 |
| 1.1.8 | cfgUsbgadget | 17 |
| 1.1.9 | cfgNetwork | 18 |
| 1.1.10 | cfgWireless | 26 |
| 1.1.11 | cfgRouting | 54 |
| 1.1.12 | cfgIpTables | 59 |
| 1.2 | rpc | 59 |
| 1.2.1 | rpcConfiguration | 59 |
| 1.2.2 | rpcFirmware | 60 |
| 1.2.3 | rpcSystem | 61 |
| 1.2.4 | rpcCertificate | 62 |
| 1.3 | settings | 62 |
| 1.3.1 | setConfiguration | 62 |
| 1.3.2 | setWireless | 62 |
| 1.3.3 | setConfmgmtd | 66 |
| 1.3.4 | setFirmware | 67 |
| 1.3.5 | setCertificate | 67 |
| 1.4 | hardware | 68 |
| 1.4.1 | hwSystem | 68 |
| 1.4.2 | hwBaseBoard | 69 |
| 1.4.3 | hwIfaceBoard | 70 |
| 1.4.4 | hwNetwork | 72 |
| 1.4.5 | hwWireless | 73 |
| 1.5 | software | 75 |
| 1.5.1 | swFirmware | 75 |
| 1.5.2 | swBootloader | 76 |
| 1.5.3 | swSystem | 77 |
| 1.5.4 | swOperatingSystem | 78 |
| 1.5.5 | swDriver | 79 |
| 1.5.6 | swRdm | 92 |

| | |
|--|------------|
| MIB Reference: NERATEC-SW6-FIREWALL-MIB | 93 |
| 2 Device configuration | 93 |
| 2.1 firewall | 93 |
| 2.1.1 configuration | 93 |
| 2.1.2 rpc | 100 |
| 2.1.3 settings | 100 |
| 2.1.4 hardware | 100 |
| 2.1.5 software | 100 |
| Message Codes | 101 |

0.1 Firewall

The Neratec Software 6 uses the well known *netfilter* to filter or mangle network traffic. The configuration is done by the *iptables* application. Most terms are based on these software components.

To use the firewall it has to be enabled. Otherwise no feature described below will work. To enable the feature the `cfgFwEnabled` flag has to be enabled.

In the following sections you can define multiple rules. Please keep in mind that the order of the rules is important! This means the rule with the index 2 will be processed before the rule with the index 3.

0.1.1 Port forward

Port forwarding can be used to forward network traffic to another destination. This is also known as *Destination Network Address Translation (DNAT)*.

To illustrate how to configure the port forward, we setup a port forward to a web server and a database server which are common use cases. The goal is to connect from Radio Modem 1 (RM1), through the wireless link to RM2, to the web server or the database server.




Figure 1: Port forward to servers behind an NT-DT50R device

At this point we will only describe the steps to configure the port forwarding. For basic configuration please read the ?? chapter in this manual.

To forward the network traffic to the web server and the database server we add two new *rules* to the port forward rules table.

For the web server we only want to forward tcp traffic to port 443.

For the database server we want to forward tcp and udp traffic for the port range 2000 - 2100 to illustrate port ranges. In addition we want to accept traffic to the wlan from anywhere.

As first step we have to enable the firewall:

- Set `cfgFwEnabled` to 1.

To configure the port forward to the web server, the following configuration has to be done. For further description of the configuration values please read the MIB references.

1. `cfgFwNatPrtFwdEnabled.0 = 1`
2. `cfgFwNatPrtFwdInterface.0 = "wlan0"`
3. `cfgFwNatPrtFwdProtocol.0 = 2`
4. `cfgFwNatPrtFwdDestinationAddress.0 = "172.16.1.0/24"`
5. `cfgFwNatPrtFwdDestinationPortStart.0 = 443`
6. `cfgFwNatPrtFwdDestinationPortEnd.0 = -1`
7. `cfgFwNatPrtFwdRedirectDestinationAddress.0 = "192.168.1.20"`
8. `cfgFwNatPrtFwdRedirectDestinationPort.0 = 443`

To configure the port forward to the database server, the following configuration has to be done.

1. `cfgFwNatPrtFwdEnabled.1 = 1`
2. `cfgFwNatPrtFwdInterface.1 = "wlan0"`
3. `cfgFwNatPrtFwdProtocol.1 = 3`
4. `cfgFwNatPrtFwdDestinationAddress.1 = "0.0.0.0/0"`
5. `cfgFwNatPrtFwdDestinationPortStart.1 = 2000`
6. `cfgFwNatPrtFwdDestinationPortEnd.1 = 2100`
7. `cfgFwNatPrtFwdRedirectDestinationAddress.1 = "192.168.1.20"`
8. `cfgFwNatPrtFwdRedirectDestinationPort.1 = 13306`

As last step, please don't forget, apply the changes by settings `rpcCfgApply` to 1.

After this configuration you should be able to connect to your web server.

0.1.2 Outbound NAT

With the outbound NAT the Neratec DT50 can control how traffic leaving the device will be translated. It's also known as Source NAT (SNAT) and used in the most home routers to rewrite the source address to the address of the WAN interface of the router so the traffic finds the way back home.

The SNAT can be done by simple masquerade, means take the address of the network interface or by defining the source address/port.

As for the port forward we use a simple example to illustrate the functionality. In Figure 2 you see a simple setup. The goal is to connect from our laptop, through RM1 to the web interface of RM2. For this example our laptop use RM1 as default gateway and the wlan0 interface of RM1 has a dynamic address.




Figure 2: Example for outbound NAT on a NT-DT50R device

At this point we will only describe the steps to configure the outbound NAT. For basic configuration please read the ?? chapter in this manual.

There are a many possibilities to set the behaviour of the rules. For all possible configurations please see [firewall](#) in the MIB reference.

For the example we keep it simple. To configure the outbound NAT

1. `cfgFwNatOutEnabled.0 = 1`
2. `cfgFwNatOutInterface.0 = "wlan0"`
3. `cfgFwNatPrtFwdProtocol.0 = 2`

This enable the first rule, set the output interface to `wlan0` and applies to TCP traffic only. Please don't forget to apply the changes by settings `rpcCfgApply` to 1.

After this configuration you should be able to connect from the laptop to 172.16.1.20, to the web interface of RM2.

MIB Reference: NERATEC-SW6-MIB

1 Device configuration

1.1 configuration

1.1.1 cfgSystem

1.1.1.1 cfgSysHostname

☐ AP ☐ STA

The hostname of the device.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.1.1 |

1.1.1.2 cfgSysTimezone

☐ AP ☐ STA

POSIX timezone string.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.1.2 |

1.1.2 cfgSsh

1.1.2.1 cfgSshEnabled

☐ AP ☐ STA

SSH disabled or enabled.

| | |
|--------------------|------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.10.1 |

1.1.2.2 cfgSshPort

☐ AP ☐ STA

SSH port.

| | |
|---------------|------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.10.2 |

1.1.3 cfgLogging

1.1.3.1 cfgLogFile

1.1.3.1.1 cfgLogFileEnabled

☐ AP ☐ STA

Log messages to file.

| | |
|--------------------|--------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.1.1 |

1.1.3.1.2 cfgLogFileLevel

☐ AP ☐ STA

Log only messages more or equal urgent than prio N (0-7).

| | |
|--------------------|--|
| <i>Enumeration</i> | warning (4) debug (7) critical (2) alert (1) notice (5) emergency (0) error (3) info (6) |
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.1.2 |

1.1.3.1.3 cfgLogFileName

☐ AP ☐ STA

Log File.

| | |
|---------------|--------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.1.3 |

1.1.3.1.4 cfgLogFileSize

☐ AP ☐ STA

Maximum size of log buffer or log file in KB.

| | |
|---------------|--------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.1.4 |

1.1.3.2 cfgLogRemote

1.1.3.2.1 cfgLogRemoteEnabled

☐ AP ☐ STA

Log messages to file.

| | |
|--------------------|--------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.2.1 |

1.1.3.2.2 cfgLogRemoteLevel

☐ AP ☐ STA

Log only messages more or equal urgent than prio N (0-7).

| | |
|--------------------|--|
| <i>Enumeration</i> | warning (4) debug (7) critical (2) alert (1) notice (5) emergency (0) error (3) info (6) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.2.2 |

1.1.3.2.3 cfgLogRemoteProtocol

AP **STA**

Protocol to send log messages. The udp(0) protocol complies with the standard syslog protocol.

| | |
|--------------------|--------------------------------|
| <i>Enumeration</i> | tcp (1) udp (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.2.3 |

1.1.3.2.4 cfgLogRemotelp

AP **STA**

Remote IP address.

| | |
|---------------|--------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.2.4 |

1.1.3.2.5 cfgLogRemotePort

AP **STA**

Remote Port.

| | |
|---------------|--------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.11.2.5 |

1.1.4 cfgSnmp

1.1.4.1 cfgSnmpd

1.1.4.1.1 cfgSnmpdLocation

AP **STA**

SNMP System Location.

| | |
|---------------|--------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.1.1 |

1.1.4.1.2 cfgSnmpdCommunity

cfgSnmpdComAdmin

☐ AP ☐ STA

Community name for the administrator.

| | |
|---------------|------------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.1.100.1 |

cfgSnmpdComMaintainer

☐ AP ☐ STA

Community name for the maintainer.

| | |
|---------------|------------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.1.100.2 |

cfgSnmpdComMonitor

☐ AP ☐ STA

Community name for the monitor.

| | |
|---------------|------------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.1.100.3 |

cfgSnmpdContact
☐ AP ☐ STA

SNMP Contact.

| | |
|---------------|--------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.1.2 |

cfgSnmpdVersion
☐ AP ☐ STA

SNMP Version

| | |
|--------------------|--------------------------------|
| <i>Enumeration</i> | usm (1) v2c (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.1.3 |

1.1.4.2 cfgSnmpTrap**1.1.4.2.1 cfgSnmpTrapEnabled**
☐ AP ☐ STA

Enable sending of SNMP traps.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.10.1 |

1.1.4.2.2 cfgSnmpTrapVersion
☐ AP ☐ STA

SNMP version with which traps are sent.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | usm (2) v1 (0) v2c (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.10.2 |

1.1.4.2.3 cfgSnmpTrapCommunity

AP **STA**

SNMP community if SNMP v2c is used. If SNMP v3 is used the Community string is the password.

| | |
|---------------|---------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.10.3 |

1.1.4.2.4 cfgSnmpTrapDest

AP **STA**

Ip address of the trap receiver.

| | |
|---------------|---------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.12.10.4 |

1.1.5 cfgDhcp

1.1.5.1 cfgDhcpGlobal

1.1.5.1.1 cfgDhcpGlobalEnabled

Enable DHCP server functionality.

| | |
|--------------------|--------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.1.1 |

1.1.5.1.2 cfgDhcpDnsmasqTable

DHCP Dnsmasq instances.

| | |
|---------------|------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.2 |

1.1.5.1.3 cfgDhcpDnsmasqTableEntry

DHCP Dnsmasq instances.

| | |
|---------------|--------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.2.1 |

1.1.5.1.4 cfgDhcpDnsmasqIndex

Entry index of Table.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.2.1.1 |

1.1.5.1.5 cfgDhcpDnsmasqDhcpid

Dhcp ID

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 8 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.2.1.2 |

1.1.5.1.6 cfgDhcpScopeTable

DHCP instance configs.

| | |
|---------------|------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3 |

1.1.5.1.7 cfgDhcpScopeTableEntry

DHCP instance configs.

| | |
|---------------|--------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1 |

1.1.5.1.8 cfgDhcpScopeIndex

Entry index of Table.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 8 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1.1 |

1.1.5.1.9 cfgDhcpScopeld

#TODO blub

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 8 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1.2 |

1.1.5.1.10 cfgDhcpScopeInterface

#TODO (bridge, eth, vlan, wlan, alias)

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1.3 |

1.1.5.1.11 cfgDhcpScopeStart

Specifies the offset from the network address of the underlying interface to calculate the minimum address that may be leased to clients. It may be greater than 255 to span subnets.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1.4 |

1.1.5.1.12 cfgDhcpScopeLimit

Specifies the maximum allowable address that may be leased to clients, calculated as network address + 'start' + 'limit'.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1.5 |

1.1.5.1.13 cfgDhcpScopeLeasetime

Specifies the lease time of addresses handed out to clients, for example 12h or 30m.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.13.3.1.6 |

1.1.6 cfgNtp

1.1.6.1 cfgNtpEnabled

☐ AP ☐ STA

Synchronize the system time with given server.

| | |
|--------------------|------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.14.1 |

1.1.6.2 cfgNtpServer1

☐ AP ☐ STA

NTP server 1. If the IP is set to 0.0.0.0 the ntp client will just listening to broadcast packages.

| | |
|---------------|------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.14.2 |

1.1.6.3 cfgNtpServer2

☐ AP ☐ STA

NTP server 2. Used as fallback if server 1 cannot be reached.

| | |
|---------------|------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.14.3 |

1.1.7 cfgHttp

1.1.7.1 cfgHttpRedirectEnabled

AP **STA**

Configure if by default all access to the http server on port 80 shall be redirected to https. This does not disable https.

| | |
|--------------------|------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.15.4 |

1.1.8 cfgUsbgadget

1.1.8.1 cfgUsbgadgetEnabled

Enable or disable USB ethernet gadget.

| | |
|--------------------|------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.16.1 |

1.1.8.2 cfgUsbgadgetIdVendor

USB gadget vendor ID Set to Neratec Solutions AG (0x2B30 or dec_11056).

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.16.2 |

1.1.8.3 cfgUsbgadgetIdProduct

USB gadget product ID Default DT60M is 0x0001.

| | |
|---------------|------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.16.3 |

1.1.9 cfgNetwork

1.1.9.1 cfgNetEthernetTable

Ethernet Network Interfaces.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1 |

1.1.9.2 cfgNetEthernetTableEntry

Ethernet Network Interfaces.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1 |

1.1.9.3 cfgNetEthIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 2 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.1 |

1.1.9.4 cfgNetEthName

☐ AP ☐ STA

Name of the ethernet interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.2 |

1.1.9.5 cfgNetEthEnabled

☐ AP ☐ STA

Ethernet interface disabled or enabled.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.3 |

1.1.9.6 cfgNetEthIp

AP **STA**

The IPv4 address of the ethernet interface. When the device is configured as part of a bridge, the address of the interface with the lowest number is used. The priority of interfaces is: eth > vlan > wlan. Example: bridge with eth0, vlan1 and wlan0. The address configured on eth0 will be used.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.4 |

1.1.9.7 cfgNetEthNetmask

AP **STA**

The subnet mask associated with the IPv4 address of this interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.5 |

1.1.9.8 cfgNetEthProto

AP **STA**

This parameter describes which protocol is used to get the IPv4 settings for this interface.
 static(0): indicates that the address is manually configured to a specified address given by the IPv4 address parameter of this interface configuration.
 dhcp(1) indicates that an IPv4 address will be obtained by the DHCP client. In case the DHCP client is not able to get a valid IPv4 address the static IP address will be used as a fallback.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | static (0) dhcp (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.6 |

1.1.9.9 cfgNetEthBridge

AP **STA**

If set to other than -1: the interface is part of bridge: -1: none 0: br0 1: br1 X: brX

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.1.1.7 |

1.1.9.10 cfgNetWlanTable

Wlan Network Interfaces.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2 |

1.1.9.11 cfgNetWlanTableEntry

Wlan Network Interfaces.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1 |

1.1.9.12 cfgNetWlanIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.1 |

1.1.9.13 cfgNetWlanName

☐ AP ☐ STA

Name of the wireless interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.2 |

1.1.9.14 cfgNetWlanEnabled

☐ AP ☐ STA

Wireless interface disabled or enabled.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.3 |

1.1.9.15 cfgNetWlanIp

AP **STA**

The IPv4 address of the wireless interface. When the device is configured as part of a bridge, the address of the interface with the lowest number is used. The priority of interfaces is: eth > vlan > wlan. Example: bridge with eth0, vlan1 and wlan0. The address configured on eth0 will be used.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.4 |

1.1.9.16 cfgNetWlanNetmask

AP **STA**

The subnet mask associated with the IPv4 address of this interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.5 |

1.1.9.17 cfgNetWlanProto

AP **STA**

This parameter describes which protocol is used to get the IPv4 settings for this interface.
 static(0): indicates that the address is manually configured to a specified address given by the IPv4 address parameter of this interface configuration.
 dhcp(1) indicates that an IPv4 address will be obtained by the DHCP client. In case the DHCP client is not able to get a valid IPv4 address the static IP address will be used as a fallback.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | static (0) dhcp (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.6 |

1.1.9.18 cfgNetWlanBridge

AP **STA**

If set to other than -1: the interface is part of bridge: -1: none 0: br0 1: br1 X: brX

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.2.1.7 |

1.1.9.19 cfgNetVlanTable

VLAN Network Interfaces.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3 |

1.1.9.20 cfgNetVlanTableEntry

VLAN Network Interface.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1 |

1.1.9.21 cfgNetVlanIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 9 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.1 |

1.1.9.22 cfgNetVlanName

AP **STA**

Name of the VLAN interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.2 |

1.1.9.23 cfgNetVlanEnabled

AP **STA**

VLAN interface disabled or enabled.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.3 |

1.1.9.24 cfgNetVlanIp

AP **STA**

The IPv4 address of the VLAN interface. When the device is configured as part of a bridge, the address of the interface with the lowest number is used. The priority of interfaces is: eth > vlan > wlan. Example: bridge with eth0, vlan1 and wlan0. The address configured on eth0 will be used.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.4 |

1.1.9.25 cfgNetVlanNetmask

AP **STA**

The subnet mask associated with the IPv4 address of this interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.5 |

1.1.9.26 cfgNetVlanProto

AP **STA**

This parameter describes which protocol is used to get the IPv4 settings for this interface.
 static(0): indicates that the address is manually configured to a specified address given by the IPv4 address parameter of this interface configuration.
 dhcp(1) indicates that an IPv4 address will be obtained by the DHCP client. In case the DHCP client is not able to get a valid IPv4 address the static IP address will be used as a fallback.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | static (0) dhcp (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.6 |

1.1.9.27 cfgNetVlanBridge

AP **STA**

If set to other than -1: the interface is part of bridge: -1: none 0: br0 1: br1 X: brX

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.7 |

1.1.9.28 cfgNetVlanParent

AP **STA**

Name of the physical parent interface on which the VLAN resides.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.8 |

1.1.9.29 cfgNetVlanVid

AP **STA**

ID of the VLAN.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.3.1.9 |

1.1.9.30 cfgNetAliasTable

IP Aliases.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4 |

1.1.9.31 cfgNetAliasTableEntry

IP Aliases.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1 |

1.1.9.32 cfgNetAliasIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1.1 |

1.1.9.33 cfgNetAliasEnabled

☐ AP ☐ STA

Alias disabled or enabled.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1.3 |

1.1.9.34 cfgNetAliasIp

☐ AP ☐ STA

The IPv4 address of the alias. When the parent interface of the alias is configured as part of a bridge, the alias will be configured on the bridge.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1.4 |

1.1.9.35 cfgNetAliasNetmask

☐ AP ☐ STA

The subnet mask associated with the IPv4 address of this alias.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1.5 |

1.1.9.36 cfgNetAliasParent

☐ AP ☐ STA

Name of the physical parent interface on which the alias resides.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1.8 |

1.1.9.37 cfgNetAliasLabel

☐ AP ☐ STA

Label with which the alias label is set up. With a value of -1 the alias is setup without a label. Example: the parent is eth0, the label is 5. The resulting label for the alias is eth0:5

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.2.4.1.9 |

1.1.10 cfgWireless

1.1.10.1 cfgWlanDeviceTable

Wireless Hardware Modules.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1 |

1.1.10.2 cfgWlanDeviceTableEntry

Wireless Hardware Modules.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1 |

1.1.10.3 cfgWlanDevIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.1 |

1.1.10.4 cfgWlanDevDistance

AP **STA**

Maximum distance in meters a client can be away from the access point. Even though the distance is set in meters, the slot time settings change in 450m steps.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 114750 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.10 |

1.1.10.5 cfgWlanDevRtsThr

AP **STA**

Frames longer than this value require a RTS/CTS handshake. RTS/CTS is used in hidden node situations. In 11bg mode, these frames are sent in DSSS modulation at 11b data rates. Otherwise OFDM rates are used. The following settings are special 2346 - maximum value, RTS/CTS is disabled 1 - minimum value, RTS/CTS is used always

Note: It is not recommended to use RTS/CTS in AP mode.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.11 |

1.1.10.6 cfgWlanDevFragmThr

AP **STA**

Frames longer than this threshold will be fragmented. Fragmentation can be used to reduce the number of retransmissions.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.12 |

1.1.10.7 cfgWlanDevShortRetry

AP **STA**

How many times transmission of the RTS frame will be retried if there is no CTS received from the AP.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 10 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.13 |

1.1.10.8 cfgWlanDevLongRetry

AP **STA**

How many times unicast data frames will be retried if there is no ACK from the receiver.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 10 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.14 |

1.1.10.9 cfgWlanDevAntennaGain

AP **STA**

Antenna gain in dBi.If multiple antennas with different gains are connected,set the value of the antenna with the highest gain.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.15 |

1.1.10.10 cfgWlanDevTxAntenna

AP **STA**

Wireless Transmission AntennasThis is a bitmask to enable/disable the chains.Example:1(001) equal to chain 0 enabled3(011) equal to chain 0 and 1 enabled7(111) equal to chain 0, 1 and 2 enabled

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.16 |

1.1.10.11 cfgWlanDevRxAntenna

AP **STA**

Wireless Receiver AntennasThis is a bitmask to enable/disable the chains.Example:1(001) equal to chain 0 enabled3(011) equal to chain 0 and 1 enabled7(111) equal to chain 0, 1 and 2 enabled

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.17 |

1.1.10.12 cfgWlanDevPhy

AP **STA**

The map between physical device and radio.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.18 |

1.1.10.13 cfgWlanDevName

☐ AP ☐ STA

Name of the wireless device.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.2 |

1.1.10.14 cfgWlanDevRfOutput

☐ AP ☐ STA

Ability to disable transmission of RF signal.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.3 |

1.1.10.15 cfgWlanDevModulation

☐ AP ☐ STA

The modulation modes of the physical wireless device are:

g(2): This modulation mode uses OFDM data rates up to 54 MBit/s in the frequency band between 2.4 and 2.4835 GHz. It supports the 802.11g standard.

bg(3): This modulation mode uses data rates up to 54 MBit/s in the frequency band between 2.4 and 2.4835 GHz. It supports the 802.11bg standard. The modulation is either DSSS for the slower rates or OFDM for the faster ones.

a(4): Mode supports data rates up to 54 MBit/s in the 5GHz frequency band and only OFDM modulation.

n(8): Mode supports data rates up to 300 MBit/s in the 2.4GHz and 5GHz frequency band and only OFDM modulation. n-rates cannot be used alone. They have to be used together with g or a to specify which frequency band shall be used. 10(ng): for 2.4GHz 12(na): for 5GHz.

| | |
|--------------------|------------------------------------|
| <i>Enumeration</i> | g (2) a (4) na (12) bg (3) ng (10) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.4 |

1.1.10.16 cfgWlanDevBandwidth

☐ AP ☐ STA

Wireless Bandwidth Mode Specifies the Bandwidth of the Channel. 0: HT20 20MHz wide channel. 1:

HT40+ 40MHz wide channel with the side channel on the top.2: HT40- 40MHz wide channel with the side channel on the bottom.

HT40+ and HT40- may not be used on all channels. The following table shows examples of what channels may be used. The full list can be found in IEEE 802.11n Annex J. Depending on the country, not all frequencies may be available.

Examples: freq HT40+ HT40- 2.4 GHz 2412 to 2452 2432 to 2472 5 GHz 5180, 5220, 5260, etc. 5200, 5240, 5280, etc.

| | |
|--------------------|-------------------------------------|
| <i>Enumeration</i> | ht40Plus (1) ht20 (0) ht40Minus (2) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.5 |

1.1.10.17 cfgWlanDevFrequency

AP **STA**

Wireless Frequency in MHz. This field will be overridden when in STA mode and a frequency list has been specified in cfgWlanInterfaceScanList.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.6 |

1.1.10.18 cfgWlanDevPower

AP **STA**

Wireless Output Power as combined power of all chains in dBm including antenna gain. (EIRP).

Remarks:

- For a setup with two antennas the transmission power on each antenna-port

is approximately 3dB lower than combined transmission power.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 6 - 30 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.1.1.8 |

1.1.10.19 cfgWlanInterfaceTable

Wireless Virtual Interfaces.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2 |

1.1.10.20 cfgWlanInterfaceTableEntry

Wireless Virtual Interface Entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1 |

1.1.10.21 cfgWlanInterfaceIndex

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.1 |

1.1.10.22 cfgWlanInterfaceDtim

AP

This attribute shall specify the number of beacon intervals that shall elapse between transmission of Beacons frames containing a TIM element whose DTIMCount field is 0. This value is transmitted in the DTIM Period field of Beacon frames.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.10 |

1.1.10.23 cfgWlanInterfaceBitrates

AP **STA**

Fixed MCS index for 802.11n rates. Set to -1 to disable (leave on auto). Allows to enter multiple indices divided by a space which are then used in auto rate. This entry is only active when an n-rate is set in `cfgWlanDevModulation` (not g-rate or a-rate).

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.11 |

1.1.10.24 cfgWlanInterfaceBeaconInterval

AP

Time in μ s (1.024 ms) between the sending of beacon frames.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 15 - 1000 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.12 |

1.1.10.25 cfgWlanIfaceWmeParameter

Reference ID to the WME parameter table. Uses all parameters in the cfgWlanWmeTable which have as cfgWlanWmId the value set here.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.13 |

1.1.10.26 cfgWlanIfaceWmeEnabled

AP

Enables usage of the WME parameter table. When using legacy rates (a-rates and g-rates) this is optional. When using n-rates this always has to be enabled.

| | |
|--------------------|----------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.14 |

1.1.10.27 cfgWlanIfaceScanList

STA

Index to specify a frequency list with frequencies to be scanned when in STA mode. To disable set to -1

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.15 |

1.1.10.28 cfgWlanIfaceBlockedList

NOT IMPLEMENTED.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.16 |

1.1.10.29 cfgWlanIfaceUsableList

NOT IMPLEMENTED.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.17 |

1.1.10.30 cfgWlanIfaceIgnoreBroadcastSsid

AP

Send empty SSID in beacons and ignore probe request frames that do not specify the full SSID, i.e., require stations to know SSID.

| | |
|--------------------|----------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.18 |

1.1.10.31 cfgWlanIfaceMacAddrAcl

AP

Mode of the MAC access control list: 0: Accept unless deny filter. Accept every MAC unless it is on the list defined in cfgWlanAclBlackTable. 1: Deny unless accept filter. Deny every MAC unless it is on the list defined in cfgWlanAclWhiteTable. 2: Use RADIUS to accept/deny clients.

| | |
|--------------------|--|
| <i>Enumeration</i> | acceptunlessdeny (0) radius (2) denyunlessaccept (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.19 |

1.1.10.32 cfgWlanIfaceName

AP STA

Name of the virtual wireless interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.2 |

1.1.10.33 cfgWlanIfaceMaxNumSta

AP

Maximum number of allowed stations which can connect to this AP.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.20 |

1.1.10.34 cfgWlanIfaceBssid

AP

BSSID of AP. Set 00:00:00:00:00:00 to use the MAC-address stored in the flash of the wireless card itself. If this is the second virtual AP on this card it will automatically set the locally assigned bit. If there are more than 2 virtual APs on a single card this field MUST be set. Shall be in the format: 00:14:5a:02:10:42

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 17 - 17 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.21 |

1.1.10.35 cfgWlanIfaceLegacyRates

AP **STA**

Wireless legacy data rates:

- 11b: 1, 2, 5.5, 11 Mbps
- 11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

The values are interpreted as flags:

- auto(0), 1Mbps(1), 2Mbps(2), 5.5Mbps(4), 6Mbps(8), 9Mbps(16),
- 11Mbps(32), 12Mbps(64), 18Mbps(128), 24Mbps(256), 36Mbps(512),
- 48Mbps(1024), 54Mbps(2048)

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 2048 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.22 |

1.1.10.36 cfgWlanIface4addr

AP **STA**

This option allows to bridge the STA side. When used on the STA, the corresponding AP has to enable this feature as well.

| | |
|--------------------|----------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.23 |

1.1.10.37 cfgWlanIface4addrBridge

AP

Specify to which bridge connecting 4addr clients shall be added. Make sure that the bridge specified for the parent interface is not the same as the bridge for the 4addr clients, otherwise bridge-loops can and will occur. Normal usecase would be: eth0: br0 (0) eth1: br0 (0) wlan0: not bridged (-1) 4addrBridge: br0 (0)

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.24 |

1.1.10.38 cfgWlanIfaceDevice

AP **STA**

Maps the virtual wireless interface to the radio device.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | radio0 (0) radio1 (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.3 |

1.1.10.39 cfgWlanIfaceMode

Wireless Operation Mode. Allowed modes are: 0: AP 1: STA 2: MONITOR

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | ap (0) sta (1) monitor (2) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.4 |

1.1.10.40 cfgWlanIfaceSsid

AP **STA**

The Service Set Identifier (SSID) of the wireless interface is the arbitrary name of the wireless network this interface is part of.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.5 |

1.1.10.41 cfgWlanIfaceEncryption

AP **STA**

Wireless Encryption Mode. Two encryption modes are supported: open(0) and wpa2(3)

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | open (0) wpa2 (3) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.6 |

1.1.10.42 cfgWlanIfacePassword

AP **STA**

Wireless password if an encryption is in use.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 8 - 63 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.7 |

1.1.10.43 cfgWlanIfacePassiveScanning

STA

Wireless Scanning Mode: If the scanning mode is set to active(0) the station will send a probe request to detect available access points if it's allowed by the country code. If the scanning mode is set to passive(1) the station will always perform passive scanning to detect available access points.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | passive (1) active (0) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.8 |

1.1.10.44 cfgWlanIfaceBeaconMiss

STA

Number of misses on consecutive beacons before the station will disconnect from the associated access point.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.2.1.9 |

1.1.10.45 cfgWlanHandoffTable

Wireless Handoff Parameters.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3 |

1.1.10.46 cfgWlanHandoffTableEntry

Wireless Handoff Parameters Entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1 |

1.1.10.47 cfgWlanHoIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.1 |

1.1.10.48 cfgWlanHoScanRateLimitTime

STA

Time in ms (jiffy steps) in which a number of attempts to connect to an AP can be tried.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.12 |

1.1.10.49 cfgWlanHoScanRateLimitTries

STA

Number of attempts to connect to an AP before the AP is blacklisted and ignored. The AP is removed from the blacklist after `cfgWlanHoScanRateLimitTime` since the first attempt.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.13 |

1.1.10.50 cfgWlanHolfaceName

STA

Name of the virtual wireless interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.2 |

1.1.10.51 cfgWlanHoEnabled

STA

Neratec improved handoff feature.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.3 |

1.1.10.52 cfgWlanHoScanningLevel

STA

When the RSSI level of the currently connected access point drops below the value configured in this parameter, the STA will scan for a better access points on all frequencies specified by the scanlist configured in cfgWlanIfaceScanList and cfgWlanFreqTable.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 95 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.5 |

1.1.10.53 cfgWlanHoBeacons

STA

Number of beacons which have to be received from an AP before a decision about handoff is allowed. Essentially forces the STA to stay on a given AP for <cfgWlanHoBeacons * cfgWlanIfaceBeaconInterval> before doing another handoff.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 4 - 20 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.6 |

1.1.10.54 **cfgWlanHoRecovery**

STA

Recovery time [ms] after a successful handoff. During this time no further handoff will be executed.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 2000 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.3.1.7 |

1.1.10.55 **cfgWlanFreqTable**

Frequency list entry.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4 |

1.1.10.56 **cfgWlanFreqTableEntry**

Frequency list entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1 |

1.1.10.57 **cfgWlanFIndex**

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 23 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.1 |

1.1.10.58 **cfgWlanFFreq8**

AP **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.10 |

1.1.10.59 cfgWlanFFreq9

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.11 |

1.1.10.60 cfgWlanFFreq10

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.12 |

1.1.10.61 cfgWlanFFreq11

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.13 |

1.1.10.62 cfgWlanFFreq12

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.14 |

1.1.10.63 cfgWlanFFreq13**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.15 |

1.1.10.64 cfgWlanFFreq14**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.16 |

1.1.10.65 cfgWlanFFreq15**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.17 |

1.1.10.66 cfgWlanFFreq16**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.18 |

1.1.10.67 cfgWlanFFreq17**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.19 |

1.1.10.68 cfgWlanFFreq0

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.2 |

1.1.10.69 cfgWlanFFreq18

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.20 |

1.1.10.70 cfgWlanFFreq19

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.21 |

1.1.10.71 cfgWlanFFreq20

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.22 |

1.1.10.72 cfgWlanFFreq21**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.23 |

1.1.10.73 cfgWlanFFreq22**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.24 |

1.1.10.74 cfgWlanFFreq23**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.25 |

1.1.10.75 cfgWlanFFreq1**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.3 |

1.1.10.76 cfgWlanFFreq2**AP** **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.4 |

1.1.10.77 cfgWlanFFreq3

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.5 |

1.1.10.78 cfgWlanFFreq4

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.6 |

1.1.10.79 cfgWlanFFreq5

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.7 |

1.1.10.80 cfgWlanFFreq6

☐ AP ☐ STA

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.8 |

1.1.10.81 cfgWlanFFreq7

AP **STA**

Frequency, 0 is interpreted as empty.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.4.1.9 |

1.1.10.82 cfgWlanWmeTable

AP

Wireless Multimedia Extensions (WME) based on the IEEE802.11e standard. It provides basic Quality of service(QoS) features to IEEE 802.11 networks.

The levels of priority in EDCA are called accesscategories (ACs). The contention window (CW) can be setaccording to the traffic expected in each access category,with a wider window needed for categories with heaviertraffic.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5 |

1.1.10.83 cfgWlanWmeTableEntry

WME Entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1 |

1.1.10.84 cfgWlanWmeIndex

AP

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.1 |

1.1.10.85 cfgWlanWmeApAifs

AP

Arbitration inter-frame space.Is used on the AP itself.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.10 |

1.1.10.86 cfgWlanWmeApBurst

AP

Maximum length for bursting (equivalent to TxOpLimit). This value is in units of 32us. Is used on the AP itself.

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.11 |

1.1.10.87 cfgWlanWmId

AP

ID of the WME parameter table. The virtual wireless interface references to this ID.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.2 |

1.1.10.88 cfgWlanWmeAc

AP

Access Category.

| | |
|--------------------|--|
| <i>Enumeration</i> | besteffort (2) background (1) none (0) voice (4) video (3) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.3 |

1.1.10.89 cfgWlanWmeCwMin

AP

Contention window minimum in exponential form. Is used on STAs connected to this AP. \$ Real value equal to $(2^n)-1$. \$

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.4 |

1.1.10.90 cfgWlanWmeCwMax

AP

Contention window maximum in exponential form. Is used on STAs connected to this AP. \$ Real value equal to $(2^n) - 1$. \$

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.5 |

1.1.10.91 cfgWlanWmeAifs

AP

Arbitration inter-frame space. Is used on STAs connected to this AP.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 15 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.6 |

1.1.10.92 cfgWlanWmeTxOpMax

AP

A Transmit Opportunity (TXOP) is a bounded time interval during which a station can send as many frames as possible (as long as the duration of the transmissions does not extend beyond the maximum duration of the TXOP). A value of 0 indicates that a single MSDU or MMPDU in addition to a possible RTS/CTS or CTS to itself may be transmitted at any PHY rate for each TXOP. This value is in units of 32us. Is used on STAs connected to this AP.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.7 |

1.1.10.93 cfgWlanWmeApCwMin

AP

Contention window minimum. Allowed values: (1, 3, 7, 15, 31, 63, 127, 255, 511, 1023). Is used on the AP itself.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 1023 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.8 |

1.1.10.94 cfgWlanWmeApCwMax

AP

Contention window maximum. Allowed values: (1, 3, 7, 15, 31, 63, 127, 255, 511, 1023) cwMax has to be more than or equal to cwMin. Is used on the AP itself.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 1 - 1023 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.5.1.9 |

1.1.10.95 cfgWlanDbgTable

Wireless Handoff Debug Parameters.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6 |

1.1.10.96 cfgWlanDbgTableEntry

Wireless Handoff Debug Parameters Entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1 |

1.1.10.97 cfgWlanDbgIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.1 |

1.1.10.98 cfgWlanDbgRatelimit

STA

Persistent default value to enable/disable the rate limiter messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|----------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.10 |

1.1.10.99 cfgWlanDbglfaceName

Name of the virtual wireless interface.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.2 |

1.1.10.100 cfgWlanDbgHandoff

STA

Persistent default value to enable/disable the handoff messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.3 |

1.1.10.101 cfgWlanDbgScan

STA

Persistent default value to enable/disable the scan messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.4 |

1.1.10.102 cfgWlanDbgMlme

STA

Persistent default value to enable/disable the MLME messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.5 |

1.1.10.103 cfgWlanDbgEvents

STA

Persistent default value to enable/disable the events messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.6 |

1.1.10.104 cfgWlanDbgBeacontrssi

STA

Persistent default value to enable/disable the beacon RSSI messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.7 |

1.1.10.105 cfgWlanDbgAckrssi

STA

Persistent default value to enable/disable the ACK RSSI messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.8 |

1.1.10.106 cfgWlanDbgBeaconfiltered

STA

Persistent default value to enable/disable the beacon filtered RSSI messages in syslog. These log messages are subject to change. DO NOT PARSE!

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.6.1.9 |

1.1.10.107 cfgWlanAclWhiteTable

Wireless MAC Access Control Whitelist

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7 |

1.1.10.108 cfgWlanAclWhiteTableEntry

Wireless MAC Access Control Whitelist Entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7.1 |

1.1.10.109 cfgWlanAclWhiteIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 63 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7.1.1 |

1.1.10.110 cfgWlanAclWhiteEnabled

AP

Enable this entry in the ACL.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7.1.2 |

1.1.10.111 cfgWlanAclWhiteInterface

AP

Name of the virtual wireless interface on which this entry is active.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7.1.3 |

1.1.10.112 cfgWlanAclWhiteAddr

AP

MAC address in the ACL. Shall be in the format: 00:14:5a:02:10:42

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 17 - 17 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7.1.4 |

1.1.10.113 cfgWlanAclWhiteMask

AP

Mask of the MAC address to be able to specify ranges of MAC addresses. To be used like CIDR notation of IP addresses.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 48 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.7.1.5 |

1.1.10.114 cfgWlanAclBlackTable

Wireless MAC Access Control Blacklist.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8 |

1.1.10.115 cfgWlanAclBlackTableEntry

Wireless MAC Access Control Blacklist Entry.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8.1 |

1.1.10.116 cfgWlanAclBlackIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 63 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8.1.1 |

1.1.10.117 cfgWlanAclBlackEnabled

AP

Enable this entry in the ACL.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8.1.2 |

1.1.10.118 cfgWlanAclBlackInterface

AP

Name of the virtual wireless interface on which this entry is active.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8.1.3 |

1.1.10.119 cfgWlanAclBlackAddr

AP

MAC address in the ACL. Shall be in the format: 00:14:5a:02:10:42

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 17 - 17 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8.1.4 |

1.1.10.120 cfgWlanAclBlackMask

AP

Mask of the MAC address to be able to specify ranges of MAC addresses. To be used like CIDR notation of IP addresses.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 48 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.8.1.5 |

1.1.10.121 cfgWlanGlobal

1.1.10.121.1 cfgWlanGlbCountry

AP STA

Wireless Country Code.

| | |
|---------------|-------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.3.9.1 |

1.1.11 cfgRouting

1.1.11.1 cfgRouteDefault

1.1.11.1.1 cfgRouteDefGateway

AP **STA**

The default gateway defines the node on an IP network that serves as a router for any other network which is not defined in the routing table.

| | |
|---------------|-------------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.1.1 |

1.1.11.1.2 cfgRouteDefGwOverride

AP **STA**

Override a previously via DHCP received default gateway with the value in cfgRouteDefGateway. If this is disabled and a default gateway already exists it will not be changed.

| | |
|--------------------|-------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.1.2 |

1.1.11.1.3 cfgRouteTable

AP **STA**

Static Routes

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2 |

1.1.11.1.4 cfgRouteTableEntry

AP **STA**

Static Route.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1 |

1.1.11.1.5 cfgRouteTableIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 265 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.1 |

1.1.11.1.6 cfgRouteTableEnabled

AP **STA**

Enable/Disable this route entry.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.2 |

1.1.11.1.7 cfgRouteTableDestination

AP **STA**

Destination network ID.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.3 |

1.1.11.1.8 cfgRouteTableNetmask

AP **STA**

Netmask of destination network.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.4 |

1.1.11.1.9 cfgRouteTableGateway

AP **STA**

Gateway to destination network.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.5 |

1.1.11.1.10 cfgRouteTableSource

AP **STA**

Source for traffic to destination network.(optional, use only if you have multiple possible source with aliases).

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.6 |

1.1.11.1.11 cfgRouteTableProto

AP **STA**

Specifies what kind of route is added.The types are defined in /etc/iproute2/rt_protosBy default we use proto 4 - staticIf anything besides 4, or the range 17-245 is used,make sure to update the removeRoutes function in /etc/init.d/routing

Reserved protocols:

- 0 unspec
- 1 redirect
- 2 kernel
- 3 boot
- 4 static
- 8 gated
- 9 ra
- 10 mrt
- 11 zebra

- 12 bird
- 13 dnroued
- 14 xorp
- 15 ntk
- 16 dhcp

Used by me for gated:

- 254 gated/aggr
- 253 gated/bgp
- 252 gated/ospf
- 251 gated/ospfase
- 250 gated/rip
- 249 gated/static
- 248 gated/conn
- 247 gated/inet
- 246 gated/default

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.2.1.7 |

1.1.11.1.12 **cfgMRouteTable**

Static Multicast Routes.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3 |

1.1.11.1.13 **cfgMRouteTableEntry**

Static Mulicast Routes.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1 |

1.1.11.1.14 cfgMRouteTableIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 9 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1.1 |

1.1.11.1.15 cfgMRouteTableEnabled

AP **STA**

Enable/Disable this multicast route entry.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1.2 |

1.1.11.1.16 cfgMRouteTableInput

AP **STA**

Input interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1.3 |

1.1.11.1.17 cfgMRouteTableSource

AP **STA**

Unicast source address to listen for.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1.4 |

1.1.11.1.18 cfgMRouteTableGroup

AP **STA**

Multicast group to forward.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1.5 |

1.1.11.1.19 cfgMRouteTableOutput

AP **STA**

Output interface(s). Can be a list of interface names.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.1.4.3.1.6 |

1.1.12 cfgIpTables

1.2 rpc

1.2.1 rpcConfiguration

1.2.1.1 rpcCfgRevert

AP **STA**

In case there are any changes in the configuration section, which are not applied yet, they can be all reverted by writing all(1) to this parameter.

Reading this parameter will indicate the status of the last rpc. If the value is less than 0 an error occurred. A value of 0 is reported when the revert process was successful.

| | |
|--------------------|-----------------------------|
| <i>Enumeration</i> | all (1) nop (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.3.1.1 |

1.2.1.2 rpcCfgApply

AP **STA**

All changes to any parameter in the configuration section have to be applied before they come into operation. To apply all new parameters to the device, set this parameter to all(1).

Reading this parameter will show the status of the apply process. A value less than 0 indicates that there occurred an error during the last apply process, nop(0) means no operation and points out that there is no apply process in operation and no error has occurred. In case the return value is all(1) the apply process is still running.

| | |
|--------------------|-----------------------------|
| <i>Enumeration</i> | all (1) nop (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Obj</i> | 1.3.6.1.4.1.41524.1.1.3.1.2 |

1.2.1.3 rpcCfgReset

AP **STA**

Reset configuration to default values.

| | |
|--------------------|-----------------------------|
| <i>Enumeration</i> | all (1) nop (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Obj</i> | 1.3.6.1.4.1.41524.1.1.3.1.3 |

1.2.1.4 rpcCfgFile

AP **STA**

Export or import a configuration to or from a file respectively. Please refer to setCfgFileUrl for more information on how to set the configuration file.

| | |
|--------------------|-------------------------------|
| <i>Enumeration</i> | export (1) import (2) nop (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Obj</i> | 1.3.6.1.4.1.41524.1.1.3.1.4 |

1.2.2 rpcFirmware

1.2.2.1 rpcFwFlash

AP **STA**

To flash a new firmware to the device define a valid URL that is accessible by the device. Change the firmware URL parameter setFwFileUrl in the settings section, if needed.

Writing flash(2) to this parameter will download and validate the new firmware file. When the downloaded file is considered as a valid firmware for this device, it will be flashed to the filesystem of the

device.

Reading this parameter will report the status of the firmware flashprocess. A value of flash_error(-2) points out that the flashprocess failed during the writing of the firmware file to the filesystem. A return value of download_error(-1) indicates an error while the firmware was downloaded or validated. A value of flash(2) means that the device is writing the firmware to the file system.

| | |
|--------------------|---|
| <i>Enumeration</i> | flash (2) flashError (-2) nop (0) download (1) downloadError (-1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Obj</i> | 1.3.6.1.4.1.41524.1.1.3.2.1 |

1.2.3 rpcSystem

1.2.3.1 rpcSysReboot

AP **STA**

Reboot system after n seconds.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Obj</i> | 1.3.6.1.4.1.41524.1.1.3.3.1 |

1.2.3.2 rpcSysFactoryReset

AP **STA**

Perform a factory reset. All settings are reset to the factory settings. NOTE: You will not be able to communicate with the device until the factory reset has finished and the device has booted again.

| | |
|--------------------|-----------------------------|
| <i>Enumeration</i> | reset (1) nop (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Obj</i> | 1.3.6.1.4.1.41524.1.1.3.3.2 |

1.2.3.3 rpcSysErrorReset

AP **STA**

Writing reset(1) to this parameter will reset all logged warning and errors of the system. It will also reset the LED settings to be normal operating states

Reading this parameter will report the status of the system. A value error(-2) indicates that a serious error appears during running the device. A value warning(-1) indicates a behavior that should have been cared about. The value nop(0) means no warning or error was reported.

| | |
|--------------------|---|
| <i>Enumeration</i> | warning (-1) reset (1) error (-2) nop (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.3.3.3 |

1.2.4 rpcCertificate

1.2.4.1 rpcCrtFile

AP **STA**

Import or export a HTTPS certification/key to or from a file respectively. Please refer to setCrtFileUrl for more information on how to set the certification/key file URL.

| | |
|--------------------|----------------------------------|
| <i>Enumeration</i> | import (1) delete (0) export (2) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.3.4.1 |

1.3 settings

1.3.1 setConfiguration

1.3.1.1 setCfgFileUrl

AP **STA**

The configuration file URL defines to or from which location the configuration file will be exported or imported, e.g. tftp://192.168.1.1/dt50.cfg. At the moment only TFTP protocol is supported.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.1.1 |

1.3.2 setWireless

1.3.2.1 setWlanDeviceTable

Wireless Hardware Modules.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.1.4.3.1 |

1.3.2.2 setWlanDeviceTableEntry

Wireless Hardware Module.

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1 |

1.3.2.3 setWlanDevIndex

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.1 |

1.3.2.4 setWlanDevName

Name of the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.2 |

1.3.2.5 setWlanDevRfOutput

Enable/disable RF output.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.3 |

1.3.2.6 setWlanDevModulation

Wireless Modulation Mode

| | |
|--------------------|--|
| <i>Enumeration</i> | nb (9) g (2) a (4) nbg (11) na (12) bg (3) b (1) ng (10) |
| <i>Status</i> | current |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.4 |

1.3.2.7 setWlanDevBandwidth

Wireless Bandwidth Mode

| | |
|--------------------|-------------------------------------|
| <i>Enumeration</i> | ht40Plus (1) ht20 (0) ht40Minus (2) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.5 |

1.3.2.8 setWlanDevFrequency

Wireless Frequency

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.6 |

1.3.2.9 setWlanDevPower

Wireless Output Power

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.1.1.8 |

1.3.2.10 setWlanDbgTable

Wireless Handoff Debug Parameters

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6 |

1.3.2.11 setWlanDbgTableEntry

Wireless Handoff Debug Parameters Entry

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1 |

1.3.2.12 setWlanDbgIndex

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.1 |

1.3.2.13 setWlanDbgIfaceName

Name of the virtual wireless interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.2 |

1.3.2.14 setWlanDbgHandoff

Volatile setting to enable/disable the Handoff Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.3 |

1.3.2.15 setWlanDbgScan

Volatile setting to enable/disable the Scan Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.4 |

1.3.2.16 setWlanDbgMIme

Volatile setting to enable/disable the MIme Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.5 |

1.3.2.17 setWlanDbgEvents

Volatile setting to enable/disable the Events Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.6 |

1.3.2.18 setWlanDbgBeaconrssi

Volatile setting to enable/disable the Beacon RSSI Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.7 |

1.3.2.19 setWlanDbgAckrssi

Volatile setting to enable/disable the ACK RSSI Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.8 |

1.3.2.20 setWlanDbgBeaconfiltered

Volatile setting to enable/disable the Beacon filtered RSSI Messages in syslog

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.3.6.1.9 |

1.3.3 setConfmgmtd

1.3.3.1 setCfdLogLevel

Log message level of the Configuration Management Daemon

| | |
|--------------------|---|
| <i>Enumeration</i> | disabled (0) warning (2) error (1) debug (4) info (3) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.4.1 |

1.3.4 setFirmware

1.3.4.1 setFwFileUrl

AP **STA**

Download firmware from this URL.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.5.1 |

1.3.4.2 setFwKeepConfig

AP **STA**

Try to import configuration from the previous firmware version.

| | |
|--------------------|-----------------------------|
| <i>Enumeration</i> | keep (1) reset (0) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.5.2 |

1.3.5 setCertificate

1.3.5.1 setCrtFileUrl

AP **STA**

The certification/key (for HTTPS) file-URL defines to or from which location the certification/key file will be downloaded or uploaded, e.g. `tftp://192.168.1.1/sw6-uttpd.crt`. At the moment only the TFTP protocol is supported.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.4.6.1 |

1.4 hardware

1.4.1 hwSystem

1.4.1.1 hwSysProduct

Product Type

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.1.1 |

1.4.1.2 hwSysSerial

Serial number of the product

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.1.2 |

1.4.1.3 hwSysRevision

ERP Revision of the product

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.1.3 |

1.4.1.4 hwSysVersion

Version of the product

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.1.4 |

1.4.2 hwBaseBoard

1.4.2.1 hwBbType

Product type of the DT50 base board

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.10.1 |

1.4.2.2 hwBbSerial

Serial number of the DT50 base board

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.10.2 |

1.4.2.3 hwBbRevision

ERP Revision of the DT50 base board

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.10.3 |

1.4.2.4 hwBbVersion

Version of the DT50 base board

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.10.4 |

1.4.2.5 hwBbPcbId

Hardware Assembly ID (Neratec Specific)

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.10.5 |

1.4.2.6 hwBbAssemblyId

Hardware Assembly ID (Neratec Specific)

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.10.6 |

1.4.3 hwIfaceBoard

1.4.3.1 hwIfBrdAssembled

Interface board present or not.

| | |
|--------------------|------------------------------|
| <i>Enumeration</i> | present (1) inexistent (0) |
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.1 |

1.4.3.2 hwIfBrdType

Product type of the interface board

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.2 |

1.4.3.3 hwIfBrdSerial

Serial number of the interface board

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.3 |

1.4.3.4 hwIfBrdRevision

ERP Revision of the interface board (Neratec Specific)

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.4 |

1.4.3.5 hwIfBrdVersion

Version of the interface board (Neratec Specific)

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.5 |

1.4.3.6 hwIfBrdPcbId

Hardware Assembly ID (Neratec Specific)

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.6 |

1.4.3.7 hwIfBrdAssemblyId

Hardware Assembly ID (Neratec Specific)

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.11.7 |

1.4.4 hwNetwork

1.4.4.1 hwNetEthernetTable

Ethernet Network Interfaces

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1 |

1.4.4.2 hwNetEthernetTableEntry

Ethernet Network Interface

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1 |

1.4.4.3 hwNetEthIndex

Entry index of table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 2 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1.1 |

1.4.4.4 hwNetEthName

Name of the ethernet interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1.2 |

1.4.4.5 hwNetEthAssembled

Ethernet interface present or not.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | present (1) inexistent (0) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1.3 |

1.4.4.6 hwNetEthMacAddress

Ethernet MAC address.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1.4 |

1.4.4.7 hwNetEthOperation

Ethernet interface plugged of unplugged

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | up (1) down (0) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1.5 |

1.4.4.8 hwNetEthSpeed

Ethernet speed

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.2.1.1.6 |

1.4.5 hwWireless

1.4.5.1 hwWlanDeviceTable

Hardware information of the wireless LAN Devices.

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1 |

1.4.5.2 hwWlanDeviceTableEntry

Wireless LAN Devices

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1 |

1.4.5.3 hwWlanDevIndex

Entry index of table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.1 |

1.4.5.4 hwWlanDevAssembled

Wireless device present or not.

| | |
|--------------------|---------------------------------|
| <i>Enumeration</i> | present (1) inexistent (0) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.2 |

1.4.5.5 hwWlanDevType

Type of the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.3 |

1.4.5.6 hwWlanDevSerial

Serial Number / Customer Field

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.4 |

1.4.5.7 hwWlanDevRevision

ERP Revision of the RF board. (Neratec Specific)

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.5 |

1.4.5.8 hwWlanDevVersion

Version of the RF board (Neratec Specific)

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.6 |

1.4.5.9 hwWlanDevPcbId

Hardware Assembly ID (Neratec Specific)

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.7 |

1.4.5.10 hwWlanDevAssemblyId

Hardware Assembly ID (Neratec Specific)

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.8 |

1.4.5.11 hwWlanDevMacAddress

MAC Address

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.5.3.1.1.9 |

1.5 software

1.5.1 swFirmware

1.5.1.1 swFwName

Firmware Name

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.2.1 |

1.5.1.2 swFwVersion

Firmware Name

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.2.2 |

1.5.1.3 swFwRevision

Firmware Name

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.2.3 |

1.5.2 swBootloader

1.5.2.1 swBootName

Name of the bootloader.

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.20.1 |

1.5.2.2 swBootVersion

Version of the bootloader.

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.20.2 |

1.5.2.3 swBootBuildDate

Date when the bootloader was built.

| | |
|---------------|------------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.20.3 |

1.5.3 swSystem

1.5.3.1 swSysRebootReason

Reason for the reboot of the system.

| | |
|--------------------|---|
| <i>Enumeration</i> | warmstart (1) watchdog (2) unknown (9) coldstart (0) oops (3) |
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.1 |

1.5.3.2 swSysMessageTable

System messages (e.g. errors, warnings)

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.100 |

1.5.3.3 swSysMessageTableEntry

System message entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.100.1 |

1.5.3.4 swSysMsgIndex

Entry index of Table

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 64 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.100.1.1 |

1.5.3.5 swSysMsgPriority

Message priority/level

| | |
|--------------------|--|
| <i>Enumeration</i> | warning (4) debug (7) critical (2) alert (1) notice (5) emergency (0) error (3) info (6) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.100.1.2 |

1.5.3.6 swSysMsgCode

Message code

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.100.1.3 |

1.5.3.7 swSysMsgText

Message

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.3.100.1.4 |

1.5.4 swOperatingSystem

1.5.4.1 swOsName

Operating System Name

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.4.1 |

1.5.4.2 swOsVersion

Operating System Version

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.4.2 |

1.5.4.3 swOsRevision

Operating System Revision

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.4.3 |

1.5.4.4 swOsUptime

Uptime of the operating system

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | TimeTicks |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.4.4 |

1.5.5 swDriver

1.5.5.1 swDrvDfsTable

DFS Driver Statistics

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1 |

1.5.5.2 swDrvDfsTableEntry

DFS Driver Statistics

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1.1 |

1.5.5.3 swDrvDfsIndex

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1.1.1 |

1.5.5.4 swDrvDfsName

Name of the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1.1.2 |

1.5.5.5 swDrvDfsPulsesDetected

Pulses detected by the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1.1.3 |

1.5.5.6 swDrvDfsPulsesProcessed

Pulses processed by the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1.1.4 |

1.5.5.7 swDrvDfsRadarDetected

Radar sequences detected by the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.1.1.5 |

1.5.5.8 swDrvCntWlanIfTable

Wireless Interface Driver Statistics

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3 |

1.5.5.9 swDrvCntWlanIfTableEntry

Wireless Interface Driver Statistics

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1 |

1.5.5.10 swDrvCntWlanIfIndex

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.1 |

1.5.5.11 swDrvCntWlanIfRxFifoErrors

Number of fifo errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.10 |

1.5.5.12 swDrvCntWlanIfRxFrameErrors

Number of frame errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.11 |

1.5.5.13 swDrvCntWlanIfRxLengthErrors

Number of length errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.12 |

1.5.5.14 swDrvCntWlanIfRxMissedErrors

Number of missed errors received on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.13 |

1.5.5.15 swDrvCntWlanIfRxOverErrors

Number of over?? errors received on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.14 |

1.5.5.16 swDrvCntWlanIfRxPackets

Number of packages received on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.15 |

1.5.5.17 swDrvCntWlanIfTxAbortedErrors

Number of errors during the transmission on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.16 |

1.5.5.18 swDrvCntWlanIfTxBytes

Number of transmitted bytes on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.17 |

1.5.5.19 swDrvCntWlanIfTxCarrierErrors

Number of carrier errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.18 |

1.5.5.20 swDrvCntWlanIfTxCompressed

Number of ?? on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.19 |

1.5.5.21 swDrvCntWlanIfName

Name of the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.2 |

1.5.5.22 swDrvCntWlanIfTxDropped

Number of packages tx has dropped on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.20 |

1.5.5.23 swDrvCntWlanIfTxErrors

Number of errors during the transmission on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.21 |

1.5.5.24 swDrvCntWlanIfTxFifoErrors

Number of fifo errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.22 |

1.5.5.25 swDrvCntWlanIfTxHeartbeatErrors

Number of tx heartbeat errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.23 |

1.5.5.26 swDrvCntWlanIfTxPackets

Number of tx packets on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.24 |

1.5.5.27 swDrvCntWlanIfTxWindowErrors

Number of tx window errors on this wlan interface

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.25 |

1.5.5.28 swDrvCntWlanIfCollisions

Number of collisions on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.3 |

1.5.5.29 swDrvCntWlanIfMulticast

Multicasts on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.4 |

1.5.5.30 swDrvCntWlanIfRxBytes

Number of bytes received on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.5 |

1.5.5.31 swDrvCntWlanIfRxCompressed

Number of ?? on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.6 |

1.5.5.32 swDrvCntWlanIfRxCrcErrors

Number of crc errors on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.7 |

1.5.5.33 swDrvCntWlanIfRxDropped

Number of frame dropped on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.8 |

1.5.5.34 swDrvCntWlanIfRxErrors

Number of rx errors on this wlan interface

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.3.1.9 |

1.5.5.35 swDrvCntWlanMacTable

Wireless MAC-Layer Statistics

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4 |

1.5.5.36 swDrvCntWlanMacTableEntry

Wireless MAC-Layer Statistics

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1 |

1.5.5.37 swDrvCntWlanMacIndex

Entry index of Table

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 1 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.1 |

1.5.5.38 swDrvCntWlanMacRxHandlersDrop

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.10 |

1.5.5.39 swDrvCntWlanMacRxHandlersQueued

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.11 |

1.5.5.40 swDrvCntWlanMacRxHandlersDropNullfunc

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.12 |

1.5.5.41 swDrvCntWlanMacRxHandlersDropDefrag

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.13 |

1.5.5.42 swDrvCntWlanMacRxHandlersDropShort

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.14 |

1.5.5.43 swDrvCntWlanMacTxExpandSkbHead

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.15 |

1.5.5.44 swDrvCntWlanMacTxExpandSkbHeadCloned

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.16 |

1.5.5.45 swDrvCntWlanMacRxExpandSkbHead

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.17 |

1.5.5.46 swDrvCntWlanMacRxExpandSkbHead2

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.18 |

1.5.5.47 swDrvCntWlanMacRxHandlersFragments

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.19 |

1.5.5.48 swDrvCntWlanMacName

Name of the wireless device

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.2 |

1.5.5.49 swDrvCntWlanMacTxstatusDrop

MAC debug entry

| | |
|---------------|----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.20 |

1.5.5.50 swDrvCntWlanMacTxHandlersDrop

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.3 |

1.5.5.51 swDrvCntWlanMacTxHandlersQueued

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.4 |

1.5.5.52 swDrvCntWlanMacTxHandlersDropUnencrypted

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.5 |

1.5.5.53 swDrvCntWlanMacTxHandlersDropFragment

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.6 |

1.5.5.54 swDrvCntWlanMacTxHandlersDropWep

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.7 |

1.5.5.55 swDrvCntWlanMacTxHandlersDropNotAssoc

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.8 |

1.5.5.56 swDrvCntWlanMacTxHandlersDropUnauthPort

MAC debug entry

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.4.1.9 |

1.5.5.57 swDrvCntWlanWmmTable

Wmm statistics

| | |
|---------------|-----------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6 |

1.5.5.58 swDrvCntWlanWmmTableEntry

Wmm statistics

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1 |

1.5.5.59 swDrvCntWlanWmmTableIndex

Entry index of Table.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 3 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.1 |

1.5.5.60 swDrvCntWlanWmmName

Name of the queue.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.2 |

1.5.5.61 swDrvCntWlanWmmTx

Number of frames sent in this queue.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.3 |

1.5.5.62 swDrvCntWlanWmmRx

Number of frames received in this queue.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.4 |

1.5.5.63 swDrvCntWlanWmmShortRetries

Number of retries for frames shorter than RTS.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.5 |

1.5.5.64 swDrvCntWlanWmmLongRetries

Number of retries for frames longer than RTS.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.6 |

1.5.5.65 swDrvCntWlanWmmExceededRetries

Number of failed transmissions due to exceeding of the retry limit.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.5.6.1.7 |

1.5.6 swRdm

1.5.6.1 swRdmMaxEirp

Maximal equivalent isotropically radiated power (EIRP) in dBm. This value shows the maximal aggregated transmit power over all configured

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.6.1 |

1.5.6.2 swRdmMaxApp

Maximal antenna port power in dBm. This value shows the maximal transmit power of a single chain.

| | |
|---------------|-----------------------------|
| <i>Access</i> | readonly |
| <i>Status</i> | current |
| <i>Type</i> | Integer32 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.1.6.6.2 |

MIB Reference:

NERATEC-SW6-FIREWALL-MIB

2 Device configuration

2.1 firewall

2.1.1 configuration

2.1.1.1 cfgFwEnabled

☐ AP
 ☐ STA

Firewall disabled or enabled

| | |
|--------------------|-----------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Access</i> | readwrite |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.1 |

2.1.1.2 cfgFwNat

2.1.1.2.1 cfgFwNatPortForwardTable

Firewall port forward rules table

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1 |

2.1.1.2.2 cfgFwNatPortForwardTableEntry

Firewall port forward rules table entry.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1 |

2.1.1.2.3 cfgFwNatPrtFwdIndex

Entry index of port forward table.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.1 |

2.1.1.2.4 cfgFwNatPrtFwdDestinationPortEnd

AP **STA**

Destination end port to redirect. When forwarding multiple port, this value is the end of the range. Set to -1 if no range is forwarded. Can only be used with TCP, UCP or TCP/UDP.

| | |
|---------------|------------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 65535 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.10 |

2.1.1.2.5 cfgFwNatPrtFwdRedirectDestinationAddress

AP **STA**

Redirect traffic to this redirection destination address.

| | |
|---------------|------------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.11 |

2.1.1.2.6 cfgFwNatPrtFwdRedirectDestinationPort

AP **STA**

Redirect traffic to this destination port. Can only be used with TCP, UCP or TCP/UDP.

| | |
|---------------|------------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 65535 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.12 |

2.1.1.2.7 cfgFwNatPrtFwdEnabled

☐ AP ☐ STA

Disable or enable the rule.

| | |
|--------------------|-----------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.2 |

2.1.1.2.8 cfgFwNatPrtFwdInterface

☐ AP ☐ STA

Name of the network interface on which the rule applies. Defines on which interface traffic is coming in.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.3 |

2.1.1.2.9 cfgFwNatPrtFwdProtocol

☐ AP ☐ STA

Choose which IP protocol the rule matches. Allowed protocols are: any(0): Any ip protocol. udp(1): Only UDP protocol. tcp(2): Only TCP protocol. udptcp(3): UDP and TCP protocol.

| | |
|--------------------|------------------------------------|
| <i>Enumeration</i> | tcp (2) any (0) udptcp (3) udp (1) |
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.4 |

2.1.1.2.10 cfgFwNatPrtFwdSourceAddress

☐ AP ☐ STA

Source address to match. This can be a specific ip address or a range in CIDR notation. Set to 0.0.0.0/0 to match all inbound traffic. Set to 172.17.29.7/32 to match the specific IP 172.17.29.7. You can use ! to invert the sense of the rule: E.g. !192.168.0.0/24. HINT: Usually you want 0.0.0.0/0.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 9 - 19 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.5 |

2.1.1.2.11 cfgFwNatPrtFwdSourcePortStart

AP **STA**

Source start port to match. Specify the port or start of a port range from which a connection originates. Can only be used with TCP, UCP or TCP/UDP. Leave this on -1 to disable. You can use ! to invert the sense of the rule: E.g. !80. When used in a range, the inversion applies to the range. HINT: Usually you want this disabled.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 6 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.6 |

2.1.1.2.12 cfgFwNatPrtFwdSourcePortEnd

AP **STA**

Destination end port to match. When matching multiple port, this value is the end of the range. Set to -1 if no range is to be matched. Can only be used with TCP, UCP or TCP/UDP. HINT: Usually you want this disabled.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 65535 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.7 |

2.1.1.2.13 cfgFwNatPrtFwdDestinationAddress

AP **STA**

Destination address to redirect. This can be a specific IP address or a range in CIDR notation. Set to 0.0.0.0/0 to match all inbound traffic on the interfaces specified in cfgFwNatPrtFwdInterface. You can use ! to invert the sense of the rule: E.g. !192.168.0.0/24. When using static IPs set this to the configured address of the respective interface or alias you want to forward. HINT: Leave this on 0.0.0.0/0 when using DHCP. Be aware, that setting 0.0.0.0/0 will redirect everything arriving on the configured interface, even if not sent to the device itself.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 9 - 19 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.8 |

2.1.1.2.14 cfgFwNatPrtFwdDestinationPortStart

AP **STA**

Destination start port to redirect. Specify the port or start of a port range for the destination. You can

use ! to invert the sense of the rule: E.g. !80When used in a range, the inversion applies to the range.Can only be used with TCP, UCP or TCP/UDP.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 65535 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.1.1.9 |

2.1.1.2.15 cfgFwNatOutboundTable

Firewall outbound NAT rules table

| | |
|---------------|-------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2 |

2.1.1.2.16 cfgFwNatOutboundTableEntry

Firewall outbound NAT rules table entry.

| | |
|---------------|---------------------------------|
| <i>Status</i> | current |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1 |

2.1.1.2.17 cfgFwNatOutIndex

Entry index of Table.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | 0 - 255 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.1 |

2.1.1.2.18 cfgFwNatOutDestinationPortEnd

☐ AP ☐ STA

Destination end port to match.When forwarding multiple port, this value is the end of the range.Set to -1 if no range is forwarded.Can only be used with TCP, UCP or TCP/UDP.HINT: Usually you want this disabled.

| | |
|---------------|------------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 65535 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.10 |

2.1.1.2.19 cfgFwNatOutSourceRewriteAddress

AP **STA**

Redirect traffic to this redirection destination address. Set the address with which outbound traffic shall be rewritten. In case you are using DHCP leave this on 0.0.0.0. HINT: If you are not rewriting the source to a specific aliases you can leave this on 0.0.0.0 as well to automatically rewrite to the configured main address of the interface.

| | |
|---------------|------------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | IpAddress |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.11 |

2.1.1.2.20 cfgFwNatOutSourceRewritePort

AP **STA**

Redirect traffic to this destination port. Can only be used with TCP, UCP or TCP/UDP. Set to -1 to disable source port rewrite. HINT: Usually you want this disabled.

| | |
|---------------|------------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 65535 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.12 |

2.1.1.2.21 cfgFwNatOutEnabled

AP **STA**

Disable or enable the rule.

| | |
|--------------------|-----------------------------------|
| <i>Enumeration</i> | disabled (0) enabled (1) |
| <i>Status</i> | current |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.2 |

2.1.1.2.22 cfgFwNatOutInterface

AP **STA**

Name of the network interface on which the rule applies. Matches traffic leaving on this interface. Needs to be set to an interface name if you are using DHCP. Set to -1 if you don't know on which interface traffic will be leaving. Match the traffic with `cfgFwNatOutDestinationAddress` instead. You can use ! to invert the sense of the rule. E.g. !wlan0

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 255 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.3 |

2.1.1.2.23 cfgFwNatOutProtocol

AP **STA**

Choose which IP protocol the rule matches. Allowed protocols are: any(0): Any ip protocol. udp(1): Only UDP protocol. tcp(2): Only TCP protocol. udptcp(3): UDP and TCP protocol.

| | |
|--------------------|------------------------------------|
| <i>Enumeration</i> | tcp (2) any (0) udptcp (3) udp (1) |
| <i>Status</i> | current |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.4 |

2.1.1.2.24 cfgFwNatOutSourceAddress

AP **STA**

Source address to match. This can be a specific ip address or a range in CIDR notation. Set to 0.0.0.0/0 to match all inbound traffic. Set to 172.17.29.7/32 to match the specific IP 172.17.29.7. You can use ! to invert the sense of the rule: E.g. !192.168.0.0/24. HINT: Usually you want 0.0.0.0/0.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 9 - 19 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.5 |

2.1.1.2.25 cfgFwNatOutSourcePortStart

AP **STA**

Source start port to match. Specify the port or start of a port range from which a connection originates. Can only be used with TCP, UCP or TCP/UDP. Leave this on -1 to disable. You can use ! to invert the sense of the rule: E.g. !80. When used in a range, the inversion applies to the range. HINT: Usually you want this disabled.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 6 |
| <i>OID</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.6 |

2.1.1.2.26 cfgFwNatOutSourcePortEnd

AP **STA**

Destination end port to match. When matching multiple port, this value is the end of the range. Set to -1 if no range is to be matched. Can only be used with TCP, UCP or TCP/UDP. HINT: Usually you want this disabled.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Range</i> | -1 - 65535 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.7 |

2.1.1.2.27 **cfgFwNatOutDestinationAddress**

AP **STA**

Destination address to match. This can be a specific ip address or a range in CIDR notation. Set to 0.0.0.0/0 to match all outbound traffic on the interfaces specified in `cfgFwNatOutInterface`. You can use `!` to invert the sense of the rule: E.g. `!192.168.0.0/24`

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 9 - 19 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.8 |

2.1.1.2.28 **cfgFwNatOutDestinationPortStart**

AP **STA**

Destination start port to match. Specify the port or start of a port range for the destination. Can only be used with TCP, UCP or TCP/UDP. You can use `!` to invert the sense of the rule: E.g. `!80`. When used in a range, the inversion applies to the range. HINT: Usually you want this disabled.

| | |
|---------------|-----------------------------------|
| <i>Status</i> | current |
| <i>Type</i> | DisplayString |
| <i>Range</i> | 1 - 6 |
| <i>Oid</i> | 1.3.6.1.4.1.41524.1.2.1.1.2.2.1.9 |

2.1.2 **rpc**

2.1.3 **settings**

2.1.4 **hardware**

2.1.5 **software**

Message Codes

Variable text, inserted at the time the message is created, is displayed using the place holder '<val>'.

- [INFO 0] <val>
Manual or WebGUI Log Reset.
- [ERROR 100] SYS_MON: <val> Voltage is out of range (to <val>)
This trap is sent when supply voltage or one of the internal voltages are outside specified limits which are hardware dependent.
- [ERROR 101] SYS_MON: <val> Temperature is out of range (to <val>)
This trap is sent when internally measured temperature is outside specified limits which are hardware dependent.
- [CRITICAL 105] SYS_MON: Failure by reading value <val>. This value isn't monitored anymore
This trap is sent when internally a value couldn't read.
- [NOTICE 200] Device has restarted because of <val>
This message is sent at boot-up process. RESET CAUSE can be either coldstart or watchdog.
- [NOTICE 201] System startup
This message is sent when the system starts up.
- [NOTICE 202] Firmware update started
This message is sent when a firmware update is initiated.
- [NOTICE 203] System reboot
This message is sent when a system reboot is issued.
- [INFO 204] Reserved
- [NOTICE 205] Factory Reset confirmed, System configuration

changed

This message is sent whenever the system configuration is changed.

- [NOTICE 206] Reserved

- [WARNING 207] Invalid upgrade image for this platform.

- [ERROR 208] Corrupt firmware package!

- [WARNING 300] NTP: time synchronization failed!
This message is generated when ntp client is configured in unicast mode and it failed to connect to NTP server.

- [NOTICE 310] Reserved

- [ERROR 320] BIST: Daemon '<val>' isn't running, recover it
This message is generated when process with name process is not running and has to be restarted by the bist

- [ERROR 321] BIST: Daemon watchdog is not running - force
restart
This message is generated when watchdog process is not running. System reboots afterwards.

- [INFO 400] WLAN: Station is associated
this message is used to trigger led status

- [INFO 401] WLAN: Station is disassociated
this message is used to trigger led status

- [ERROR 402] Reserved

- [ERROR 403] WLAN: Authentication failure
- [ERROR 404] WLAN: Association failure
- [NOTICE 405] Reserved
- [ERROR 406] WLAN: Max number of station exceeded
- [ERROR 407] Reserved
- [NOTICE 410] <val>:
Handoff: |<val>|<val>|<val>|<val>|<val>|<val>|
- [NOTICE 430] TS|<val>|<val>|RSSI_BCN|<val>
- [NOTICE 432] Reserved
- [CRITICAL 500] CONFIG: Unable to connect to IPC system (ubus)!
- [CRITICAL 501] CONFIG: Unable to read from UCI!
- [ERROR 510] CONFIG: Invalid configuration, reverting to previous configuration!
- [ERROR 511] CONFIG: Unable to save new configuration!

- [CRITICAL 512] CONFIG: Unable to apply previous configuration!
- [WARNING 513] CONFIG: Unable to set through snmp: <val>
Warning for import config through snmpcfgfile
- [ERROR 580] CONFIG FILE: Transfer failed!
- [WARNING 581] CONFIG FILE: <val>
- [ERROR 582] CONFIG FILE: Unable to read or parse!
- [ERROR 585] CONFIG Certificate: https certificate
import/export failed!
- [ERROR 700] NET: Configuration failed!
This message is sent if the network couldn't be set up. Possible reason are wrong proto, missing
or invalide netmask or ipaddress.
- [WARNING 701] NET: Configuration failed, but try to continue
anyway.
This message is sent if the network couldn't be set up. Possible reason are the interface we try
to configure does not exist.
- [ERROR 710] NET: Unable to set the default gateway!
This message is sent if the default gateway couldn't be set properly. This happens if the
destination can not be reached, or no matching subnet exist.
- [WARNING 711] NET: Unable to set the default gateway!
This message is sent if the default gateway couldn't be set properly. This can happen if the
default gateway is already set by DHCP.

- [ERROR 712] NET: Unable to set a static route!
This message is sent when an static route couldn't be set.
- [WARNING 713] NET: Unable to set a static route!
This message is sent when an static route couldn't be set.
- [ERROR 720] NET: Wireless configuration failed!
This message is sent when the configuration manager is not able to set up a wireless interface.
- [ERROR 730] NET: Creation of alias failed!
This message is sent if an alias couldn't be set up. Possible reason are missing or invalide netmask or ipaddress.
- [WARNING 731] NET: Parent interface missing for alias.
This message is sent if the parent interface for an alias doesn't exist.
- [ERROR 740] NET: Creation of VLAN failed!
This message is sent if the creation of a vlan failed.
- [WARNING 741] NET: Parent interface missing for VLAN.
This message is sent if the creation of a vlan failed because the parent doesn't exist.
- [WARNING 750] NET: Adding a QoS rule failed.
- [INFO 800] DFS: Starting CAC on <val> MHz.
This message is sent when a CAC or Off-Channel CAC is started.
- [INFO 801] DFS: Radar found on <val> MHz.
This message is sent when a radar pattern during In-Service Monitoring, CAC or Off-Channel CAC is detected.
- [INFO 802] DFS: Channel on <val> MHz becomes Available.
This message is sent when a channel on the given frequency becomes Available after a CAC or Off-Channel CAC.

- [INFO 803] DFS: Channel on <val> MHz becomes Usable again.
This message is sent when a channel on the given frequency becomes Usable after the NOP time.
- [INFO 804] DFS: Starting In-Service Monitoring on <val> MHz.
This message is sent when the In-Service Monitoring for the Operating Channel on the given frequency.
- [INFO 805] DFS: All initial CACs done.
This message is sent when all DFS frequencies have passed the initial CAC.