







### ISO/IEC17025Accredited Lab.

Report No: FCC 1504075
File reference No: 2015-04-20

Applicant: JiaChuangBo Technology Co., Ltd

Product: Tablet PC

Model No: MiTraveler 708, MiTraveler 720, MiTraveler 748, MiTraveler

808, MiTraveler 820, MiTraveler 848, MiTraveler 908, MiTraveler 920, MiTraveler 948, MiTraveler 10C3 Combo, Michley 700, Michley 718, Michley 7D8, Michley 800, Michley 818, Michley 880, Michley 900, Michley 918, Michley 980, C11, C18, Q8, Q9, Y88, Y88X, Y108, JCB 702, JCB 748, JCB 802, JCB 848, JCB 880, JCB 902, JCB 920, A705, A805, A820,

X692, X720, X892

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4,FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: April 20, 2015

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TESTING LABORATORIES

Room 512-519, 5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen, Guangdong, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timewaytech.com

Report No: FCC1504075 Page 2 of 101

Date: 2015-04-20



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

### **CNAL-LAB Code: L2292**


The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

### FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

# IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.



Date: 2015-04-20



# **Test Report Conclusion**

### Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	8
3.1	Summary of Test Results	8
3.2	Test Standards	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT.	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test.	13
6.1	Test Method and Test Procedure.	13
6.2	Configuration of the EUT.	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	14
7.0	6dB Bandwidth Measurement	38
8.0	Maximum Peak Output Power	58
9.0	Power Spectral Density Measurement.	61
10.0	Out of Band Measurement	79
11.0	Antenna Requirement.	90
12.0	FCC ID Label	91
13.0	Photo of Test Setup and EUT View.	92

Date: 2015-04-20



### 1.0 General Details

### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Room 512-519,5/F., East Tower, Building 4, Anhua Industrial Zone, Futian District, Shenzhen,

Guangdong China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

### 1.2 Applicant Details

Applicant: JiaChuangBo Technology Co., Ltd

Address: 2nd&3rd Floor, Building 5 No.262 Yueling Rd, Gaoxin Dist, Anshan city, Liaoning Province,

China

Telephone: 0412-5061691 Fax: 0412-5061691

### 1.3 Description of EUT

Product: Tablet PC

Manufacturer: JiaChuangBo Technology Co., Ltd

Address: 2nd&3rd Floor, Building 5 No.262 Yueling Rd, Gaoxin Dist, Anshan city,

Liaoning Province, China

Brand Name: N/A

Model Number: MiTraveler 708

Additional Model Number: MiTraveler 720, MiTraveler 748, MiTraveler 808, MiTraveler 820, MiTraveler 848, MiTraveler 908, MiTraveler 920, MiTraveler 948, MiTraveler 10C3 Combo , Michley 700, Michley 718, Michley 7D8, Michley 800, Michley 818, Michley 880, Michley 900, Michley 918, Michley 980, C11, C18, Q8, Q9, Y88, Y88X, Y108, JCB 702, JCB 748, JCB 802, JCB 848, JCB 880, JCB 902, JCB 920, A705, A805, A820, X692, X720, X892

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n HT20/HT40: OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n HT20: 2412-2462MHz; IEEE 802.11n HT40: 2422-2452MHz;

Channel Spacing IEEE 802.11b/g/n HT20/HT40 : 5MHz

Antenna: Integral antenna used.
Antenna Gain: Maximum 1.0dBi

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: FCC1504075 Page 5 of 101

Date: 2015-04-20



IEEE 802.11b: 11, 5.5, 2, 1 Mbps Air Data Rate

> IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps IEEE 802.11n HT20/HT40: up to 150Mbps

Frequency Selection By software

Power Supply: JHD-AP012U-050150AB Input: 100-240V, 50/60Hz, 0.35A; Output: 5V, 1500mA

Channel Number IEEE 802.11b/g/n HT20: 11 Channels; IEEE 802.11n HT40: 7 Channels

Submitted Sample: 2 Samples

1.5 Test Duration

2015-04-20 to 2015-04-20

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 101

Report No: FCC1504075

Date: 2015-04-20



2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2014-08-22	2015-08-21
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2014-08-22	2015-08-21
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2014-08-22	2015-08-21
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2014-08-22	2015-08-21
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2014-08-22	2015-08-21
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2014-08-22	2015-08-21
System Controller	CT	SC100	-		
Loop Antenna	EMCO	6502	00042960	2014-08-22	2015-08-21
Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2014-08-22	2015-08-21
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2014-08-23	2015-08-21
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2014-08-23	2015-08-21
Power meter	Anritsu	ML2487A	6K00003613	2014-08-22	2015-08-21
Power sensor	Anritsu	MA2491A	32263	2014-08-22	2015-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2014-08-23	2015-08-21
LISN	AFJ	LS16C	10010947251	2014-08-22	2015-08-21
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2014-08-22	2015-08-21
9*6*6 Anechoic			N/A	2014-08-22	2015-08-21
EMI Test Receiver	RS	ESCS30	100139	2014-08-22	2015-08-21

### **Auxiliary Equipment** 2.1

Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
Passive Earphone					

Report No: FCC1504075 Page 7 of 101

Date: 2015-04-20



### 3. DESCRIPTION OF TEST MODES

### IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 6Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 150Mbps data rate (worst case) were chosen for full testing

### IEEE 802.11n HT40

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Mid	2437
High	2452

IEEE 802.11n HT40 mode: 150Mbps data rate (worst case) was chosen for full testing.

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.

Note: EUT Test With 100% Duty cycle.

Date: 2015-04-20



### 3.0 **Technical Details**

### 3.1 **Summary of test results**

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107 & 15.207	<b>Conducted Emission Test</b>	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit:	PASS	Complies

### 3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

### 4.0 **EUT Modification**

No modification by Shenzhen Timeway Technology Consulting Co., Ltd

Page 9 of 101


Report No: FCC1504075

Date: 2015-04-20



### 5. **Power Line Conducted Emission Test**

### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013 and ANSI C63.4 -2009.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

Page 10 of 101

Report No: FCC1504075

Date: 2015-04-20



### **EUT** A.

Device	Manufacturer	Model	FCC ID
Tablet PC	JiaChuangBo Technology Co., Ltd	MiTraveler 708, MiTraveler 720, MiTraveler 748, MiTraveler 808, MiTraveler 820, MiTraveler 848, MiTraveler 908, MiTraveler 920, MiTraveler 948, MiTraveler 10C3 Combo, Michley 700, Michley 718, Michley 7D8, Michley 800, Michley 818, Michley 880, Michley 900, Michley 918, Michley 980, C11, C18, Q8, Q9, Y88, Y88X, Y108, JCB 702, JCB 748, JCB 802, JCB 848, JCB 880, JCB 902, JCB 920, A705, A805, A820, X692, X720, X892	2AEJJ-JCB A9X

### B. Internal Device

Device	Manufacturer	Model	Rating

### C. Peripherals

Device	Manufacturer	Model	Rating

### 5.4 **EUT Operating Condition**

Operating condition is according to ANSI C63.10 -2013.

- Setup the EUT and simulators as shown on follow A
- В Enable AF signal and confirm EUT active to normal condition

### Power line conducted Emission Limit according to Paragraph 15.207 and 15.107 and RSS-210 5.5

Frequency	Class A Lim	its (dB μ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into an will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-04-20



### Conducted Emission on Live Terminal (150kHz to 30MHz) A:

**EUT Operating Environment** 


Atmospheric Pressure: 101 KPa Temperature: 26°C Humidity: 65%RH

**EUT set Condition: Keeping WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual



No. M	k. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBu∀	dB	Detector	Comment
1	0.4486	29.50	11.32	40.82	56.90	-16.08	QP	
2	0.4486	7.20	11.32	18.52	46.90	-28.38	AVG	
3 *	0.8003	29.20	11.69	40.89	56.00	-15.11	QP	
4	0.8003	2.30	11.69	13.99	46.00	-32.01	AVG	
5	1.2640	27.20	12.01	39.21	56.00	-16.79	QP	
6	1.2640	6.30	12.01	18.31	46.00	-27.69	AVG	
7	29.8348	27.80	11.30	39.10	60.00	-20.90	QP	
8	29.8348	20.10	11.30	31.40	50.00	-18.60	AVG	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into an will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-04-20



### B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Keeping WIFI Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



No. I	Иk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1921	41.40	11.04	52.44	63.95	-11.51	QP	
2		0.1921	8.10	11.04	19.14	53.95	-34.81	AVG	
3		0.2522	33.30	11.11	44.41	61.68	-17.27	QP	
4		0.2522	9.80	11.11	20.91	51.68	-30.77	AVG	
5		0.6976	27.30	11.58	38.88	56.00	-17.12	QP	
6		0.6976	4.40	11.58	15.98	46.00	-30.02	AVG	
7		0.3197	29.00	11.18	40.18	59.71	-19.53	QP	
8		0.3197	5.60	11.18	16.78	49.71	-32.93	AVG	
9		0.5753	26.60	11.45	38.05	56.00	-17.95	QP	
10		0.5753	8.70	11.45	20.15	46.00	-25.85	AVG	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No: FCC1504075 Page 13 of 101

Date: 2015-04-20



### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10 –2013. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013 and ANSI C63.4 -2009.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

# Block diagram of Test setup Distance = 3m Computer Pre -Amplifier Furn-table Receiver

- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No: FCC1504075 Page 14 of 101

Date: 2015-04-20



### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

### Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB $\mu$ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Page 15 of 101

Date: 2015-04-20



### Test result

Report No: FCC1504075

### General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

**EUT set Condition: Keeping WIFI Transmitting** 

**Results: Pass** 

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
30.120	30.32	Н	40.00
444.360	40.96	Н	43.50
100.000	32.51	Н	46.00
111.560	30.19	V	43.50
33.560	37.20	V	40.00
968.240	39.22	V	46.00


Page 16 of 101

Report No: FCC1504075

Date: 2015-04-20



### Test Figure:



13.APR.2015 13:05:28 Date:


Page 17 of 101

Report No: FCC1504075

Date: 2015-04-20



### Test Figure:



13.APR.2015 13:07:32 Date:

Report No: FCC1504075 Page 18 of 101

Date: 2015-04-20



### Operation Mode: Keeping WIFI Transmitting under CH01 for 11g at 6Mbps

	1 0		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4824.00	52.28 (PK)	Н	74(Peak)/ 54(AV)
4824.00	52.32 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6Mbps

Date: 2015-04-20



### Operation Mode: Keeping WIFI Transmitting under CH06 for 11g at 6Mbps

1	1 0	0	0 1
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4874.00	50.97 (PK)	Н	74(Peak)/ 54(AV)
4874.00	52.70 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 6 Mbps

### Operation Mode: Keeping WIFI Transmitting under CH11 for 11g at 6Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4924	51.58 (PK)	Н	74(Peak)/ 54(AV)
4924	51.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 6 Mbps

Date: 2015-04-20




Please refer to the following test plots for details:

### CH01 for 11g at 6Mbps: Horizontal



# CH01 for 11g at 6Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-04-20



# CH06 for 11g at 6Mbps: Vertical



# CH06 for 11g at 6Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-04-20



### CH11 for 11g at 6Mbps: Vertical



# CH11 for 11g at 6Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-04-20



### Operation Mode: Keeping WIFI Transmitting under CH01 for 11b at 11Mbps

			_
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4824.00	50.82 (PK)	Н	74(Peak)/ 54(AV)
4824.00	51.09 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

# Operation Mode: Keeping WIFI Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4874.00	49.01 (PK)	Н	74(Peak)/ 54(AV)
4874.00	51.50 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Report No: FCC1504075 Page 24 of 101

Date: 2015-04-20



### Operation Mode: Keeping WIFI Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4924	50.79 (PK)	Н	74(Peak)/ 54(AV)
4924	50.63 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps

Date: 2015-04-20




Please refer to the following test plots for details:

# CH01 for 11b at 11Mbps: Horizontal



### CH01 for 11b at 11Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-04-20



# CH06 for 11b at 11Mbps: Vertical



# CH06 for 11b at 11Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-04-20



# CH11 for 11b at 11Mbps: Vertical



# CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Date: 2015-04-20



### Operation Mode: Keeping WIFI Transmitting under CH01 for 11n HT20 at 150Mbps

	1 0	0	1
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
4824.00	52.35 (PK)	Н	74(Peak)/ 54(AV)
4824.00	52.59 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 150Mbps

# Operation Mode: Keeping WIFI Transmitting under CH06 for 11n HT20 at 150Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4874.00	51.54 (PK)	Н	74(Peak)/ 54(AV)
4874.00	52.38 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 150Mbps

Report No: FCC1504075 Page 29 of 101

Date: 2015-04-20



### Operation Mode: Keeping WIFI Transmitting under CH11 for 11n HT20 at 150Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
4924	52.19 (PK)	Н	74(Peak)/ 54(AV)
4924	52.14 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24620		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 150Mbps

Date: 2015-04-20




Please refer to the following test plots for details:

### CH01 for 11n HT20 at 150Mbps: Horizontal



### CH01 for 11n HT20 at 150Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-04-20



### CH06 for 11n HT20 at 150Mbps: Vertical



# CH06 for 11n HT20 at 150Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Date: 2015-04-20



### CH11 for 11n HT20 at 150Mbps: Vertical



# CH11 for 11n HT20 at 150Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Date: 2015-04-20



### Operation Mode: Transmitting under CH01 for 11n HT40 at 150Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4844.00	51.51 (PK)	Н	74(Peak)/ 54(AV)
4844.00	52.27 (PK)	V	74(Peak)/ 54(AV)
7266.00	-	H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376	-	H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 150Mbps

# Operation Mode: Transmitting under CH04 for 11n HT40 at 150Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
4874.00	51.68 (PK)	Н	74(Peak)/ 54(AV)
4874.00	52.53 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 150Mbps

Report No: FCC1504075 Page 34 of 101

Date: 2015-04-20



### Operation Mode: Transmitting under CH07 for 11n HT40 at 150Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
4904	52.23 (PK)	Н	74(Peak)/ 54(AV)
4904	50.08 (PK)	V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 150Mbps

Date: 2015-04-20




Please refer to the following test plots for details:

# CH01 for 11n HT40 at 150Mbps: Horizontal



# CH01 for 11n HT40 at 150Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report


discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2015-04-20



### CH04 for 11n HT40 at 150Mbps: Vertical



# CH04 for 11n HT40 at 150Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No: FCC1504075


Date: 2015-04-20



## CH07 for 11n HT40 at 150Mbps: Vertical



#### CH07 for 11n HT40 at 150Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.


Report No: FCC1504075 Page 38 of 101

Date: 2015-04-20



#### 7.0 6dB Bandwidth Measurement

## 7.1 Test Setup



#### 7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

#### 7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 7.4 Test Result

Report No: FCC1504075 Page 39 of 101

Date: 2015-04-20



### 6dB Occupied Bandwidth

EUT		Tablet PC	Model		MiTraveler 708			
Mode		802.11b		Input	Input Voltage		AC120	)V
Temperati	ure	24 deg. C,		Hum	idity		56% R	Н
Channel	Char	Channel Frequency Transfer 6 (MHz) Rate (Mbps)		6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass/ Fail	
1		2412		1 10.04		1	0.5	Pass
6		2437		1 10.04		1	0.5	Pass
11		2462		1	1 10.0		0.5	Pass
1		2412 11		9.32		0.5	Pass	
6		2437	37 11 9.32			0.5	Pass	
11	2462 11 9		9.32		0.5	Pass		


Page 40 of 101

Report No: FCC1504075

Date: 2015-04-20



### 1. 802.11b at 1Mbps of CH01



Date: 11.APR.2015 11:23:21


Page 41 of 101

Report No: FCC1504075

Date: 2015-04-20



### 2. 802.11b at 1Mbps of CH06



Date: 11.APR.2015 11:47:02


Page 42 of 101

Report No: FCC1504075

Date: 2015-04-20



### 3. 802.11b at 1Mbps of CH11




Date: 11.APR.2015 11:50:30 Report No: FCC1504075 Page 43 of 101

Date: 2015-04-20



### 4. 802.11b at 11Mbps of CH01




Date: 11.APR.2015 11:34:44 Report No: FCC1504075 Page 44 of 101

Date: 2015-04-20



### 5. 802.11b at 11Mbps of CH06



Date: 11.APR.2015 11:41:16


Page 45 of 101

Report No: FCC1504075

Date: 2015-04-20



### 6. 802.11b at 11Mbps of CH11



Date: 11.APR.2015 11:57:43 Report No: FCC1504075 Page 46 of 101

Date: 2015-04-20



### 6dB Occupied Bandwidth

EUT	EUT Tablet PC M		Model		MiTraveler 708			
Mode		802.11g		Input Voltage			V	
Temperat	ure	24 deg. C,		Hum	idity		56% RI	H
Channel	Char	nnel Frequency (MHz)	Trai	ata nsfer ate bps)	6 dB Band (MHz		Minimum Limit (MHz)	Pass/ Fail
1		2412		6	16.41		0.5	Pass
6		2437		6	16.41	l	0.5	Pass
11		2462		6	16.41	l	0.5	Pass

Page 47 of 101


Report No: FCC1504075

Date: 2015-04-20



#### **Test Plots:**

### 1. 802.11g at 6Mbps of CH01



Date:


Page 48 of 101

Report No: FCC1504075

Date: 2015-04-20



### 2. 802.11g at 6Mbps of CH06



Date: 11.APR.2015 11:43:40


Page 49 of 101

Report No: FCC1504075

Date: 2015-04-20



### 3. 802.11g at 6Mbps of CH11



Date: 11.APR.2015 11:54:27 Report No: FCC1504075 Page 50 of 101

Date: 2015-04-20



## 6dB Occupied Bandwidth

EUT	EUT Tablet PC			Model		MiTraveler 708		
Mode		802.11n HT	20	Input Voltage AC120V		0V		
Temperati	ure	24 deg. C,		Hu	midity		56% R	RH
Channel	Chai	nnel Frequency (MHz)	Dat Trans Rat (Mb)	sfer e	6 dB Band (MHz		Minimum Limit (MHz)	Pass/ Fail
1		2412		150 17.50		6	0.5	Pass
6	2437		150 17.50		5	0.5	Pass	
11		2462		0	17.50	6	0.5	Pass

Page 51 of 101


Report No: FCC1504075

Date: 2015-04-20



#### **Test Plots:**

#### 1. 802.11n at HT20 of CH01



11.APR.2015 12:07:04 Date:


Page 52 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 2. 802.11n at HT20 of CH06




Date: 11.APR.2015 12:04:58 Report No: FCC1504075 Page 53 of 101

Date: 2015-04-20



#### 3. 802.11n at HT20 of CH11



Date: 11.APR.2015 12:03:33 Report No: FCC1504075 Page 54 of 101

Date: 2015-04-20



## 6dB Occupied Bandwidth

EUT	EUT Tablet PC Model		odel	MiTraveler 708				
Mode		802.11n HT	40	0 Input Voltage			AC12	0V
Temperat	ure	24 deg. C,		Hu	midity		56% R	RH
Channel	Char	nnel Frequency (MHz)	Dat Trans Rat (Mb)	sfer e	6 dB Band (MHz		Minimum Limit (MHz)	Pass/ Fail
1		2422		150 35.39		9	0.5	Pass
4	2437		150	150 35.30		6	0.5	Pass
7		2452		0	35.39	9	0.5	Pass

Page 55 of 101


Report No: FCC1504075

Date: 2015-04-20



#### **Test Plots:**

### 1. 802.11n at HT40 of CH01



11.APR.2015 12:09:45 Date:


Page 56 of 101

Report No: FCC1504075

Date: 2015-04-20



### 2.802.11n at HT40 of CH06



Date: 11.APR.2015 12:12:18


Page 57 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 3. 802.11n at HT40 of CH11



Date: 11.APR.2015 12:14:43 Report No: FCC1504075


Date: 2015-04-20



Page 58 of 101

## 8. Maximum Peak Output Power

## 8.1 Test Setup



#### 8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

#### **8.3 Test Procedure**

The RF power output was measured with a Power meter connected to the RF Antenna connector ( conducted measurement ) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Page 59 of 101

Report No: FCC1504075

Date: 2015-04-20



## **8.4Test Results**

EUT	Tablet PC	Model	MiTraveler 708		08	
Mode	802.11b	Input Voltage	AC120V			
Temperature	24 deg. C,	Humidity	56% RH			
Channel	Channel Frequency	Max. Power (	Output	Power Limit	Pass/ Fail	
Chamer	(MHz)	(dBm)		(dBm)		
1	2412	9.17		30	Pass	
6	2437	9.51		30	Pass	
11	2462	9.43		30	Pass	

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow: Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	Tablet PC	Model	MiTraveler 708				
Mode	802.11g	Input Voltage	AC120V				
Temperature	24 deg. C,	Humidity	56% RH				
Channel	Channel Frequency	Max. Powe	r Output	Power Limit	Pass/ Fail		
Chamiei	(MHz)	(dBn	n)	(dBm)			
1	2412	6.02	2	30	Pass		
6	2437	6.57	7	30	Pass		
11	2462	6.37	7	30	Pass		

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow: Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Page 60 of 101

Report No: FCC1504075

Date: 2015-04-20



EUT	Tablet PC	Model	MiTraveler 708				
Mode	802.11n (HT20)	Input Voltage	AC120V				
Temperature	24 deg. C,	Humidity	56% RH				
Channel	Channel Frequency (MHz)	Max. Power (dBm	•	Power Limit (dBm)	Pass/ Fail		
1	2412	6.33		30	Pass		
6	2437	6.79		30	Pass		
11	2462	6.75		30	Pass		

Note: 1. At finial test to get the worst-case emission at 150Mbps 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow: Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	Tablet PC	Model		MiTraveler	708	
Mode	802.11n (HT40)	Input Voltage	AC120V			
Temperature	24 deg. C,	Humidity	56% RH		I	
Channel	Channel Frequency (MHz)	Max. Power (dBm	•	Power Limit (dBm)	Pass/ Fail	
1	2422	6.08		30	Pass	
4	2437	6.23		30	Pass	
7	2452	6.43		30	Pass	

Note: 1. At finial test to get the worst-case emission at 150Mbps of 11n HT40 for CH01, CH04 and CH7

- 2. The result basic equation calculation as follow:
  - Max. Power Output = Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded


Report No: FCC1504075 Page 61 of 101

Date: 2015-04-20



# 9. Power Spectral Density Measurement

### 9.1 Test Setup



### 9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

#### 9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW  $\geq$  30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be  $\leq 8$  dBm.

Report No: FCC1504075 Page 62 of 101

Date: 2015-04-20



#### 9.4Test Result

EUT	EUT Tablet PC		Model	MiTraveler 708		
Mode	Mode 802.11b 11Mbps		Input Voltage	AC120V		
Temperatur	e	24 deg. C,	Humidity	56% RH		
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)			
			11Mbps			
1		2412	-14.95	8	Pass	
6	2437		-14.40	8	Pass	
11		2462	-14.62	8	Pass	

EUT	EUT		Model		MiTraveler 708		
Mode	Mode 802.11b 1Mbps		Input Voltage	AC120V			
Temperatur	e 24 deg. C,		Humidity		56% RH		
Channel	Channel Frequency		Final RF Power		Maximum Limit	Pass/ Fail	
Channel		(MHz)	Level (dBm)		(dBm)		
			1Mbps	}			
1	2412		-15.42		8	Pass	
6	2437		-15.27		8	Pass	
11		2462	-15.44		8	Pass	

Report No: FCC1504075

Date: 2015-04-20



EUT	EUT Tablet PC		Model	MiTraveler 708		
Mode 802.11g 6Mbps		Input Voltage		AC120V		
Temperatur	e	24 deg. C,	Humidity		56% RH	
C11	Cł	nannel Frequency	Final RF Power		Maximum Limit	Pass/ Fail
Channel		(MHz)	Level (dBm)		(dBm)	
			6Mbps			
1		2412	-23.59		8	Pass
6		2437	-22.61		8	Pass
11		2462	-22.21		8	Pass

EUT	EUT Tablet PC		Model	MiTraveler 7	08
Mode		802.11n HT20 150Mbps	Input Voltage	AC120V	
Temperatur	е	24 deg. C,	Humidity	56% RH	
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
			150Mbps		
1		2412	-21.80	8	Pass
6		2437	-21.49	8	Pass
11		2462	-21.49	8	Pass

EUT		Tablet PC	Model	MiTraveler 708	
Mode		802.11n (HT40) 150Mbps	Input Voltage	AC120V	
Temperature		24 deg. C,	Humidity	56% RH	
Channel		nannel Frequency (MHz)	Final RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
150Mbps					
1		2422	-25.20	8	Pass
4		2437	-25.18	8	Pass
7		2452	-25.01	8	Pass

The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduct event or which may be convenient.

adopt any other remedies which may be appropriate.

Page 64 of 101


Report No: FCC1504075

Date: 2015-04-20



## 9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01



11.APR.2015 16:06:44 Date:


Page 65 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 2. 802.11b at 11Mbps at CH06



Date: 11.APR.2015 16:06:07


Page 66 of 101

Report No: FCC1504075

Date: 2015-04-20



### 3. 802.11b at 11Mbps of CH11



Date: 11.APR.2015 16:04:34


Page 67 of 101

Report No: FCC1504075

Date: 2015-04-20



### 4. 802.11b at 1Mbps of CH1



Date: 11.APR.2015 15:56:23


Page 68 of 101

Report No: FCC1504075

Date: 2015-04-20



### 5. 802.11b at 1Mbps of CH6



Date: 11.APR.2015 16:02:21


Page 69 of 101

Report No: FCC1504075

Date: 2015-04-20



### 6. 802.11b at 1Mbps of CH11



Date: 11.APR.2015 15:54:40


Page 70 of 101

Report No: FCC1504075

Date: 2015-04-20



### 7. 802.11g at 6Mbps of CH1



Date: 11.APR.2015 16:00:19


Page 71 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 8. 802.11g at 6 Mbps of CH6



11.APR.2015 15:59:30 Date:


Page 72 of 101

Report No: FCC1504075

Date: 2015-04-20



## 9. 802.11g at 6 Mbps of CH11



Date: 11.APR.2015 16:03:36


Page 73 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 10. 802.11n at HT20 of CH01



11.APR.2015 15:49:53 Date:


Page 74 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 11. 802.11n at HT20 of CH06



11.APR.2015 15:51:15 Date:


Page 75 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 12. 802.11n at HT20 of CH11



11.APR.2015 15:53:53 Date:


Page 76 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 13. 802.11n at HT40 of CH01



Date: 11.APR.2015 15:45:24


Page 77 of 101

Report No: FCC1504075

Date: 2015-04-20



# 14. 802.11n at HT40 of CH04



Date: 11.APR.2015 15:48:25


Page 78 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 15. 802.11n at HT40 of CH07



Date: 11.APR.2015 15:44:15


Date: 2015-04-20



Page 79 of 101

# 10 Out of Band Measurement

# 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

# 10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### **10.3 Test Procedure**

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector)

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

# 10.4 Test Result

Please see next pages

Note: For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Date: 2015-04-20




# For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	MiTraveler 708	
Mode	Keeping Transmitting	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2400	PK (dBμV/m)	57.1	Limit	74(dBµV/m)
	AV (dBμV/m)	39.3	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	41.2	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Liiiit	$54(dB\mu V/m)$

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into an will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 81 of 101

Report No: FCC1504075

Date: 2015-04-20




# CH11 at 11Mbps

Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	MiTraveler 708	
Mode	Keeping Transmitting	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBµV/m)	43.7	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)			$54(dB\mu V/m)$

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2015-04-20




# For 802.11b mode

CH01 at 1Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	MiTraveler 708			
Mode	Keeping Transmitting	Input Voltage	DC3.7V			
Temperature	24 deg. C,	Humidity	56% RH			
Test Result:	Pass	Detector	PK			
2400	PK (dBμV/m)	56.8	T ::4	$74(dB\mu V/m)$		
	AV (dBμV/m)	39.0	Limit	$54(dB\mu V/m)$		
2390	PK (dBμV/m)	41.1	Limit	$74(dB\mu V/m)$		
	AV (dBμV/m)		Lillit	54(dBμV/m)		

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into an will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 83 of 101

Report No: FCC1504075

Date: 2015-04-20




# CH11 at 1Mbps

Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	MiTraveler 708	
Mode	Keeping Transmitting	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBμV/m)	42.0	T : :/	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2015-04-20




# For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	N	/IiTraveler 708
Mode	Keeping Transmitting	Input Voltage		DC3.7V
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2400	PK (dBμV/m)	60.2	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)	41.9	Limit	54(dBμV/m)
2390	PK (dBμV/m)	43.6	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Lillit	$54(dB\mu V/m)$

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 85 of 101

Report No: FCC1504075

Date: 2015-04-20




# CH11 at 6Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	MiTraveler 708	
Mode	Keeping Transmitting	g Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBμV/m)	45.5	T * */	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2015-04-20




# For 802.11n (HT20) mode

CH01 at 150Mbps

10.4 Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	N	AiTraveler 708
Mode	Keeping Transmitting	Input Voltage		DC3.7V
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2400	PK (dBμV/m)	61.2	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)	42.3	Limit	54(dBμV/m)
2390	PK (dBμV/m)	44.1	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Liiiit	$54(dB\mu V/m)$

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into an will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 87 of 101

Report No: FCC1504075

Date: 2015-04-20




# CH11 at 150Mbps

# Band-edge and Restricted band Measurement

EUT	Tablet PC	Model	MiTraveler 708	
EUI	Tablet PC	Model	Miliraveier 708	
Mode	Keeping Transmitting	g Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBµV/m)	46.4	T : .,	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2015-04-20




# For 802.11n (HT40) mode

CH01 at 150Mbps

10.4 Band-edge and Restricted band Measurement

	101. Build 4084 with 11000110000 outle 111000011011011						
EUT	Tablet PC	Model	MiTraveler 708				
Mode	Keeping Transmitting	Input Voltage	DC3.7V				
Temperature	24 deg. C,	Humidity	56% RH				
Test Result:	Pass	Detector	PK				
2400	PK (dBμV/m)	58.6	T ::4	$74(dB\mu V/m)$			
	AV (dBμV/m)	40.2	Limit	$54(dB\mu V/m)$			
2390	PK (dBµV/m)	40.9	Limit	74(dBμV/m)			
	AV (dBμV/m)		LIIIII	54(dBμV/m)			

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into an will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 89 of 101

Report No: FCC1504075

Date: 2015-04-20




# CH7 at 150Mbps

Band-edge and Restricted band Measurement

EUT	Tablet PC	Model		MiTraveler 708
Mode	Keeping Transmitting	Input Voltage	DC3.7V	
Temperature	24 deg. C,	Humidity	56% RH	
Test Result:	Pass	Detector	PK	
2483.5	PK (dBμV/m)	49.8	T,	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBµV/m)

# **Test Figure:**



Note: The Max. FS in Restrict Band are measured in conventional method.

Date: 2015-04-20



Page 90 of 101

# 11.0 Antenna Requirement

# 11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

# 11.2 Antenna Connected construction

Integral antennas used. The maximum Gain of each antenna is 1.0 dBi.

Report No: FCC1504075 Page 91 of 101

Date: 2015-04-20




# 12.0 FCC Label

# FCC ID: 2AEJJ-JCBA9X

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### Mark Location:



Page 92 of 101

Report No: FCC1504075

Date: 2015-04-20



#### 13.0 **Photo of testing**

Conducted Emission Test Setup:



Page 93 of 101

Report No: FCC1504075

Date: 2015-04-20



# Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduce the report of the report.

Page 94 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduct event or which may be converted.

Page 95 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to detect any other remodules which may be expressible.

Page 96 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 97 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 98 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 99 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduce the report of the report.


Page 100 of 101


Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate

Page 101 of 101

Report No: FCC1504075

Date: 2015-04-20



# **Photos of EUT**





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to reduct event or which may be converted.