



# FCC PART15B TEST REPORT

For

Product Name:	<b>3-Channel Door Popper System Controller</b>
Trademark:	<b>N/A</b>
FCC ID:	<b>2AEL5PC-3</b>
Model Number:	<b>PC-3</b>
Prepared For :	<b>Digitel, LLC</b>
Address :	2094 N Dragoon St, Tucson AZ,USA
Prepared By :	<b>Shenzhen BCTC Technology Co., Ltd.</b>
Address :	A. Floor 3, 44 Building, Tanglang Industrial Park B, Taoyuan Street, Nanshan District, Shenzhen, China
Test Date:	<b>Apr. 13 - Apr. 20, 2015</b>
Date of Report :	<b>Apr. 20, 2015</b>
Report No.:	<b>BCTC-150403969</b>



## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION</b> .....	<b>3</b>
<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
1.1. Report information .....	4
1.2. Measurement Uncertainty .....	4
1.3. Test Facility.....	4
1.4. Test Uncertainty .....	4
<b>2. PRODUCT DESCRIPTION</b> .....	<b>5</b>
2.1. EUT Description .....	5
2.2. Block Diagram of EUT Configuration.....	5
2.3. Test Conditions .....	5
<b>3. TEST RESULTS SUMMARY</b> .....	<b>6</b>
<b>4. TEST EQUIPMENT USED</b> .....	<b>7</b>
4.1. For Conducted Emission Test .....	7
4.2. For Radiated Emission Measurement .....	7
<b>5. CONDUCTED EMISSION TEST</b> .....	<b>8</b>
5.1. Block Diagram of Test Setup .....	8
5.2. Test Standard.....	8
5.3. Conducted Emission Limit (Class B).....	8
5.4. EUT Configuration on Test.....	8
5.5. Operating Condition of EUT .....	8
5.6. Test Procedure.....	9
5.7. Test Result.....	9
<b>6. RADIATED EMISSION MEASUREMENT</b> .....	<b>10</b>
6.1. Block Diagram of Test Setup .....	10
6.2. Test Standard.....	11
6.3. Radiated Emission Limit(Class B).....	11
6.4. EUT Configuration on Test.....	12
6.5. Test Procedure.....	12
6.6. Test Result.....	12
<b>APPENDIX I (PHOTOS OF THE EUT)</b> .....	<b>17</b>
<b>APPENDIX II (TEST PHOTOS OF THE EUT)</b> .....	<b>21</b>



## TEST REPORT DECLARATION

Applicant	:	Digitel, LLC
Address	:	2094 N Dragoon St, Tucson AZ USA
EUT Description	:	<b>3-Channel Door Popper System Controller</b>
Model Number	:	<b>PC-3</b>
Operation Frequency:		<b>433.92MHz(Only receiver)</b>

Test Standards:

**FCC Part 15 B: 2014**

**ANSI C63.4-2014**

The EUT described above is tested by US to determine the maximum emission levels emanating from the EUT, the maximum emission levels are compared to the FCC Part 15 B Subpart Class B limits.

The measurement results are contained in this test report and Shenzhen BCTC Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these measurements.

Also, this report shows that the EUT is to be technically compliant with the FCC requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen BCTC Technology Co., Ltd.

Date of Test:

Apr. 13 - Apr. 20, 2015

Prepared by(Engineer):

Shan Zeng

Reviewer(Quality Manager):

Sophie Lee

Approved & Authorized Signer(Manager):

Casey Wang





## 1. GENERAL INFORMATION

### 1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BCTC approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BCTC in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BCTC therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BCTC, unless the applicant has authorized BCTC in writing to do so.

### 1.2. Measurement Uncertainty

Available upon request.

### 1.3. Test Facility

Site Description	
Name of Firm	: Shenzhen BCTC Technology Co., Ltd.
Site Location	: No.101, Yousong Road, Longhua New District, Shenzhen, China
FCC Registration No.	187086

### 1.4. Test Uncertainty

Conducted Emission Uncertainty	=	$\pm 2.66\text{dB}$
Radiated Emission Uncertainty	=	$\pm 4.15\text{dB}$



## 2. PRODUCT DESCRIPTION

### 2.1.EUT Description


Description : **3-Channel Door Popper System Controller**

Applicant : **Digitel, LLC**  
2094 N Dragoon St, Tucson AZ USA

Manufacturer : **Zhongshan Eagle Electronic Technology Co., Ltd.**  
No.40 Yanhe East Road, Dongsheng Town, Zhongshan City,  
Guangdong, China

Model Number : **PC-3**

### 2.2.Block Diagram of EUT Configuration



### 2.3.Test Conditions

Temperature: 23~25℃

Relative Humidity: 55~63 %



### 3. TEST RESULTS SUMMARY

**Table 1 Test Results Summary**

Test Items	Test Results
Conducted disturbance	N/A
Radiated disturbance	Pass

Remark: "N/A" means "Not applicable."



## 4. TEST EQUIPMENT USED

### 4.1. For Conducted Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Aug. 25, 14	1 Year
2	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Aug. 25, 14	1 Year
3	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Aug. 25, 14	1 Year
4	Conical	Emtek	N/A	N/A	N/A	N/A
5	Voltage Probe	Schwarzbeck	TK9416	N/A	Aug. 25, 14	1 Year
6	Coaxial Switch	Anritsu	MP59B	6100214550	Aug. 25, 14	1 Year


### 4.2. For Radiated Emission Measurement

#### Anechoic Chamber

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.05	1 Year
2	Test Receiver	R&S	ESPI	101318	2014.06.06	1 Year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.05	1 Year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.06	1 Year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.06	1 Year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.05	1 Year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.05	1 Year
8	Amplifier	EM	EM-30180	060538	2014.12.21	1 Year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.07	1 Year
10	Power Meter	R&S	NRVS	100696	2014.07.05	1 Year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.05	1 Year
12	RF cables	R&S	R203	R20X	2014.07.05	1 Year

## 5. CONDUCTED EMISSION TEST

### 5.1. Block Diagram of Test Setup



(EUT: **3-Channel Door Popper System Controller** )

### 5.2. Test Standard

FCC Part 15 B: 2014

### 5.3. Conducted Emission Limit (Class B)

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.

### 5.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet Part 15 B requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

#### 5.4.1. **3-Channel Door Popper System Controller**

Model Number: **PC-3**

### 5.5. Operating Condition of EUT

5.5.1. Setup the EUT and simulators as shown in Section 5.1.

5.5.2. Turn on the power of all equipments.

5.5.3. Let the EUT work in test modes (EUT Working) and test it.





## 5.6. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESHS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

The bandwidth of the test receiver (R&S Test Receiver ESHS30) is set at 10KHz.


## 5.7. Test Result

Powered by car battery solely, so Conducted emission is not applicable

## 6. RADIATED EMISSION MEASUREMENT

### 6.1. Block Diagram of Test Setup


#### 6.1.1. Block Diagram of connection between the EUT and the simulators




(EUT: **3-Channel Door Popper System Controller** )

#### 6.1.2. Anechoic Chamber Test Setup Diagram

Radiated Emission Test-Up Frequency 30MHz~1GHz



Radiated Emission Test-Up Frequency Above 1GHz





## 6.2. Test Standard

FCC Part 15 B: 2014

## 6.3. Radiated Emission Limit(Class B)

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB $\mu$ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0

Note:(1) The smaller limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or system.



#### 6.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize Its emission characteristics in normal application.

##### Operating Condition of EUT

6.4.1.Setup the EUT as shown on Section 6.1

6.4.2.Turn on the power of all equipments.

6.4.3.Let the EUT work in test mode(EUT working) and measure it.

#### 6.5.Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

The bandwidth setting on the test receiver is 120 KHz.

The EUT is tested in Anechoic Chamber. The frequency range from 30MHz to 1000MHz is checked. All the test results are listed in Section 6.6.

#### 6.6.Test Result

**PASS**

Please refer to the following pages.

Receive mode:

倍测检测  
BCTC TESTAddress: No. 101, Yousong Road, Longhua New District,  
Shenzhen, Guangdong P.R. China  
Tel: 400-788-9558

## Radiated Emission Measurement


File : 4

Data : #284

Date: 2015/04/17

Time: 17:33:39

80.0 dBuV/m



Site: 966 BCTC Chamber #1

Limit: FCC\_PART15\_Rx\_03m\_QP

EUT: 3-Channel Door Popper System Controller

M/N: PC-3

Polarization: **Horizontal**

Power: DC 12V

Distance: 3m

Temperature: 26

Humidity: 55 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		80.9275	42.36	-18.10	24.26	40.00	-15.74	QP		
2		91.1746	50.15	-17.39	32.76	43.50	-10.74	QP		
3	*	97.4560	50.65	-16.76	33.89	43.50	-9.61	QP		
4		107.8877	44.36	-15.75	28.61	43.50	-14.89	QP		
5		143.3261	41.27	-13.21	28.06	43.50	-15.44	QP		
6		210.0482	48.88	-15.91	32.97	43.50	-10.53	QP		



Address: No. 101, Yousong Road, Longhua New District,  
Shenzhen, Guangdong P.R. China  
Tel: 400-788-9558

**Radiated Emission Measurement**


File : 4

Data : #283

Date: 2015/04/17

Time: 17:28:03

80.0 dBuV/m



Site 966 BCTC Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC\_PART15\_Rx\_03m\_QP

Power: DC 12V

Humidity: 55 %

EUT: 3-Channel Door Popper System Controller

Distance: 3m

M/N: PC-3

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		91.4949	39.01	-17.36	21.65	43.50	-21.85	QP		
2		97.7983	38.56	-16.71	21.85	43.50	-21.65	QP		
3		143.3261	30.73	-13.21	17.52	43.50	-25.98	QP		
4	*	210.0482	38.24	-15.91	22.33	43.50	-21.17	QP		
5		232.5318	33.78	-14.91	18.87	46.00	-27.13	QP		
6		952.0937	25.13	-0.46	24.67	46.00	-21.33	QP		




## ABOVE 1GHz: (1G-6GHz)

EUT:	3-Channel Door Popper System Controller	Model Name:	PC-3
Temperature:	24 °C	Relative Humidity:	54 %
Pressure:	1010 hPa	Polarization :	Horizontal
Test Power :	DC 12V	Test Mode :	Receive mode

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1714.840	52.38	-15.54	36.84	74.00	-37.16	peak
3492.606	50.23	-9.42	40.81	74.00	-33.19	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.






EUT:	3-Channel Door Popper System Controller	Model Name:	PC-3
Temperature:	24 °C	Relative Humidity:	54 %
Pressure:	1010 hPa	Polarization :	Vertical
Test Power :	DC 12V	Test Mode :	Receive mode

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
1089.811	54.94	-19.58	35.36	74.00	-37.64	peak
4074.465	50.23	-6.07	44.16	74.00	-29.84	peak

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.









## **APPENDIX I (PHOTOS OF THE EUT)**

**EUT Photo 1****EUT Photo 2**

**EUT Photo 3****EUT Photo 4**




**EUT Photo 5**





## **APPENDIX II (TEST PHOTOS OF THE EUT)**



\*\*\*\*\* END OF REPORT \*\*\*\*\*