## RF EXPOSURE EVALUATION

## **EUT Specification**

Report No.: NTC1412675F-1

EUT	Instant Comfort(Personal Comfort)				
Frequency band	□WLAN: 2.412GHz ~ 2.462GHz				
(Operating)	□WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz				
	□WLAN: 5.745GHz ~ 5825GHz				
	⊠Others(Bluetooth: 2.402GHz ~ 2.480GHz)				
Device category	☐Portable (<20cm separation)				
	⊠Mobile (>20cm separation)				
	Others				
Antenna diversity	⊠Single antenna				
	☐Multiple antennas				
	☐Tx diversity				
	☐Rx diversity				
	☐Tx/Rx diversity				
Max. output power	4.04dBm(2.54mW)				
Antenna gain	0dBi (declared by manufacturer)				
Evaluation applied					
	☐SAR Evaluation				

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power	Average Time				
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm <sup>2</sup> )					
(A) Limits for Occupational/Control Exposures								
300-1500		F/300		6				
1500-100000			5	6				
(B) Limits for General Population/Uncontrol Exposures								
300-1500			F/1500	6				
1500-100000		1		30				

## Friis transmission formula: Pd=(Pout\*G)\(4\*pi\*R<sup>2</sup>)

Where

Pd= Power density in mW/cm<sup>2</sup>

Pout=output power to antenna in Mw

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Report No.: NTC1412675F-1

## **Measurement Result**

Channel	Channel	Max	Tolerance	Max	Power	Power		
	Frequency	Output		Tune-UP	density at	density		
	(MHz)	power		power	20cm (mW/	Limits		
		(dBm)		(mW)	cm <sup>2</sup> )	(mW/cm <sup>2</sup> )		
For BLE GFSK								
Low	2402.00	3.90	±0.1	2.51	5.00e-4	1		
Middle	2442.00	4.04	±0.1	2.59	5.16e-4	1		
High	2480.00	3.34	±0.1	2.21	4.39e-4	1		