

Emissions Test Report

EUT Name: Wi-Fi Router

Model No.: B010001 (USA), B010002 (IC)

CFR 47 Part 15.247: 2016 and RSS 247: 2017

Prepared for:

Clifford Clarke
eero inc.
500 Howard Street, Suite 900
San Francisco, CA 94105
Tel: (415) 738-7972
Fax:

Prepared by:

TUV Rheinland of North America, Inc.
1279 Quarry Lane
Pleasanton, CA 94566
Tel: (925) 249-9123
Fax: (925) 249-9124
<http://www.tuv.com/>

Report/Issue Date: May 10, 2017
Job # 0000146430
Report Number: 31761398.001

Revisions

Revision No.	Date MM/DD/YYYY	Reason for Change	Author
0	05/10/2017	Original Document	N/A

Note: Latest revision report will replace all previous reports.

Statement of Compliance

Manufacturer: eero inc.
500 Howard Street, Suite 900
San Francisco, CA 94105
(415) 738-7972

Requester / Applicant: Clifford Clarke

Name of Equipment: Wi-Fi Router
Model No. B010001 (USA), B010002 (IC)
Type of Equipment: Intentional Radiator
Application of Regulations: CFR 47 Part 15.247: 2016 and RSS 247: 2017
Test Dates: 01 May 2017 to 04 May 2017

Guidance Documents:

Emissions: ANSI C63.10-2013, KDB 558074 D01 DTS Measurement Guidance v03r05, KDB 662911 D01 Multiple Transmitter Output v02r01

Test Methods:

Emissions: ANSI C63.10-2013, KDB 558074 D01 DTS Measurement Guidance v03r05, KDB 662911 D01 Multiple Transmitter Output v02r01

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report contains data that are not covered by A2LA accreditation. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.

Kerwinn Corpuz

Test Engineer

Date May 10, 2017

David Spencer

A2LA Signatory

Date May 10, 2017



Industry
Canada Industrie
Canada

Testing Cert #3331.02

US1131

2932M

Table of Contents

1	Executive Summary	7
1.1	Scope	7
1.2	Purpose	7
1.3	Summary of Test Results	8
1.4	Special Accessories	8
1.5	Equipment Modifications	8
2	Laboratory Information	9
2.1	Accreditations & Endorsements	9
2.1.1	US Federal Communications Commission	9
2.1.2	NIST / A2LA	9
2.1.3	Canada – Industry Canada	9
2.1.4	Japan – VCCI	9
2.1.5	Acceptance by Mutual Recognition Arrangement	10
2.2	Test Facilities	10
2.2.1	Emission Test Facility	10
2.2.2	Immunity Test Facility	10
2.3	Measurement Uncertainty	10
2.3.1	Sample Calculation – radiated & conducted emissions	11
2.3.2	Measurement Uncertainty	11
2.3.3	Measurement Uncertainty Immunity	12
2.4	Calibration Traceability	12
3	Product Information	13
3.1	Product Description	13
3.2	Equipment Configuration	13
3.3	Operating Mode	13
3.4	Unique Antenna Connector	14
3.4.1	Results	14
4	Emissions	15
4.1	Output Power Requirements	15
4.1.1	Test Method	15
4.1.2	Results	16
4.2	Occupied Bandwidth	18
4.2.1	Test Method	18
4.2.2	Results	18
4.3	Peak Power Spectral Density	21
4.3.1	Test Method	21
4.3.2	Results	21
4.4	Out of Band Emissions	24
4.4.1	Test Method	24
4.4.2	Results	24

Table of Contents

4.5	Transmit Spurious Emissions	28
4.5.1	Test Methodology	28
4.5.2	Transmitter Spurious Emission Limit	29
4.5.3	Test Results	29
4.6	AC Conducted Emissions	42
4.6.1	Test Methodology	42
4.6.2	Test Results	42
4.7	Maximum Permissible Exposure	48
4.7.1	Test Methodology	48
4.7.2	RF Exposure Limit	48
4.7.3	EUT Operating Condition	49
4.7.4	Classification	49
4.7.5	Test Results	49
4.7.6	Sample Calculation	49
5	Test Equipment List	50
5.1	Equipment List	50
6	EMC Test Plan	51
6.1	Introduction	51
6.2	Customer	51
6.3	Equipment Under Test (EUT)	52
6.4	Test Specifications	56

Index of Tables

Table 1: Summary of Test Results	8
Table 2: RF Output Power at the Antenna Port – Test Results – Non Beamforming	16
Table 3: Occupied Bandwidth – Test Results.....	19
Table 4: Peak Power Spectral Density – Test Results – Non Beamforming	22
Table 5: Emissions at the Band-Edge – Test Results.....	25
Table 6: Transmit Spurious Emission at Band-Edge Requirements.....	30
Table 7: AC Conducted Emissions – Test Results.....	43
Table 8: Customer Information	51
Table 9: Technical Contact Information.....	51
Table 10: EUT Specifications	52
Table 11: Antenna Information	53
Table 12: EUT Channel Power Specifications	54
Table 13: Interface Specifications	55
Table 14: Supported Equipment	55
Table 15: Description of Sample used for Testing.....	55
Table 16: Description of Test Configuration used for Radiated Measurement.....	55
Table 17: Test Specifications	56

1 Executive Summary

1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.247: 2016 and RSS 247: 2017 based on the results of testing performed on 01 May 2017 to 04 May 2017 on the Wi-Fi Router Model B010001 (USA), B010002 (IC) manufactured by eero inc. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report. The 2402 MHz to 2480 MHz frequency band for Bluetooth LE, 2405 MHz to 2475 MHz frequency band for Thread (Zigbee) and 2412 MHz to 2462 MHz frequency band for WiFi are covered in this document.

1.3 Summary of Test Results

Table 1: Summary of Test Results

Test	Test Method ANSI C63.10	Test Parameters (Measured)	Result
Spurious Emission in Transmitted Mode	CFR47 15.209, 2.1053, 2.1057, RSS-GEN Sect.8.9	Class B	Complied
Restricted Bands of Operation	CFR47 15.205, RSS GEN Sect.8.10	Class B	Complied
AC Power Conducted Emission	CFR47 15.207, RSS-GEN Sect.8.8	Class B	Complied
Occupied Bandwidth	CFR47 15.247 (a1), 2.1049, RSS GEN Sect.6.6	See plots	Complied
Maximum Output Power	CFR47 15.247 (b), 2.1046, RSS 247 Sect. 5.4 (d)	18.40 dBm (Thread)	Complied
Peak Power Spectral Density	CFR47 15.247 (e), RSS 247 Sect. 5.2 (b)	< 8 dBm/3kHz	Complied
Out of Band Emission	CFR47 15.247 (d), 2.1051, 2.1057, RSS 247 Sect.5.5	30 MHz - 26 GHz < 20 dBm/100kHz	Complied
RF Exposure	CFR47 15.247 (i), 2.1093 RSS-102 Issue 5	General Population	Complied

Note: This test report covers 2400 MHz to 2483.5 MHz band.

1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

1.5 Equipment Modifications

None

2 Laboratory Information

2.1 Accreditations & Endorsements

2.1.1 US Federal Communications Commission



TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 is recognized by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (US1131). The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, and 90. The accreditation is updated every 3 years.

2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:1999 and ISO 9002 (Lab Code Testing Cert #3331.02). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

2.1.3 Canada – Industry Canada



TUV Rheinland of North America at the 1279 Quarry Ln, Pleasanton, CA 94566 address is accredited by Industry Canada for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by Industry Canada (File Number 2932M). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0261

2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member

country.

2.2 Test Facilities

All of the test facilities are located at 1279 Quarry Lane, Pleasanton, California 94566, USA. The 2305 Mission College, Santa Clara, 95054, USA location is considered a Pleasanton annex.

2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 and 5 meters. The site is listed with the FCC and accredited by A2LA (Lab Code Testing Cert #3331.02). The 3/5-meter semi-anechoic chamber used to collect the radiated data has been verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 meter and 5 meters. A report detailing this site can be obtained from TUV Rheinland of North America.

2.2.2 Immunity Test Facility

ESD, EFT, Surge, PQF: These tests are performed in an environmentally controlled room with a 3.7 m x 4.8 m x 3.175 mm thick aluminum floor connected to PE ground.

For ESD testing, tabletop equipment is placed on an insulated mat with a surface resistivity of 10^9 Ohms/square on a 1.6 m x 0.8 m x 0.8 m high non-conductive table with a 3.175 mm aluminum top (Horizontal Coupling Plane). The HCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors. The Vertical Coupling Plane consists of an aluminum plate 50 cm x 50 cm x 3.175 mm thick. The VCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors.

For EFT, Surge, PQF, the HCP and VCP are removed.

RF Field Immunity testing is performed in a 7.3m x 4.3m x 4.1m anechoic chamber.

RF Conducted and Magnetic Field Immunity testing is performed on a 4.8m x 3.7m x 3.175mm thick aluminum ground plane.

All test areas allow a minimum distance of 1 meter from the EUT to walls or conducting objects.

2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1st Edition, 1995.

The *Combined Standard Uncertainty* is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dBμV)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V} / \text{m}}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

2.3.2 Measurement Uncertainty

Per CISPR 16-4-2	U _{lab}	U _{cispr}
Radiated Disturbance @ 10 meters		
30 – 1,000 MHz	2.25 dB	4.51 dB
Radiated Disturbance @ 3 meters		
30 – 1,000 MHz	2.26 dB	4.52 dB
1 – 6 GHz	2.12 dB	4.25 dB
6 – 18 GHz	2.47 dB	4.93 dB
Conducted Disturbance @ Mains Terminals		
150 kHz – 30 MHz	1.09 dB	2.18 dB
Disturbance Power		
30 MHz – 300 MHz	3.92 dB	4.3 dB

Voltech PM6000A

The estimated combined standard uncertainty for harmonic current and flicker measurements is $\pm 5.0\%$.	Per CISPR 16-4-2 Methods
--	--------------------------

2.3.3 Measurement Uncertainty Immunity

The estimated combined standard uncertainty for ESD immunity measurements is $\pm 8.2\%$.	Per IEC 61000-4-2
The estimated combined standard uncertainty for radiated immunity measurements is ± 4.10 dB.	Per IEC 61000-4-3
The estimated combined standard uncertainty for conducted immunity measurements with CDN is ± 3.66 dB	Per IEC 61000-4-6
The estimated combined standard uncertainty for power frequency magnetic field immunity is $\pm 2.9\%$.	Per IEC 61000-4-8

Thermo KeyTek EMC Pro

The estimated combined standard uncertainty for EFT fast transient immunity measurements is $\pm 2.6\%$.
The estimated combined standard uncertainty for surge immunity measurements is $\pm 2.6\%$.
The estimated combined standard uncertainty for voltage variation and interruption measurements is $\pm 1.74\%$.

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

3 Product Information

3.1 Product Description

The Model B010001 (USA), B010002 (IC), Wi-Fi Router, is a Wi-Fi router for the home capable of operating in the 2.4 GHz and 5 GHz frequency bands over 20 MHz, 40 MHz and 80 MHz channels.

3.2 Equipment Configuration

A description of the equipment configuration is given in the Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of an EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.3 Operating Mode

A description of the operation mode is given in the Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

The final operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.4 Unique Antenna Connector

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

3.4.1 Results

The Wi-Fi Router has five FPCB antennas. The 2.4GHz band uses Flex Printed Circuit Board (FPCB) dipole antennas (Antenna 2, Antenna 4 and Antenna 7) and has maximum gain +5.43 dBi for WiFi and +3.09 dBi for BLE and Thread (Zigbee). Antenna 5 is used independently for Bluetooth LE / Thread (Zigbee) and has no beam forming capability.

Refer to Table 11 for additional antenna information.

There is no additional antenna available.

4 Emissions

Testing was performed in accordance with CFR 47 Part 15.247: 2016 and RSS 247: 2017. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in section 8 of the standard were used.

4.1 Output Power Requirements

The maximum output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.


The maximum output power and harmonics shall not exceed CFR47 Part 15.247 (b):2016 and RSS 247: 2017 Sect. 5.4 (d).

The maximum transmitted power in the band 2400-2483.5 MHz: 1 W

4.1.1 Test Method

The ANSI C63.10-2013 Section 11.9.2.2.2. Conducted method was used to measure the channel power output. The preliminary investigation was performed at different data rate / chain to determine the highest power output for each mode. The worst findings were conducted on 3 channels in each operating range per CFR47 Part 15.247(b) and RSS 247 Sect. 5.4(d); 2400 MHz to 2483.5 MHz. The worst mode results indicated below.

Test Setup:



Method AVGSA-1 of "KDB 558074 – DTS Measurement Guidance v03r05" applies since the EUT continuously transmits with duty cycle greater than 98%. Sample detector was used.

Each chain was measured individually and applied the measure-and-sum approach per KDB662911.

The total directional gain (7.68 dBi) was calculated by summing Antenna 4 (3.84 dBi) and Antenna 7 (5.43 dBi).

The duty cycle, CF = 10Log(1/duty cycle), was applied for BLE.

4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 2: RF Output Power at the Antenna Port – Test Results – Non Beamforming

Test Conditions: Conducted Measurement, Normal Temperature				
Antenna Type: FPCB		Power Setting: See test plan		
Total Directional Gain: + 7.68 dBi (WiFi) Max. Directional Gain: Antenna 4 = + 3.84 dBi (WiFi); Antenna 7 = + 5.43 dBi (WiFi); Antenna 2 = + 3.09 dBi (BLE and Thread)				
Signal State: Modulated at 100%.				
Ambient Temp.: 22° C		Relative Humidity: 38%		
802.15.4				
Operating Channel (MHz)	Packet	Limit [dBm]	Max. Power [dBm]	Margin [dB]
2405.00	Thread	30.00	18.40	-11.60
2440.00	Thread	30.00	18.16	-11.84
2475.00	Thread	30.00	17.72	-12.28
Note: 1. The highest output power was observed at Thread, 1 Data Streams. 2. Plots for all the measurements stated above were taken, to reduce complexity and bulkiness of the report Highlighted Plots are placed in the report.				




Figure 1: Maximum Transmitted Power, 2405 MHz for Thread

4.2 Occupied Bandwidth

The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.


The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.

The minimum 6 dB bandwidth shall be at least 500 kHz.

4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth according to ANSI C63.10:2013 Section 11.8. The measurement was performed with modulation per CFR47 15.247 (a) (2) 2016 and RSS Gen Sect. 6.6 2014. The preliminary investigation was performed to find the narrowest 26 dB bandwidth for each operational mode at different data rates. This worst finding was performed on 3 channels in each operating frequency range; 2400 MHz to 2483.5 MHz, a 6 dB bandwidth was used. The worst results indicated below.

Test Setup:



4.2.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 3: Occupied Bandwidth – Test Results

Test Conditions: Conducted Measurement, Normal Temperature			
Antenna Type: FPCB		Power Setting: See test plan	
Total Directional Gain: + 7.68 dBi (WiFi) Max. Directional Gain: Antenna 4 = + 3.84 dBi (WiFi); Antenna 7 = + 5.43 dBi (WiFi); Antenna 2 = + 3.09 dBi (BLE and Thread)			
Signal State: Modulated at 100%.			
Ambient Temp.: 22° C		Relative Humidity: 38%	
Bandwidth (MHz) for 802.15.4			
Freq. (MHz)	Packet	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
2405	Thread	1.630	2.2617
2440	Thread	1.630	2.2685
2475	Thread	1.631	2.2786
Note: 1. The bandwidth was measured at Thread, 1 Data Streams. 2. Plots for all the measurements stated above were taken, to reduce complexity and bulkiness of the report Highlighted Plots are placed in the report.			




Figure 2: 6dB & 99% Occupied Bandwidth, 2475 MHz for Thread


4.3 Peak Power Spectral Density

According to the CFR47 Part 15.247 (e) and RSS 247 Sect.5.2 (b), the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.1 Test Method

The conducted method was used to measure the channel power output per ANSI C63.10-2013 Section 11.10.3. The measurement was performed with modulation per CFR47 Part 15.247 (e) and RSS 247 Sect.5.2 (b). The pre-evaluation was performed to find the worst modes. The worst findings were conducted on 3 channels in each operating frequency range of 2400 MHz to 2483.5 MHz. The worst sample result indicated below.

Test Setup:



Method AVGSA-1 of “KDB 558074 – DTS Measurement Guidance v03r05” applies since the EUT continuously transmits with duty cycle greater than 98%. Sample detector was used.

Each chain was measured individually and applied the measure-and-sum approach per KDB662911.

The total directional gain (7.68 dBi) was calculated by summing Antenna 4 (3.84 dBi) and Antenna 7 (5.43 dBi).

The duty cycle, CF = 10Log(1/duty cycle), was applied for BLE.

4.3.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 4: Peak Power Spectral Density – Test Results – Non Beamforming

Test Conditions: Conducted Measurement, Normal Temperature				
Antenna Type: FPCB			Power Setting: See test plan	
Total Directional Gain: + 7.68 dBi (WiFi)				
Max. Directional Gain: Antenna 4 = + 3.84 dBi (WiFi); Antenna 7 = + 5.43 dBi (WiFi); Antenna 2 = + 3.09 dBi (BLE and Thread)				
Signal State: Modulated at 100%.				
Ambient Temp.: 22° C			Relative Humidity: 38%	
Peak Power Spectral Density				
802.15.4				
Freq. (MHz)	Packet	Max. PSD [dBm/3kHz]	Limit [dBm/3kHz]	Margin [dB]
2405	Thread	-4.597	8.000	-12.597
2440	Thread	-5.039	8.000	-13.039
2475	Thread	-5.667	8.000	-13.667
Note: 1. The highest peak output power was observed at Thread per data stream. 2. Limited number of plots are placed in the report.				




Figure 3: Power Spectral Density, 2405 MHz for Thread


4.4 Out of Band Emissions

Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmitting mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS-247 Sect. 5.5, RSS-GEN Sect. 8.9 and 8.10.

4.4.1 Test Method

The conducted method was used to measure the undesirable emission requirement. The measurement was performed with modulation. This test was conducted on 3 channels of Sample in each mode on Sample. The worst sample result indicated below.

Test Setup:



Measurement Procedure AVG2 of KDB 662911

4.4.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 5: Emissions at the Band-Edge – Test Results

Test Conditions: Conducted Measurement, Normal Temperature and Voltage only						
Antenna Type: FPCB			Power Setting: See test plan			
Total Directional Gain: + 7.68 dBi (WiFi) Max. Directional Gain: Antenna 4 = + 3.84 dBi (WiFi); Antenna 7 = + 5.43 dBi (WiFi); Antenna 2 = + 3.09 dBi (BLE and Thread)						
Signal State: Modulated at 100%.						
Ambient Temp.: 22° C			Relative Humidity: 38%			
Non-Restricted Frequency Band Emissions						
Freq. (MHz)	Mode	Chain	Measured (dBm)	Limit (dBm)	Plots	Results
2400	Thread	0	-40.49	-15.03	Fig. 4, 5	Pass
2483.5	Thread	0	-48.39	-15.77	Fig. 6, 7	Pass
Note: 1. The stated limits for 30 dBr are relative to each individual output per KDB 662911 Method. 2. The worst case of each data rate is recorded.						




Figure 4: Measured Bandedge for Thread at 2405 MHz




Figure 5: Out of Band Emissions for Thread at 2405 MHz




Figure 6: Measured Bandedge for Thread at 2475 MHz




Figure 7: Out of Band Emissions for Thread at 2475 MHz

4.5 Transmit Spurious Emissions

Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmit mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS 247 Sect.5.5, RSS-GEN Sect. 8.9 and 8.10.

4.5.1 Test Methodology

4.5.1.1 Preliminary Test

A test program that controls instrumentation and data logging was used to automate the preliminary RF emission test procedure. The frequency range of interest was divided into sub-ranges to yield a frequency resolution of approximately 120 kHz and provide a reading at each frequency for no more than 12° of turntable rotation. For each frequency sub-range the turntable was rotated 360° while peak emission data was recorded and plotted over the frequency range of interest in horizontal and vertical antenna polarization's.

Preliminary emission profile testing was performed inside the anechoic chamber. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm (<1 GHz) and 150cm (>1 GHz) above the floor. The EUT was positioned as shown in the setup photographs. The receiving antenna was placed at a distance of 3m at a fixed height of 1m. Measurement equipment was located outside of the chamber. A video camera was placed inside the chamber to view the EUT.

Pre-scans were performed to determine the worst data rate / chains for 802.15.1, 802.15.4, 802.11g, 802.11n (HT20 and HT40)

4.5.1.2 Final Test

For each frequency measured, the peak emission was maximized by manipulating the receiving antenna from 1 to 4 meters above the ground plane and placing it at the position that produced the maximum signal strength reading. The turntable was then rotated through 360° while observing the peak signal and placing the EUT at the position that produced maximum radiation. The six highest emissions relative to the limit were measured unless such emissions were more than 20 dB below the limit. If less than six emissions are within 20 dB of the limit, then the noise level of the receiver is measured at frequencies where emissions are expected. Multiples of all oscillator and microprocessor frequencies were also checked.


Final testing was performed on an NSA compliant test site. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm (<1 GHz) and 150cm (>1 GHz) above the ground plane. The placement of EUT and cables were the same as for preliminary testing and is shown in the setup photographs.

Final results are: 802.11g (Chain 0 and Chain 1) and HT40 (Chain 0 and Chain 1). 20MHz channel BW worse case is 802.11g and covers HT20.

4.5.1.3 Deviations

None.

Test Setup:



4.5.2 Transmitter Spurious Emission Limit

The spurious emissions of the transmitter shall not exceed the values in CFR47 Part 15.205, 15.209: 2015 and RSS Gen Sect. 8.9 and 8.10: 2014.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490.....	2400/F (kHz)	300
0.490-1.705.....	24000/F (kHz)	30
1.705-30.0.....	30	30
30-88.....	100 **	3
88-216.....	150 **	3
216-960.....	200 **	3
Above 960.....	500	3

All harmonics and spurious emission which are outside of the restricted band shall be 20dB below the in-band emission.


4.5.3 Test Results

The final measurement data was taken under the worst case operating modes, configurations, and/or cable positions. It also reflects the results including any modifications and/or special accessories listed in Sections 1.4 and test plan.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).


Table 6: Transmit Spurious Emission at Band-Edge Requirements

Test Conditions: Radiated Measurement, Normal Temperature and Voltage only								
Antenna Type: FPCB			Power Setting: See test plan					
Total Directional Gain: + 7.68 dBi (WiFi) Max. Directional Gain: Antenna 4 = + 3.84 dBi (WiFi); Antenna 7 = + 5.43 dBi (WiFi); Antenna 2 = + 3.09 dBi (BLE and Thread)								
Signal State: Modulated at 100%.								
Ambient Temp.: 20° C			Relative Humidity: 45%					
Band-Edge Results								
Freq. (MHz)	Level (dBuV/m)	Pol. (H/V)	Limit (dBuV/m)	Margin (dB)	Det.	Table Deg.	Tower (cm)	Note
2390	54.79	V	74	-19.21	Pk	259	285	PLOT 8: Thread-2405MHz-TP19
2390	41.64	V	54	-12.36	Ave	259	285	PLOT 9: Thread-2405MHz-TP19
2390	55.40	H	74	-18.60	Pk	175	150	PLOT 10: Thread-2405MHz-TP19
2390	41.81	H	54	-12.19	Ave	175	150	PLOT 11: Thread-2405MHz-TP19
2483.5	59.72	H	74	-14.28	Pk	360	266	PLOT 12: Thread-2475MHz-TP19
2483.5	46.48	H	54	-7.52	Ave	360	266	PLOT 13: Thread-2475MHz-TP19
2483.5	55.06	V	74	-18.94	Pk	106	298	PLOT 14: Thread-2475MHz-TP19
2483.5	43.10	V	54	-10.90	Ave	106	298	PLOT 15: Thread-2475MHz-TP19
Note: 1. The emissions were measured at the adjacent restricted band of the fundamental signal. 2. All the band-edge measurements met the restricted band requirements of CFR47 15.205.								




Date: 4.MAY.2017 16:57:54

Figure 8: Thread Radiated Emission at the Edge for 2390 MHz – Vert. (Pk)




Date: 4.MAY.2017 17:00:22

Figure 9: Thread Radiated Emission at the Edge for 2390 MHz – Vert. (Ave)




Date: 4.MAY.2017 17:07:25

Figure 10: Thread Radiated Emission at the Edge for 2390 MHz – Horz. (Pk)




Date: 4.MAY.2017 17:09:04

Figure 11: Thread Radiated Emission at the Edge for 2390 MHz – Horz. (Ave)




Date: 4.MAY.2017 17:21:37

Figure 12: Thread Radiated Emission at the Edge for 2483.5 MHz – Horz. (Pk)




Date: 4.MAY.2017 17:23:32

Figure 13: Thread Radiated Emission at the Edge for 2483.5 MHz – Horz. (Ave)



Date: 4.MAY.2017 17:28:17

Figure 14: Thread Radiated Emission at the Edge for 2483.5 MHz – Vert. (Pk)



Date: 4.MAY.2017 17:29:47

Figure 15: Thread Radiated Emission at the Edge for 2483.5 MHz – Vert. (Ave)


SOP 1 Radiated Emissions

Tracking # 31761398.001 Page 1 of 7

EUT Name	Wi-Fi Router	Date	May 3, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 40%rh
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)	Temp / Hum out	N/A
EUT Config.	802.15.4 (Thread)	Line AC / Freq	120 Vac / 60 Hz
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN	RBW / VBW	120 kHz/ 300 kHz
Dist/Ant Used	3m / JB3	Performed by	Colton Aliff

30 MHz – 1 GHz Transmit at 2440 MHz

Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB
39.29	39.46	2.64	-13.54	28.56	QP	V	113	150	40.00	-11.44
56.21	50.41	2.78	-20.74	32.45	QP	V	158	346	40.00	-7.55
162.41	44.62	3.38	-15.74	32.26	QP	V	110	358	43.50	-11.24
66.07	49.17	2.86	-20.31	31.72	Pk	V	100	270	40.00	-8.28
384.05	45.42	4.20	-12.52	37.10	Pk	H	100	1	46.00	-8.90
111.84	47.72	3.13	-15.21	35.64	Pk	V	100	360	43.50	-7.86



Spec Margin = E-Field QP - Limit, E-Field QP = FIM QP+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: 1. Worst case was observed on Mid channel of Thread mode.

2. No significant emission was observed below 30MHz.

3. To reduce complexity and bulkiness of the report Worst case Plots is placed in the report.


SOP 1 Radiated Emissions

Tracking # 31761398.001 Page 2 of 7

EUT Name	Wi-Fi Router	Date	May 3, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 40%rh
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)	Temp / Hum out	N/A
EUT Config.	802.15.4 (Thread)	Line AC / Freq	120 Vac / 60 Hz
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN	RBW / VBW	1 MHz/ 3 MHz
Dist/Ant Used	3m – EMCO3115 / 1m – AHA-840	Performed by	Colton Aliff

1 – 18 GHz Transmit at 2405 MHz (Low Channel)

Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB
7213.12	44.31	2.20	-16.45	30.05	Ave	H	216	250	54.00	-23.95
15549.27	38.65	3.42	-12.51	29.56	Ave	V	189	168	54.00	-24.45
17892.03	40.15	3.72	-3.41	40.45	Ave	V	141	36	54.00	-13.55



Spec Margin = E-Field AVG - Limit, E-Field AVG = FIM AVG+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: Worst case was observed on Thread.


SOP 1 Radiated Emissions

Tracking # 31761398.001 Page 3 of 7

EUT Name	Wi-Fi Router	Date	May 3, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 40%rh
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)	Temp / Hum out	N/A
EUT Config.	802.15.4 (Thread)	Line AC / Freq	120 Vac / 60 Hz
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN	RBW / VBW	1 MHz/ 3 MHz
Dist/Ant Used	3m – EMCO3115 / 1m – AHA-840	Performed by	Colton Aliff

18 – 25 GHz Transmit at 2405 MHz (Low Channel)

Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB
20839.91	40.54	7.44	-9.09	38.89	Ave	V	120	360	54.00	-15.11
21829.22	29.49	7.68	-9.97	27.20	Ave	V	194	18	54.00	-26.80



Spec Margin = E-Field AVG - Limit, E-Field AVG = FIM AVG+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: Worst case was observed on Thread.


SOP 1 Radiated Emissions

Tracking # 31761398.001 Page 4 of 7

EUT Name	Wi-Fi Router	Date	May 3, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 40%rh
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)	Temp / Hum out	N/A
EUT Config.	802.15.4 (Thread)	Line AC / Freq	120 Vac / 60 Hz
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN	RBW / VBW	1 MHz/ 3 MHz
Dist/Ant Used	3m – EMCO3115 / 1m – AHA-840	Performed by	Colton Aliff

1 – 18 GHz Transmit at 2440 MHz (Mid Channel)

Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB
17874.15	40.37	3.71	-3.51	40.56	Ave	H	205	26	54.00	-13.44
15534.67	38.29	3.43	-12.48	29.24	Ave	V	153	180	54.00	-24.77



Spec Margin = E-Field AVG - Limit, E-Field AVG = FIM AVG+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: Worst case was observed on Thread.

SOP 1 Radiated Emissions						Tracking # 31761398.001 Page 5 of 7					
EUT Name	Wi-Fi Router					Date	May 3, 2017				
EUT Model	B010001 (USA), B010002 (IC)					Temp / Hum in	22° C / 40%rh				
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)					Temp / Hum out	N/A				
EUT Config.	802.15.4 (Thread)					Line AC / Freq	120 Vac / 60 Hz				
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN					RBW / VBW	1 MHz/ 3 MHz				
Dist/Ant Used	3m – EMCO3115 / 1m – AHA-840					Performed by	Colton Aliff				
18 – 25 GHz Transmit at 2440 MHz (Mid Channel)											
Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin	
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB	
18026.39	25.99	6.91	-7.05	25.85	Ave	V	184	20	54.00	-28.16	
20839.99	31.85	7.44	-9.09	30.20	Ave	V	185	46	54.00	-23.80	

dBuV/m

TUV Rheinland of North America

100.0

90.0

80.0

70.0

60.0

50.0

40.0

30.0

20.0

10.0

0.0

18000.0

25000.0

15

20

25

30

35

40

45

50

55

60

65

70

75

80

85

90

95

100

[1] Horizontal

[2] Vertical

Av Limit

Formal

Meas Dist 1m

Spec Dist 3m

Frequency: MHz

Eero, Piccino and Unico, Channel 15, 2440 MHz, 802.15.4

Filename: c:\program files (x86)\emisoft - vasona\results\Eero-2017-0503-RE11.emi

Spec Margin = E-Field AVG - Limit, E-Field AVG = FIM AVG+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: Worst case was observed on Thread.


SOP 1 Radiated Emissions

Tracking # 31761398.001 Page 6 of 7

EUT Name	Wi-Fi Router	Date	May 3, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 40%rh
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)	Temp / Hum out	N/A
EUT Config.	802.15.4 (Thread)	Line AC / Freq	120 Vac / 60 Hz
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN	RBW / VBW	1 MHz/ 3 MHz
Dist/Ant Used	3m – EMCO3115 / 1m – AHA-840	Performed by	Colton Aliff

1 – 18 GHz Transmit at 2475 MHz (Hi Channel)

Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB
7423.37	56.67	2.23	-15.56	43.34	Ave	H	227	262	54.00	-10.66
10361.96	40.69	2.68	-12.75	30.62	Ave	H	176	84	54.00	-23.39
15663.84	39.92	3.46	-12.72	30.66	Ave	V	189	94	54.00	-23.34



Spec Margin = E-Field AVG - Limit, E-Field AVG = FIM AVG+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: Worst case was observed on Thread.


SOP 1 Radiated Emissions

Tracking # 31761398.001 Page 7 of 7

EUT Name	Wi-Fi Router	Date	May 3, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 40%rh
EUT Serial	MF701114110316 (Piccino), SPE28JY (Unico)	Temp / Hum out	N/A
EUT Config.	802.15.4 (Thread)	Line AC / Freq	120 Vac / 60 Hz
Standard	CFR47 Part 15 Subpart C, RSS-247, RSS-GEN	RBW / VBW	1 MHz/ 3 MHz
Dist/Ant Used	3m – EMCO3115 / 1m – AHA-840	Performed by	Colton Aliff

18 – 25 GHz Transmit at 2475 MHz (Hi Channel)

Frequency	Raw	Cable Loss	AF	Level	Detector	Polarity	Height	Azimuth	Limit	Margin
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB
20839.95	35.01	7.44	-9.09	33.36	Ave	V	130	20	54.00	-20.64
21927.34	29.84	7.62	-10.09	27.38	Ave	V	130	50	54.00	-26.62



Spec Margin = E-Field AVG - Limit, E-Field AVG = FIM AVG+ Total CF ± Uncertainty

Total CF= AF+ Cable Loss AF= Antenna factor + Preamp

Note: Worst case was observed on Thread.

4.6 AC Conducted Emissions

Testing was performed in accordance with ANSI C63.4: 2014. These test methods are listed under the laboratory's A2LA Scope of Accreditation.

This test measures the levels emanating from the EUT's AC input port, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

The AC conducted emissions of equipment under test shall not exceed the values in CFR47 Part 15.207 and RSS-GEN. Sect. 8.8.

4.6.1 Test Methodology

A test program that controls instrumentation and data logging was used to automate the AC Power Line Conducted emission test procedure. The frequency range of interest was divided into sub-ranges such as to yield a frequency resolution of 9 kHz. Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a set of 50 μ H / 50 Ω LISNs.

Testing is performed in Lab 5. The setup photographs clearly identify which site was used. The vertical ground plane used in the semi-anechoic chamber is a 2m x 2m solid aluminum frame and panel, and it is bonded to the horizontal ground plane.

In the case of tabletop equipment, the EUT is placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane and 40cm from a vertical ground reference plane. The rear of the EUT was positioned flush with the backside of the table and directly over the LISNs. The power and I/O cables were routed over the edge of the table and bundled approximately 40cm from the ground plane. Support equipment was powered from a separate LISN.

Preliminary test were performed: 802.11g, 802.11n, BLE and Thread (Zigbee).

4.6.1.1 Deviations

There were no deviations from this test methodology.

4.6.2 Test Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 7: AC Conducted Emissions – Test Results

Test Conditions: Conducted Measurement at Normal Conditions only		
Antenna Type: FPCB		Power Level: See Test Plan
AC Power: 120 Vac/60 Hz		Configuration: Tabletop
Ambient Temperature: 21° C		Relative Humidity: 44% RH
Configuration	Frequency Range	Test Result
Line 1 (Hot)	0.15 to 30 MHz	Pass
Line 2 (Neutral)	0.15 to 30 MHz	Pass

SOP 2 Conducted Emissions

Tracking # 31761398.001 Page 1 of 4

EUT Name	Wi-Fi Router	Date	Apr 14, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 41% rh
EUT Serial	SPE28JY	Temp / Hum out	N/A
EUT Config.	TX mode / chain 0 & 1	Line AC / Freq	120Vac / 60Hz
Standard	CFR47 Part 15.207 and RSS Gen	RBW / VBW	9 kHz / 30 kHz
Lab/LISN	Lab #5 /Com-Power, Line 1	Performed by	Colton Aliff

Frequency	Raw	Limiter	Ins. Loss	Level	Detector	Line	Limit	Margin	Result
MHz	dBuV	dB	dB	dBuV			dBuV	dB	
0.161	46.95	9.82	0.05	56.82	QP	Live	65.40	-8.58	Pass
0.161	20.44	9.82	0.05	30.31	Avg	Live	55.40	-25.09	Pass
0.229	40.97	9.83	0.04	50.84	QP	Live	62.50	-11.66	Pass
0.229	19.23	9.83	0.04	29.10	Avg	Live	52.50	-23.41	Pass
0.311	36.23	9.83	0.03	46.09	QP	Live	59.95	-13.86	Pass
0.311	15.61	9.83	0.03	25.47	Avg	Live	49.95	-24.48	Pass
0.524	29.32	9.84	0.03	39.19	QP	Live	56.00	-16.81	Pass
0.524	12.08	9.84	0.03	21.95	Avg	Live	46.00	-24.05	Pass
2.330	31.21	9.89	0.03	41.12	QP	Live	56.00	-14.88	Pass
2.330	19.67	9.89	0.03	29.58	Avg	Live	46.00	-16.42	Pass
3.496	29.55	9.91	0.03	39.48	QP	Live	56.00	-16.52	Pass
3.496	18.54	9.91	0.03	28.47	Avg	Live	46.00	-17.53	Pass

Spec Margin = QP./Ave. - Limit, ± Uncertainty


Combined Standard Uncertainty $U_c(y) = \pm 1.2$ dB Expanded Uncertainty $U = kU_c(y)$ $k = 2$ for 95% confidence

Notes: EUT was setup as table top equipment and transmitted at 2442 MHz in BLE at 1Mbps (worse case).

SOP 2 Conducted Emissions

Tracking # 31761398.001 Page 2 of 4

EUT Name	Wi-Fi Router	Date	Apr 14, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 41% rh
EUT Serial	SPE28JY	Temp / Hum out	N/A
EUT Config.	TX mode / chain 0 & 1	Line AC	120Vac / 60Hz
Standard	CFR47 Part 15.207 and RSS Gen	RBW / VBW	9 kHz / 30 kHz
Lab/LISN	Lab #5 /Com-Power, Line 1	Performed by	Colton Aliff




SOP 2 Conducted Emissions						Tracking # 31761398.001 Page 3 of 4			
EUT Name	Wi-Fi Router					Date	Apr 14, 2017		
EUT Model	B010001 (USA), B010002 (IC)					Temp / Hum in	22° C / 41% rh		
EUT Serial	SPE28JY					Temp / Hum out	N/A		
EUT Config.	TX mode / chain 0 & 1					Line AC / Freq	120Vac / 60Hz		
Standard	CFR47 Part 15.207 and RSS Gen					RBW / VBW	9 kHz / 30 kHz		
Lab/LISN	Lab #5 /Com-Power, Line 2					Performed by	Colton Aliff		
Frequency	Raw	Limiter	Ins. Loss	Level	Detector	Line	Limit	Margin	Result
MHz	dBuV	dB	dB	dBuV			dBuV	dB	
0.161	44.59	9.82	0.05	54.46	QP	Neutral	65.40	-10.94	Pass
0.161	21.55	9.82	0.05	31.42	Avg	Neutral	55.40	-23.98	Pass
0.202	44.20	9.83	0.04	54.07	QP	Neutral	63.51	-9.44	Pass
0.202	19.85	9.83	0.04	29.72	Avg	Neutral	53.51	-23.79	Pass
1.664	26.25	9.88	0.03	36.16	QP	Neutral	56.00	-19.84	Pass
1.664	18.40	9.88	0.03	28.31	Avg	Neutral	46.00	-17.69	Pass
2.528	31.69	9.89	0.03	41.61	QP	Neutral	56.00	-14.39	Pass
2.528	20.56	9.89	0.03	30.48	Avg	Neutral	46.00	-15.52	Pass
3.163	30.79	9.90	0.03	40.73	QP	Neutral	56.00	-15.27	Pass
3.163	20.16	9.90	0.03	30.09	Avg	Neutral	46.00	-15.91	Pass
6.663	30.44	9.94	0.03	40.41	QP	Neutral	60.00	-19.59	Pass
6.663	22.14	9.94	0.03	32.11	Avg	Neutral	50.00	-17.89	Pass
Spec Margin = QP./Ave. - Limit, ± Uncertainty									
Combined Standard Uncertainty $u_c(y) = \pm 1.2$ dB Expanded Uncertainty $U = k u_c(y)$ $k = 2$ for 95% confidence									
Notes: EUT was setup as table top equipment and transmitted at 2442 MHz in BLE at 1Mbps (worse case).									

SOP 2 Conducted Emissions

Tracking # 31761398.001 Page 4 of 4

EUT Name	Wi-Fi Router	Date	Apr 14, 2017
EUT Model	B010001 (USA), B010002 (IC)	Temp / Hum in	22° C / 41% rh
EUT Serial	SPE28JY	Temp / Hum out	N/A
EUT Config.	TX mode / chain 0 & 1	Line AC	120Vac / 60Hz
Standard	CFR47 Part 15.207 and RSS Gen	RBW / VBW	9 kHz / 30 kHz
Lab/LISN	Lab #5 /Com-Power, Line 2	Performed by	Colton Aliff



4.7 Maximum Permissible Exposure

4.7.1 Test Methodology

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this calculation is declared by the manufacturer, and the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

4.7.2 RF Exposure Limit

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	1.0	6
300 - 1500	f/300	6
1500 - 100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/ f ²)	30
30–300	27.5	0.037	0.2	30
300 - 1500	f/1500	30
1500 - 100,000	1.0	30

F = Frequency in MHz

* = Plane-wave equivalent power density

4.7.3 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

4.7.4 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in user's manual. So, this device is classified as a **Mobile Device**.

See below calculation for 2.437 GHz RF Exposure at a distance of 20cm.

4.7.5 Test Results

4.7.5.1 Antenna Gain

The 2.405 GHz transmitting max antenna gain is +3.09 dBi or 2.04 (numeric).

4.7.5.2 Output Power into Antenna & RF Exposure value at distance 20cm:

Calculations for this report are based on highest power measurement.

Limit for MPE (from FCC part 1.1310 table1) is 1.0 mW/cm²

The highest measured power is +18.40 dBm or 69.18 mW.

Using the Friss transmission formula, the EIRP is Pout*G, and R is 20cm.

$P_d = (69.18 * 2.04) / (1600\pi) = 0.0281 \text{ mW/cm}^2$, which is 0.9719 mW/cm² below to the limit.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

4.7.6 Sample Calculation

The Friss transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where;

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi \approx 3.1416$

R = distance between observation point and center of the radiator

in cm

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).

5 Test Equipment List

5.1 Equipment List

Equipment	Manufacturer	Model #	Serial/Inst #	Last Cal mm/dd/yyyy	Next Cal mm/dd/yyyy
Bilog Antenna	Sunol Sciences	JB3	A102606	06/15/2016	06/15/2018
Horn Antenna	Sunol Sciences	3115	9710-5301	10/08/2015	10/08/2017
Antenna (18-40 GHz)	Com-Power	AHA-840	105005	07/08/2015	07/08/2017
Loop Antenna	EMCO	6502	9110-2683	06/13/2016	06/13/2017
Spectrum Analyzer	Rohde & Schwarz	FSL6	100169	01/13/2017	01/13/2018
Spectrum Analyzer	Agilent	N9038A	MY552260210	01/16/2017	01/16/2018
Spectrum Analyzer	Agilent	N9030A	MY52350885	05/17/2016	05/17/2017
Spectrum Analyzer	Rohde Schwarz	ESIB40	832427/002	01/16/2017	01/16/2018
Spectrum Analyzer	Rohde Schwarz	FSV40	1321.3008K40	08/30/2016	08/30/2017
Amplifier	Sonoma Instruments	310	165516	01/19/2017	01/19/2018
Amplifier	Miteq	TTA1800-30-HG	2020728	11/12/2016	11/12/2017
Amplifier	Rohde & Schwarz	TS-PR26	100011	11/04/2017	11/04/2018
Amplifier	Rohde & Schwarz	TS-PR40	100012	08/02/2017	08/02/2017
Power Meter	Agilent	E4418B	MY45103902	01/11/2017	01/11/2018
Power Sensor	Hewlett Packard	8482A	1925A04647	01/01/2017	01/01/2018
Thermometer	Fluke	52II	88650033	11/04/2016	11/04/2017
Thermo Chamber	Espec	BTZ-133	0613436	NCR	NCR
Multimeter	Fluke	177	92780312	01/11/2017	01/11/2018
DC Power Supply	Agilent	E3634A	MY400004331	01/12/2017	01/12/2018
Notch Filter	Micro-Tronics	BRM50702	037	07/18/2016	07/18/2017
Signal Generator	Anritsu	MG3694A	42803	01/13/2017	01/13/2018
Signal Generator	Rohde & Schwarz	SMF100A	1167.0000K02	09/06/2016	09/06/2017
Signal Generator	Rohde & Schwarz	SMBV100A	1407.6004K02	09/06/2016	09/06/2017
Power Sensors	Rohde & Schwarz	OSP120	1520.9010.02	09/06/2016	09/06/2017

* Calibration of equipment past due for re-calibration will be performed expeditiously. If any equipment is found to be out of tolerance at that time, affected customers will be notified accordingly.

NCR = No Calibration Required

6 EMC Test Plan

6.1 Introduction

This section provides a description of the Equipment Under Test (EUT), configurations, operating conditions, and performance acceptance criteria. It is an overview of information provided by the manufacturer so that the test laboratory may perform the requested testing.

6.2 Customer

Table 8: Customer Information

Company Name	eero inc.
Address	500 Howard Street, Suite 900
City, State, Zip	San Francisco, CA 94105
Country	USA
Phone	(415) 738-7972
Fax	

Table 9: Technical Contact Information

Name	Clifford Clarke
E-mail	cliff@eero.com
Phone	(415) 738-7972
Fax	

6.3 Equipment Under Test (EUT)

Table 10: EUT Specifications

EUT Specifications	
Dimensions	W: 4.75in (121mm) x D: 4.75in (121mm) x H: 0.85-1.26in (22-33mm)
AC Input	100-240V AC, 50 – 60 Hz
Environment	Indoor
Operating Temperature Range:	0 to 35 degrees C
Multiple Feeds:	<input type="checkbox"/> Yes and how many <input checked="" type="checkbox"/> No
Product Marketing Name (PMN)	B010001 (USA), B010002 (IC)
Hardware Version Identification Number (HVIN)	B010001 (USA), B010002 (IC)
Firmware Version Identification Number (FVIN)	3.0.0
802.11-radio modules	
Operating Mode	802.15.1, 802.15.4, 802.11g, 802.11n (HT20 and HT40)
Transmitter Frequency Band	2.4 GHz – 2.4835 GHz
Max. Rated Power Output	See Channel Planning Table.
Power Setting @ Operating Channel	See Channel Planning Table.
Antenna Type	Qty 7 – 3 custom antennas at 2.4GHz. See Table 11 for details
Antenna Gain	Antenna 3 = +4.08 dBi, Antenna 4 = +3.64 dBi, Antenna 5 = +4.14 dBi
Modulation Type	<input checked="" type="checkbox"/> Thread (Zigbee) <input checked="" type="checkbox"/> BLE <input checked="" type="checkbox"/> DSSS <input checked="" type="checkbox"/> OFDM <input checked="" type="checkbox"/> Other describe: 16QAM and 64 QAM
Data Rate	Thread (Zigbee): 250 kbps BLE: 1-2 Mbps 802.11g: 2 Spatial Streams: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n HT20: 2 Spatial Streams: 13, 26, 39, 52, 78, 104, 117, 130 /156 Mbps (LGI) 802.11n HT40: 2 Spatial Streams: 27, 54, 81, 108, 162, 216, 243, 270 / 324, 370 Mbps (LGI)
TX/RX Chain (s)	MIMO (2x2); single for BLE and Thread (Zigbee)

EUT Specifications	
Directional Gain Type	<input type="checkbox"/> Correlated <input checked="" type="checkbox"/> Beam-Forming <input type="checkbox"/> Other describe:
Type of Equipment	<input checked="" type="checkbox"/> Table Top <input type="checkbox"/> Wall-mount <input type="checkbox"/> Floor standing cabinet <input type="checkbox"/> Other: Wall-mount at AC outlet
Note: All 2 chains will be on / transmitted at all time.	

Table 11: Antenna Information

Number	Antenna Type	Description	Max Gain (dBi)
Antenna 1	Flex PCB	5 GHz Wi-Fi U-NII-1 Band, Chain 0	3.01
Antenna 1	Flex PCB	5 GHz Wi-Fi U-NII-2A Band, Chain 0	2.52
Antenna 2	Flex PCB	Bluetooth LE and Thread (Zigbee)	3.09
Antenna 3	Flex PCB	5 GHz Wi-Fi U-NII-1 Band, Chain 1	4.58
Antenna 3	Flex PCB	5 GHz Wi-Fi U-NII-2A Band, Chain 1	4.37
Antenna 4	Flex PCB	2.4 GHz Wi-Fi Chain 0	3.84
Antenna 5	Flex PCB	5 GHz Wi-Fi U-NII-2C Band, Chain 0	4.46
Antenna 5	Flex PCB	5 GHz Wi-Fi U-NII-3 Band, Chain 0	3.84
Antenna 6	Flex PCB	5 GHz Wi-Fi U-NII-2C Band, Chain 1	3.34
Antenna 6	Flex PCB	5 GHz Wi-Fi U-NII-3 Band, Chain 1	3.29
Antenna 7	Flex PCB	2.4 GHz Wi-Fi Chain 1	5.43

Table 12: EUT Channel Power Specifications

Total Power (Summed 2 Chains) for Non-Beamforming Mode

No.	Frequency (MHz)	Target Power Value dBm					
		802.11g	802.11n HT20	802.11n HT40	BLE	Thread (Zigbee)	
1	2412	27.50**	27.41**				
3	2422			27.07*			
5	2432						
6	2437	29.55*****	29.50*****	28.95***			
9	2452			29.76****			
11	2462	29.42*****	29.43*****				
0	2402				10.96*****		
20	2442				10.66*****		
39	2480				11.82*****		
11	2405					18.40*****	
18	2440					18.16*****	
25	2475					17.72*****	
Note: 1. The adjusted power target values are updated at the evaluated frequencies. 2. TP setting: * = 24, ** = 24.5, *** = 26, **** = 26.5, ***** = 12, ***** = 19, *****27. 3. BLE and Thread (Zigbee) are Max Power measured.							

Total Power (Summed 2 Chains) for Beamforming Mode

No.	Frequency (MHz)	Target Power Value dBm					
		802.11b	802.11g	802.11n HT20	802.11n HT40		
1	2412		27.50**	27.41**			
3	2422				27.07*		
5	2432						
6	2437		28.12****	28.06****	27.94***		
9	2452				27.99***		
11	2462		28.19****	28.03****			
Note: 1. The adjusted power target values are updated at the evaluated frequencies. 2. TP setting: * = 24, ** = 24.5, *** = 25, **** = 25.5.							

Table 13: Interface Specifications

Interface Type	Cabled with what type of cable?	Is the cable shielded?	Maximum potential length of the cable?	Metallic (M), Coax (C), Fiber (F), or Not Applicable?
Ethernet	RJ45	<input checked="" type="checkbox"/> No	<input checked="" type="checkbox"/> Metric: 2 m	<input type="checkbox"/> N/A

Table 14: Supported Equipment

Equipment	Manufacturer	Model	Serial	Used for
Laptop	Dell	Latitude	35521341769	Setup EUT operating channel
Note: None.				

Table 15: Description of Sample used for Testing

Device	Serial	RF Connection	CFR47 Part 15.247
Wi-Fi Router	SPE28JY	FPCB Antenna	TX Emissions, AC Conducted Emission
		Direct Connection	Peak Transmit Power, Peak Power Spectral Density, Occupied Bandwidth Band-Edge Out-of-Band Emission
Note: N/A			

Table 16: Description of Test Configuration used for Radiated Measurement.

Device	Antenna	Mode	Setup Photo (X-Axis)	Setup Photo (Y-Axis)	Setup Photo (Z-Axis)
Wi-Fi Router	FPCB	Transmit	EUT laid flat	N/A	N/A
Note: N/A.					

6.4 Test Specifications

Table 17: Test Specifications

Emissions and Immunity	
Standard	Requirement
CFR 47 Part 15.247: 2016	All
RSS 247 Issue 2, 2017	All

END OF REPORT