

# RF EXPOSURE REPORT

**Product:** B Series B402

**Model Name:** B402,B402S

**FCC ID:** 2AEMI-B402

**Applicant:** Particle Industries,Inc

**Address:** 126 Post St,4th floor, San Francisco,CA 94108 USA

**Manufacturer:** Particle Industries,Inc

**Address:** 126 Post St,4th floor, San Francisco,CA 94108 USA

**Prepared by:** BV 7Layers Communications Technology (Shenzhen) Co. Ltd

**Lab Location:** No.B102, Dazhu Chuangxin Mansion, North of Beihuan Avenue,  
North Area, Hi-Tech Industrial Park, Nanshan District,  
Shenzhen, Guangdong, China

**TEL:** +86 755 8869 6566

**FAX:** +86 755 8869 6577

**E-MAIL:** [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)

**Report No.:** SA190606W003

**Received Date:** Jul. 19, 2019

**Test Date:** Jul. 20, 2019 ~ Jul. 21, 2019

**Issued Date:** Jul. 24, 2019

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## TABLE OF CONTENTS

<b>RF EXPOSURE REPORT</b>	<b>1</b>
<b>RELEASE CONTROL RECORD</b>	<b>3</b>
<b>1 CERTIFICATION</b>	<b>4</b>
<b>2 GENERAL INFORMATION</b>	<b>5</b>
2.1 GENERAL DESCRIPTION OF EUT	5
<b>3 RF EXPOSURE</b>	<b>6</b>
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA	6
3.3 CLASSIFICATION	6
3.4 CONDUCTED POWER	7
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	8
3.6 CONCLUSION OF SIMULTANEOUS TRANSMITTER	9



Test Report No.: SA190606W003

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA190606W003	Original release	Jul. 24, 2019



Test Report No.: SA190606W003

## 1 CERTIFICATION

**PRODUCT:** B Series B402  
**BRAND NAME:** Particle  
**MODEL NAME:** B402,B402S  
**APPLICANT:** Particle Industries,Inc  
**TESTED:** Jul. 20, 2019 ~ Jul. 21, 2019  
**TEST SAMPLE:** Identical Prototype  
**STANDARDS:** **FCC Part 2 (Section 2.1091)**  
**FCC OET Bulletin 65, Supplement C (01-01)**  
**KDB 447498 D01 General RF Exposure Guidance v06**  
**IEEE C95.1**

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Alex, **DATE:** Jul. 24, 2019  
(Alex Chen/ Engineer)

**APPROVED BY :** Luke Lu, **DATE:** Jul. 24, 2019  
(Luke Lu / Manager)



## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	B Series B402	
<b>MODEL NAME</b>	B402,B402S	
<b>NOMINAL VOLTAGE</b>	Li+ PIN /Battery connector: DC 3.7V from Li-ion Battery or VUSB PIN /USB connector :DC 5V from USB Host Unit	
<b>OPERATING TEMPERATURE RANGE</b>	-20 ~ 75°C	
<b>MODULATION TYPE</b>	<b>LTE/BLE</b>	QPSK&16QAM, GFSK(1MHz, 2MHz)
<b>OPERATING FREQUENCY</b>	<b>LTE/BLE</b>	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 779.5MHz ~ 784.5MHz (FOR LTE Band13) 2402MHz ~ 2480MHz (FOR BLE)
<b>ANTENNA GAIN</b>	<b>LTE Band 2</b>	Fixed External Antenna with 3.5dBi gain
	<b>LTE Band 4</b>	Fixed External Antenna with 3.5dBi gain
	<b>LTE Band 5</b>	Fixed External Antenna with 1.0dBi gain
	<b>LTE Band 12</b>	Fixed External Antenna with 1.0dBi gain
	<b>LTE Band 13</b>	Fixed External Antenna with 1.0dBi gain
	<b>BLE</b>	FPCB Antenna with 2.0dBi gain
<b>HW VERSION</b>	V1.00	
<b>SW VERSION</b>	V1.2.1	
<b>I/O PORTS</b>	Refer to user's manual	
<b>CABLE SUPPLIED</b>	N/A	

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3 RF EXPOSURE

#### 3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

#### 3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

#### 3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



### 3.4 CONDUCTED POWER

#### TUNE-UP POWER TABLE

Band	Frequency (MHz)	Operating Mode	Tune-Up Power And Tolerance (dBm)
BLE	2402	GFSK(1MHz)	-4.0
BLE	2480	GFSK(2MHz)	-9.0
LTE 2	1880	QPSK	24.8
LTE 4	1732.5	QPSK	25.0
LTE 5	836.5	QPSK	25.0
LTE 12	707.5	QPSK	25.0
LTE 13	782	QPSK	25.0



BUREAU  
VERITAS

Test Report No.: SA190606W003

### 3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

#### BT

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm <sup>2</sup> )	limit (mW/cm <sup>2</sup> )	PASS / FAIL
BLE	2402	GFSK(1MHz)	2	-4	0.631	0.000126	1.00	PASS
BLE	2480	GFSK(2MHz)	2	-9	0.199	0.000040	1.00	PASS

#### LTE

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm <sup>2</sup> )	limit (mW/cm <sup>2</sup> )	PASS / FAIL
Band 2	1880	QPSK	3.50	24.80	676.083	0.135	1.00	PASS
Band 4	1720	QPSK	3.50	25.00	707.946	0.141	1.00	PASS
Band 5	829	QPSK	1.00	25.00	398.107	0.079	0.56	PASS
Band 12	707.5	QPSK	1.00	25.00	398.107	0.079	0.47	PASS
Band 13	782.0	QPSK	1.00	25.00	398.107	0.079	0.52	PASS



### 3.6 CONCLUSION OF SIMULTANEOUS TRANSMITTER

Both of the BT and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1/LPD1+CPD2/LPD2+.....etc. < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is, which is less than “1”, This confirmed that the device comply with FCC 1.1310 MPE limit.

Band	Frequency ( MHz )	Power Density (mW/cm <sup>2</sup> )	limit (mW/cm <sup>2</sup> )	Power Density / Limit	MPE Limit	PASS / FAIL
BLE(1MHz)	2402	0.000126	1	0.000126	1.000	PASS
LTE BAND 4	1720	0.141	1	0.141		

--END--