
MILWAUKEE LOGO TO BE PRINTED WHITE, ALL OTHER "WHITE" TEXT AND GRAPHICS TO BE BASE STOCK MATERIAL



## FINISHED LABEL



REFERENCE DIMENSIONS

## NOTES:

TITLE:

SERIAL NUMBER CODING METHOD:

NAMEPLATE

- TYPE STYLE FOR VARIABLE INFORMATION TO BE BLACK, 6 POINT SIZE IN AN APPROVED FONT, SUCH AS HELVETICA BOLD CONDENSED, ARIAL BOLD, OR COURIER BOLD.
- 2. REFER TO ES 19-1 FOR SERIALIZATION PROCEDURE.
  - A.) A THREE CHARACTER PREFIX (NUMERIC OR ALPHA-NUMERIC) TO DEFINE THE CATALOG NO. (G88)
    B.) ONE ALPHA CHARACTER (A-Z) FOR SPL BREAKS (A)
    C.) ONE CHARACTER (NUMERIC (0-9) FOR ALPHA (A-Z) FOR MANUFACTURING PLANT LOCATION (9)
    D.) TWO DIGITS (00-99) FOR THE YEAR OF MANUFACTURE
    E.) TWO DIGITS (00-52) FOR THE WEEK OF MANUFACTURE

  - F.) FIVE DIGITS (00001-99999) FOR INDIVIDUAL UNIT SERIALIZATION
  - G.) THE DATE CODE AND SERIAL NUMBER (IF ANY) CAN BE THERMAL PRINTED ON THE TOP OF THE LAMINATION.

Quality Assurance

## **EDITION: A**

CURRENT VERSION 01 **MATERIAL** PART NO. ITEM ID NO. MM00013890 DWN BY CORE: 50# UL silver foil LAMINATION: Gloss PET+Matt UV **APP BY** 64.87x24.95 (±0.2mm) SIZE ADHESIVE: 2 MILACRYLIC BASED SYSTEM FOR USE ON POLYCARBONATE, NYLON,AND POLYPROPYLENE. 05/06/2015 **VENDOR** DATE MUST BE A UL RECOGNIZED AND C.S.A. APPROVED MARKING AND LABELING SYSTEM. **MILWAUKEE PART NUMBER** 12-25-0101 SCALE COLOR Approved By: R.Hollis Approved By: Approved By: Approved By: M.Hickok White + Black + PMS 186C + PMS 152C Total: 4C

Chief Graphic Dsigner / Engg, Manager

Pantone 186C Pantone 1520

White Black СМ

ΥK