

FCC PART 15.247

TEST REPORT

For

MAXWEST INTERNATIONAL LIMITED

No.1, Longgang Road, Buji, Longgang, Shenzhen City, Guangdong Province, P.R. China

FCC ID: 2AEN3GRAVITY5LTE

Report Type: Original Report	Product Type: Gravity 5LTE
Test Engineer:	Lion Xiao <i>Lion Xiao</i>
Report Number:	RDG151125001-00B
Report Date:	2015-12-04
Reviewed By:	Jerry Zhang EMC Manager <i>Jerry Zhang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	10
APPLICABLE STANDARD	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY.....	12
EUT SETUP.....	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
MEASUREMENT UNCERTAINTY.....	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST RESULTS SUMMARY	21
TEST DATA	21
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST DATA	35
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	44

APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST EQUIPMENT LIST AND DETAILS.....	44
TEST DATA	44
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS.....	46
TEST DATA	46
FCC §15.247(e) - POWER SPECTRAL DENSITY	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST EQUIPMENT LIST AND DETAILS.....	52
TEST DATA	52
DECLARATION LETTER	61

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The MAXWEST INTERNATIONAL LIMITED's product, model number: *Gravity 5LTE* (FCC ID: 2AEN3GRAVITY5LTE) (the "EUT") in this report was a *Gravity 5LTE*, which was measured approximately: 14.6 cm (L) x 7.2 cm (W) x 1.0 cm (H), rated input voltage: DC3.8V rechargeable Li-ion battery or DC5.0V charging from adapter.

Adapter information:

Model: LPL-A005050100Z

Input: AC100-240V, 50/60 Hz 200mA MAX

Output: DC 5V, 1000mA

Note: The model Gravity 5LTE have different samples, they are the same electromagnetic emissions and electromagnetic compatibility characteristics, the difference between them is the colour, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 151125001 (Assigned byBACL, Dongguan). The EUT was received on 2015-11-25.

Objective

This report is prepared on behalf of MAXWEST INTERNATIONAL LIMITED. in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID:2AEN3GRAVITY5LTE.

FCC Part 15C DSS submissions with FCC ID:2AEN3GRAVITY5LTE.

FCC Part 22H, 24E, 27 PCE submissions with FCC ID:2AEN3GRAVITY5LTE.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxihu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.
For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	Engineering Mode-TX		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	9	9	8
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	8	8	7
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	8	8	7
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	8	8	8
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	BLE	N/A	N/A	N/A


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	1.05	USB Port of Adater	EUT
Earphone Cable	no	no	1.5	Audio Port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For WiFi mode

The maximum peak conducted output power= 9.7 dBm (9.33 mW) at 2452 MHz
 $[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 9.33/5 \cdot (\sqrt{2.452}) = 2.92 < 3.0$

For bluetooth LE mode

The maximum peak conducted output power= -3 dBm (0.50 mW) at 2440 MHz
 $[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.50/5 \cdot (\sqrt{2.44}) = 0.157 < 3.0$

So both WiFi mode and the stand-alone for BLE mode SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for WiFi/BT, which was permanently attached and the antenna gain is -0.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

7.10 dB at 0.563041 MHz in the **Neutral** conducted mode for **Wi-Fi**.


Test Data**Environmental Conditions**

Temperature:	26.4°C
Relative Humidity:	50 %
ATM Pressure:	100.2 kPa

The testing was performed by Lion Xiao on 2015-11-27.


Test Mode: Transmitting (Wi-Fi)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.472507	41.9	9.000	L1	0.2	14.6	56.5	Compliance
0.511698	45.8	9.000	L1	0.2	10.2	56.0	Compliance
0.567545	46.5	9.000	L1	0.2	9.5	56.0	Compliance
0.738241	44.7	9.000	L1	0.2	11.3	56.0	Compliance
1.745563	45.2	9.000	L1	0.2	10.8	56.0	Compliance
27.061912	45.5	9.000	L1	3.3	14.5	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.507637	34.9	9.000	L1	0.2	11.1	46.0	Compliance
0.563041	32.8	9.000	L1	0.2	13.2	46.0	Compliance
0.676289	30.8	9.000	L1	0.2	15.2	46.0	Compliance
0.738241	30.9	9.000	L1	0.2	15.1	46.0	Compliance
1.637763	32.4	9.000	L1	0.2	13.6	46.0	Compliance
1.802095	33.6	9.000	L1	0.2	12.4	46.0	Compliance


AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.225205	47.4	9.000	N	0.2	15.2	62.6	Compliance
0.393383	43.6	9.000	N	0.2	14.4	58.0	Compliance
0.511698	47.0	9.000	N	0.2	9.0	56.0	Compliance
0.614619	41.8	9.000	N	0.2	14.2	56.0	Compliance
0.744147	40.8	9.000	N	0.2	15.2	56.0	Compliance
25.798550	43.6	9.000	N	2.6	16.4	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.338116	37.5	9.000	N	0.2	11.7	49.2	Compliance
0.450448	36.0	9.000	N	0.2	10.9	46.9	Compliance
0.507637	37.8	9.000	N	0.2	8.2	46.0	Compliance
0.563041	38.9	9.000	N	0.2	7.1	46.0	Compliance
0.619536	33.1	9.000	N	0.2	12.9	46.0	Compliance
0.786832	33.0	9.000	N	0.2	13	46.0	Compliance


Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.340821	47.4	9.000	L1	0.2	11.8	59.2	Compliance
0.476287	41.3	9.000	L1	0.2	15.1	56.4	Compliance
0.572086	46.1	9.000	L1	0.2	9.9	56.0	Compliance
0.744147	43.2	9.000	L1	0.2	12.8	56.0	Compliance
1.816511	42.5	9.000	L1	0.2	13.5	56.0	Compliance
26.422681	45.9	9.000	L1	3.1	14.1	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.507637	35.3	9.000	L1	0.2	10.7	46.0	Compliance
0.567545	32.1	9.000	L1	0.2	13.9	46.0	Compliance
0.624492	32.2	9.000	L1	0.2	13.8	46.0	Compliance
0.681699	32.6	9.000	L1	0.2	13.4	46.0	Compliance
0.738241	31.5	9.000	L1	0.2	14.5	46.0	Compliance
1.982914	31.9	9.000	L1	0.2	14.1	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.171759	55.5	9.000	N	0.2	9.4	64.9	Compliance
0.230654	51.5	9.000	N	0.2	10.9	62.4	Compliance
0.241949	43.6	9.000	N	0.2	18.4	62.0	Compliance
0.286019	47.5	9.000	N	0.2	13.1	60.6	Compliance
0.406123	45.4	9.000	N	0.2	12.3	57.7	Compliance
0.524077	44.4	9.000	N	0.2	11.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.173134	43.8	9.000	N	0.2	11.0	54.8	Compliance
0.346296	36.6	9.000	N	0.2	12.5	49.1	Compliance
0.461346	33.8	9.000	N	0.2	12.9	46.7	Compliance
0.519918	36.0	9.000	N	0.2	10.0	46.0	Compliance
0.576662	34.3	9.000	N	0.2	11.7	46.0	Compliance
0.634524	32.0	9.000	N	0.2	14.0	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 2 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

8.80 dB at 2390 MHz in the Horizontal polarization for 802.11 n ht40 Mode

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	49 %
ATM Pressure:	100.1 kPa

* The testing was performed by Lion Xiao on 2015-11-30.

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	69.42	PK	H	25.67	3.68	0.00	98.77	N/A	N/A
2412	60.28	AV	H	25.67	3.68	0.00	89.63	N/A	N/A
2412	67.71	PK	V	25.67	3.68	0.00	97.06	N/A	N/A
2412	58.86	AV	V	25.67	3.68	0.00	88.21	N/A	N/A
2390	26.93	PK	H	25.61	3.63	0.00	56.17	74.00	17.83
2390	13.55	AV	H	25.61	3.63	0.00	42.79	54.00	11.21
4824	31.79	PK	H	30.64	5.03	27.41	40.05	74.00	33.95
4824	18.45	AV	H	30.64	5.03	27.41	26.71	54.00	27.29
7236	32.78	PK	H	34.17	6.65	25.90	47.70	74.00	26.30
7236	18.9	AV	H	34.17	6.65	25.90	33.82	54.00	20.18
9648	30.69	PK	H	36.06	8.55	27.46	47.84	74.00	26.16
9648	16.32	AV	H	36.06	8.55	27.46	33.47	54.00	20.53
3582	35.73	PK	H	28.98	4.58	27.26	42.03	74.00	31.97
3582	23.02	AV	H	28.98	4.58	27.26	29.32	54.00	24.68
279.1	34.6	QP	H	13.77	2.02	21.51	28.88	46.00	17.12
Middle Channel: 2437 MHz									
2437	69.95	PK	H	25.74	3.75	0.00	99.44	N/A	N/A
2437	60.53	AV	H	25.74	3.75	0.00	90.02	N/A	N/A
2437	67.88	PK	V	25.74	3.75	0.00	97.37	N/A	N/A
2437	58.02	AV	V	25.74	3.75	0.00	87.51	N/A	N/A
4874	32.2	PK	H	30.77	5.14	27.42	40.69	74.00	33.31
4874	18.69	AV	H	30.77	5.14	27.42	27.18	54.00	26.82
7311	33.05	PK	H	34.35	6.74	25.88	48.26	74.00	25.74
7311	19.03	AV	H	34.35	6.74	25.88	34.24	54.00	19.76
9748	30.93	PK	H	36.30	8.61	27.24	48.60	74.00	25.40
9748	16.53	AV	H	36.30	8.61	27.24	34.20	54.00	19.80
3085	33.9	PK	H	27.47	6.78	27.46	40.69	74.00	33.31
3085	21.15	AV	H	27.47	6.78	27.46	27.94	54.00	26.06
3582	35.32	PK	H	28.98	4.58	27.26	41.62	74.00	32.38
3582	23.19	AV	H	28.98	4.58	27.26	29.49	54.00	24.51
279.1	34.2	QP	H	13.77	2.02	21.51	28.48	46.00	17.52
High Channel: 2462 MHz									
2462	69.84	PK	H	25.80	3.75	0.00	99.39	N/A	N/A
2462	60.01	AV	H	25.80	3.75	0.00	89.56	N/A	N/A
2462	67.62	PK	V	25.80	3.75	0.00	97.17	N/A	N/A
2462	58.82	AV	V	25.80	3.75	0.00	88.37	N/A	N/A
2483.5	26.92	PK	H	25.86	3.67	0.00	56.45	74.00	17.55
2483.5	13.97	AV	H	25.86	3.67	0.00	43.50	54.00	10.50
4924	32.14	PK	H	30.90	5.34	27.43	40.95	74.00	33.05
4924	18.61	AV	H	30.90	5.34	27.43	27.42	54.00	26.58
7386	32.86	PK	H	34.53	6.83	25.86	48.36	74.00	25.64
7386	19.25	AV	H	34.53	6.83	25.86	34.75	54.00	19.25
9848	30.93	PK	H	36.54	8.66	26.94	49.19	74.00	24.81
9848	16.62	AV	H	36.54	8.66	26.94	34.88	54.00	19.12
3582	35.88	PK	H	28.98	4.58	27.26	42.18	74.00	31.82
3582	23.65	AV	H	28.98	4.58	27.26	29.95	54.00	24.05
279.1	34.8	QP	H	13.77	2.02	21.51	29.08	46.00	16.92

*within uncertainty measurement!

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	68.38	PK	H	25.67	3.68	0.00	97.73	N/A	N/A
2412	57.51	AV	H	25.67	3.68	0.00	86.86	N/A	N/A
2412	66.06	PK	V	25.67	3.68	0.00	95.41	N/A	N/A
2412	55.3	AV	V	25.67	3.68	0.00	84.65	N/A	N/A
2390	26.75	PK	H	25.61	3.63	0.00	55.99	74.00	18.01
2390	14.41	AV	H	25.61	3.63	0.00	43.65	54.00	10.35
4824	32	PK	H	30.64	5.03	27.41	40.26	74.00	33.74
4824	18.37	AV	H	30.64	5.03	27.41	26.63	54.00	27.37
7236	32.18	PK	H	34.17	6.65	25.90	47.10	74.00	26.90
7236	18.62	AV	H	34.17	6.65	25.90	33.54	54.00	20.46
9648	30.44	PK	H	36.06	8.55	27.46	47.59	74.00	26.41
9648	17.34	AV	H	36.06	8.55	27.46	34.49	54.00	19.51
3582	35.74	PK	H	28.98	4.58	27.26	42.04	74.00	31.96
3582	22.9	AV	H	28.98	4.58	27.26	29.20	54.00	24.80
279.1	34.1	QP	H	13.77	2.02	21.51	28.38	46.00	17.62
Middle Channel: 2437 MHz									
2437	68.9	PK	H	25.74	3.75	0.00	98.39	N/A	N/A
2437	57.68	AV	H	25.74	3.75	0.00	87.17	N/A	N/A
2437	66.25	PK	V	25.74	3.75	0.00	95.74	N/A	N/A
2437	55.5	AV	V	25.74	3.75	0.00	84.99	N/A	N/A
4874	32.04	PK	H	30.77	5.14	27.42	40.53	74.00	33.47
4874	18.83	AV	H	30.77	5.14	27.42	27.32	54.00	26.68
7311	32.53	PK	H	34.35	6.74	25.88	47.74	74.00	26.26
7311	18.92	AV	H	34.35	6.74	25.88	34.13	54.00	19.87
9748	30.94	PK	H	36.30	8.61	27.24	48.61	74.00	25.39
9748	17.78	AV	H	36.30	8.61	27.24	35.45	54.00	18.55
2950	36.36	PK	H	27.07	6.61	27.54	42.50	74.00	31.50
2950	23.36	AV	H	27.07	6.61	27.54	29.50	54.00	24.50
3632	34.45	PK	H	29.09	4.57	27.29	40.82	74.00	33.18
3632	21.37	AV	H	29.09	4.57	27.29	27.74	54.00	26.26
279.1	34.6	QP	H	13.77	2.02	21.51	28.88	46.00	17.12
High Channel: 2462 MHz									
2462	68.55	PK	H	25.80	3.75	0.00	98.10	N/A	N/A
2462	57.19	AV	H	25.80	3.75	0.00	86.74	N/A	N/A
2462	66.3	PK	V	25.80	3.75	0.00	95.85	N/A	N/A
2462	55.04	AV	V	25.80	3.75	0.00	84.59	N/A	N/A
2483.5	27.39	PK	H	25.86	3.67	0.00	56.92	74.00	17.08
2483.5	14.23	AV	H	25.86	3.67	0.00	43.76	54.00	10.24
4924	32.28	PK	H	30.90	5.34	27.43	41.09	74.00	32.91
4924	18.72	AV	H	30.90	5.34	27.43	27.53	54.00	26.47
7386	32.49	PK	H	34.53	6.83	25.86	47.99	74.00	26.01
7386	18.92	AV	H	34.53	6.83	25.86	34.42	54.00	19.58
9848	30.86	PK	H	36.54	8.66	26.94	49.12	74.00	24.88
9848	17.73	AV	H	36.54	8.66	26.94	35.99	54.00	18.01
3683	36.24	PK	H	29.20	4.60	27.32	42.72	74.00	31.28
3683	23.62	AV	H	29.20	4.60	27.32	30.10	54.00	23.90
279.1	34.9	QP	H	13.77	2.02	21.51	29.18	46.00	16.82

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	68.8	PK	H	25.67	3.68	0.00	98.15	N/A	N/A
2412	56.04	AV	H	25.67	3.68	0.00	85.39	N/A	N/A
2412	66.52	PK	V	25.67	3.68	0.00	95.87	N/A	N/A
2412	54.89	AV	V	25.67	3.68	0.00	84.24	N/A	N/A
2390	27.06	PK	H	25.61	3.63	0.00	56.30	74.00	17.70
2390	15.47	AV	H	25.61	3.63	0.00	44.71	54.00	9.29
4824	31.79	PK	H	30.64	5.03	27.41	40.05	74.00	33.95
4824	18.31	AV	H	30.64	5.03	27.41	26.57	54.00	27.43
7236	31.81	PK	H	34.17	6.65	25.90	46.73	74.00	27.27
7236	18.42	AV	H	34.17	6.65	25.90	33.34	54.00	20.66
9648	30.28	PK	H	36.06	8.55	27.46	47.43	74.00	26.57
9648	17.1	AV	H	36.06	8.55	27.46	34.25	54.00	19.75
3582	35.74	PK	H	28.98	4.58	27.26	42.04	74.00	31.96
3582	22.76	AV	H	28.98	4.58	27.26	29.06	54.00	24.94
279.1	34.5	QP	H	13.77	2.02	21.51	28.78	46.00	17.22
Middle Channel: 2437 MHz									
2437	68.11	PK	H	25.74	3.75	0.00	97.60	N/A	N/A
2437	56.35	AV	H	25.74	3.75	0.00	85.84	N/A	N/A
2437	66.89	PK	V	25.74	3.75	0.00	96.38	N/A	N/A
2437	54.99	AV	V	25.74	3.75	0.00	84.48	N/A	N/A
4874	32.03	PK	H	30.77	5.14	27.42	40.52	74.00	33.48
4874	18.38	AV	H	30.77	5.14	27.42	26.87	54.00	27.13
7311	32.12	PK	H	34.35	6.74	25.88	47.33	74.00	26.67
7311	18.63	AV	H	34.35	6.74	25.88	33.84	54.00	20.16
9748	30.44	PK	H	36.30	8.61	27.24	48.11	74.00	25.89
9748	17.42	AV	H	36.30	8.61	27.24	35.09	54.00	18.91
2005	35.81	PK	H	24.61	3.16	27.48	36.10	74.00	37.90
2005	23.25	AV	H	24.61	3.16	27.48	23.54	54.00	30.46
3632	34.36	PK	H	29.09	4.57	27.29	40.73	74.00	33.27
3632	21.16	AV	H	29.09	4.57	27.29	27.53	54.00	26.47
279.1	34.3	QP	H	13.77	2.02	21.51	28.58	46.00	17.42
High Channel: 2462 MHz									
2462	68.82	PK	H	25.80	3.75	0.00	98.37	N/A	N/A
2462	56.61	AV	H	25.80	3.75	0.00	86.16	N/A	N/A
2462	66.64	PK	V	25.80	3.75	0.00	96.19	N/A	N/A
2462	54.37	AV	V	25.80	3.75	0.00	83.92	N/A	N/A
2483.5	27.85	PK	H	25.86	3.67	0.00	57.38	74.00	16.62
2483.5	15.05	AV	H	25.86	3.67	0.00	44.58	54.00	9.42
4924	32.23	PK	H	30.90	5.34	27.43	41.04	74.00	32.96
4924	18.75	AV	H	30.90	5.34	27.43	27.56	54.00	26.44
7386	32.63	PK	H	34.53	6.83	25.86	48.13	74.00	25.87
7386	19.01	AV	H	34.53	6.83	25.86	34.51	54.00	19.49
9848	30.77	PK	H	36.54	8.66	26.94	49.03	74.00	24.97
9848	17.88	AV	H	36.54	8.66	26.94	36.14	54.00	17.86
3682	36.41	PK	H	29.20	4.60	27.32	42.89	74.00	31.11
3682	23.55	AV	H	29.20	4.60	27.32	30.03	54.00	23.97
279.1	34.1	QP	H	13.77	2.02	21.51	28.38	46.00	17.62

802.11 n ht40 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	67.07	PK	H	25.70	3.71	0.00	96.48	N/A	N/A
2422	55.92	AV	H	25.70	3.71	0.00	85.33	N/A	N/A
2422	65.55	PK	V	25.70	3.71	0.00	94.96	N/A	N/A
2422	53.3	AV	V	25.70	3.71	0.00	82.71	N/A	N/A
2390	28.25	PK	H	25.61	3.63	0.00	57.49	74.00	16.51
2390	15.96	AV	H	25.61	3.63	0.00	45.20	54.00	8.80
4844	31.56	PK	H	30.69	4.99	27.42	39.82	74.00	34.18
4844	18.17	AV	H	30.69	4.99	27.42	40.32	54.00	13.68
7266	32.06	PK	H	34.24	6.68	25.89	33.41	74.00	40.59
7266	18.38	AV	H	34.24	6.68	25.89	33.41	54.00	20.59
9688	30.16	PK	H	36.15	8.58	27.37	47.52	74.00	26.48
9688	17.26	AV	H	36.15	8.58	27.37	34.62	54.00	19.38
3582	35.58	PK	H	28.98	4.58	27.26	41.88	74.00	32.12
3582	22.95	AV	H	28.98	4.58	27.26	29.25	54.00	24.75
279.1	34.8	QP	H	13.77	2.02	21.51	29.08	46.00	16.92
Middle Channel: 2437 MHz									
2437	67.9	PK	H	25.74	3.75	0.00	97.39	N/A	N/A
2437	55.25	AV	H	25.74	3.75	0.00	84.74	N/A	N/A
2437	65.13	PK	V	25.74	3.75	0.00	94.62	N/A	N/A
2437	53.79	AV	V	25.74	3.75	0.00	83.28	N/A	N/A
4874	31.68	PK	H	30.77	5.14	27.42	40.17	74.00	33.83
4874	18.13	AV	H	30.77	5.14	27.42	26.62	54.00	27.38
7311	32.1	PK	H	34.35	6.74	25.88	47.31	74.00	26.69
7311	18.4	AV	H	34.35	6.74	25.88	33.61	54.00	20.39
9748	30.28	PK	H	36.30	8.61	27.24	47.95	74.00	26.05
9748	17.2	AV	H	36.30	8.61	27.24	34.87	54.00	19.13
1810	35.69	PK	H	24.22	2.69	27.53	35.07	74.00	38.93
1810	22.9	AV	H	24.22	2.69	27.53	22.28	54.00	31.72
3632	33.92	PK	H	29.09	4.57	27.29	40.29	74.00	33.71
3632	21.01	AV	H	29.09	4.57	27.29	27.38	54.00	26.62
279.1	34.5	QP	H	13.77	2.02	21.51	28.78	46.00	17.22
High Channel: 2452 MHz									
2452	67.58	PK	H	25.78	3.78	0.00	97.14	N/A	N/A
2452	55.25	AV	H	25.78	3.78	0.00	84.81	N/A	N/A
2452	65.06	PK	V	25.78	3.78	0.00	94.62	N/A	N/A
2452	53.84	AV	V	25.78	3.78	0.00	83.40	N/A	N/A
2483.5	28.93	PK	H	25.86	3.67	0.00	58.46	74.00	15.54
2483.5	15.27	AV	H	25.86	3.67	0.00	44.80	54.00	9.20
4904	31.84	PK	H	30.85	5.31	27.43	40.57	74.00	33.43
4904	18.51	AV	H	30.85	5.31	27.43	27.24	54.00	26.76
7356	32.35	PK	H	34.45	6.79	25.87	47.72	74.00	26.28
7356	18.68	AV	H	34.45	6.79	25.87	34.05	54.00	19.95
9808	30.65	PK	H	36.44	8.64	27.09	48.64	74.00	25.36
9808	17.5	AV	H	36.44	8.64	27.09	35.49	54.00	18.51
3683	36.07	PK	H	29.20	4.60	27.32	42.55	74.00	31.45
3683	23.31	AV	H	29.20	4.60	27.32	29.79	54.00	24.21
279.1	34	QP	H	13.77	2.02	21.51	28.28	46.00	17.72

BLE Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	62.56	PK	H	25.65	3.66	0.00	91.87	N/A	N/A
2402	52.87	AV	H	25.65	3.66	0.00	82.18	N/A	N/A
2402	60.38	PK	V	25.65	3.66	0.00	89.69	N/A	N/A
2402	50.21	AV	V	25.65	3.66	0.00	79.52	N/A	N/A
2390	26.84	PK	H	25.61	3.63	0.00	56.08	74.00	17.92
2390	14.81	AV	H	25.61	3.63	0.00	44.05	54.00	9.95
4804	31.41	PK	H	30.59	5.06	27.41	39.65	74.00	34.35
4804	19.26	AV	H	30.59	5.06	27.41	27.50	54.00	26.50
7206	32.12	PK	H	34.09	6.61	25.91	46.91	74.00	27.09
7206	20.86	AV	H	34.09	6.61	25.91	35.65	54.00	18.35
9608	30.88	PK	H	35.96	8.53	27.55	47.82	74.00	26.18
9608	18.34	AV	H	35.96	8.53	27.55	35.28	54.00	18.72
1690	33.68	PK	H	23.98	2.88	27.68	32.86	74.00	41.14
1690	21.42	AV	H	23.98	2.88	27.68	20.60	54.00	33.40
239.4	35.7	QP	H	12.21	1.86	21.48	28.29	46.00	17.71
Middle Channel: 2440 MHz									
2440	62.91	PK	H	25.74	3.76	0.00	92.41	N/A	N/A
2440	52.57	AV	H	25.74	3.76	0.00	82.07	N/A	N/A
2440	60.96	PK	V	25.74	3.76	0.00	90.46	N/A	N/A
2440	50.83	AV	V	25.74	3.76	0.00	80.33	N/A	N/A
4880	31.48	PK	H	30.79	5.18	27.42	40.03	74.00	33.97
4880	19.18	AV	H	30.79	5.18	27.42	27.73	54.00	26.27
7320	32.06	PK	H	34.37	6.75	25.88	47.30	74.00	26.70
7320	20.72	AV	H	34.37	6.75	25.88	35.96	54.00	18.04
9760	30.8	PK	H	36.32	8.62	27.21	48.53	74.00	25.47
9760	18.42	AV	H	36.32	8.62	27.21	36.15	54.00	17.85
4365	33.29	PK	H	29.83	5.00	26.92	41.20	74.00	32.80
4365	21.57	AV	H	29.83	5.00	26.92	29.48	54.00	24.52
1690	33.52	PK	H	23.98	2.88	27.68	32.70	74.00	41.30
1690	21.44	AV	H	23.98	2.88	27.68	20.62	54.00	33.38
239.4	35.4	QP	H	12.21	1.86	21.48	27.99	46.00	18.01
High Channel: 2480 MHz									
2480	62.57	PK	H	25.85	3.68	0.00	92.10	N/A	N/A
2480	52.42	AV	H	25.85	3.68	0.00	81.95	N/A	N/A
2480	60.3	PK	V	25.85	3.68	0.00	89.83	N/A	N/A
2480	50.25	AV	V	25.85	3.68	0.00	79.78	N/A	N/A
2483.5	26.74	PK	H	25.86	3.67	0.00	56.27	74.00	17.73
2483.5	14.41	AV	H	25.86	3.67	0.00	43.94	54.00	10.06
4960	31.91	PK	H	31.00	5.34	27.43	40.82	74.00	33.18
4960	19.76	AV	H	31.00	5.34	27.43	28.67	54.00	25.33
7440	32.41	PK	H	34.66	6.89	25.97	47.99	74.00	26.01
7440	20.92	AV	H	34.66	6.89	25.97	36.50	54.00	17.50
9920	31.06	PK	H	36.71	8.71	26.66	49.82	74.00	24.18
9920	18.87	AV	H	36.71	8.71	26.66	37.63	54.00	16.37
1690	33.71	PK	H	23.98	2.88	27.68	32.89	74.00	41.11
1690	21.5	AV	H	23.98	2.88	27.68	20.68	54.00	33.32
239.4	35.9	QP	H	12.21	1.86	21.48	28.49	46.00	17.51

Conducted Spurious Emissions at Antenna Port


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n ht20 Low Channel




802.11n ht20 Middle Channel




802.11n ht20 High Channel




802.11n ht40 Low Channel




802.11n ht40 Middle Channel




802.11n ht40 High Channel




BLE Low Channel



BLE Middle Channel



BLE High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	49 %
ATM Pressure:	100.1 kPa


* The testing was performed by Lion Xiao on 2015-11-30.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.261	≥ 0.5
	Middle	2437	10.261	≥ 0.5
	High	2462	10.261	≥ 0.5
802.11g	Low	2412	16.593	≥ 0.5
	Middle	2437	16.593	≥ 0.5
	High	2462	16.593	≥ 0.5
802.11n20	Low	2412	17.796	≥ 0.5
	Middle	2437	17.796	≥ 0.5
	High	2462	17.796	≥ 0.5
802.11n40	Low	2422	35.591	≥ 0.5
	Middle	2437	35.591	≥ 0.5
	High	2452	35.591	≥ 0.5
BLE	Low	2402	0.745	≥ 0.5
	Middle	2440	0.745	≥ 0.5
	High	2480	0.745	≥ 0.5

802.11b Low Channel



Ref Lvl
15 dBm

Delta 1 [T1]
-2.14 dB

RBW
100 kHz

RF Att
30 dB

VSWR
300 kHz

SWT
10 ms

Unit
dBm

Marker	Type	Freq [MHz]	Power [dBm]
1	[T1]	2.43190882	-7.35
2	[T1]	2.42990581	-15.23
3	[T1]	2.44425451	-13.96
4	[T1]	2.43869739	-13.96
5	[T1]	2.43190882	-2.14
6	[T1]	2.43190882	-7.35

Center 2.437 GHz

Span 40 MHz

Ref Lvl 15 dBm

Delta 1 [T1] -2.63 dB

10.26052104 MHz

RBW 100 kHz

VBW 300 kHz

SWT 10 ms

RF Att 30 dB

Unit dBm

1 dB Offset

D1 0.13 dBm

D2 -5.87 dBm

1MAX

1 [T1] -7.08 dBm

2 [T1] -2.63 dBm

3 [T1] -10.26052104 MHz

4 [T1] -14.21 dBm

5 [T1] -15.48 dBm

6 [T1] -2.45690882 GHz

7 [T1] -2.45490581 GHz

8 [T1] -2.46917435 GHz


Center 2.462 GHz

4 MHz/


Span 40 MHz



Date: 30.NOV.2015 15:47:09

802.11g Low Channel



802.11g Middle Channel



802.11g High Channel**802.11n ht20 Low Channel**

Ref Lvl 15 dBm

Delta 1 [T1] -0.46 dB

RBW 100 kHz

SWT 10 ms

Unit dBm

1 dB Offset

D1 -1.56 dBm

D2 -7.56 dBm

1MAX

1 [T1] -8.84 dBm

2.42814228 GHz

17.79559118 MHz

17.71543086 MHz

2.42814228 GHz

1 [T1] -0.46 dBm

2 [T1] -7.61 dBm

2.44585772 GHz

1MA

Center 2.437 GHz

4 MHz

Span 40 MHz

Date: 30.NOV.2015 16:30:47

Ref Lvl 15 dBm

Delta 1 [T1] -0.19 dB

RBW 100 kHz RF Att 30 dB

VBW 300 kHz

SWT 10 ms Unit dBm

1 dB Offset

D1 -1.76 dBm

D2 -7.76 dBm

1MAX

1MA

Center 2.462 GHz

4 MHz/

Span 40 MHz

1 [T1] -8.82 dBm

2.45314228 GHz

2 [T1] -0.19 dB

17.79559118 MHz


3 [T1] -8.82 dBm

2.45314228 GHz


4 [T1] -7.39 dBm

2.47085772 GHz

802.11n ht40 Low Channel



802.11n ht40 Middle Channel



Delta 1 [T1] 1.14 dB
 RBW 100 kHz
 VBW 300 kHz
 SWT 20 ms
 RF Att 30 dB
 Ref Lvl 15 dBm
 35.59118236 MHz
 Unit dBm


1 dB Offset
 -D1 -3.58 dBm
 -D2 -9.58 dBm
 1MAX
 1 [T1] -11.03 dBm
 2.43428457 GHz
 1.14 dB
 35.59118236 MHz
 35.91182365 MHz
 -10.86 dBm
 2.43412425 GHz
 -11.05 dBm
 2.47883587 GHz
 1MA

Center 2.452 GHz
 8 MHz/
 Span 80 MHz


Date: 30.NOV.2015 17:20:00

[illegible]

BLE Middle Channel



BLE High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2015-11-03	2016-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2015-11-03	2016-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2015-11-03	2016-11-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	49 %
ATM Pressure:	100.1 kPa

* The testing was performed by Lion Xiao on 2015-11-30.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Max Conducted Average Output Power	Limit
		(MHz)	(dBm)	(dBm)	(dBm)
802.11b	Low	2412	10.93	9.53	30
	Middle	2437	10.85	9.47	30
	High	2462	10.78	9.42	30
802.11g	Low	2412	13.42	9.56	30
	Middle	2437	13.35	9.48	30
	High	2462	13.49	9.60	30
802.11n20	Low	2412	13.73	9.49	30
	Middle	2437	13.69	9.45	30
	High	2462	13.61	9.37	30
802.11n40	Low	2422	14.78	9.50	30
	Middle	2437	14.90	9.58	30
	High	2452	14.94	9.62	30
BLE	Low	2402	-3.26	/	30
	Middle	2440	-3.1	/	30
	High	2480	-3.43	/	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	25.5 °C
Relative Humidity:	49 %
ATM Pressure:	100.1 kPa

* The testing was performed by Lion Xiao on 2015-11-30.


Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side





802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side




802.11n ht20 Band Edge, Left Side**802.11n ht20 Band Edge, Right Side**


802.11n ht40 Band Edge, Left Side




802.11n ht40 Band Edge, Right Side



BLE Band Edge , Left Side



BLE Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.5 °C
Relative Humidity:	49 %
ATM Pressure:	100.1 kPa


* The testing was performed by Lion Xiao on 2015-11-30.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-14.93	≤ 8
	Middle	2437	-14.98	≤ 8
	High	2462	-15.00	≤ 8
802.11g	Low	2412	-16.02	≤ 8
	Middle	2437	-16.05	≤ 8
	High	2462	-15.97	≤ 8
802.11n20	Low	2412	-16.61	≤ 8
	Middle	2437	-16.62	≤ 8
	High	2462	-16.65	≤ 8
802.11n40	Low	2422	-19.19	≤ 8
	Middle	2437	-19.10	≤ 8
	High	2452	-19.08	≤ 8
BLE	Low	2402	-18.58	≤ 8
	Middle	2440	-18.48	≤ 8
	High	2480	-18.64	≤ 8

Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Date: 30.NOV.2015 15:39:51

Power Spectral Density, 802.11b High Channel




Date: 30.NOV.2015 15:50:34


Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n ht20 Low Channel




Power Spectral Density, 802.11n ht20 Middle Channel




Power Spectral Density, 802.11n ht20 High Channel




Power Spectral Density, 802.11n ht40 Low Channel




Power Spectral Density, 802.11n ht40 Middle Channel




Power Spectral Density, 802.11n ht40 High Channel



Power Spectral Density, BLE Low Channel




Power Spectral Density, BLE Middle Channel



Date: 30.NOV.2015 15:13:55

Power Spectral Density, BLE High Channel



Date: 30.NOV.2015 15:13:19

DECLARATION LETTER

MAXWEST INTERNATIONAL LIMITED

Add: No.1, Longgang Road, Buji, Longgang, Shenzhen City, Guangdong Province, P.R. China

Tel: 9498007607

Fax: 9498007607

DECLARATION OF SIMILARITY

Date: 2015-11-25

Dear Sir or Madam:

We, MAXWEST INTERNATIONAL LIMITED, hereby declare that product name: Gravity 5LTE, model: Gravity 5LTE, they are the same electromagnetic emissions and electromagnetic compatibility characteristics. A description of the difference among the 3 samples and those that are declared similar are as follows:

1) They have different colours: golden, black and silver.


The rest are the same.

Please contact me should there be need for any additional clarification or information.

Best Regards,

Signature:

Rita Yu



Assistant Manager

***** END OF REPORT *****