

FCC PART 15.247 TEST REPORT

For

MAXWEST INTERNATIONAL LIMITED.

No.1, Longgang Road, Buji, Longgang, Shenzhen, China

FCC ID: 2AEN3ASTRO5NLTE

Report Type: **Product Name:** Original Report Mobile Phone

Report Number: RDG171020005 -00B

Report Date: 2017-11-16

Jerry Zhang

EMC Manager

Reviewed By:

Bay Area Compliance Laboratories Corp. (Dongguan)

Jerry Zhang

Test Laboratory: No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-8685888

Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
EQUIPMENT MODIFICATIONS	
SUPPORT CABLE LIST AND DETAILS	6
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	
APPLICABLE STANDARD	8
FCC §15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST DATA	16
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	
APPLICABLE STANDARD	22
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
TEST DATA	
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	
APPLICABLE STANDARD	
TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS	
TEST EQUITMENT LIST AND DETAILS	∠o

TEST DATA	28
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	34
TEST DATA	34
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	38
APPLICABLE STANDARD	38
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	38
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	54
APPLICABLE STANDARD	54
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(d) - BAND EDGES TESTING	60
APPLICABLE STANDARD	60
TEST PROCEDURE	60
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	61

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *MAXWEST INTERNATIONAL LIMITED*.'s product, model number: *Astro 5N LTE* (*FCC ID: 2AEN3ASTRO5NLTE*) (the "EUT") in this report was a *Mobile Phone*, which was measured approximately: 14.4 cm (L) x 7.4 cm (W) x 1.1 cm (H), rated input voltage: DC 3.8V from battery or DC 5.0V from adapter.

Adapter Information: Model: AsTro 5N LTE

Input: AC100-240V 50/60Hz 0.2A

Output: 5.0V, 1A

*All measurement and test data in this report was gathered from production sample serial number: 171010005 (Assigned by BACL,Dongguan). The EUT was received on 2017-10-10.

Objective

This report is prepared on behalf of *MAXWEST INTERNATIONAL LIMITED*. in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: 2AEN3ASTRO5NLTE. FCC Part 15B JBP submissions with FCC ID: 2AEN3ASTRO5NLTE. FCC Part 22H, 24E, 27 PCE submissions with FCC ID: 2AEN3ASTRO5NLTE.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical
Unwanted Emissions, radiated	200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical
	1G~6GHz: 4.45 dB, 6G~26.5GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1℃
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

Bay Area Compliance Laboratories Corp. (Dongguan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L5662). And accredited to ISO/IEC 17025 by NVLAP(Test Laboratory Accreditation Certificate Number 500069-0), the FCC Designation No. CN5002 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Dongguan) was registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The system configured the maximum power level as below setting:

Test Software Version	Engineer Mode								
Test Frequency	2402MHz	2402MHz 2441MHz 2480MHz							
GFSK	33 33 33								
π / 4DQPSK	33	33	33						
8-DPSK	33	33	33						


Equipment Modifications

No modification was made to the EUT.

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
USB Cable	no	no	0.89	EUT	Adapter
earphone	no	no	1.19	earphone	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
\$15.205, \$15.209, \$15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is 9.2 dBm (8.32 mW). [(max. power of channel, mW)/(min. test separation distance, mm)][$\sqrt{f(GHz)}$] = 8.32/5*($\sqrt{2}$.480) = 2.6< 3.0

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W		
150 kHz – 30 MHz	9 kHz		

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 V_C : corrected voltage amplitude V_R : reading voltage amplitude A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Model Serial Number		Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2016/12/8	2017/12/8
R&S	Two-line V-network	ENV 216 3560.6550.12		2016/12/8	2017/12/8
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
N/A	Coaxial Cable	C-NJNJ-50	C-0200-01	2017/9/5	2018/9/5
EVERFINE	TRIPLE-LOOP antenna	LLA-2	903002	2015/7/16	2018/7/16

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	24.9 °C
Relative Humidity:	52 %
ATM Pressure:	100.9 kPa

The testing was performed by Alex You on 2017-11-16.

Report No.: RDG171020005 -00B

Test Mode: Transmitting

AC120V, 60 Hz, Line:




Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.387164	50.9	9.000	L1	10.0	7.2	58.1	Compliance
0.439808	46.7	9.000	L1	9.9	10.4	57.1	Compliance
0.799472	44.1	9.000	L1	9.8	11.9	56.0	Compliance
1.171949	44.9	9.000	L1	9.8	11.1	56.0	Compliance
2.030886	42.8	9.000	L1	9.7	13.2	56.0	Compliance
2.199332	42.1	9.000	L1	9.7	13.9	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.351859	39.3	9.000	L1	10.0	9.6	48.9	Compliance
0.393383	42.9	9.000	L1	10.0	5.1	48.0	Compliance
0.439808	38.6	9.000	L1	9.9	8.5	47.1	Compliance
0.780588	36.9	9.000	L1	9.8	9.1	46.0	Compliance
1.065081	37.4	9.000	L1	9.8	8.6	46.0	Compliance
1.407671	34.1	9.000	L1	9.7	11.9	46.0	Compliance

K

Report No.: RDG171020005 -00B

AC120V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.703777	44.0	9.000	N	9.8	12.0	56.0	Compliance
0.750100	43.9	9.000	N	9.8	12.1	56.0	Compliance
0.865782	43.2	9.000	N	9.8	12.8	56.0	Compliance
1.065081	43.8	9.000	N	9.8	12.2	56.0	Compliance
1.219583	44.7	9.000	N	9.8	11.3	56.0	Compliance
1.548915	43.4	9.000	N	9.7	12.6	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.351859	29.4	9.000	N	10.0	19.5	48.9	Compliance
0.393383	28.9	9.000	N	10.0	19.1	48.0	Compliance
0.429420	29.9	9.000	N	9.9	17.4	47.3	Compliance
0.703777	31.8	9.000	N	9.8	14.2	46.0	Compliance
1.108371	34.4	9.000	N	9.8	11.6	46.0	Compliance
1.289541	35.0	9.000	N	9.8	11.0	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above I GHZ	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2017/9/1	2018/9/1
Sunol Sciences	Antenna	JB3	A060611-2	2017/8/25	2020/8/25
HP	Amplifier	8447D	2727A05902	2017/9/5	2018/9/5
Agilent	Spectrum Analyzer	E4440A	SG43360054	2016/12/8	2017/12/8
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016/1/5	2019/1/5
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2017/9/5	2018/9/5
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-02 1304	2016/11/18	2019/11/18
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017/6/27	2018/6/27
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017/9/5	2018/9/5
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017/9/5	2018/9/5
N/A	Coaxial Cable	C-NJNJ-50	C-1000-01	2017/9/5	2018/9/5
N/A	Coaxial Cable	C-SJSJ-50	C-0800-01	2017/9/5	2018/9/5
Farad	Test Software	EZ-EMC	V1.1.42	N/A	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data

Environmental Conditions


Temperature:	26.8°C
Relative Humidity:	28.8 %
ATM Pressure:	101 kPa

The testing was performed by Sunny Cen from 2017-10-11

Test Mode: Transmitting

1) 30MHz-1GHz(8DPSK Low channel was the worst)


Horizontal:



Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.9700	26.35	QP	0.35	26.70	40.00	13.30
78.5000	34.71	QP	-11.11	23.60	40.00	16.40
123.1200	25.98	QP	-4.78	21.20	43.50	22.30
175.5000	29.81	QP	-7.71	22.10	43.50	21.40
257.9500	23.31	QP	-5.71	17.60	46.00	28.40
304.5100	24.66	QP	-4.46	20.20	46.00	25.80

Report No.: RDG171020005 -00B

Vertical:



Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)
40.6700	43.25	QP	-6.75	36.50	40.00	3.50
48.4300	43.59	QP	-11.09	32.50	40.00	7.50
79.4700	40.91	QP	-11.11	29.80	40.00	10.20
172.5900	33.97	QP	-7.57	26.40	43.50	17.10
285.1100	24.20	QP	-3.80	20.40	46.00	25.60
362.7100	25.89	QP	-2.89	23.00	46.00	23.00

1GHz-25GHz:

BDR Mode (GFSK):

BDR Mode (eiver	Rx A	ntenna	Cable	Amplifier	Corrected		
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402.00	72.13	PK	Н	28.10	1.80	0.00	102.03	N/A	N/A
2402.00	66.71	AV	Н	28.10	1.80	0.00	96.61	N/A	N/A
2402.00	66.89	PK	V	28.10	1.80	0.00	96.79	N/A	N/A
2402.00	56.9	AV	V	28.10	1.80	0.00	86.80	N/A	N/A
2390.00	28.55	PK	Н	28.08	1.80	0.00	58.43	74.00	15.57
2390.00	15.38	AV	Н	28.08	1.80	0.00	45.26	54.00	8.74
4804.00	37.21	PK	Н	32.91	3.17	37.20	36.09	74.00	37.91
4804.00	25.4	AV	Н	32.91	3.17	37.20	24.28	54.00	29.72
7206.00	37.96	PK	Н	35.74	4.82	37.23	41.29	74.00	32.71
7206.00	24.88	AV	Н	35.74	4.82	37.23	28.21	54.00	25.79
2375.00	38.08	PK	Н	28.05	1.79	36.42	31.50	74.00	42.50
2375.00	26.08	AV	Н	28.05	1.79	36.42	19.50	54.00	34.50
				Middle Cha		l MHz			
2441.00	70.3	PK	Н	28.18	1.82	0.00	100.30	N/A	N/A
2441.00	60.71	AV	Н	28.18	1.82	0.00	90.71	N/A	N/A
2441.00	63.62	PK	V	28.18	1.82	0.00	93.62	N/A	N/A
2441.00	54.83	AV	V	28.18	1.82	0.00	84.83	N/A	N/A
4882.00	37.49	PK	Н	33.06	3.27	37.21	36.61	74.00	37.39
4882.00	25.85	AV	Н	33.06	3.27	37.21	24.97	54.00	29.03
7323.00	37.39	PK	Н	36.04	4.62	37.38	40.67	74.00	33.33
7323.00	25.86	AV	Н	36.04	4.62	37.38	29.14	54.00	24.86
1692.00	38.28	PK	Н	26.01	1.64	36.14	29.79	74.00	44.21
1692.00	25.59	AV	Н	26.01	1.64	36.14	17.10	54.00	36.9
2754.00	38.22	PK	Н	29.21	1.91	36.52	32.82	74.00	41.18
2754.00	25.8	AV	Н	29.21	1.91	36.52	20.40	54.00	33.6
				High Chan					
2480.00	70.52	PK	Н	28.26	1.84	0.00	100.62	N/A	N/A
2480.00	62.83	AV	Н	28.26	1.84	0.00	92.93	N/A	N/A
2480.00	65.26	PK	V	28.26	1.84	0.00	95.36	N/A	N/A
2480.00	54.53	AV	V	28.26	1.84	0.00	84.63	N/A	N/A
2483.50	28.75	PK	Н	28.27	1.84	0.00	58.86	74.00	15.14
2483.50	15.08	AV	Н	28.27	1.84	0.00	45.19	54.00	8.81
4960.00	38.91	PK	Н	33.22	3.23	37.25	38.11	74.00	35.89
4960.00	25.39	AV	Н	33.22	3.23	37.25	24.59	54.00	29.41
7440.00	38.17	PK	Н	36.34	4.41	37.52	41.40	74.00	32.6
7440.00	24.91	AV	Н	36.34	4.41	37.52	28.14	54.00	25.86
2437.00	37.73	PK	Н	28.17	1.82	36.40	31.32	74.00	42.68
2437.00	25.94	AV	Н	28.17	1.82	36.40	19.53	54.00	34.47

EDR Mode ($\pi/4$ -DQPSK):

.	Rec	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	T	3.6
Frequency (MHz)	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402.00	73.6	PK	Н	28.10	1.80	0.00	103.50	N/A	N/A
2402.00	60.6	AV	Н	28.10	1.80	0.00	90.50	N/A	N/A
2402.00	68.4	PK	V	28.10	1.80	0.00	98.30	N/A	N/A
2402.00	58.93	AV	V	28.10	1.80	0.00	88.83	N/A	N/A
2390.00	28.7	PK	Н	28.08	1.80	0.00	58.58	74.00	15.42
2390.00	15.03	AV	Н	28.08	1.80	0.00	44.91	54.00	9.09
4804.00	38.24	PK	Н	32.91	3.17	37.20	37.12	74.00	36.88
4804.00	26.23	AV	Н	32.91	3.17	37.20	25.11	54.00	28.89
7206.00	36.99	PK	Н	35.74	4.82	37.23	40.32	74.00	33.68
7206.00	25.54	AV	Н	35.74	4.82	37.23	28.87	54.00	25.13
2457.00	39.19	PK	Н	28.21	1.83	36.39	32.84	74.00	41.16
2457.00	25.5	AV	Н	28.21	1.83	36.39	19.15	54.00	34.85
			N	Middle Cha	nnel: 244	1 MHz			
2441.00	71.53	PK	Н	28.18	1.82	0.00	101.53	N/A	N/A
2441.00	59.89	AV	Н	28.18	1.82	0.00	89.89	N/A	N/A
2441.00	65.39	PK	V	28.18	1.82	0.00	95.39	N/A	N/A
2441.00	54.28	AV	V	28.18	1.82	0.00	84.28	N/A	N/A
4882.00	37.32	PK	Н	33.06	3.27	37.21	36.44	74.00	37.56
4882.00	25.48	AV	Н	33.06	3.27	37.21	24.60	54.00	29.4
7323.00	37.68	PK	Н	36.04	4.62	37.38	40.96	74.00	33.04
7323.00	26.44	AV	Н	36.04	4.62	37.38	29.72	54.00	24.28
2884.00	37.94	PK	Н	29.68	2.10	37.02	32.70	74.00	41.3
2884.00	25.59	AV	Н	29.68	2.10	37.02	20.35	54.00	33.65
1377.00	38.94	PK	Н	24.78	1.62	36.00	29.34	74.00	44.66
1377.00	26.49	AV	Н	24.78	1.62	36.00	16.89	54.00	37.11
				High Chan	nel: 2480	MHz			
2480.00	72.77	PK	Н	28.26	1.84	0.00	102.87	N/A	N/A
2480.00	63.94	AV	Н	28.26	1.84	0.00	94.04	N/A	N/A
2480.00	64.03	PK	V	28.26	1.84	0.00	94.13	N/A	N/A
2480.00	57.36	AV	V	28.26	1.84	0.00	87.46	N/A	N/A
2483.50	28.84	PK	Н	28.27	1.84	0.00	58.95	74.00	15.05
2483.50	14.47	AV	Н	28.27	1.84	0.00	44.58	54.00	9.42
4960.00	38.14	PK	Н	33.22	3.23	37.25	37.34	74.00	36.66
4960.00	24.98	AV	Н	33.22	3.23	37.25	24.18	54.00	29.82
7440.00	37.97	PK	Н	36.34	4.41	37.52	41.20	74.00	32.8
7440.00	24.72	AV	Н	36.34	4.41	37.52	27.95	54.00	26.05
1837.00	37.54	PK	Н	26.62	1.66	35.96	29.86	74.00	44.14
1837.00	25.70	AV	Н	26.62	1.66	35.96	18.02	54.00	35.98

Report No.: RDG171020005 -00B

EDR Mode (8-DPSK):

	Rec	eiver	Rx A	ntenna	Cable	Amplifier	Corrected		3.5
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402.00	74.74	PK	Н	28.10	1.80	0.00	104.64	N/A	N/A
2402.00	64.27	AV	Н	28.10	1.80	0.00	94.17	N/A	N/A
2402.00	67.37	PK	V	28.10	1.80	0.00	97.27	N/A	N/A
2402.00	58.38	AV	V	28.10	1.80	0.00	88.28	N/A	N/A
2390.00	29.99	PK	Н	28.08	1.80	0.00	59.87	74.00	14.13
2390.00	15.24	AV	Н	28.08	1.80	0.00	45.12	54.00	8.88
4804.00	38.42	PK	Н	32.91	3.17	37.20	37.30	74.00	36.70
4804.00	26.07	AV	Н	32.91	3.17	37.20	24.95	54.00	29.05
7206.00	38.03	PK	Н	35.74	4.82	37.23	41.36	74.00	32.64
7206.00	26.65	AV	Н	35.74	4.82	37.23	29.98	54.00	24.02
2388.00	37.88	PK	Н	28.08	1.79	36.42	31.33	74.00	42.67
2388.00	26.35	AV	Н	28.08	1.79	36.42	19.80	54.00	34.20
	_	_		Middle Cha	nnel: 244	1 MHz			
2441.00	71.94	PK	Н	28.18	1.82	0.00	101.94	N/A	N/A
2441.00	59.81	AV	Н	28.18	1.82	0.00	89.81	N/A	N/A
2441.00	65.03	PK	V	28.18	1.82	0.00	95.03	N/A	N/A
2441.00	54.74	AV	V	28.18	1.82	0.00	84.74	N/A	N/A
4882.00	37.36	PK	Н	33.06	3.27	37.21	36.48	74.00	37.52
4882.00	25.23	AV	Н	33.06	3.27	37.21	24.35	54.00	29.65
7323.00	38.24	PK	Н	36.04	4.62	37.38	41.52	74.00	32.48
7323.00	25.48	AV	Н	36.04	4.62	37.38	28.76	54.00	25.24
1441.00	37.97	PK	Н	25.00	1.69	36.05	28.61	74.00	45.39
1441.00	25.09	AV	Н	25.00	1.69	36.05	15.73	54.00	38.27
2658.00	37.93	PK	Н	28.87	1.87	36.43	32.24	74.00	41.76
2658.00	25.87	AV	Н	28.87	1.87	36.43	20.18	54.00	33.82
				High Chan	nel: 2480	MHz			
2480.00	72.78	PK	Н	28.26	1.84	0.00	102.88	N/A	N/A
2480.00	62.41	AV	Н	28.26	1.84	0.00	92.51	N/A	N/A
2480.00	67.49	PK	V	28.26	1.84	0.00	97.59	N/A	N/A
2480.00	57.10	AV	V	28.26	1.84	0.00	87.20	N/A	N/A
2483.50	27.44	PK	Н	28.27	1.84	0.00	57.55	74.00	16.45
2483.50	14.65	AV	Н	28.27	1.84	0.00	44.76	54.00	9.24
4960.00	38.22	PK	Н	33.22	3.23	37.25	37.42	74.00	36.58
4960.00	25.51	AV	Н	33.22	3.23	37.25	24.71	54.00	29.29
7440.00	37.59	PK	Н	36.34	4.41	37.52	40.82	74.00	33.18
7440.00	24.28	AV	Н	36.34	4.41	37.52	27.51	54.00	26.49
2245.00	39.29	PK	Н	27.79	1.75	36.28	32.55	74.00	41.45
2245.00	25.48	AV	Н	27.79	1.75	36.28	18.74	54.00	35.26

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

^{*} The testing was performed by George Pang on 2017-10-24.

Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
nnn	Low	2402	1.004	0.56
BDR (GFSK)	Middle	2441	1.004	0.56
(OFSK)	High	2480	0.996	0.56
EDD	Low	2402	1.004	0.87
EDR (π/4-DQPSK)	Middle	2441	1.004	0.87
(M4-DQF3K)	High	2480	1.004	0.87
EDD	Low	2402	1.004	0.85
EDR (8DPSK)	Middle	2441	1.004	0.85
(ODI SK)	High	2480	1.000	0.85

Note: Limit= $(2/3) \times 20dB$ *bandwidth*

BDR Mode (GFSK):


Low Channel



Date: 24.OCT.2017 16:11:33


Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 16:12:50

High Channel




Date: 24.OCT.2017 16:13:51

Report No.: RDG171020005 -00B


EDR Mode (\pi/4-DQPSK):





Date: 24.OCT.2017 16:15:26


Middle Channel



Date: 24.OCT.2017 16:16:38

High Channel


Report No.: RDG171020005 -00B



Date: 24.OCT.2017 16:17:47

EDR Mode (8-DPSK):


Low Channel



Date: 24.OCT.2017 16:19:25


Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 16:20:30

High Channel



Date: 24.OCT.2017 16:21:54

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

^{*} The testing was performed by George Pang on 2017-10-24.

Test Result: Compliance.

Please refer to following tables and plots


Report No.: RDG171020005 -00B

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
DDD 14. 1	Low	2402	0.84
BDR Mode (GFSK)	Middle	2441	0.84
	High	2480	0.84
EDR Mode (π/4-DQPSK)	Low	2402	1.31
	Middle	2441	1.31
	High	2480	1.31
EDR Mode (8-DPSK)	Low	2402	1.28
	Middle	2441	1.28
	High	2480	1.28

BDR Mode (GFSK):


Low Channel



Date: 24.OCT.2017 15:09:52


Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 15:11:19

High Channel




Date: 24.OCT.2017 15:12:39

Report No.: RDG171020005 -00B


EDR Mode ($\pi/4$ -DQPSK):





Date: 24.OCT.2017 15:14:58


Middle Channel



Date: 24.OCT.2017 15:17:43

High Channel


Report No.: RDG171020005 -00B



Date: 24.OCT.2017 15:18:51

EDR Mode (8-DPSK):


Low Channel



Date: 24.OCT.2017 15:20:37


Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 15:22:02

High Channel



Date: 24.OCT.2017 15:23:12

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

^{*} The testing was performed by George Pang on 2017-10-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




Date: 24.OCT.2017 15:31:54

EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels




Date: 24.OCT.2017 15:41:49

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Number of Hopping Channels



Date: 24.OCT.2017 15:57:08

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

^{*} The testing was performed by George Pang on 2017-10-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.450	0.144	0.4	Compliance	
DH1	Middle	0.448	0.143	0.4	Compliance	
DIII	High	0.450	0.144	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
DH3	Low	1.716	0.275	0.4	Compliance	
	Middle	1.722	0.276	0.4	Compliance	
DIIS	High	1.716	0.275	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s					
	Low	2.970	0.317	0.4	Compliance	
DH5	Middle	2.970	0.317	0.4	Compliance	
DIIS	High	2.980	0.318	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s					

DH1: Low Channel




Date: 24.OCT.2017 16:23:01

DH1: Middle Channel



Date: 24.OCT.2017 16:23:07


DH1: High Channel



Date: 24.OCT.2017 16:23:14


DH3: Low Channel

Report No.: RDG171020005 -00B




Date: 24.OCT.2017 16:25:25

DH3: Middle Channel




Date: 24.OCT.2017 16:25:31

DH3: High Channel




Date: 24.OCT.2017 16:25:37

DH5: Low Channel




Date: 24.OCT.2017 16:26:11

DH5: Middle Channel



Date: 24.OCT.2017 16:26:18

DH5: High Channel




Date: 24.OCT.2017 16:26:24

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.446	0.143	0.4	Compliance	
2DH1	Middle	0.446	0.143	0.4	Compliance	
2DH1	High	0.446	0.143	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
2DH3	Low	1.71	0.274	0.4	Compliance	
	Middle	1.716	0.275	0.4	Compliance	
2D113	High	1.716	0.275	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s					
	Low	2.97	0.317	0.4	Compliance	
2DH5	Middle	2.97	0.317	0.4	Compliance	
	High	2.97	0.317	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s					

2DH1: Low Channel




Date: 24.OCT.2017 16:34:42

2DH1: Middle Channel




Date: 24.OCT.2017 16:34:48

2DH1: High Channel




Date: 24.OCT.2017 16:34:55

2DH3: Low Channel




Date: 25.OCT.2017 20:37:38

2DH3: Middle Channel




Date: 24.OCT.2017 16:36:50

2DH3: High Channel




Date: 24.OCT.2017 16:36:59

2DH5: Low Channel




Date: 24.OCT.2017 16:44:48

2DH5: Middle Channel



Date: 24.OCT.2017 16:44:54

2DH5: High Channel




Date: 24.OCT.2017 16:47:42

EDR Mode (8-DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.446	0.143	0.4	Compliance	
3DH1	Middle	0.446	0.143	0.4	Compliance	
зипі	High	0.446	0.143	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s					
	Low	1.71	0.274	0.4	Compliance	
3DH3	Middle	1.716	0.275	0.4	Compliance	
SDIIS	High	1.71	0.274	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s					
	Low	2.97	0.317	0.4	Compliance	
3DH5	Middle	2.97	0.317	0.4	Compliance	
SDIIS	High	2.98	0.318	0.4	Compliance	
	Note: Dwell ti	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

3DH1: Low Channel




Date: 24.OCT.2017 16:50:28

3DH1: Middle Channel




Date: 24.OCT.2017 16:50:37

3DH1: High Channel




Date: 24.OCT.2017 16:50:44

3DH3: Low Channel



Date: 24.OCT.2017 16:52:42


3DH3: Middle Channel



Date: 24.OCT.2017 16:53:17


3DH3: High Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 16:53:42


3DH5: Low Channel



Date: 24.OCT.2017 16:54:55


3DH5: Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 16:55:28

3DH5: High Channel



Date: 24.OCT.2017 16:56:01

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

^{*} The testing was performed by George Pang on 2017-10-24.

Test Result: Compliance.


Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
22274	2402	7.36	30
BDR Mode (GFSK)	2441	5.38	30
(GrSK)	2480	5.75	30
	2402	8.74	30
EDR Mode (π/4-DQPSK)	2441	6.82	30
(W4-DQFSK)	2480	7.43	30
	2402	9.01	30
EDR Mode (8-DPSK)	2441	7.06	30
(0-DPSK)	2480	7.79	30

Note: The data above was tested in conducted mode.

BDR Mode (GFSK):


Low Channel



Date: 24.OCT.2017 15:10:15


Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 15:11:40

High Channel




Date: 24.OCT.2017 15:13:01

Report No.: RDG171020005 -00B


EDR Mode ($\pi/4$ -DQPSK):





Date: 24.OCT.2017 15:15:19


Middle Channel



Date: 24.OCT.2017 15:18:04

High Channel


Report No.: RDG171020005 -00B



Date: 24.OCT.2017 15:19:12

EDR Mode (8-DPSK):


Low Channel



Date: 24.OCT.2017 15:20:57


Middle Channel

Report No.: RDG171020005 -00B



Date: 24.OCT.2017 15:22:33

High Channel



Date: 24.OCT.2017 15:23:41

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	101121	2017/3/2	2018/3/2
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each Time	/

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa


^{*} The testing was performed by George Pang on 2017-10-24.

Test Result: Compliance

Report No.: RDG171020005 -00B


BDR Mode (GFSK):

Band Edge, Left Side



Date: 24.OCT.2017 15:10:29


Band Edge, Right Side



Date: 24.OCT.2017 15:13:29


EDR Mode (\pi/4-DQPSK):

Band Edge, Left Side



Date: 24.OCT.2017 15:15:33

Band Edge, Right Side




Date: 24.OCT.2017 15:19:27

EDR Mode (8-DPSK):

Date: 24.OCT.2017 15:21:12

Center 2.4 GHz



Date: 24.OCT.2017 15:24:03

***** END OF REPORT *****

Report No.: RDG171020005 -00B

Span 8 MHz