

FCC Radio Test Report

FCC ID: 2AEP6XM-JPV1-1

Original Grant

Report No. : TB-FCC144820
Applicant : HangZhou XiongMai Technology CO., LTD
Equipment Under Test (EUT)
EUT Name : Raindrop Camera
Model No. : XM-JPV1-1
Series No. : XM-JPV1-1F, XM-JPV1-1R
Brand Name : XM
Receipt Date : 2015-07-16
Test Date : 2015-07-16 to 2015-07-23
Issue Date : 2015-07-24
Standards : FCC Part 15, Subpart C (15.247:2014)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC and IC requirements


Test/Witness Engineer :

IVAN SU

**Approved &
Authorized**

:

Long Ha



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	6
1.7 Measurement Uncertainty	7
1.7 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	20
5.5 Test Data.....	20
6. RESTRICTED BANDS REQUIREMENT	47
6.1 Test Standard and Limit.....	47
6.2 Test Setup.....	47
6.3 Test Procedure.....	47
6.4 EUT Operating Condition	48
6.5 Test Data.....	48
7. BANDWIDTH TEST.....	69
7.1 Test Standard and Limit.....	69
7.2 Test Setup.....	69
7.3 Test Procedure.....	69
7.4 EUT Operating Condition	69
7.5 Test Data.....	70
8. PEAK OUTPUT POWER TEST.....	78
8.1 Test Standard and Limit.....	78
8.2 Test Setup.....	78

8.3 Test Procedure.....	78
8.4 EUT Operating Condition	78
8.5 Test Data.....	79
9. POWER SPECTRAL DENSITY TEST	80
9.1 Test Standard and Limit.....	80
9.2 Test Setup.....	80
9.3 Test Procedure.....	80
9.4 EUT Operating Condition	80
9.5 Test Data.....	81
10. ANTENNA REQUIREMENT.....	89
10.1 Standard Requirement.....	89
10.2 Antenna Connected Construction.....	89

1. General Information about EUT

1.1 Client Information

Applicant : HangZhou XiongMai Technology CO., LTD
Address : 9th Floor, Building 9, Yinhu Innovation Center, No.9 FuXian Road, YinHu Street, Hangzhou, China
Manufacturer : HangZhou XiongMai Technology CO., LTD
Address : 9th Floor, Building 9, Yinhu Innovation Center, No.9 FuXian Road, YinHu Street, Hangzhou, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Raindrop Camera	
Models No.	:	XM-JPV1-1, XM-JPV1-1F, XM-JPV1-1R	
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name for commercial.	
Product Description	:	Operation Frequency: 802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz	
	:	Number of Channel:	802.11b/g/n(HT20):11 channels see note(3) 802.11n(HT40): 7 channels see note(3)
	:	RF Output Power:	802.11b: 8.65 dBm 802.11g: 8.39 dBm 802.11n (HT20): 8.64 dBm 802.11n (HT40): 8.24 dBm
	:	Antenna Gain:	2 dBi PCB Antenna
	:	Modulation Type:	802.11b: CCK, DQPSK, DBPSK 802.11g: 64-QAM,QPSK,BPSK 802.11n: 64-QAM,16-QAM,QPSK,BPSK
	:	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
	:		
Power Supply	:	DC Voltage supplied from AC/DC adapter	
Power Rating	:	AC/DC Adapter: Input: AC 100~240V, 50/60 Hz, 150mA Output: DC 5V 1000mA	
Connecting I/O Port(S)	:	Please refer to the User's Manual	


Note:

- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v03r02.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		
Note:CH 01~CH 11 for 802.11b/g/n(HT20) CH 03~CH 09 for 802.11n(HT40)					

- (4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode

1.4 Description of Support Units

Equipment Information				
Name	Model	S/N	Manufacturer	Used “√”
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	AC Charging with TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 3	TX Mode B Mode Channel 01/06/11
Mode 4	TX Mode G Mode Channel 01/06/11
Mode 5	TX Mode N(HT20) Mode Channel 01/06/11
Mode 6	TX Mode N(HT40) Mode Channel 03/06/09

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

- 802.11b Mode: CCK (1 Mbps)
- 802.11g Mode: OFDM (6 Mbps)
- 802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
- 802.11n (HT40) Mode: MCS 0 (13 Mbps)

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	N/A		
Channel	CH 01	CH 06	CH 11
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF
	CH 03	CH 06	CH 09
IEEE 802.11n (HT40)	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz	± 3.42 dB
	150kHz to 30MHz	± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.7 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

May 22, 2014 certificated by TUV Rheinland(China) Co., Ltd. with TUV certificate No.: UA 50282953 0001 and report No.: 17026822 002. The certificate is valid until the next scheduled audit or up to 18 months, at the discretion of TUV Rhineland.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: “/” for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

AC Main Conducted Emission					
Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE& SCHWARZ	ESCI	100321	Aug. 08, 2014	Aug. 07, 2015
50ΩCoaxial Switch	Anritsu	MP59B	X10321	Aug. 08, 2014	Aug. 07, 2015
L.I.S.N	Rohde & Schwarz	ENV216	101131	Aug. 08, 2014	Aug. 07, 2015
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	Aug. 08, 2014	Aug. 07, 2015
Radiation Spurious Emission					
Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Sep. 01, 2014	Aug. 31, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	100010/007	Aug. 08, 2014	Aug.07, 2015
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Aug. 08, 2014	Aug.07, 2015
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 06, 2015	Mar.05, 2016
Pre-amplifier	Sonoma	310N	185903	Mar. 06, 2015	Mar.05, 2016
Pre-amplifier	HP	8447B	3008A00849	Mar. 06, 2015	Mar.05, 2016
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 06, 2015	Mar.05, 2016
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Sep. 01, 2014	Aug. 31, 2015
EMI Test Receiver	Rohde & Schwarz	ESCI	100010/007	Aug. 08, 2014	Aug. 07, 2015

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC Part 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please see the next page.

EUT:	Raindrop Camera	Model Name :	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	AC Charging with TX B Mode		
Remark:	Only worse case is reported		




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	0.1660	29.45	9.95	39.40	65.15	-25.75	QP
2	0.1660	14.24	9.95	24.19	55.15	-30.96	AVG
3	0.4780	24.15	10.02	34.17	56.37	-22.20	QP
4	0.4780	15.51	10.02	25.53	46.37	-20.84	AVG
5	0.5860	30.39	10.06	40.45	56.00	-15.55	QP
6 *	0.5860	20.75	10.06	30.81	46.00	-15.19	AVG
7	1.1860	25.52	10.06	35.58	56.00	-20.42	QP
8	1.1860	12.61	10.06	22.67	46.00	-23.33	AVG
9	1.9220	23.03	10.06	33.09	56.00	-22.91	QP
10	1.9220	9.96	10.06	20.02	46.00	-25.98	AVG
11	27.6660	27.88	10.21	38.09	60.00	-21.91	QP
12	27.6660	6.02	10.21	16.23	50.00	-33.77	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Raindrop Camera	Model Name :	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	AC Charging with TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.5899	32.79	10.02	42.81	56.00	-13.19	QP
2	*	0.5899	26.51	10.02	36.53	46.00	-9.47	AVG
3		0.8820	24.99	10.10	35.09	56.00	-20.91	QP
4		0.8820	17.41	10.10	27.51	46.00	-18.49	AVG
5		1.1620	25.10	10.14	35.24	56.00	-20.76	QP
6		1.1620	17.72	10.14	27.86	46.00	-18.14	AVG
7		1.3980	23.77	10.12	33.89	56.00	-22.11	QP
8		1.3980	15.19	10.12	25.31	46.00	-20.69	AVG
9		1.9700	23.92	10.06	33.98	56.00	-22.02	QP
10		1.9700	16.23	10.06	26.29	46.00	-19.71	AVG
11		4.0340	21.92	10.06	31.98	56.00	-24.02	QP
12		4.0340	15.53	10.06	25.59	46.00	-20.41	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Raindrop Camera	Model Name :	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Line		
Test Mode:	AC Charging with TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2940	26.80	10.02	36.82	60.41	-23.59	QP
2		0.2940	16.37	10.02	26.39	50.41	-24.02	AVG
3	*	0.6020	30.71	10.07	40.78	56.00	-15.22	QP
4		0.6020	20.44	10.07	30.51	46.00	-15.49	AVG
5		0.7580	28.26	10.11	38.37	56.00	-17.63	QP
6		0.7580	17.81	10.11	27.92	46.00	-18.08	AVG
7		1.3619	27.62	10.06	37.68	56.00	-18.32	QP
8		1.3619	16.81	10.06	26.87	46.00	-19.13	AVG
9		1.8820	27.85	10.06	37.91	56.00	-18.09	QP
10		1.8820	16.57	10.06	26.63	46.00	-19.37	AVG
11		2.4180	26.93	10.05	36.98	56.00	-19.02	QP
12		2.4180	16.23	10.05	26.28	46.00	-19.72	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Raindrop Camera	Model Name :	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Neutral		
Test Mode:	AC Charging with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.5940	33.53	10.02	43.55	56.00	-12.45	QP
2	*	0.5940	28.10	10.02	38.12	46.00	-7.88	AVG
3		0.7260	29.86	10.03	39.89	56.00	-16.11	QP
4		0.7260	24.05	10.03	34.08	46.00	-11.92	AVG
5		1.3300	29.84	10.13	39.97	56.00	-16.03	QP
6		1.3300	24.22	10.13	34.35	46.00	-11.65	AVG
7		1.8420	29.02	10.08	39.10	56.00	-16.90	QP
8		1.8420	23.01	10.08	33.09	46.00	-12.91	AVG
9		2.9020	28.66	10.06	38.72	56.00	-17.28	QP
10		2.9020	22.34	10.06	32.40	46.00	-13.60	AVG
11		4.8700	21.71	10.06	31.77	56.00	-24.23	QP
12		4.8700	15.09	10.06	25.15	46.00	-20.85	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard
FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class A (dBuV/m)(at 3 M)		Class B (dBuV/m)(at 3 M)	
	Peak	Average	Peak	Average
Above 1000	80	60	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)


5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.

EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	175.0368	56.86	-20.88	35.98	43.50	-7.52	peak
2		225.3080	53.44	-19.30	34.14	46.00	-11.86	peak
3		275.1570	51.52	-17.57	33.95	46.00	-12.05	peak
4		325.5958	53.12	-16.11	37.01	46.00	-8.99	peak
5		375.9385	47.10	-14.40	32.70	46.00	-13.30	peak
6		601.4265	44.49	-9.41	35.08	46.00	-10.92	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	!	41.2765	55.09	-20.70	34.39	40.00	-5.61	peak
2		73.8756	47.96	-23.49	24.47	40.00	-15.53	peak
3		91.1746	53.46	-22.59	30.87	43.50	-12.63	peak
4		325.5958	47.77	-16.11	31.66	46.00	-14.34	peak
5	*	601.4265	51.61	-9.41	42.20	46.00	-3.80	peak
6		833.3171	44.48	-6.42	38.06	46.00	-7.94	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.966	45.09	13.56	58.65	74.00	-15.35	peak
2	*	4823.983	33.87	13.56	47.43	54.00	-6.57	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.993	44.39	13.56	57.95	74.00	-16.05	peak
2	*	4824.104	32.69	13.56	46.25	54.00	-7.75	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.968	34.26	13.86	48.12	54.00	-5.88	AVG
2		4874.367	45.21	13.86	59.07	74.00	-14.93	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.687	44.01	13.86	57.87	74.00	-16.13	peak
2	*	4873.992	32.52	13.86	46.38	54.00	-7.62	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.875	33.50	14.15	47.65	54.00	-6.35	AVG
2		4924.035	44.83	14.15	58.98	74.00	-15.02	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.897	32.17	14.15	46.32	54.00	-7.68	AVG
2		4923.988	43.74	14.15	57.89	74.00	-16.11	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.745	42.91	13.56	56.47	74.00	-17.53	peak
2	*	4823.826	30.29	13.56	43.85	54.00	-10.15	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4823.659	30.65	13.56	44.21	54.00	-9.79	AVG
2		4823.785	42.76	13.56	56.32	74.00	-17.68	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4873.686	42.12	13.86	55.98	74.00	-18.02	peak
2	*	4874.023	30.16	13.86	44.02	54.00	-9.98	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.865	30.03	13.86	43.89	54.00	-10.11	AVG
2		4873.943	42.60	13.86	56.46	74.00	-17.54	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.467	29.73	14.15	43.88	54.00	-10.12	AVG
2		4923.574	41.34	14.15	55.49	74.00	-18.51	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		4923.877	41.69	14.15	55.84	74.00	-18.16 peak
2	*	4924.003	29.97	14.15	44.12	54.00	-9.88 AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		4823.511	42.28	13.56	55.84	74.00	-18.16 peak
2	*	4823.641	30.12	13.56	43.68	54.00	-10.32 AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.582	30.12	13.56	43.68	54.00	-10.32	AVG
2		4823.644	42.28	13.56	55.84	74.00	-18.16	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.689	30.49	13.86	44.35	54.00	-9.65	AVG
2		4874.201	41.61	13.86	55.47	74.00	-18.53	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4873.862	29.39	13.86	43.25	54.00	-10.75	AVG
2		4874.327	41.58	13.86	55.44	74.00	-18.56	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.657	29.50	14.15	43.65	54.00	-10.35	AVG
2		4923.855	41.06	14.15	55.21	74.00	-18.79	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.814	29.52	14.15	43.67	54.00	-10.33	AVG
2		4923.974	41.28	14.15	55.43	74.00	-18.57	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4843.674	30.34	13.68	44.02	54.00	-9.98	AVG
2		4843.964	41.68	13.68	55.36	74.00	-18.64	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		4823.684	41.77	13.56	55.33	74.00	-18.67 peak
2	*	4843.674	29.86	13.68	43.54	54.00	-10.46 AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.954	29.76	13.86	43.62	54.00	-10.38	AVG
2		4874.384	41.40	13.86	55.26	74.00	-18.74	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4874.064	29.98	13.86	43.84	54.00	-10.16	AVG
2		4874.136	41.95	13.86	55.81	74.00	-18.19	peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4903.898	29.29	14.03	43.32	54.00	-10.68	AVG
2		4903.981	41.61	14.03	55.64	74.00	-18.36	peak

Emission Level= Read Level+ Correct Factor

EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4903.658	29.79	14.03	43.82	74.00	-30.18	peak
2	*	4903.865	41.63	14.03	55.66	74.00	-18.34	peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit


6.1.1 Test Standard

FCC Part 15.209 FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3 M)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please see the next page.

(1) Radiation Test


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	32.05	0.77	32.82	74.00	-41.18	peak
2		2390.000	21.70	0.77	22.47	54.00	-31.53	AVG
3	*	2411.300	84.36	0.86	85.22	Fundamental Frequency		AVG
4	X	2413.500	88.82	0.86	89.68	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		2390.000	30.36	0.77	31.13	74.00	-42.87 peak
2		2390.000	19.36	0.77	20.13	54.00	-33.87 AVG
3	X	2410.700	84.19	0.86	85.05	Fundamental Frequency	peak
4	*	2411.300	79.51	0.86	80.37	Fundamental Frequency	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2461.200	82.62	1.07	83.69	Fundamental Frequency		AVG
2	X	2463.400	87.38	1.08	88.46	Fundamental Frequency		peak
3		2483.500	31.39	1.17	32.56	74.00	-41.44	peak
4		2483.500	20.47	1.17	21.64	54.00	-32.36	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1	*	2462.700	78.85	1.08	79.93	Fundamental Frequency	AVG
2	X	2463.400	83.59	1.08	84.67	Fundamental Frequency	peak
3		2483.500	30.17	1.17	31.34	74.00	-42.66 peak
4		2483.500	18.73	1.17	19.90	54.00	-34.10 AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	39.73	0.77	40.50	74.00	-33.50	peak
2		2390.000	26.99	0.77	27.76	54.00	-26.24	AVG
3	X	2408.800	88.51	0.85	89.36	Fundamental Frequency		peak
4	*	2410.800	77.83	0.86	78.69	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	37.29	0.77	38.06	74.00	-35.94	peak
2		2390.000	25.32	0.77	26.09	54.00	-27.91	AVG
3	X	2410.700	86.37	0.86	87.23	Fundamental Frequency		peak
4	*	2414.400	75.82	0.88	76.70	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2458.000	89.01	1.06	90.07	Fundamental Frequency		peak
2	*	2460.700	78.65	1.06	79.71	Fundamental Frequency		AVG
3		2483.500	41.05	1.17	42.22	74.00	-31.78	peak
4		2483.500	28.10	1.17	29.27	54.00	-24.73	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2463.700	86.40	1.08	87.48	Fundamental Frequency		peak
2	*	2464.800	75.67	1.09	76.76	Fundamental Frequency		AVG
3		2483.500	37.09	1.17	38.26	74.00	-35.74	peak
4		2483.500	25.20	1.17	26.37	54.00	-27.63	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	39.50	0.77	40.27	74.00	-33.73	peak
2		2390.000	26.08	0.77	26.85	54.00	-27.15	AVG
3	X	2408.900	86.55	0.85	87.40	Fundamental Frequency		peak
4	*	2415.100	75.75	0.88	76.63	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	37.96	0.77	38.73	74.00	-35.27	peak
2		2390.000	24.27	0.77	25.04	54.00	-28.96	AVG
3	*	2408.800	74.74	0.85	75.59	Fundamental Frequency		AVG
4	X	2415.400	85.67	0.88	86.55	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2459.800	85.55	1.06	86.61	Fundamental Frequency		peak
2	*	2465.200	74.83	1.09	75.92	Fundamental Frequency		AVG
3		2483.500	36.26	1.17	37.43	74.00	-36.57	peak
4		2483.500	24.14	1.17	25.31	54.00	-28.69	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2460.200	83.48	1.06	84.54	Fundamental Frequency		peak
2	*	2465.100	72.86	1.09	73.95	Fundamental Frequency		AVG
3		2483.500	33.79	1.17	34.96	74.00	-39.04	peak
4		2483.500	22.29	1.17	23.46	54.00	-30.54	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	43.64	0.77	44.41	74.00	-29.59	peak
2		2390.000	31.82	0.77	32.59	54.00	-21.41	AVG
3	X	2419.600	86.65	0.89	87.54	Fundamental Frequency		peak
4	*	2427.800	75.66	0.94	76.60	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	42.52	0.77	43.29	74.00	-30.71	peak
2		2390.000	30.62	0.77	31.39	54.00	-22.61	AVG
3	X	2425.200	85.15	0.93	86.08	Fundamental Frequency		peak
4	*	2427.800	74.48	0.94	75.42	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2449.600	86.62	1.02	87.64	Fundamental Frequency		peak
2	*	2450.100	75.69	1.02	76.71	Fundamental Frequency		AVG
3		2483.500	44.22	1.17	45.39	74.00	-28.61	peak
4		2483.500	32.92	1.17	34.09	54.00	-19.91	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2454.200	74.93	1.04	75.97	Fundamental Frequency		AVG
2	X	2454.900	85.65	1.05	86.70	Fundamental Frequency		peak
3		2483.500	45.06	1.17	46.23	74.00	-27.77	peak
4		2483.500	31.96	1.17	33.13	54.00	-20.87	AVG


Emission Level= Read Level+ Correct Factor

(2) Conducted Test


EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		




Date: 20.JUL.2015 16:28:37




Date: 20.JUL.2015 16:30:08



EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		




Date: 20.JUL.2015 16:53:34




Date: 20.JUL.2015 16:54:59

EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode:	TX N(HT40) Mode 2422MHz / TX N(HT40) Mode 2452MHz		
Remark:	The EUT is programed in continuously transmitting mode		



Date: 20.JUL.2015 16:15:49



Date: 20.JUL.2015 16:09:32


7. Bandwidth Test

7.1 Test Standard and Limit

- 7.1.1 Test Standard
FCC Part 15.247 (a)(2)
- 7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup




7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (3)Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition


The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

7.5 Test Data



802.11B Mode


2437 MHz




Date: 20.JUL.2015 16:23:11

802.11B Mode

2462 MHz




Date: 20.JUL.2015 16:24:08



802.11G Mode


2437 MHz



Date: 20.JUL.2015 16:57:25

802.11G Mode

2462 MHz




Date: 20.JUL.2015 16:58:20

TB-RF-074-1.0

802.11N(HT20) Mode


2437 MHz




Date: 20.JUL.2015 16:48:58

802.11N(HT20) Mode

2462 MHz




Date: 20.JUL.2015 16:50:41



802.11N(HT40) Mode


2437 MHz



Date: 20.JUL.2015 16:13:30

802.11N(HT40) Mode

2452 MHz



Date: 20.JUL.2015 16:12:18

8. Peak Output Power Test

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v03r02.

The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data

EUT:	Raindrop Camera	Model Name :	XM-JPV1-1
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	8.53	30
	2437	8.39	
	2462	8.65	
802.11g	2412	8.39	
	2437	7.82	
	2462	8.24	
802.11n (HT20)	2412	8.64	
	2437	8.11	
	2462	8.07	
802.11n (HT40)	2422	8.24	
	2437	7.83	
	2452	7.67	
Result: PASS			

9. Power Spectral Density Test

9.1 Test Standard and Limit

9.1.1 Test Standard

FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure


The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v03r02.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition


The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

9.5 Test Data



802.11B Mode


2437 MHz




Date: 20.JUL.2015 16:26:00


802.11B Mode

2462 MHz




Date: 20.JUL.2015 16:25:29







Date: 20.JUL.2015 16:39:50




Date: 20.JUL.2015 16:40:47





Date: 20.JUL.2015 16:51:52



Date: 20.JUL.2015 16:51:18

EUT:	Raindrop Camera	Model:	XM-JPV1-1
Temperature:	25 °C	Temperature:	25 °C
Test Voltage:	AC 120V/60Hz		
Test Mode:	TX 802.11N(HT40) Mode		

Channel Frequency (MHz)	Power Density (3 kHz/dBm)	Limit (dBm)
2422	-29.39	8
2437	-29.15	
2452	-30.04	


802.11N(HT40) Mode

2422 MHz

Date: 20.JUL.2015 16:17:46

802.11N(HT40) Mode


2437 MHz



Date: 20.JUL.2015 16:18:36

802.11N(HT40) Mode

2452 MHz



Date: 20.JUL.2015 16:19:44

10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 2 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna