

# TEST REPORT

**Reference No.**..... : WTS18S05111958-3W V1  
**FCC ID** ..... : 2AEPIELEMENTPLUS  
**Applicant**..... : COLOMBIANA DE COMERCIO S.A.  
**Address**..... : Car. 43E No 8-71, Medellin, Colombia  
**Manufacturer** ..... : SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD  
**Address**..... : A-SIDE A2 BUILDING 2/F ENET NEW INDUSTRIAL PARK,NO.20  
DAFU INDUSTRIAL ZONE, AOBEI COMMUNITY, GUANLAN,  
LONGHUA NEW DISTRICT, SHENZHEN CHINA  
**Product**..... : Smart Phone  
**Model(s)** ..... : ELEMENT PLUS  
**Brand Name**..... : Kalley  
**Standards**..... : FCC CFR47 Part 15.247:2017  
**Date of Receipt sample** .... : 2018-05-17  
**Date of Test** ..... : 2018-05-18 to 2018-05-29  
**Date of Issue**..... : 2018-07-02  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

**Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District,  
Shenzhen, Guangdong, China**

**Tel :+86-755-83551033**

**Fax:+86-755-83552400**

Compiled by:

*Ford Wang*

Ford Wang / Project Engineer

Approved by:



*Philo Zhong*

Philo Zhong / Manager

## 2 Laboratories Introduction

**Waltek Services (Shenzhen) Co., Ltd** is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. Electro Magnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

**Test Facility:**

**A. Accreditations for Conformity Assessment (International)**

Country/Region	Accreditation Body	Scope	Note
USA	<b>A2LA</b> <b>(Certificate No.: 4243.01)</b>	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India		<b>International Services</b>	WPC
Thailand	NTC		-
Singapore	IDA		-
Note:			
1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.			
2. IC Canada Registration No.: 7760A			

**B. TCBs and Notify Bodies Recognized Testing Laboratory.**

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

### 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 LABORATORIES INTRODUCTION.....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 REVISION HISTORY .....</b>	<b>6</b>
<b>5 GENERAL INFORMATION.....</b>	<b>7</b>
5.1 GENERAL DESCRIPTION OF E.U.T. ....	7
5.2 DETAILS OF E.U.T. ....	7
5.3 CHANNEL LIST .....	9
5.4 TEST MODE .....	10
<b>6 TEST SUMMARY .....</b>	<b>11</b>
<b>7 EQUIPMENT USED DURING TEST .....</b>	<b>12</b>
7.1 EQUIPMENTS LIST .....	12
7.2 DESCRIPTION OF SUPPORT UNITS .....	13
7.3 MEASUREMENT UNCERTAINTY .....	13
7.4 TEST EQUIPMENT CALIBRATION .....	13
<b>8 CONDUCTED EMISSION .....</b>	<b>14</b>
8.1 E.U.T. OPERATION .....	14
8.2 EUT SETUP.....	14
8.3 MEASUREMENT DESCRIPTION .....	14
8.4 CONDUCTED EMISSION TEST RESULT .....	15
<b>9 RADIATED EMISSIONS.....</b>	<b>19</b>
9.1 EUT OPERATION.....	19
9.2 TEST SETUP .....	20
9.3 SPECTRUM ANALYZER SETUP .....	21
9.4 TEST PROCEDURE .....	22
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION .....	22
9.6 SUMMARY OF TEST RESULTS .....	23
<b>10 CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>39</b>
10.1 TEST PROCEDURE.....	39
10.2 TEST RESULT .....	40
<b>11 BAND EDGE MEASUREMENT .....</b>	<b>56</b>
11.1 TEST PRODUCE .....	56
11.2 TEST RESULT .....	57
<b>12 6 DB BANDWIDTH MEASUREMENT .....</b>	<b>62</b>
12.1 TEST PROCEDURE:.....	62
12.2 TEST RESULT: .....	62
<b>13 MAXIMUM PEAK OUTPUT POWER .....</b>	<b>71</b>
13.1 TEST PROCEDURE:.....	71
13.2 TEST RESULT: .....	72
<b>14 DUTY CYCLE.....</b>	<b>81</b>
<b>15 POWER SPECTRAL DENSITY .....</b>	<b>82</b>
15.1 TEST PROCEDURE:.....	82
15.2 TEST RESULT: .....	82
<b>16 ANTENNA REQUIREMENT .....</b>	<b>91</b>
<b>17 RF EXPOSURE.....</b>	<b>92</b>

<b>18</b>	<b>PHOTOGRAPHS OF TEST SETUP AND EUT.....</b>	<b>93</b>
-----------	---	-----------

## 4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS18S05111 958-3W	2018-05-17	2018-05-18 to 2018-05-29	2018-05-30	original	-	Replaced
WTS18S05111 958-3W V1	2018-05-17	2018-05-18 to 2018-05-29	2018-07-02	Version 1	Updated	Valid

## 5 General Information

### 5.1 General Description of E.U.T.

Product:	Smart Phone
Model(s):	ELEMENT PLUS
Model Description:	N/A
GSM Band(s):	GSM 850/900/1800/1900MHz
GPRS Class:	12
WCDMA Band(s):	FDD Band II/V
LTE Band(s):	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Bluetooth Version:	Bluetooth v4.0 with BLE
GPS:	Support
NFC:	N/A
Hardware Version:	WD393B_MB_V1.0_20170810
Software Version:	Kalley_K-BOOK73G_v01
Highest frequency (Exclude Radio):	1.25GHz
Storage Location:	Internal Storage
Note:	N/A

### 5.2 Details of E.U.T.

Operation Frequency:	GSM/GPRS 850: 824~849MHz PCS/GPRS 1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz Bluetooth: 2402~2480MHz
Max. RF output power:	GSM 850: 32.17dBm PCS1900: 28.37dBm WCDMA Band II: 22.31dBm WCDMA Band V: 22.76dBm WiFi(2.4G): 9.48dBm Bluetooth: 1.76dBm
Type of Modulation:	GSM,GPRS: GMSK WCDMA: BPSK, 16QAM

	WiFi: CCK, OFDM Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK
Antenna installation:	GSM/WCDMA: internal permanent antenna WiFi/Bluetooth: internal permanent antenna
Antenna Gain:	GSM 850: -1.5dBi PCS1900: 0.2dBi WCDMA Band II: 0.2dBi WCDMA Band V: -1.5dBi WiFi(2.4G): 0.7dBi Bluetooth: 0.7dBi
Ratings:	Battery DC 3.8V, 3000mAh DC 5V, 1.0A, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.2A)
Adapter:	Manufacturer: Shenzhen ACT Industrial Model No.: ELEMENT PLUS



### 5.3 Channel List

#### WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

#### BT BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

## 5.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Table 2 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX

**Note** :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

## 6 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

## 7 Equipment Used during Test

### 7.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11
2.	LISN	R&S	ENV216	101215	2017-09-12	2018-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2017-09-12	2018-09-11
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2017-09-12	2018-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017-09-12	2018-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2017-09-12	2018-09-11
4.	Cable	LARGE	RF300	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2018-04-29	2019-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2018-04-09	2019-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2018-04-09	2019-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017-09-12	2018-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2018-04-09	2019-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2018-04-09	2019-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2018-04-13	2019-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2018-04-13	2019-04-12
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2018-04-13	2019-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2018-04-09	2019-04-08
3	Amplifier	Compliance direction systems inc	PAP-0203	22024	2018-04-13	2019-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2018-04-13	2019-04-12

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2017-09-12	2018-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2017-09-12	2018-09-11
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2017-09-12	2018-09-11

## 7.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

## 7.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 <sup>-7</sup> Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

## 7.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

## 8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207  
Test Method: ANSI C63.10:2013  
Test Result: PASS  
Frequency Range: 150kHz to 30MHz  
Class/Severity: Class B  
Limit:

Frequency (MHz)	Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

### 8.1 E.U.T. Operation

Operating Environment :


Temperature: 21.5 °C  
Humidity: 51.9 % RH  
Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the worst data were shown in the report.

### 8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



### 8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

## 8.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: WIFI mode ( 802.11b mode low channel )

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1819	41.72	9.88	51.60	64.39	-12.79	QP	
2	0.1819	26.15	9.88	36.03	54.39	-18.36	AVG	
3	0.2340	32.24	9.98	42.22	62.30	-20.08	QP	
4	0.2340	16.63	9.98	26.61	52.30	-25.69	AVG	
5	0.5140	31.72	10.08	41.80	56.00	-14.20	QP	
6	0.5140	20.42	10.08	30.50	46.00	-15.50	AVG	
7	1.0420	20.58	10.17	30.75	56.00	-25.25	QP	
8	1.0420	10.78	10.17	20.95	46.00	-25.05	AVG	
9	4.9459	18.79	10.25	29.04	56.00	-26.96	QP	
10	4.9459	7.12	10.25	17.37	46.00	-28.63	AVG	
11	15.8899	15.16	10.40	25.56	60.00	-34.44	QP	
12	15.8899	-6.73	10.40	3.67	50.00	-46.33	AVG	

Neutral line:




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1580	29.02	9.98	39.00	65.56	-26.56	QP	
2	0.1580	11.63	9.98	21.61	55.56	-33.95	AVG	
3	0.2100	20.71	9.93	30.64	63.20	-32.56	QP	
4	0.2100	12.61	9.93	22.54	53.20	-30.66	AVG	
5	0.3740	28.02	10.05	38.07	58.41	-20.34	QP	
6	0.3740	15.42	10.05	25.47	48.41	-22.94	AVG	
7	0.5140	36.37	10.08	46.45	56.00	-9.55	QP	
8	0.5140	24.80	10.08	34.88	46.00	-11.12	AVG	
9	1.0260	29.93	10.14	40.07	56.00	-15.93	QP	
10	1.0260	16.36	10.14	26.50	46.00	-19.50	AVG	
11	14.8660	19.60	10.38	29.98	60.00	-30.02	QP	
12	14.8660	5.53	10.38	15.91	50.00	-34.09	AVG	




Worst Mode: BLE mode (low channel )

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1780	38.09	9.87	47.96	64.57	-16.61	QP	
2	0.1780	23.05	9.87	32.92	54.57	-21.65	AVG	
3	0.3420	25.66	10.05	35.71	59.15	-23.44	QP	
4	0.3420	14.30	10.05	24.35	49.15	-24.80	AVG	
5	0.5100	31.97	10.08	42.05	56.00	-13.95	QP	
6	0.5100	18.18	10.08	28.26	46.00	-17.74	AVG	
7	1.0859	22.20	10.23	32.43	56.00	-23.57	QP	
8	1.0859	8.44	10.23	18.67	46.00	-27.33	AVG	
9	15.3380	17.37	10.39	27.76	60.00	-32.24	QP	
10	15.3380	1.67	10.39	12.06	50.00	-37.94	AVG	
11	29.1700	2.97	10.64	13.61	60.00	-46.39	QP	
12	29.1700	-2.17	10.64	8.47	50.00	-41.53	AVG	

Neutral line:



## 9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

### 9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.


## 9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



### 9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed ..... Auto  
IF Bandwidth.....10kHz  
Video Bandwidth.....10kHz  
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto  
Detector .....PK  
Resolution Bandwidth.....100kHz  
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed ..... Auto  
Detector .....PK  
Resolution Bandwidth.....1MHz  
Video Bandwidth.....3MHz  
Detector .....Ave.  
Resolution Bandwidth.....1MHz  
Video Bandwidth.....10Hz

## 9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

## 9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

## 9.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.032	25.01	QP	21.84	40.00	6.85	29.54	-22.69
8.051	24.56	QP	21.02	40.00	5.58	29.54	-23.96
26.215	24.35	QP	20.55	40.00	4.90	29.54	-24.64
802.11g							
6.032	24.53	QP	21.84	40.00	6.37	29.54	-23.17
8.051	24.71	QP	21.02	40.00	5.73	29.54	-23.81
26.215	25.06	QP	20.55	40.00	5.61	29.54	-23.93
802.11n(HT20)							
6.032	25.17	QP	21.84	40.00	7.01	29.54	-22.53
8.051	25.03	QP	21.02	40.00	6.05	29.54	-23.49
26.215	24.42	QP	20.55	40.00	4.97	29.54	-24.57
802.11n(HT40)							
6.032	25.11	QP	21.84	40.00	6.95	29.54	-22.59
8.051	25.23	QP	21.02	40.00	6.25	29.54	-23.29
26.215	24.57	QP	20.55	40.00	5.12	29.54	-24.42

**Test Frequency : 30MHz ~ 18GHz**

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
223.45	42.97	QP	41	1.7	H	-11.62	31.35	46.00	-14.65
223.45	36.29	QP	81	1.2	V	-11.62	24.67	46.00	-21.33
4824.00	48.79	PK	51	1.0	V	-1.06	47.73	74.00	-26.27
4824.00	46.74	Ave	51	1.0	V	-1.06	45.68	54.00	-8.32
7236.00	40.00	PK	208	1.3	H	1.33	41.33	74.00	-32.67
7236.00	43.36	Ave	208	1.3	H	1.33	44.69	54.00	-9.31
2315.51	45.17	PK	173	1.9	V	-13.19	31.98	74.00	-42.02
2315.51	38.16	Ave	173	1.9	V	-13.19	24.97	54.00	-29.03
2353.21	43.93	PK	86	1.7	H	-13.14	30.79	74.00	-43.21
2353.21	38.05	Ave	86	1.7	H	-13.14	24.91	54.00	-29.09
2486.82	42.94	PK	239	1.2	V	-13.08	29.86	74.00	-44.14
2486.82	37.63	Ave	239	1.2	V	-13.08	24.55	54.00	-29.45



Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
223.45	41.87	QP	9	1.7	H	-11.62	30.25	46.00	-15.75
223.45	37.23	QP	276	1.6	V	-11.62	25.61	46.00	-20.39
4874.00	49.99	PK	228	1.2	V	-0.62	49.37	74.00	-24.63
4874.00	48.11	Ave	228	1.2	V	-0.62	47.49	54.00	-6.51
7311.00	40.54	PK	322	1.5	H	2.21	42.75	74.00	-31.25
7311.00	42.49	Ave	322	1.5	H	2.21	44.70	54.00	-9.30
2311.36	46.12	PK	210	1.5	V	-13.19	32.93	74.00	-41.07
2311.36	37.32	Ave	210	1.5	V	-13.19	24.13	54.00	-29.87
2383.76	44.08	PK	23	1.8	H	-13.14	30.94	74.00	-43.06
2383.76	38.70	Ave	23	1.8	H	-13.14	25.56	54.00	-28.44
2486.00	44.17	PK	262	2.0	V	-13.08	31.09	74.00	-42.91
2486.00	37.83	Ave	262	2.0	V	-13.08	24.75	54.00	-29.25

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
223.45	41.34	QP	38	1.7	H	-11.62	29.72	46.00	-16.28
223.45	38.55	QP	50	1.9	V	-11.62	26.93	46.00	-19.07
4924.00	50.89	PK	29	1.2	V	-0.24	50.65	74.00	-23.35
4924.00	46.85	Ave	29	1.2	V	-0.24	46.61	54.00	-7.39
7386.00	39.08	PK	227	1.6	H	2.84	41.92	74.00	-32.08
7386.00	42.28	Ave	227	1.6	H	2.84	45.12	54.00	-8.88
2337.62	46.45	PK	7	1.6	V	-13.19	33.26	74.00	-40.74
2337.62	38.67	Ave	7	1.6	V	-13.19	25.48	54.00	-28.52
2359.41	44.45	PK	94	1.7	H	-13.14	31.31	74.00	-42.69
2359.41	36.53	Ave	94	1.7	H	-13.14	23.39	54.00	-30.61
2497.91	44.30	PK	349	1.1	V	-13.08	31.22	74.00	-42.78
2497.91	36.47	Ave	349	1.1	V	-13.08	23.39	54.00	-30.61

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
223.45	41.36	QP	310	1.4	H	-11.62	29.74	46.00	-16.26
223.45	38.30	QP	298	1.9	V	-11.62	26.68	46.00	-19.32
4824.00	50.56	PK	131	1.1	V	-1.06	49.50	74.00	-24.50
4824.00	47.66	Ave	131	1.1	V	-1.06	46.60	54.00	-7.40
7236.00	38.14	PK	287	1.9	H	1.33	39.47	74.00	-34.53
7236.00	41.04	Ave	287	1.9	H	1.33	42.37	54.00	-11.63
2328.03	46.19	PK	8	1.8	V	-13.19	33.00	74.00	-41.00
2328.03	37.34	Ave	8	1.8	V	-13.19	24.15	54.00	-29.85
2358.12	43.03	PK	181	1.4	H	-13.14	29.89	74.00	-44.11
2358.12	38.60	Ave	181	1.4	H	-13.14	25.46	54.00	-28.54
2486.15	44.85	PK	181	1.1	V	-13.08	31.77	74.00	-42.23
2486.15	36.25	Ave	181	1.1	V	-13.08	23.17	54.00	-30.83

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
223.45	41.62	QP	94	1.6	H	-11.62	30.00	46.00	-16.00
223.45	37.11	QP	260	1.8	V	-11.62	25.49	46.00	-20.51
4874.00	51.68	PK	14	1.6	V	-0.62	51.06	74.00	-22.94
4874.00	46.71	Ave	14	1.6	V	-0.62	46.09	54.00	-7.91
7311.00	38.26	PK	148	1.5	H	2.21	40.47	74.00	-33.53
7311.00	39.59	Ave	148	1.5	H	2.21	41.80	54.00	-12.20
2336.89	46.38	PK	315	1.7	V	-13.19	33.19	74.00	-40.81
2336.89	39.15	Ave	315	1.7	V	-13.19	25.96	54.00	-28.04
2353.77	43.98	PK	196	1.7	H	-13.14	30.84	74.00	-43.16
2353.77	37.33	Ave	196	1.7	H	-13.14	24.19	54.00	-29.81
2483.66	42.57	PK	358	1.1	V	-13.08	29.49	74.00	-44.51
2483.66	38.40	Ave	358	1.1	V	-13.08	25.32	54.00	-28.68

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
223.45	42.07	QP	58	1.1	H	-11.62	30.45	46.00	-15.55
223.45	36.98	QP	330	1.1	V	-11.62	25.36	46.00	-20.64
4924.00	51.71	PK	185	1.1	V	-0.24	51.47	74.00	-22.53
4924.00	47.30	Ave	185	1.1	V	-0.24	47.06	54.00	-6.94
7386.00	39.66	PK	19	1.3	H	2.84	42.50	74.00	-31.50
7386.00	40.40	Ave	19	1.3	H	2.84	43.24	54.00	-10.76
2346.27	46.75	PK	354	1.9	V	-13.19	33.56	74.00	-40.44
2346.27	38.10	Ave	354	1.9	V	-13.19	24.91	54.00	-29.09
2365.99	43.87	PK	303	1.3	H	-13.14	30.73	74.00	-43.27
2365.99	36.54	Ave	303	1.3	H	-13.14	23.40	54.00	-30.60
2493.51	42.30	PK	200	1.7	V	-13.08	29.22	74.00	-44.78
2493.51	36.05	Ave	200	1.7	V	-13.08	22.97	54.00	-31.03

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Low Channel 2412MHz									
223.45	41.73	QP	254	1.5	H	-11.62	30.11	46.00	-15.89
223.45	37.77	QP	275	1.9	V	-11.62	26.15	46.00	-19.85
4824.00	52.87	PK	360	1.7	V	-1.06	51.81	74.00	-22.19
4824.00	47.43	Ave	360	1.7	V	-1.06	46.37	54.00	-7.63
7236.00	41.16	PK	146	1.6	H	1.33	42.49	74.00	-31.51
7236.00	39.01	Ave	146	1.6	H	1.33	40.34	54.00	-13.66
2333.48	46.39	PK	207	1.7	V	-13.19	33.20	74.00	-40.80
2333.48	39.31	Ave	207	1.7	V	-13.19	26.12	54.00	-27.88
2384.50	44.87	PK	252	1.9	H	-13.14	31.73	74.00	-42.27
2384.50	37.00	Ave	252	1.9	H	-13.14	23.86	54.00	-30.14
2497.40	43.84	PK	312	1.5	V	-13.08	30.76	74.00	-43.24
2497.40	38.07	Ave	312	1.5	V	-13.08	24.99	54.00	-29.01

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Middle Channel 2437MHz									
223.45	41.97	QP	99	1.5	H	-11.62	30.35	46.00	-15.65
223.45	37.64	QP	221	1.5	V	-11.62	26.02	46.00	-19.98
4874.00	51.49	PK	205	1.4	V	-0.62	50.87	74.00	-23.13
4874.00	46.74	Ave	205	1.4	V	-0.62	46.12	54.00	-7.88
7311.00	40.09	PK	85	1.3	H	2.21	42.30	74.00	-31.70
7311.00	39.62	Ave	85	1.3	H	2.21	41.83	54.00	-12.17
2341.89	45.14	PK	8	1.8	V	-13.19	31.95	74.00	-42.05
2341.89	37.77	Ave	8	1.8	V	-13.19	24.58	54.00	-29.42
2369.29	42.42	PK	23	1.8	H	-13.14	29.28	74.00	-44.72
2369.29	38.67	Ave	23	1.8	H	-13.14	25.53	54.00	-28.47
2492.82	42.95	PK	102	1.7	V	-13.08	29.87	74.00	-44.13
2492.82	37.20	Ave	102	1.7	V	-13.08	24.12	54.00	-29.88

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: High Channel 2462MHz									
223.45	43.05	QP	55	1.7	H	-11.62	31.43	46.00	-14.57
223.45	36.92	QP	44	1.2	V	-11.62	25.30	46.00	-20.70
4924.00	51.94	PK	288	1.4	V	-0.24	51.70	74.00	-22.30
4924.00	48.15	Ave	288	1.4	V	-0.24	47.91	54.00	-6.09
7386.00	40.46	PK	250	1.8	H	2.84	43.30	74.00	-30.70
7386.00	40.13	Ave	250	1.8	H	2.84	42.97	54.00	-11.03
2320.80	46.75	PK	51	1.5	V	-13.19	33.56	74.00	-40.44
2320.80	39.20	Ave	51	1.5	V	-13.19	26.01	54.00	-27.99
2372.55	43.77	PK	191	1.2	H	-13.14	30.63	74.00	-43.37
2372.55	38.44	Ave	191	1.2	H	-13.14	25.30	54.00	-28.70
2485.15	44.33	PK	129	2.0	V	-13.08	31.25	74.00	-42.75
2485.15	37.34	Ave	129	2.0	V	-13.08	24.26	54.00	-29.74



Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Low Channel 2422MHz									
223.45	42.50	QP	73	1.3	H	-11.62	30.88	46.00	-15.12
223.45	35.60	QP	15	1.3	V	-11.62	23.98	46.00	-22.02
4844.00	50.02	PK	163	1.7	V	-1.06	48.96	74.00	-25.04
4844.00	46.05	Ave	163	1.7	V	-1.06	44.99	54.00	-9.01
7266.00	38.71	PK	344	1.8	H	1.33	40.04	74.00	-33.96
7266.00	38.65	Ave	344	1.8	H	1.33	39.98	54.00	-14.02
2348.73	45.73	PK	88	1.4	V	-13.19	32.54	74.00	-41.46
2348.73	37.28	Ave	88	1.4	V	-13.19	24.09	54.00	-29.91
2367.68	43.97	PK	162	2.0	H	-13.14	30.83	74.00	-43.17
2367.68	37.03	Ave	162	2.0	H	-13.14	23.89	54.00	-30.11
2487.70	42.20	PK	128	2.0	V	-13.08	29.12	74.00	-44.88
2487.70	37.52	Ave	128	2.0	V	-13.08	24.44	54.00	-29.56

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Middle Channel 2437MHz									
223.45	41.65	QP	63	1.2	H	-11.62	30.03	46.00	-15.97
223.45	35.17	QP	69	1.6	V	-11.62	23.55	46.00	-22.45
4874.00	49.21	PK	333	2.0	V	-0.62	48.59	74.00	-25.41
4874.00	45.39	Ave	333	2.0	V	-0.62	44.77	54.00	-9.23
7311.00	38.73	PK	182	1.7	H	2.21	40.94	74.00	-33.06
7311.00	39.43	Ave	182	1.7	H	2.21	41.64	54.00	-12.36
2320.92	45.66	PK	357	1.9	V	-13.19	32.47	74.00	-41.53
2320.92	39.69	Ave	357	1.9	V	-13.19	26.50	54.00	-27.50
2350.85	43.10	PK	150	1.7	H	-13.14	29.96	74.00	-44.04
2350.85	36.58	Ave	150	1.7	H	-13.14	23.44	54.00	-30.56
2488.11	45.00	PK	342	1.8	V	-13.08	31.92	74.00	-42.08
2488.11	37.08	Ave	342	1.8	V	-13.08	24.00	54.00	-30.00

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: High Channel 2452MHz									
223.45	42.25	QP	187	1.3	H	-11.62	30.63	46.00	-15.37
223.45	35.97	QP	203	1.8	V	-11.62	24.35	46.00	-21.65
4904.00	50.13	PK	125	1.3	V	-0.24	49.89	74.00	-24.11
4904.00	44.41	Ave	125	1.3	V	-0.24	44.17	54.00	-9.83
7356.00	38.90	PK	283	1.8	H	2.84	41.74	74.00	-32.26
7356.00	39.34	Ave	283	1.8	H	2.84	42.18	54.00	-11.82
2316.31	45.03	PK	85	1.2	V	-13.19	31.84	74.00	-42.16
2316.31	37.01	Ave	85	1.2	V	-13.19	23.82	54.00	-30.18
2384.01	44.95	PK	204	1.7	H	-13.14	31.81	74.00	-42.19
2384.01	37.76	Ave	204	1.7	H	-13.14	24.62	54.00	-29.38
2494.50	42.86	PK	9	1.1	V	-13.08	29.78	74.00	-44.22
2494.50	36.17	Ave	9	1.1	V	-13.08	23.09	54.00	-30.91

**Test Frequency: 18GHz~25GHz**

The measurements were more than 20 dB below the limit and not reported.

**BT BLE:****Test Frequency: 9KHz~26MHz**

Remark: only the worst data (GFSK modulation Low channel mode) were recorded.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.021	25.36	QP	21.84	40.00	7.20	29.54	-22.34
15.730	24.67	QP	21.35	40.00	6.02	29.54	-23.52
25.680	25.14	QP	20.67	40.00	5.81	29.54	-23.73

**Test Frequency : 26MHz ~ 30MHz**

The measurements were more than 20 dB below the limit and not reported.

**Test Frequency : 30MHz ~ 18GHz**

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel 2402MHz									
269.33	33.28	QP	98	1.7	H	-13.35	19.93	46.00	-26.07
269.33	39.83	QP	317	1.2	V	-13.35	26.48	46.00	-19.52
4804.00	44.63	PK	110	1.7	V	-1.06	43.57	74.00	-30.43
4804.00	41.86	Ave	110	1.7	V	-1.06	40.80	54.00	-13.20
7206.00	45.34	PK	263	1.9	H	1.33	46.67	74.00	-27.33
7206.00	37.02	Ave	263	1.9	H	1.33	38.35	54.00	-15.65
2339.42	46.73	PK	300	2.0	V	-13.19	33.54	74.00	-40.46
2339.42	38.11	Ave	300	2.0	V	-13.19	24.92	54.00	-29.08
2364.20	43.00	PK	95	1.0	H	-13.14	29.86	74.00	-44.14
2364.20	36.61	Ave	95	1.0	H	-13.14	23.47	54.00	-30.53
2490.55	44.32	PK	234	1.4	V	-13.08	31.24	74.00	-42.76
2490.55	36.54	Ave	234	1.4	V	-13.08	23.46	54.00	-30.54

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel 2440MHz									
269.33	33.75	QP	63	1.3	H	-13.35	20.40	46.00	-25.60
269.33	39.31	QP	264	1.1	V	-13.35	25.96	46.00	-20.04
4880.00	43.46	PK	149	1.2	V	-0.62	42.84	74.00	-31.16
4880.00	42.61	Ave	149	1.2	V	-0.62	41.99	54.00	-12.01
7320.00	45.05	PK	65	1.8	H	2.21	47.26	74.00	-26.74
7320.00	37.37	Ave	65	1.8	H	2.21	39.58	54.00	-14.42
2347.67	46.52	PK	76	1.3	V	-13.19	33.33	74.00	-40.67
2347.67	39.24	Ave	76	1.3	V	-13.19	26.05	54.00	-27.95
2371.57	44.37	PK	314	1.3	H	-13.14	31.23	74.00	-42.77
2371.57	36.07	Ave	314	1.3	H	-13.14	22.93	54.00	-31.07
2489.38	43.21	PK	242	1.5	V	-13.08	30.13	74.00	-43.87
2489.38	37.60	Ave	242	1.5	V	-13.08	24.52	54.00	-29.48

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel 2480MHz									
269.33	33.63	QP	192	1.6	H	-13.35	20.28	46.00	-25.72
269.33	38.46	QP	200	1.9	V	-13.35	25.11	46.00	-20.89
4960.00	43.99	PK	133	1.2	V	-0.24	43.75	74.00	-30.25
4960.00	42.78	Ave	133	1.2	V	-0.24	42.54	54.00	-11.46
7440.00	43.65	PK	29	1.7	H	2.84	46.49	74.00	-27.51
7440.00	36.29	Ave	29	1.7	H	2.84	39.13	54.00	-14.87
2329.51	46.22	PK	54	1.9	V	-13.19	33.03	74.00	-40.97
2329.51	37.52	Ave	54	1.9	V	-13.19	24.33	54.00	-29.67
2381.75	43.81	PK	331	1.8	H	-13.14	30.67	74.00	-43.33
2381.75	38.32	Ave	331	1.8	H	-13.14	25.18	54.00	-28.82
2497.42	43.21	PK	328	2.0	V	-13.08	30.13	74.00	-43.87
2497.42	37.99	Ave	328	2.0	V	-13.08	24.91	54.00	-29.09

**Test Frequency: 18GHz~25GHz**

The measurements were more than 20 dB below the limit and not reported.

## 10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247  
Test Method: KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017  
Test Result: PASS  
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:

Below 1GHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold

Above 1GHz:



For WIFI mode

RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold



For BLE mode



RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold

10.2 Test Result















802.11n HT20  
Low Channel



Middle Channel










BLE

Low Channel



Middle Channel






### Above 30MHz

802.11b


Low Channel

Fundamental



### Middle Channel

Fundamental





### High Channel


Fundamental



802.11g


### Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20

Low Channel

Fundamental




Middle Channel

Fundamental



### High Channel


Fundamental



### 802.11n HT40


#### Low Channel

Fundamental



Middle Channel

Fundamental



High Channel


Fundamental



BLE

Low Channel

Fundamental




Middle Channel

Fundamental



### High Channel

Fundamental



## 11 Band Edge Measurement

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting



### 11.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.




11.2 Test Result


Test result plots shown as follows:




TX 11g: Band edge-left side




TX 11g: Band edge-right side




TX 11n HT20: Band edge-left side




TX 11n HT20: Band edge-right side




TX 11n HT40: Band edge-left side




TX 11n HT40: Band edge-right side



BLE: Band edge-left side



BLE: Band edge-right side



## 12 6 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017



### 12.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

### 12.2 Test Result:



Operation mode	Test Channel	Bandwidth (MHz)
TX 11b	Channel 1	10.028
	Channel 6	10.028
	Channel 11	10.028
TX 11g	Channel 1	16.417
	Channel 6	16.417
	Channel 11	16.417
TX 11n HT20	Channel 1	17.623
	Channel 6	17.623
	Channel 11	17.623
TX 11n HT40	Channel 3	36.010
	Channel 6	36.010
	Channel 9	36.010
BLE	Channel 0	0.719
	Channel 19	0.713
	Channel 39	0.707



Test result plot:






















BLE: channel 0



BLE: channel 19





## 13 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017

### 13.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the  $RBW \geq DTS$  bandwidth.
- b) Set  $VBW \geq 3 \times RBW$ .
- c) Set  $span \geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.

- a) Set the  $RBW = 1 \text{ MHz}$ .
- b) Set the  $VBW \geq 3 \times RBW$
- c) Set the  $span \geq 1.5 \times DTS$  bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.


**13.2 Test Result:**

Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	9.24	1W/30dBm
	Middle-2437	9.18	1W/30dBm
	High-2462	9.12	1W/30dBm
TX 11g	Low-2412	9.04	1W/30dBm
	Middle-2437	9.29	1W/30dBm
	High-2462	9.04	1W/30dBm
TX 11n HT20	Low-2412	9.32	1W/30dBm
	Middle-2437	9.04	1W/30dBm
	High-2462	9.25	1W/30dBm
TX 11n HT40	Low-2422	9.48	1W/30dBm
	Middle-2437	9.12	1W/30dBm
	High-2452	9.22	1W/30dBm
BLE	Low-2402	-6.33	1W/30dBm
	Middle-2440	-7.84	1W/30dBm
	High-2480	-9.22	1W/30dBm






Test Plot



Mode: TX 11b channel 1







Mode: TX 11b channel 6
























## 14 Duty cycle

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10: 2013
Test Limit:	N/A
Test Result:	PASS
Remark:	EUT transmitting continuously

## 15 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017



### 15.1 Test Procedure:



KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017 section 10.2



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.



### 15.2 Test Result:



Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-15.97	8dBm per 3kHz
	Middle-2437	-16.64	8dBm per 3kHz
	High-2462	-16.87	8dBm per 3kHz
TX 11g	Low-2412	-24.85	8dBm per 3kHz
	Middle-2437	-22.90	8dBm per 3kHz
	High-2462	-23.35	8dBm per 3kHz
TX 11n HT20	Low-2412	-24.01	8dBm per 3kHz
	Middle-2437	-24.54	8dBm per 3kHz
	High-2462	-23.35	8dBm per 3kHz
TX 11n HT40	Low-2422	-26.99	8dBm per 3kHz
	Middle-2437	-28.20	8dBm per 3kHz
	High-2452	-28.24	8dBm per 3kHz
BLE	Low-2402	-22.11	8dBm per 3kHz
	Middle-2440	-23.91	8dBm per 3kHz
	High-2480	-25.10	8dBm per 3kHz
























## **16 Antenna Requirement**

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

## **17 RF Exposure**

Remark: refer to SAR test report: WTS18S05111958-1W.

## **18 Photographs of test setup and EUT.**

Note: Please refer to appendix: WTS18S05111958W\_Photo.

=====End of Report=====