

## RF EXPOSURE REPORT

### FOR

<b>Applicant</b>	:	HongKong Sunwe Electronic Technology Limited
<b>Address</b>	:	Flat/RM B, 10/F LEE MAY BUILDING 788-790 NATHAN ROAD, MONGKOK, KOWLOON, Hong Kong
<b>Equipment under Test</b>	:	Wireless Headphones
<b>Model No.</b>	:	SAHB328, SW-B68
<b>Trade Mark</b>	:	SOUND AURA
<b>FCC ID</b>	:	2AEPRSAHB328
<b>Manufacturer</b>	:	HongKong Sunwe Electronic Technology Limited
<b>Address</b>	:	Flat/RM B, 10/F LEE MAY BUILDING 788-790 NATHAN ROAD, MONGKOK, KOWLOON, Hong Kong

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-89201699, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## TABLE OF CONTENTS

Test report	
declares.....	3
1. General information .....	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory .....	5
2. RF Exposure evaluation for FCC .....	5

## TEST REPORT DECLARE

<b>Applicant</b>	:	HongKong Sunwe Electronic Technology Limited
<b>Address</b>	:	Flat/RM B, 10/F LEE MAY BUILDING 788-790 NATHAN ROAD, MONGKOK, KOWLOON, Hong Kong
<b>Equipment under Test</b>	:	Wireless Headphones
<b>Model No.</b>	:	SAHB328, SW-B68
<b>Trade mark</b>	:	SOUND AURA
<b>Manufacturer</b>	:	HongKong Sunwe Electronic Technology Limited
<b>Address</b>	:	Flat/RM B, 10/F LEE MAY BUILDING 788-790 NATHAN ROAD, MONGKOK, KOWLOON, Hong Kong

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R18042004-2E3		
<b>Date of Receipt:</b>	May 18, 2018	<b>Date of Test:</b>	May 18, 2018 ~ Jun. 04, 2018

**Prepared By:**

*Sam Li*

**Sam Li/Engineer**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jun. 04, 2018	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Wireless Headphones
Model Number	: SAHB328, SW-B68
Difference of models	: All models are identical except the model number, there for the test performed on the model SAHB328.
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V from external AC/DC power adapter DC 3.7V 250mAh Li-ion rechargeable built-in battery
Radio Specification	: Bluetooth V4.2
Operation frequency	: 2402MHz -2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data rate	: 1Mbps, 2Mbps, 3Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: 2dBi
Sample Type	: Series production

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808

Tel: +86-0769-89201699, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

## 2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz, 5.77dBm (3.78mW) output power]

$(3.78/5) \cdot [\sqrt{2.402(\text{GHz})}] = 1.172 < 3.0$  for 1-g SAR

Then SAR evaluation is not required

**END OF REPORT**