



---

# FCC Test Report

---

Report No.: AGC04563150401FE03

**FCC ID** : 2AEPXELK010  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : Laser Projection Keyboard  
**BRAND NAME** : N/A  
**MODEL NAME** : ELK010,ELK011  
**CLIENT** : Shenzhen E-Power Electronic Co., Ltd.  
**DATE OF ISSUE** : May.06,2015  
**STANDARD(S)**  
**TEST PROCEDURE(S)** : FCC Part 15 Rules  
**REPORT VERSION** : V1.0

**Attestation of Global Compliance (Shenzhen) Co., Ltd**

**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May.06,2015	Valid	Original Report

## TABLE OF CONTENTS

<b>1. VERIFICATION OF CONFORMITY .....</b>	<b>4</b>
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
2.1. PRODUCT DESCRIPTION.....	5
2.2. TABLE OF CARRIER FREQUENCIES.....	5
<b>3. MEASUREMENT UNCERTAINTY.....</b>	<b>6</b>
<b>4. DESCRIPTION OF TEST MODES.....</b>	<b>6</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>6</b>
5.1. CONFIGURATION OF EUT SYSTEM .....	6
5.2. EQUIPMENT USED IN EUT SYSTEM .....	7
5.3. SUMMARY OF TEST RESULTS .....	7
<b>6. TEST FACILITY .....</b>	<b>8</b>
<b>7 ALL TEST EQUIPMENT LIST .....</b>	<b>8</b>
<b>8. RADIATED EMISSION .....</b>	<b>9</b>
8.1TEST LIMIT.....	9
8.2. MEASUREMENT PROCEDURE .....	10
8.3. TEST SETUP .....	12
8.4. TEST RESULT(Worst modulation:GFSK).....	14
<b>9. BAND EDGE EMISSION .....</b>	<b>27</b>
9.1. MEASUREMENT PROCEDURE .....	27
9.2 TEST SETUP .....	27
9.3 RADIATED TEST RESULT(Worst modulation:GFSK).....	28
<b>10. 20DB BANDWIDTH.....</b>	<b>32</b>
10.1. MEASUREMENT PROCEDURE .....	32
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	32
10.3. LIMITS AND MEASUREMENT RESULTS.....	32
<b>11. FCC LINE CONDUCTED EMISSION TEST .....</b>	<b>35</b>
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....	35
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....	35
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	36
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	36
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST .....	37
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>39</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>41</b>

## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	Shenzhen E-Power Electronic Co., Ltd.
<b>Address</b>	No 4/F, Bldg 21, No 3, Liu Xian RD, District 71, Bao'an, Shenzhen, China
<b>Manufacturer</b>	Shenzhen E-Power Electronic Co., Ltd.
<b>Address</b>	No 4/F, Bldg 21, No 3, Liu Xian RD, District 71, Bao'an, Shenzhen, China
<b>Product Designation</b>	Laser Projection Keyboard
<b>Brand Name</b>	N/A
<b>Test Model</b>	ELK010
<b>Series Model</b>	ELK011
<b>Different Description</b>	All the same except that ELK011 has display screen ,while ELK010 does not
<b>Date of test</b>	May.04,2015 to May.05,2015
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Compliance Certification Service(Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Prepared By



Water Zuo May.06,2015

Checked By



Forrest Lei May.06,2015

Authorized By



Solger Zhang May.06,2015

## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.402 GHz to 2.480GHz
<b>RF Output Power</b>	-4.56Bm(Max)
<b>Bluetooth Version</b>	V3.0
<b>Modulation</b>	GFSK
<b>Number of channels</b>	79
<b>Hardware Version</b>	1.2
<b>Software Version</b>	1.0
<b>Antenna Designation</b>	PCB Antenna (Met 15.203 Antenna requirement)
<b>Antenna Gain</b>	0dBi
<b>Power Supply</b>	DC3.7V

Note: The USB port only used for charging and can't be used to transfer data with PC.

### 2.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
10	Normal operation (BT)


Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. Two models ELK 010 and ELK 011 have been verified for radiation emission. test result was compliance for limit. Then ELK 010 was selected for test model .Because it have same PCB with ELK011 except for display unit.


### 5. SYSTEM TEST CONFIGURATION

#### 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



## 5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Laser Projection Keyboard	N/A	ELK010	EUT
2	Control box	N/A	N/A	AE.
3	PC	Dell	INSPIRON	AE.
4	USB Cable 1	N/A	1.2m unshielded	AE.
5	USB Cable 2	N/A	1.5m unshielded	AE.
6	Cable connecting with Control box	N/A	0.2m unshielded	AE.

## 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant

## 6. TEST FACILITY

<b>Site</b>	Compliance Certification Service(Shenzhen) Inc.
<b>Location</b>	No.10-1 Mingkeda Logistics Park, No.18 Huanguan South RD. Guan lan Town,Baoan Distr
<b>FCC Registration No.</b>	441872
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

## 7 ALL TEST EQUIPMENT LIST

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/01/2015	03/01/2016
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2015	03/08/2016
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2015	03/17/2016
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2015	03/17/2016
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	07/10/2014	07/09/2015
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/01/2015	03/01/2016
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/01/2015	03/01/2016
Loop Antenna	COM-POWER	AL-130	121044	09/27/2014	09/26/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2015	02/27/2016
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2015	03/08/2016
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	03/09/2015	03/08/2016
LISN	EMCO	3825/2	8901-1459	03/09/2015	03/08/2016
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2015	03/03/2016
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			



## 8. RADIATED EMISSION

### 8.1 TEST LIMIT

#### Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		$\mu$ V/m	dB( $\mu$ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average)	

Remark: (1) Emission level  $\text{dB } \mu \text{ V} = 20 \log \text{ Emission level } \mu \text{ V/m}$   
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

## 8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

### 8.3. TEST SETUP


#### Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz




8.4. TEST RESULT(Worst modulation:GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation	Power:	Humidity: 60 %
EUT:Laser Projection Keyboard	Distance: 3m	
M/N:ELK010		
Mode:Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		156.0999	21.99	15.30	37.29	43.50	-6.21	peak			
2	*	317.7667	24.64	16.59	41.23	46.00	-4.77	peak			
3	!	348.4832	22.58	18.64	41.22	46.00	-4.78	peak			
4		497.2167	17.49	21.10	38.59	46.00	-7.41	peak			
5	!	516.6167	18.62	21.58	40.20	46.00	-5.80	peak			
6	!	767.2000	14.11	26.87	40.98	46.00	-5.02	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010

Mode:Low Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		67.1833	28.52	5.36	33.88	40.00	-6.12	peak			
2		149.6333	20.15	15.26	35.41	43.50	-8.09	peak			
3		343.6333	16.79	18.32	35.11	46.00	-10.89	peak			
4		443.8667	18.24	20.40	38.64	46.00	-7.36	peak			
5	*	516.6167	20.04	21.58	41.62	46.00	-4.38	peak			
6		768.8167	11.26	26.89	38.15	46.00	-7.85	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010

Mode:Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	59.1000	23.85	11.16	35.01	40.00	-4.99	peak			
2	!	156.1000	22.65	15.30	37.95	43.50	-5.55	peak			
3		227.2333	21.84	13.03	34.87	46.00	-11.13	peak			
4	!	335.5500	22.30	17.78	40.08	46.00	-5.92	peak			
5	*	516.6167	20.23	21.58	41.81	46.00	-4.19	peak			
6		600.6833	14.66	23.73	38.39	46.00	-7.61	peak			

**RESULT: PASS**



## RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010

Mode:Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	67.1833	28.73	5.36	34.09	40.00	-5.91	peak			
2		138.3167	18.52	14.50	33.02	43.50	-10.48	peak			
3		342.0167	15.35	18.21	33.56	46.00	-12.44	peak			
4		443.8667	19.42	20.40	39.82	46.00	-6.18	peak			
5	*	527.9333	19.86	21.88	41.74	46.00	-4.26	peak			
6	!	623.3167	17.62	23.25	40.87	46.00	-5.13	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation	Power:	Humidity: 60 %
EUT:Laser Projection Keyboard	Distance: 3m	
M/N:ELK010		
Mode:High Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	63.9500	24.01	10.80	34.81	40.00	-5.19	peak			
2	!	156.1000	23.63	15.30	38.93	43.50	-4.57	peak			
3	!	316.1500	25.59	16.49	42.08	46.00	-3.92	peak			
4	!	516.6167	20.55	21.58	42.13	46.00	-3.87	peak			
5	!	600.6833	17.43	23.73	41.16	46.00	-4.84	peak			
6	*	896.5333	13.66	28.52	42.18	46.00	-3.82	peak			

RESULT: PASS

## RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010


Mode:High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	!	156.1000	22.70	15.30	38.00	43.50	-5.50	peak			
2		332.3167	18.08	17.56	35.64	46.00	-10.36	peak			
3		443.8667	17.16	20.40	37.56	46.00	-8.44	peak			
4	!	527.9333	19.28	21.88	41.16	46.00	-4.84	peak			
5		768.8167	12.18	26.89	39.07	46.00	-6.93	peak			
6	*	914.3167	12.41	29.01	41.42	46.00	-4.58	peak			

**RESULT: PASS****Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

**RADIATED EMISSION ABOVE 1GHZ****RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL**

Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	100.23	-9.68	90.55	114.00	-23.45	peak			
2		4016.667	50.03	-4.75	45.28	74.00	-28.72	peak			
3		4941.667	47.70	-1.95	45.75	74.00	-28.25	peak			
4	*	2402.000	99.33	-9.68	89.65	94.00	-4.35	AVG	150	91	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1300.000	60.95	-15.46	45.49	74.00	-28.51	peak			
2		2402.000	100.23	-9.68	90.55	114.00	-23.45	peak			
3		3500.000	54.70	-7.89	46.81	74.00	-27.19	peak			
4	*	2402.000	98.71	-9.68	89.03	94.00	-4.97	AVG	150	100	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1708.333	60.11	-13.19	46.92	74.00	-27.08	peak			
2		2441.000	99.79	-9.63	90.16	114.00	-23.84	peak			
3		4541.667	50.24	-3.00	47.24	74.00	-26.76	peak			
4	*	2441.000	98.05	-9.63	88.42	94.00	-5.58	AVG	150	100	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	99.73	-9.63	90.10	114.00	-23.90	peak			
2		3058.333	55.09	-8.30	46.79	74.00	-27.21	peak			
3		4400.000	50.52	-3.45	47.07	74.00	-26.93	peak			
4	*	2441.000	98.58	-9.63	88.95	94.00	-5.05	AVG	150	360	

**RESULT: PASS**

## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010

Mode: High Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	99.37	-9.59	89.78	114.00	-24.22	peak			
2		3058.333	53.79	-8.30	45.49	74.00	-28.51	peak			
3		5041.667	47.23	-1.80	45.43	74.00	-28.57	peak			
4	*	2480.000	97.54	-9.59	87.95	94.00	-6.05	AVG	150	91	

**RESULT: PASS**



## RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance: 3m

M/N:ELK010

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1525.000	60.01	-15.12	44.89	74.00	-29.11	peak			
2		2480.000	99.37	-9.59	89.78	114.00	-24.22	peak			
3		4991.667	49.45	-1.82	47.63	74.00	-26.37	peak			
4	*	2480.000	97.65	-9.59	88.06	94.00	-5.94	AVG	150	100	

**RESULT: PASS**

**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

### Field strength of the fundamental signal

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	100.23	-9.68	90.55	114	-23.45	Horizontal
2402	100.23	-9.68	90.55	114	-23.45	Vertical
2441	99.79	-9.63	90.16	114	-23.84	Horizontal
2441	99.73	-9.63	90.10	114	-23.90	Vertical
2480	99.37	-9.59	89.78	114	-24.22	Horizontal
2480	99.37	-9.59	89.78	114	-24.22	Vertical

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	99.33	-9.68	89.65	94	-4.35	Horizontal
2402	98.71	-9.68	89.03	94	-4.97	Vertical
2441	98.05	-9.63	88.42	94	-5.58	Horizontal
2441	98.58	-9.63	88.95	94	-5.05	Vertical
2480	97.54	-9.59	87.95	94	-6.05	Horizontal
2480	97.65	-9.59	88.06	94	-5.94	Vertical

## 9. BAND EDGE EMISSION

### 9.1. MEASUREMENT PROCEDURE

1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.


2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO


(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

### 9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




CONDUCTED TEST SETUP



9.3 RADIATED TEST RESULT(Worst modulation:GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

EUT:Laser Projection Keyboard

M/N:ELK010

Mode: Low Channel TX

Note:

Polarization: *Horizontal*

Power:


Distance:

Temperature: 26

Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2255.008	36.79	10.16	46.95	74.00	-27.05	peak			
2		2390.000	36.50	10.31	46.81	74.00	-27.19	peak			
3	*	2402.000	80.22	10.32	90.54	74.00	16.54	peak			

## TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance:


M/N:ELK010

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2261.842	36.80	10.17	46.97	74.00	-27.03	peak			
2		2390.000	36.21	10.31	46.52	74.00	-27.48	peak			
3	*	2402.000	80.59	10.32	90.91	74.00	16.91	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance:


M/N:ELK010

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	79.55	10.41	89.96	74.00	15.96	peak			
2		2483.500	35.19	10.41	45.60	74.00	-28.40	peak			
3		2497.030	36.67	10.43	47.10	74.00	-26.90	peak			

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT:Laser Projection Keyboard

Distance:

M/N:ELK010

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	79.32	10.41	89.73	74.00	15.73	peak			
2		2483.500	35.26	10.41	45.67	74.00	-28.33	peak			
3		2491.017	37.95	10.42	48.37	74.00	-25.63	peak			

**RESULT: PASS****Note:** The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.


The "Factor" value can be calculated automatically by software of measurement system.

## 10. 20DB BANDWIDTH

### 10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



### 10.3. LIMITS AND MEASUREMENT RESULTS


BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	0.901	PASS
	Middle Channel	0.885	PASS
	High Channel	0.877	PASS




TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



## 11. FCC LINE CONDUCTED EMISSION TEST


### 11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



### **11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by PC which received 120V/60Hz power by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### **11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
  3. The test data of the worst case condition(s) was reported on the Summary Data page.


## 11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1P	0.1660	43.21	22.52	9.61	52.82	32.13	65.15	55.16	-12.33	-23.03	Pass
2*	0.2100	42.73	21.05	9.69	52.42	30.74	63.20	53.21	-10.78	-22.47	Pass
3P	0.5860	26.69	20.58	9.72	36.41	30.30	56.00	46.00	-19.59	-15.70	Pass
4P	3.5540	28.39	18.81	9.71	38.10	28.52	56.00	46.00	-17.90	-17.48	Pass
5P	21.1060	24.78	10.64	9.84	34.62	20.48	60.00	50.00	-25.38	-29.52	Pass
6P	23.8420	24.22	12.13	9.88	34.10	22.01	60.00	50.00	-25.90	-27.99	Pass

Line Conducted Emission Test Line 2-N



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1*	0.1660	43.00	22.50	9.78	52.78	32.28	65.15	55.16	-12.37	-22.88	Pass
2P	0.2500	34.90	22.51	9.77	44.67	32.28	61.75	51.76	-17.08	-19.48	Pass
3P	0.5899	27.48	22.76	9.68	37.16	32.44	56.00	46.00	-18.84	-13.56	Pass
4P	3.2300	28.72	18.25	9.75	38.47	28.00	56.00	46.00	-17.53	-18.00	Pass
5P	20.2939	25.11	13.74	9.73	34.84	23.47	60.00	50.00	-25.16	-26.53	Pass
6P	23.9980	26.31	15.44	9.78	36.09	25.22	60.00	50.00	-23.91	-24.78	Pass


## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP







## APPENDIX B: PHOTOGRAPHS OF EUT

Model ELK010

TOTAL VIEW OF EUT



TOP VIEW OF EUT







BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT






RIGHT VIEW OF EUT




VIEW OF EUT (PORT)



OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1







INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5






**Model ELK011**  
TOTAL VIEW OF EUT



TOP VIEW OF EUT






BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT




LEFT VIEW OF EUT





RIGHT VIEW OF EUT



----END OF REPORT----