

**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/GSM 850 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.072 \text{ mW/g}$


**Left Cheek/GSM 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.00 \text{ V/m}$ ; Power Drift =  $0.124 \text{ dB}$

Peak SAR (extrapolated) =  $0.077 \text{ W/kg}$

**SAR(1 g) =  $0.070 \text{ mW/g}$ ; SAR(10 g) =  $0.057 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.073 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/GSM 850 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.034 \text{ mW/g}$


**Left Tilt/GSM 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.65 \text{ V/m}$ ; Power Drift =  $0.136 \text{ dB}$

Peak SAR (extrapolated) =  $0.035 \text{ W/kg}$

**SAR(1 g) =  $0.033 \text{ mW/g}$ ; SAR(10 g) =  $0.027 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.034 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/GSM 850 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.101 \text{ mW/g}$


**Right Cheek/GSM 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.73 \text{ V/m}$ ; Power Drift =  $-0.164 \text{ dB}$

Peak SAR (extrapolated) =  $0.123 \text{ W/kg}$

**SAR(1 g) =  $0.096 \text{ mW/g}$ ; SAR(10 g) =  $0.068 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.103 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/GSM 850 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.040 \text{ mW/g}$


**Right Tilt/GSM 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $4.31 \text{ V/m}$ ; Power Drift =  $-0.097 \text{ dB}$

Peak SAR (extrapolated) =  $0.043 \text{ W/kg}$

**SAR(1 g) =  $0.037 \text{ mW/g}$ ; SAR(10 g) =  $0.029 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.038 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 836.6 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Body-worn/GSM 850 Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.199 \text{ mW/g}$


**Body-worn/GSM 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $13.4 \text{ V/m}$ ; Power Drift =  $-0.069 \text{ dB}$

Peak SAR (extrapolated) =  $0.259 \text{ W/kg}$

**SAR(1 g) =  $0.187 \text{ mW/g}$ ; SAR(10 g) =  $0.130 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.200 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GPRS bands-4slots; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/GPRS 850 Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.540 \text{ mW/g}$


**Hotspot Back/GPRS 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $23.5 \text{ V/m}$ ; Power Drift =  $0.075 \text{ dB}$

Peak SAR (extrapolated) =  $0.707 \text{ W/kg}$

**SAR(1 g) =  $0.504 \text{ mW/g}$ ; SAR(10 g) =  $0.351 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.541 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GPRS bands-4slots; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/GPRS850 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.347 \text{ mW/g}$


**Hotspot Right/GPRS850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $18.0 \text{ V/m}$ ; Power Drift =  $0.088 \text{ dB}$

Peak SAR (extrapolated) =  $0.445 \text{ W/kg}$

**SAR(1 g) =  $0.325 \text{ mW/g}$ ; SAR(10 g) =  $0.228 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.344 \text{ mW/g}$





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GPRS bands-4slots; Frequency: 836.6 MHz; Duty Cycle: 1:2

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/GPRS 850 Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.465 \text{ mW/g}$


**Hotspot Bottom/GPRS 850 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $17.9 \text{ V/m}$ ; Power Drift =  $0.040 \text{ dB}$

Peak SAR (extrapolated) =  $0.681 \text{ W/kg}$

**SAR(1 g) =  $0.403 \text{ mW/g}$ ; SAR(10 g) =  $0.221 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.454 \text{ mW/g}$





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/GSM 1900 Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.040 mW/g


**Left Cheek/GSM 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.94 V/m; Power Drift = -0.095 dB

Peak SAR (extrapolated) = 0.123 W/kg

**SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.025 mW/g**

Maximum value of SAR (measured) = 0.040 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/WCDMA Band 2 Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.025 mW/g


**Left Tilt/WCDMA Band 2 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.80 V/m; Power Drift = -0.120 dB

Peak SAR (extrapolated) = 0.031 W/kg

**SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.016 mW/g**

Maximum value of SAR (measured) = 0.024 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/GSM 1900 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.063 mW/g


**Right Cheek/GSM 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.71 V/m; Power Drift = 0.065 dB

Peak SAR (extrapolated) = 0.085 W/kg

**SAR(1 g) = 0.055 mW/g; SAR(10 g) = 0.035 mW/g**

Maximum value of SAR (measured) = 0.060 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/GSM 1900 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.016 mW/g


**Right Tilt/GSM 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.28 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.046 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00966 mW/g**

Maximum value of SAR (measured) = 0.016 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GSM bands; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Body-worn/GSM 1900 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.163 mW/g


**Body-worn/GSM 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.92 V/m; Power Drift = -0.069 dB

Peak SAR (extrapolated) = 0.259 W/kg

**SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.075 mW/g**

Maximum value of SAR (measured) = 0.161 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GPRS bands-2slots; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/GPRS 1900 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.194 mW/g


**Hotspot Back/GPRS 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.65 V/m; Power Drift = 0.043 dB

Peak SAR (extrapolated) = 0.495 W/kg

**SAR(1 g) = 0.262 mW/g; SAR(10 g) = 0.133 mW/g**

Maximum value of SAR (measured) = 0.295 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GPRS bands-2slots; Frequency: 1880 MHz;Duty Cycle: 1:4

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/GPRS 1900 Mid/Area Scan (81x161x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.186 mW/g


**Hotspot Right/GPRS 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.50 V/m; Power Drift = -0.109 dB

Peak SAR (extrapolated) = 0.297 W/kg

**SAR(1 g) = 0.157 mW/g; SAR(10 g) = 0.079 mW/g**

Maximum value of SAR (measured) = 0.180 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: GPRS bands-2slots; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/GPRS 1900 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.537 mW/g


**Hotspot Bottom/GPRS 1900 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.5 V/m; Power Drift = 0.084 dB

Peak SAR (extrapolated) = 0.893 W/kg

**SAR(1 g) = 0.460 mW/g; SAR(10 g) = 0.224 mW/g**

Maximum value of SAR (measured) = 0.530 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/WCDMA Band 5 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.052 \text{ mW/g}$


**Left Cheek/WCDMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.51 \text{ V/m}$ ; Power Drift =  $0.032 \text{ dB}$

Peak SAR (extrapolated) =  $0.057 \text{ W/kg}$

**SAR(1 g) =  $0.050 \text{ mW/g}$ ; SAR(10 g) =  $0.040 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.052 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/WCDMA Band 5 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.020 \text{ mW/g}$


**Left Tilt/WCDMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.35 \text{ V/m}$ ; Power Drift =  $-0.101 \text{ dB}$

Peak SAR (extrapolated) =  $0.022 \text{ W/kg}$

**SAR(1 g) =  $0.020 \text{ mW/g}$ ; SAR(10 g) =  $0.016 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.022 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/WCDMA Band 5 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.052 \text{ mW/g}$


**Right Cheek/WCDMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.09 \text{ V/m}$ ; Power Drift =  $-0.152 \text{ dB}$

Peak SAR (extrapolated) =  $0.060 \text{ W/kg}$

**SAR(1 g) =  $0.049 \text{ mW/g}$ ; SAR(10 g) =  $0.036 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.053 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/WCDMA Band 5 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.025 \text{ mW/g}$


**Right Tilt/WCDMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.63 \text{ V/m}$ ; Power Drift =  $-0.108 \text{ dB}$

Peak SAR (extrapolated) =  $0.024 \text{ W/kg}$

**SAR(1 g) =  $0.022 \text{ mW/g}$ ; SAR(10 g) =  $0.018 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.023 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/WCDMA Band 5 Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.131 \text{ mW/g}$

**Hotspot Back/WCDMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,


$dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $11.4 \text{ V/m}$ ; Power Drift =  $-0.115 \text{ dB}$

Peak SAR (extrapolated) =  $0.169 \text{ W/kg}$

**SAR(1 g) =  $0.123 \text{ mW/g}$ ; SAR(10 g) =  $0.086 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.131 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/WCMA Band 5 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.091 \text{ mW/g}$

**Hotspot Right/WCMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,


$dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $9.11 \text{ V/m}$ ; Power Drift =  $0.033 \text{ dB}$

Peak SAR (extrapolated) =  $0.116 \text{ W/kg}$

**SAR(1 g) =  $0.085 \text{ mW/g}$ ; SAR(10 g) =  $0.061 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.089 \text{ mW/g}$





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.6 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/WCMA Band 5 Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.110 \text{ mW/g}$


**Hotspot Bottom/WCMA Band 5 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $8.72 \text{ V/m}$ ; Power Drift =  $0.130 \text{ dB}$

Peak SAR (extrapolated) =  $0.164 \text{ W/kg}$

**SAR(1 g) =  $0.095 \text{ mW/g}$ ; SAR(10 g) =  $0.053 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.119 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.16$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/WCDMA Band 4 Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.025 mW/g


**Left Cheek/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.81 V/m; Power Drift = -1.18 dB

Peak SAR (extrapolated) = 0.076 W/kg

**SAR(1 g) = 0.023 mW/g; SAR(10 g) = 0.015 mW/g**

Maximum value of SAR (measured) = 0.025 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.16$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/WCDMA Band 4 Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.013 mW/g


**Left Tilt/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.61 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 0.017 W/kg

**SAR(1 g) = 0.0021 mW/g; SAR(10 g) = 0.000678 mW/g**

Maximum value of SAR (measured) = 0.014 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.16$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/WCDMA Band 4 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.035 mW/g


**Right Cheek/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.04 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.063 W/kg

**SAR(1 g) = 0.031 mW/g; SAR(10 g) = 0.020 mW/g**

Maximum value of SAR (measured) = 0.034 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.16$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/WCDMA Band 4 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.012 mW/g


**Right Tilt/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.67 V/m; Power Drift = -0.104 dB

Peak SAR (extrapolated) = 0.035 W/kg

**SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00732 mW/g**

Maximum value of SAR (measured) = 0.012 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/WCDMA Band 4 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.204 mW/g

**Hotspot Back/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 5.93 V/m; Power Drift = -0.063 dB

Peak SAR (extrapolated) = 0.299 W/kg

**SAR(1 g) = 0.163 mW/g; SAR(10 g) = 0.086 mW/g**

Maximum value of SAR (measured) = 0.180 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/WCDMA Band 4 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.068 mW/g


**Hotspot Right/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.62 V/m; Power Drift = 0.100 dB

Peak SAR (extrapolated) = 0.103 W/kg

**SAR(1 g) = 0.059 mW/g; SAR(10 g) = 0.032 mW/g**

Maximum value of SAR (measured) = 0.069 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1732.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1732.6$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/WCDMA Band 4 Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.346 mW/g


**Hotspot Bottom/WCDMA Band 4 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.178 dB

Peak SAR (extrapolated) = 0.600 W/kg

**SAR(1 g) = 0.292 mW/g; SAR(10 g) = 0.136 mW/g**

Maximum value of SAR (measured) = 0.340 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 39.64$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/WCDMA Band 2 High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.063 mW/g


**Left Cheek/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.01 V/m; Power Drift = -0.150 dB

Peak SAR (extrapolated) = 0.085 W/kg

**SAR(1 g) = 0.059 mW/g; SAR(10 g) = 0.041 mW/g**

Maximum value of SAR (measured) = 0.064 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 39.64$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/WCDMA Band 2 High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.051 mW/g


**Left Tilt/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.37 V/m; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 0.066 W/kg

**SAR(1 g) = 0.046 mW/g; SAR(10 g) = 0.029 mW/g**

Maximum value of SAR (measured) = 0.051 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 39.64$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/WCDMA Band 2 High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.113 mW/g

**Right Cheek/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 3.29 V/m; Power Drift = -0.183 dB

Peak SAR (extrapolated) = 0.192 W/kg

**SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.057 mW/g**

Maximum value of SAR (measured) = 0.108 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.43$  mho/m;  $\epsilon_r = 39.64$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/WCDMA Band 2 High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.035 mW/g


**Right Tilt/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.43 V/m; Power Drift = -0.069 dB

Peak SAR (extrapolated) = 0.057 W/kg

**SAR(1 g) = 0.027 mW/g; SAR(10 g) = 0.018 mW/g**

Maximum value of SAR (measured) = 0.030 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/WCDMA Band 2 High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.407 mW/g

**Hotspot Back/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 6.66 V/m; Power Drift = -0.226 dB

Peak SAR (extrapolated) = 0.677 W/kg

**SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.182 mW/g**

Maximum value of SAR (measured) = 0.410 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/WCDMA Band 2 High/Area Scan (81x161x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.254 mW/g


**Hotspot Right/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.65 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.410 W/kg

**SAR(1 g) = 0.212 mW/g; SAR(10 g) = 0.105 mW/g**

Maximum value of SAR (measured) = 0.241 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 3G Bands; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1907.6$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.51$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/WCDMA Band 2 High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.686 mW/g


**Hotspot Bottom/WCDMA Band 2 High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.3 V/m; Power Drift = 0.149 dB

Peak SAR (extrapolated) = 1.18 W/kg

**SAR(1 g) = 0.608 mW/g; SAR(10 g) = 0.297 mW/g**

Maximum value of SAR (measured) = 0.703 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 2 Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.108 mW/g


**Left Cheek/LTE Band 2 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.10 V/m; Power Drift = 0.102 dB

Peak SAR (extrapolated) = 0.144 W/kg

**SAR(1 g) = 0.102 mW/g; SAR(10 g) = 0.069 mW/g**

Maximum value of SAR (measured) = 0.109 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.60$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 2 50RB High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.103 mW/g


**Left Cheek/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.33 V/m; Power Drift = -0.144 dB

Peak SAR (extrapolated) = 0.138 W/kg

**SAR(1 g) = 0.100 mW/g; SAR(10 g) = 0.067 mW/g**

Maximum value of SAR (measured) = 0.107 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 2 Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.070 mW/g


**Left Tilt/LTE Band 2 Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.66 V/m; Power Drift = -0.043 dB

Peak SAR (extrapolated) = 0.093 W/kg

**SAR(1 g) = 0.064 mW/g; SAR(10 g) = 0.041 mW/g**

Maximum value of SAR (measured) = 0.069 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.60$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 2 50RB High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.065 mW/g


**Left Tilt/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.76 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 0.083 W/kg

**SAR(1 g) = 0.057 mW/g; SAR(10 g) = 0.037 mW/g**

Maximum value of SAR (measured) = 0.062 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 2 1RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.142 mW/g


**Right Cheek/LTE Band 2 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.31 V/m; Power Drift = 0.152 dB

Peak SAR (extrapolated) = 0.198 W/kg

**SAR(1 g) = 0.130 mW/g; SAR(10 g) = 0.080 mW/g**

Maximum value of SAR (measured) = 0.143 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.60$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 2 50RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.144 mW/g


**Right Cheek/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.35 V/m; Power Drift = 0.081 dB

Peak SAR (extrapolated) = 0.200 W/kg

**SAR(1 g) = 0.131 mW/g; SAR(10 g) = 0.081 mW/g**

Maximum value of SAR (measured) = 0.147 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.44$  mho/m;  $\epsilon_r = 39.33$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 2 1RB Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.032 mW/g


**Right Tilt/LTE Band 2 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.84 V/m; Power Drift = 0.060 dB

Peak SAR (extrapolated) = 0.041 W/kg

**SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.035 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.41$  mho/m;  $\epsilon_r = 40.60$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.71, 8.71, 8.71); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 2 50RB High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.032 mW/g


**Right Tilt/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.07 V/m; Power Drift = 0.035 dB

Peak SAR (extrapolated) = 0.041 W/kg

**SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.019 mW/g**

Maximum value of SAR (measured) = 0.032 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 2 1RB Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.450 mW/g


**Hotspot Back/LTE Band 2 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 0.753 W/kg

**SAR(1 g) = 0.397 mW/g; SAR(10 g) = 0.198 mW/g**

Maximum value of SAR (measured) = 0.452 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52.07$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 2 50RB High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.438 mW/g


**Hotspot Back/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.9 V/m; Power Drift = 0.110 dB

Peak SAR (extrapolated) = 0.738 W/kg

**SAR(1 g) = 0.389 mW/g; SAR(10 g) = 0.194 mW/g**

Maximum value of SAR (measured) = 0.448 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 2 1RB Mid/Area Scan (101x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.291 mW/g


**Hotspot Right/LTE Band 2 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.56 V/m; Power Drift = 0.134 dB

Peak SAR (extrapolated) = 0.473 W/kg

**SAR(1 g) = 0.251 mW/g; SAR(10 g) = 0.126 mW/g**

Maximum value of SAR (measured) = 0.282 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52.07$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 2 50RB High/Area Scan (101x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.218 mW/g


**Hotspot Right/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.51 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 0.363 W/kg

**SAR(1 g) = 0.190 mW/g; SAR(10 g) = 0.096 mW/g**

Maximum value of SAR (measured) = 0.217 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.52$  mho/m;  $\epsilon_r = 52.49$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 2 1RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.571 mW/g


**Hotspot Bottom/LTE Band 2 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = 0.090 dB

Peak SAR (extrapolated) = 0.951 W/kg

**SAR(1 g) = 0.507 mW/g; SAR(10 g) = 0.258 mW/g**

Maximum value of SAR (measured) = 0.567 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.54$  mho/m;  $\epsilon_r = 52.07$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(8.31, 8.31, 8.31); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 2 50RB High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.544 mW/g


**Hotspot Bottom/LTE Band 2 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = 0.208 dB

Peak SAR (extrapolated) = 0.905 W/kg

**SAR(1 g) = 0.487 mW/g; SAR(10 g) = 0.249 mW/g**

Maximum value of SAR (measured) = 0.543 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.15$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 4 1RB Low/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.036 mW/g


**Left Cheek/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.13 V/m; Power Drift = 0.093 dB

Peak SAR (extrapolated) = 0.042 W/kg

**SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.023 mW/g**

Maximum value of SAR (measured) = 0.032 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745 \text{ MHz}$ ;  $\sigma = 1.39 \text{ mho/m}$ ;  $\epsilon_r = 40.01$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 4 50RB High/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.098 \text{ mW/g}$


**Left Cheek/LTE Band 4 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $1.60 \text{ V/m}$ ; Power Drift =  $0.086 \text{ dB}$

Peak SAR (extrapolated) =  $0.159 \text{ W/kg}$

**SAR(1 g) =  $0.088 \text{ mW/g}$ ; SAR(10 g) =  $0.047 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.108 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.15$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 4 1RB Low/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.015 mW/g


**Left Tilt/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.14 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 0.035 W/kg

**SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.017 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745 \text{ MHz}$ ;  $\sigma = 1.39 \text{ mho/m}$ ;  $\epsilon_r = 40.01$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 4 50RB High/Area Scan (91x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.017 \text{ mW/g}$


**Left Tilt/LTE Band 4 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $1.81 \text{ V/m}$ ; Power Drift =  $0.052 \text{ dB}$

Peak SAR (extrapolated) =  $0.022 \text{ W/kg}$

**SAR(1 g) =  $0.00486 \text{ mW/g}$ ; SAR(10 g) =  $0.00131 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.018 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.15$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 4 1RB Low/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.041 mW/g


**Right Cheek/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.20 V/m; Power Drift = 0.137 dB

Peak SAR (extrapolated) = 0.099 W/kg

**SAR(1 g) = 0.038 mW/g; SAR(10 g) = 0.024 mW/g**

Maximum value of SAR (measured) = 0.040 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 40.01$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 4 50RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.040 mW/g


**Right Cheek/LTE Band 4 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.27 V/m; Power Drift = 0.042 dB

Peak SAR (extrapolated) = 0.081 W/kg

**SAR(1 g) = 0.037 mW/g; SAR(10 g) = 0.022 mW/g**

Maximum value of SAR (measured) = 0.040 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 40.15$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 4 1RB Low/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.019 mW/g


**Right Tilt/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.08 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.028 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.011 mW/g**

Maximum value of SAR (measured) = 0.018 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 40.01$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(9.06, 9.06, 9.06); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 4 50RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.015 mW/g


**Right Tilt/LTE Band 4 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.94 V/m; Power Drift = 0.109 dB

Peak SAR (extrapolated) = 0.031 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.010 mW/g**

Maximum value of SAR (measured) = 0.018 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 4 1RB Low/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.192 mW/g


**Hotspot Back/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.02 V/m; Power Drift = 0.126 dB

Peak SAR (extrapolated) = 0.307 W/kg

**SAR(1 g) = 0.170 mW/g; SAR(10 g) = 0.086 mW/g**

Maximum value of SAR (measured) = 0.193 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 4 50RB High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.189 mW/g


**Hotspot Back/LTE Band 4 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.77 V/m; Power Drift = -0.160 dB

Peak SAR (extrapolated) = 0.398 W/kg

**SAR(1 g) = 0.152 mW/g; SAR(10 g) = 0.055 mW/g**

Maximum value of SAR (measured) = 0.224 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 4 1RB Low/Area Scan (101x101x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.070 mW/g


**Hotspot Right/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.65 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 0.108 W/kg

**SAR(1 g) = 0.061 mW/g; SAR(10 g) = 0.032 mW/g**

Maximum value of SAR (measured) = 0.071 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 4 50RB High/Area Scan (101x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.055 mW/g


**Hotspot Right/LTE Band 4 50RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.32 V/m; Power Drift = -0.198 dB

Peak SAR (extrapolated) = 0.083 W/kg

**SAR(1 g) = 0.048 mW/g; SAR(10 g) = 0.026 mW/g**

Maximum value of SAR (measured) = 0.059 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1720 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1720$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 4 1RB Low/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.216 mW/g


**Hotspot Bottom/LTE Band 4 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.84 V/m; Power Drift = -0.158 dB

Peak SAR (extrapolated) = 0.325 W/kg

**SAR(1 g) = 0.170 mW/g; SAR(10 g) = 0.086 mW/g**

Maximum value of SAR (measured) = 0.206 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 1745 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1745$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 53.43$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN7382; ConvF(8.65, 8.65, 8.65); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 4 50RB High 2/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.157 mW/g


**Hotspot Bottom/LTE Band 4 50RB High 2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.86 V/m; Power Drift = -0.112 dB

Peak SAR (extrapolated) = 0.258 W/kg

**SAR(1 g) = 0.137 mW/g; SAR(10 g) = 0.069 mW/g**

Maximum value of SAR (measured) = 0.163 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 5 1RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.059 \text{ mW/g}$


**Left Cheek/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.61 \text{ V/m}$ ; Power Drift =  $0.074 \text{ dB}$

Peak SAR (extrapolated) =  $0.064 \text{ W/kg}$

**SAR(1 g) =  $0.057 \text{ mW/g}$ ; SAR(10 g) =  $0.047 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.060 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 5 50RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.047 \text{ mW/g}$


**Left Cheek/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $1.95 \text{ V/m}$ ; Power Drift =  $0.194 \text{ dB}$

Peak SAR (extrapolated) =  $0.051 \text{ W/kg}$

**SAR(1 g) =  $0.045 \text{ mW/g}$ ; SAR(10 g) =  $0.037 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.047 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 41.86$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 5 1RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.026 mW/g


**Left Tilt/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.52 V/m; Power Drift = 0.148 dB

Peak SAR (extrapolated) = 0.028 W/kg

**SAR(1 g) = 0.025 mW/g; SAR(10 g) = 0.021 mW/g**

Maximum value of SAR (measured) = 0.027 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 5 50RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.020 \text{ mW/g}$


**Left Tilt/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.08 \text{ V/m}$ ; Power Drift =  $0.131 \text{ dB}$

Peak SAR (extrapolated) =  $0.021 \text{ W/kg}$

**SAR(1 g) =  $0.020 \text{ mW/g}$ ; SAR(10 g) =  $0.017 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.021 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5$  MHz;  $\sigma = 0.92$  mho/m;  $\epsilon_r = 41.86$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 5 1RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.064 mW/g


**Right Cheek/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.94 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.073 W/kg

**SAR(1 g) = 0.058 mW/g; SAR(10 g) = 0.042 mW/g**

Maximum value of SAR (measured) = 0.062 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 5 50RB Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) =  $0.049 \text{ mW/g}$


**Right Cheek/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  
 $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.18 \text{ V/m}$ ; Power Drift =  $0.073 \text{ dB}$

Peak SAR (extrapolated) =  $0.055 \text{ W/kg}$

**SAR(1 g) =  $0.046 \text{ mW/g}$ ; SAR(10 g) =  $0.033 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.049 \text{ mW/g}$





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 5 1RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.026 \text{ mW/g}$


**Right Tilt/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $3.12 \text{ V/m}$ ; Power Drift =  $0.026 \text{ dB}$

Peak SAR (extrapolated) =  $0.030 \text{ W/kg}$

**SAR(1 g) =  $0.026 \text{ mW/g}$ ; SAR(10 g) =  $0.021 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.026 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.92 \text{ mho/m}$ ;  $\epsilon_r = 41.86$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.50, 10.50, 10.50); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 5 50RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.022 \text{ mW/g}$


**Right Tilt/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.92 \text{ V/m}$ ; Power Drift =  $0.168 \text{ dB}$

Peak SAR (extrapolated) =  $0.022 \text{ W/kg}$

**SAR(1 g) =  $0.020 \text{ mW/g}$ ; SAR(10 g) =  $0.016 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.022 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 5 1RB Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) =  $0.162 \text{ mW/g}$


**Hotspot Back/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $12.9 \text{ V/m}$ ; Power Drift =  $-0.026 \text{ dB}$

Peak SAR (extrapolated) =  $0.208 \text{ W/kg}$

**SAR(1 g) =  $0.151 \text{ mW/g}$ ; SAR(10 g) =  $0.106 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.161 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 5 50RB Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.129 \text{ mW/g}$

**Hotspot Back/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,


$dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $11.4 \text{ V/m}$ ; Power Drift =  $-0.186 \text{ dB}$

Peak SAR (extrapolated) =  $0.151 \text{ W/kg}$

**SAR(1 g) =  $0.112 \text{ mW/g}$ ; SAR(10 g) =  $0.079 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.120 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 5 1RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.025 \text{ mW/g}$


**Hotspot Right/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $4.57 \text{ V/m}$ ; Power Drift =  $0.065 \text{ dB}$

Peak SAR (extrapolated) =  $0.031 \text{ W/kg}$

**SAR(1 g) =  $0.024 \text{ mW/g}$ ; SAR(10 g) =  $0.018 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.026 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 5 50RB Mid/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.021 \text{ mW/g}$


**Hotspot Right/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $4.12 \text{ V/m}$ ; Power Drift =  $-0.025 \text{ dB}$

Peak SAR (extrapolated) =  $0.028 \text{ W/kg}$

**SAR(1 g) =  $0.020 \text{ mW/g}$ ; SAR(10 g) =  $0.015 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.022 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 5 1RB Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) = 0.133 mW/g


**Hotspot Bottom/LTE Band 5 1RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  
 $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 11.3 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 0.182 W/kg

**SAR(1 g) = 0.110 mW/g; SAR(10 g) = 0.063 mW/g**

Maximum value of SAR (measured) = 0.123 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 836.5 \text{ MHz}$ ;  $\sigma = 0.96 \text{ mho/m}$ ;  $\epsilon_r = 55.47$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.54, 10.54, 10.54); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 5 50RB Mid/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) = 0.101 mW/g


**Hotspot Bottom/LTE Band 5 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 9.84 V/m; Power Drift = 0.121 dB

Peak SAR (extrapolated) = 0.141 W/kg

**SAR(1 g) = 0.088 mW/g; SAR(10 g) = 0.050 mW/g**

Maximum value of SAR (measured) = 0.099 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 39.52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 7 1RB High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.024 mW/g


**Left Cheek/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.68 V/m; Power Drift = -0.013 dB

Peak SAR (extrapolated) = 0.024 W/kg

**SAR(1 g) = 0.017 mW/g; SAR(10 g) = 0.010 mW/g**

Maximum value of SAR (measured) = 0.024 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 1.9$  mho/m;  $\epsilon_r = 39.31$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 7 50RB Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.032 mW/g


**Left Cheek/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.78 V/m; Power Drift = 0.079 dB

Peak SAR (extrapolated) = 0.062 W/kg

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00425 mW/g**

Maximum value of SAR (measured) = 0.031 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 39.52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 7 1RB High/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.021 mW/g


**Left Tilt/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.89 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 0.050 W/kg

**SAR(1 g) = 0.016 mW/g; SAR(10 g) = 0.00439 mW/g**

Maximum value of SAR (measured) = 0.024 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 1.9$  mho/m;  $\epsilon_r = 39.31$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 7 50RB Mid/Area Scan (91x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.030 mW/g


**Left Tilt/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.62 V/m; Power Drift = -0.096 dB

Peak SAR (extrapolated) = 0.041 W/kg

**SAR(1 g) = 0.00905 mW/g; SAR(10 g) = 0.00324 mW/g**

Maximum value of SAR (measured) = 0.021 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 39.52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 7 1RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.024 mW/g

**Right Cheek/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 1.61 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 0.090 W/kg

**SAR(1 g) = 0.026 mW/g; SAR(10 g) = 0.015 mW/g**

Maximum value of SAR (measured) = 0.026 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 1.9$  mho/m;  $\epsilon_r = 39.31$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 7 50RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.023 mW/g

**Right Cheek/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm,


dy=5mm, dz=5mm

Reference Value = 1.78 V/m; Power Drift = 0.066 dB

Peak SAR (extrapolated) = 0.055 W/kg

**SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.00983 mW/g**

Maximum value of SAR (measured) = 0.023 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 39.52$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 7 1RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.028 mW/g


**Right Tilt/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.57 V/m; Power Drift = -0.079 dB

Peak SAR (extrapolated) = 0.019 W/kg

**SAR(1 g) = 0.00225 mW/g; SAR(10 g) = 0.00103 mW/g**

Maximum value of SAR (measured) = 0.015 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 1.9$  mho/m;  $\epsilon_r = 39.31$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.48, 7.48, 7.48); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 7 50RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.022 mW/g


**Right Tilt/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.51 V/m; Power Drift = 0.142 dB

Peak SAR (extrapolated) = 0.028 W/kg

**SAR(1 g) = 0.00542 mW/g; SAR(10 g) = 0.0012 mW/g**

Maximum value of SAR (measured) = 0.020 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 2.19$  mho/m;  $\epsilon_r = 52.85$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.59, 7.59, 7.59); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 7 1RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.055 mW/g


**Hotspot Back/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.09 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 0.080 W/kg

**SAR(1 g) = 0.031 mW/g; SAR(10 g) = 0.017 mW/g**

Maximum value of SAR (measured) = 0.036 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 2.12$  mho/m;  $\epsilon_r = 54.11$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.59, 7.59, 7.59); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 7 50RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.039 mW/g


**Hotspot Back/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.12 V/m; Power Drift = -0.076 dB

Peak SAR (extrapolated) = 0.053 W/kg

**SAR(1 g) = 0.013 mW/g; SAR(10 g) = 0.00557 mW/g**

Maximum value of SAR (measured) = 0.028 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 2.19$  mho/m;  $\epsilon_r = 52.85$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.59, 7.59, 7.59); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 7 1RB High/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.015 mW/g


**Hotspot Right/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.49 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.042 W/kg

**SAR(1 g) = 0.00632 mW/g; SAR(10 g) = 0.0022 mW/g**

Maximum value of SAR (measured) = 0.014 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 2.12$  mho/m;  $\epsilon_r = 54.11$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.59, 7.59, 7.59); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Right/LTE Band 7 50RB Mid/Area Scan (101x121x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.014 mW/g


**Hotspot Right/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.11 V/m; Power Drift = 0.136 dB

Peak SAR (extrapolated) = 0.046 W/kg

**SAR(1 g) = 0.00672 mW/g; SAR(10 g) = 0.0023 mW/g**

Maximum value of SAR (measured) = 0.017 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 2.19$  mho/m;  $\epsilon_r = 52.85$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.59, 7.59, 7.59); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 7 1RB High/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.031 mW/g


**Hotspot Bottom/LTE Band 7 1RB High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.54 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.061 W/kg

**SAR(1 g) = 0.025 mW/g; SAR(10 g) = 0.014 mW/g**

Maximum value of SAR (measured) = 0.028 mW/g



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2535$  MHz;  $\sigma = 2.12$  mho/m;  $\epsilon_r = 54.11$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(7.59, 7.59, 7.59); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 7 50RB Mid/Area Scan (91x101x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.021 mW/g


**Hotspot Bottom/LTE Band 7 50RB Mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.58 V/m; Power Drift = 0.024 dB

Peak SAR (extrapolated) = 0.094 W/kg

**SAR(1 g) = 0.020 mW/g; SAR(10 g) = 0.012 mW/g**

Maximum value of SAR (measured) = 0.023 mW/g





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 17 1RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.044 \text{ mW/g}$


**Left Cheek/LTE Band 17 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $1.54 \text{ V/m}$ ; Power Drift =  $0.077 \text{ dB}$

Peak SAR (extrapolated) =  $0.046 \text{ W/kg}$

**SAR(1 g) =  $0.040 \text{ mW/g}$ ; SAR(10 g) =  $0.033 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.042 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Cheek/LTE Band 17 50RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.059 \text{ mW/g}$

**Left Cheek/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,


$dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.48 \text{ V/m}$ ; Power Drift =  $0.130 \text{ dB}$

Peak SAR (extrapolated) =  $0.061 \text{ W/kg}$

**SAR(1 g) =  $0.055 \text{ mW/g}$ ; SAR(10 g) =  $0.046 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.057 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 17 1RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.019 \text{ mW/g}$


**Left Tilt/LTE Band 17 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $1.72 \text{ V/m}$ ; Power Drift =  $0.042 \text{ dB}$

Peak SAR (extrapolated) =  $0.021 \text{ W/kg}$

**SAR(1 g) =  $0.019 \text{ mW/g}$ ; SAR(10 g) =  $0.016 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.020 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Left Tilt/LTE Band 17 50RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.028 \text{ mW/g}$


**Left Tilt/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.69 \text{ V/m}$ ; Power Drift =  $0.118 \text{ dB}$

Peak SAR (extrapolated) =  $0.030 \text{ W/kg}$

**SAR(1 g) =  $0.027 \text{ mW/g}$ ; SAR(10 g) =  $0.023 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.028 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 17 1RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) =  $0.044 \text{ mW/g}$


**Right Cheek/LTE Band 17 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  
 $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $1.55 \text{ V/m}$ ; Power Drift =  $0.088 \text{ dB}$

Peak SAR (extrapolated) =  $0.048 \text{ W/kg}$

**SAR(1 g) =  $0.041 \text{ mW/g}$ ; SAR(10 g) =  $0.031 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.042 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Cheek/LTE Band 17 50RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.060 \text{ mW/g}$


**Right Cheek/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.15 \text{ V/m}$ ; Power Drift =  $0.058 \text{ dB}$

Peak SAR (extrapolated) =  $0.066 \text{ W/kg}$

**SAR(1 g) =  $0.056 \text{ mW/g}$ ; SAR(10 g) =  $0.043 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.059 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 17 1RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.022 \text{ mW/g}$


**Right Tilt/LTE Band 17 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.25 \text{ V/m}$ ; Power Drift =  $0.139 \text{ dB}$

Peak SAR (extrapolated) =  $0.021 \text{ W/kg}$

**SAR(1 g) =  $0.020 \text{ mW/g}$ ; SAR(10 g) =  $0.017 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.021 \text{ mW/g}$





**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.90 \text{ mho/m}$ ;  $\epsilon_r = 43.05$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(11.04, 11.04, 11.04); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Right Tilt/LTE Band 17 50RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.029 \text{ mW/g}$


**Right Tilt/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $2.72 \text{ V/m}$ ; Power Drift =  $0.200 \text{ dB}$

Peak SAR (extrapolated) =  $0.031 \text{ W/kg}$

**SAR(1 g) =  $0.029 \text{ mW/g}$ ; SAR(10 g) =  $0.024 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.030 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.94, 10.94, 10.94); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 17 1RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.139 \text{ mW/g}$


**Hotspot Back/LTE Band 17 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $9.97 \text{ V/m}$ ; Power Drift =  $0.062 \text{ dB}$

Peak SAR (extrapolated) =  $0.180 \text{ W/kg}$

**SAR(1 g) =  $0.129 \text{ mW/g}$ ; SAR(10 g) =  $0.091 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.136 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.94, 10.94, 10.94); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Back/LTE Band 17 50RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.110 \text{ mW/g}$


**Hotspot Back/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $10.8 \text{ V/m}$ ; Power Drift =  $-0.174 \text{ dB}$

Peak SAR (extrapolated) =  $0.139 \text{ W/kg}$

**SAR(1 g) =  $0.102 \text{ mW/g}$ ; SAR(10 g) =  $0.072 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.109 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.94, 10.94, 10.94); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Body right/LTE Band 17 Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.040 \text{ mW/g}$


**Body right/LTE Band 17 Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $6.11 \text{ V/m}$ ; Power Drift =  $-0.103 \text{ dB}$

Peak SAR (extrapolated) =  $0.049 \text{ W/kg}$

**SAR(1 g) =  $0.038 \text{ mW/g}$ ; SAR(10 g) =  $0.028 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.041 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.94, 10.94, 10.94); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Body right/LTE Band 17 50RB Low/Area Scan (101x121x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.027 \text{ mW/g}$

**Body right/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,


$dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $4.60 \text{ V/m}$ ; Power Drift =  $0.061 \text{ dB}$

Peak SAR (extrapolated) =  $0.031 \text{ W/kg}$

**SAR(1 g) =  $0.025 \text{ mW/g}$ ; SAR(10 g) =  $0.018 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.026 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.94, 10.94, 10.94); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 17 1RB Low/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.050 \text{ mW/g}$


**Hotspot Bottom/LTE Band 17 1RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $7.72 \text{ V/m}$ ; Power Drift =  $-0.148 \text{ dB}$

Peak SAR (extrapolated) =  $0.063 \text{ W/kg}$

**SAR(1 g) =  $0.038 \text{ mW/g}$ ; SAR(10 g) =  $0.023 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.042 \text{ mW/g}$



**DUT: Smartphone with 4G (voice), GPS and BT; Type: Smartphone 6.2 Lite;**

Communication System: 4G Bands; Frequency: 709 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 709 \text{ MHz}$ ;  $\sigma = 0.97 \text{ mho/m}$ ;  $\epsilon_r = 56.71$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 – SN7382; ConvF(10.94, 10.94, 10.94); Calibrated: 26/10/2016
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

**Hotspot Bottom/LTE Band 17 50RB Low/Area Scan (91x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $0.056 \text{ mW/g}$

**Hotspot Bottom/LTE Band 17 50RB Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $7.25 \text{ V/m}$ ; Power Drift =  $0.167 \text{ dB}$

Peak SAR (extrapolated) =  $0.077 \text{ W/kg}$

**SAR(1 g) =  $0.049 \text{ mW/g}$ ; SAR(10 g) =  $0.029 \text{ mW/g}$**

Maximum value of SAR (measured) =  $0.055 \text{ mW/g}$

