

FCC TEST REPORT

for

Ittim Technology Co.,Ltd.

WIFI Module

Model Number: ITM-UB12-S06PXX0000NV2

FCC ID: 2AEU8UB12

Prepared for : Ittim Technology Co.,Ltd.
Address : Bldg A2, No.6th Fuqiao Industry Area, Qiaotou Community,
Fuyong, Bao'an district, Shenzhen, China

Prepared by : Keyway Testing Technology Co., Ltd.
Address : Baishun Industrial Zone, Zhangmutou Town,
Dongguan, Guangdong, China

Report No. : 15KWE052579R
Date of Test : May 14~19, 2015
Date of Report : May 20, 2015

TABLE OF CONTENTS

Test Report Declaration	Page
1. TEST SUMMARY	4
2. GENERAL PRODUCT INFORMATION	4
2.1. Product Function	4
2.2. Description of Device (EUT)	4
2.3. Independent Operation Modes	5
2.4. Test Supporting System	5
3. TEST SITES	6
3.1. Test Facilities	6
3.2. List of Test and Measurement Instruments	7
4. TEST SET-UP AND OPERATION MODES	8
4.1. Principle of Configuration Selection	8
4.2. Block Diagram of Test Set-up	8
4.3. Test Operation Mode and Test Software	8
4.4. Special Accessories and Auxiliary Equipment	8
4.5. Countermeasures to Achieve EMC Compliance	8
4.6. Test Environment	8
5. EMISSION TEST RESULTS	9
5.1. Radiated Emission Test	9
6. 6DB OCCUPY BANDWIDTH	24
6.1. Limits	24
6.2. Test setup	24
6.3. Test result	24
7. BAND EDGE COMPLIANCE TEST	31
7.1. Limits	31
7.2. Test setup	31
8. OUTPUT POWER TEST	33
8.1. Limits	33
8.2. Test setup	33
8.3. Test result	33
9. POWER SPECTRAL DENSITY TEST	34
9.1. Limits	34
9.2. Test setup	34
9.3. Test result	34
10. ANTENNA REQUIREMENTS	37
10.1. Limits	37
10.2. Result	37
11. PHOTOGRAPHS OF THE EUT	38

Keyway Testing Technology Co., Ltd.

Applicant:	Ittim Technology Co.,Ltd.		
Address:	Bldg A2,No.6th Fuqiao Industry Area,Qiaotou Community, Fuyong,Bao'an district,Shenzhen,China		
Manufacturer:	Ittim Technology Co.,Ltd.		
Address:	Bldg A2,No.6th Fuqiao Industry Area,Qiaotou Community, Fuyong,Bao'an district,Shenzhen,China		
E.U.T:	WIFI Module		
Model Number:	ITM-UB12-S06PXX0000NV2		
Trade Name:	-----	Serial No.:	-----
Date of Receipt:	May 14, 2015	Date of Test:	May 14~19, 2015
Test Specification:	FCC Part 15, Subpart C Section 15.247: 2014 ANSI C63.4:2009 KDB558074 D01 DTS Meas Guidance v03r02		
Test Result:	The equipment under test was found to be compliance with the requirements of the standards applied.		
Issue Date: May 20, 2015			
Tested by:	Reviewed by:	Approved by:	
 <hr style="width: 100%;"/>	 <hr style="width: 100%;"/>	 <hr style="width: 100%;"/>	
Daisy/ Engineer	Andy Gao / Supervisor	Jade Yang/ Supervisor	
Other Aspects:	None.		
<i>Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested</i>			
<i>This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Keyway Testing Technology Co., Ltd.</i>			

1.TEST SUMMARY

Test Items	Test Requirement	Result
Conducted Emissions	15.207	N/A
Radiated Emissions	15.205(a)15.209 15.247(d)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Power density	15.247(e)	PASS
Maximum Peak Output Power	15.247(b)(3)	PASS
Emissions from out of band	15.247(d)	PASS
Antenna Requirement	15.203	PASS

2.GENERAL PRODUCT INFORMATION

2.1. Product Function

Refer to Technical Construction Form and User Manual.

2.2. Description of Device (EUT)

Product Name:	WIFI Module
Model No.:	ITM-UB12-S06PXX0000NV2
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20)) 2422MHz~2452MHz (802.11n(H40))
Channel numbers:	WIFI: 11 for 802.11b/802.11g/802.11n(H20) , 7 for 802.11n(H40)
Channel separation:	WIFI : 5MHz
Modulation technology:	WIFI: Direct Sequence Spread Spectrum (DSSS) for 802.11b Orthogonal Frequency Division Multiplexing(OFDM) for 802.11g/n
Data rate:	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps 802.11n: Up to 150Mbps
Antenna Type:	Chip Antenna
Antenna gain:	0dBi (declare by Applicant)
Power supply:	DC 3.3V

2.3. Independent Operation Modes

The basic operation modes are:

2.3.1. EUT work continues TX mode and frequency as below:

	Channel	Frequency
802.11b	Low	2412MHz
	Middle	2437MHz
	High	2462MHz
802.11g	Low	2412MHz
	Middle	2437MHz
	High	2462MHz
802.11n(HT20)	Low	2412MHz
	Middle	2437MHz
	High	2462MHz
802.11 n(HT40)	Low	2422MHz
	Middle	2437MHz
	High	2452MHz

Remark: According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup” 11MHz for 802.11b, 6MHz for 802.11g, 13Mbps for 802.11n(H20), 54Mbps for 802.11n(H40).

2.4. Test Supporting System

Decoding board

M/N: UBXX&IOEXX DVB

Notebook:

Manufacturer: Lenovo
M/N: Lenovo G475
S/N: GB14477457

3. TEST SITES

3.1. Test Facilities

Lab Qualifications : 944 Shielded Room built by ETS-Lindgren, USA
Date of completion: March 28, 2011

966 Chamber built by ETS-Lindgren, USA
Date of completion: March 28, 2011

Certificated by TUV Rheinland, Germany.
Registration No.: UA 50207153
Date of registration: July 13, 2011

Certificated by UL, USA
Registration No.: 100567-237
Date of registration: September 1, 2011

Certificated by Intertek
Registration No.: 2011-RTL-L1-31
Date of registration: October 11, 2011

Certificated by Industry Canada
Registration No.: 9868A
Date of registration: December 8, 2011

Certificated by FCC, USA
Registration No.: 370994
Date of registration: February 21, 2012

Certificated by CNAS China
Registration No.: CNAS L5783
Date of registration: August 8, 2012

Name of Firm : Keyway Testing Technology Co., Ltd.

Site Location : Baishun Industrial Zone, Zhangmutou Town,
Dongguan, Guangdong, China

3.2. List of Test and Measurement Instruments

3.2.1. For radiated emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 27,15	Apr. 27,16
System Simulator	Agilent	E5515C	GB43130245	Apr. 30,15	Apr. 30,16
Power Splitter	Weinschel	1506A	NW425	Apr. 30,15	Apr. 30,16
Bilog Antenna	ETS-LINDGREEN	3142D	135452	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	Agilent	E4411B	MY4511304	Apr. 27,15	Apr. 27,16
3m Semi-anechoic Chamber	ETS-LINDGREEN	966	KW01	Apr. 27,15	Apr. 27,16
Signal WIFI Module	SONOMA	310	187016	Apr. 27,15	Apr. 27,16
Signal WIFI Module	Agilent	8449B	3008A00251	Apr. 27,15	Apr. 27,16
RF Cable	IMRO	IMRO-400	966 Cable 1#	N/A	N/A
MULTI-DEVICE Controller	ETS-LINDGREEN	2090	126913	N/A	N/A
Horn Antenna	DAZE	ZN30701	11003	Apr. 27,15	Apr. 27,16
Horn Antenna	SCHWARZBECK	BBHA9170	9170-068	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	Agilent	8593E	3911A04271	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	Agilent	E4408B	MY44211125	Apr. 30,15	Apr. 30,16
Signal WIFI Module	DAZE	ZN3380C	11001	Apr. 27,15	Apr. 27,16
High Pass filter	Micro	HPM50111	324216	Apr. 30,15	Apr. 30,16
Filter	COM-MW	ZBSF-C836.5-25-X	KW032	Apr. 30,15	Apr. 30,16
Filter	COM-MW	ZBSF-C1747.5-75-X2	KW035	Apr. 30,15	Apr. 30,16
Filter	COM-MW	ZBSF-C1880-60-X2	KW037	Apr. 30,15	Apr. 30,16
DC Power Supply	LongWei	PS-305D	010964729	Apr. 27,15	Apr. 27,16
Constant temperature and humidity box	GF	GTH-800-40-1P	MAA9906-005	Apr. 27,15	Apr. 27,16
Universal radio communication tester	Rohde&Schwarz	CMU200	3215420	Apr. 27,15	Apr. 27,16
Splitter	Agilent	11636B	0025164	Apr. 27,15	Apr. 27,16

4. TEST SET-UP AND OPERATION MODES

4.1. Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

4.2. Block Diagram of Test Set-up

Please see item 11.

4.3. Test Operation Mode and Test Software

None.

4.4. Special Accessories and Auxiliary Equipment

None.

4.5. Countermeasures to Achieve EMC Compliance

None.

4.6. Test Environment:

Ambient conditions in the test laboratory:

Items	Actual
Temperature (°C)	21~23
Humidity (%RH)	50~65

5. EMISSION TEST RESULTS

5.1. Radiated Emission Test

5.1.1. Limit 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

5.1.2. Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

5.1.3. Test setup

The EUT was placed on a turn table which was 0.8 m above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 m away from the receiving antenna which was mounted on an antenna tower. The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 m to 4 m for both horizontal and vertical polarizations.

The EUT was tested in the Chamber Site. It was pre-scanned with a Peak detector from the spectrum, and all the final readings from the test receiver were measured with the Quasi-Peak detector.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz. For all test, used peak detector.


The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

Notes: 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading-Preamp Factor.

2. Measurement Uncertainty: ± 3.2 dB at a level of confidence of 95%.


3. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

4. For emissions below 1GHz, pretest for all mode, The test data of the worst case condition(s) was reported on the following pages.




Test Data Below 1GHz

WIFI Mode Horizontal polarizations



	Preamp Freq	Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	30.00	31.41	28.18	0.56	16.13	40.00	-23.87	QP
2	41.64	31.38	39.83	0.56	21.24	40.00	-18.76	QP
3	47.46	31.39	39.44	0.75	18.64	40.00	-21.36	QP
4	86.26	31.35	32.23	0.94	10.51	40.00	-29.49	QP
5	196.84	31.11	31.03	1.46	12.10	43.50	-31.40	QP
6	224.00	30.95	32.53	1.53	15.26	46.00	-30.74	QP

WIFI Mode Vertical polarizations



	Preamp	Read	Cable		Limit	Over	
	Freq	Factor	Level	Loss	Line	Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB
1	41.64	31.38	42.93	0.56	24.34	40.00	-15.66 QP
2	47.46	31.39	41.04	0.75	20.24	40.00	-19.76 QP
3	83.35	31.35	42.62	0.94	20.58	40.00	-19.42 QP
4	183.26	31.15	32.33	1.39	12.87	43.50	-30.63 QP
5	224.00	30.95	34.43	1.53	17.16	46.00	-28.84 QP
6	248.25	30.96	34.13	1.70	17.72	46.00	-28.28 QP

Above 1GHz

Test mode: 802.11b 2412MHz

Polarization: HORIZONTAL

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	32.38	12.01	32.99	49.88	74.00	-24.12	Peak
2	7236.00	27.95	23.52	16.61	37.30	49.48	74.00	-24.52	Peak
3	9772.00	28.71	17.18	16.94	38.22	43.63	74.00	-30.37	Peak
4	11829.00	28.98	17.04	17.33	39.57	44.96	74.00	-29.04	Peak
5	13699.00	29.34	11.42	19.02	43.20	44.30	74.00	-29.70	Peak
6	16606.00	29.94	12.59	21.04	43.65	47.34	74.00	-26.66	Peak

Test mode: 802.11b 2412MHz

Polarization: VERTICAL

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	32.07	12.01	32.99	49.57	74.00	-24.43	Peak
2	7236.00	27.95	23.55	16.61	37.30	49.51	74.00	-24.49	Peak
3	9007.00	28.40	22.95	16.88	37.40	48.83	74.00	-25.17	Peak
4	9993.00	28.80	20.18	16.97	38.40	46.75	74.00	-27.25	Peak
5	13410.00	29.28	15.26	18.69	42.60	47.27	74.00	-26.73	Peak
6	14634.00	29.49	16.36	19.77	40.04	46.68	74.00	-27.32	Peak

Test mode: 802.11b 2437MHz

Polarization: HORIZONTAL

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.91	12.14	33.11	49.63	74.00	-24.37	Peak
2	7311.00	27.96	22.66	16.62	37.32	48.64	74.00	-25.36	Peak
3	9194.00	28.48	18.68	16.89	37.63	44.72	74.00	-29.28	Peak
4	11081.00	28.91	15.36	17.18	39.57	43.20	74.00	-30.80	Peak
5	13903.00	29.38	10.88	19.24	43.40	44.14	74.00	-29.86	Peak
6	15705.00	29.66	15.24	20.44	39.19	45.21	74.00	-28.79	Peak

Test mode: 802.11b 2437MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	32.15	12.14	33.11	49.87	74.00	-24.13	Peak
2	7311.00	27.96	23.14	16.62	37.32	49.12	74.00	-24.88	Peak
3	8922.00	28.37	19.99	16.86	37.30	45.78	74.00	-28.22	Peak
4	10622.00	28.86	19.79	17.09	39.27	47.29	74.00	-26.71	Peak
5	13495.00	29.30	16.47	18.77	43.00	48.94	74.00	-25.06	Peak
6	15671.00	29.65	16.64	20.42	39.06	46.47	74.00	-27.53	Peak

Test mode: 802.11b 2462MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.40	12.28	33.23	49.35	74.00	-24.65	Peak
2	7386.00	27.98	23.12	16.62	37.36	49.12	74.00	-24.88	Peak
3	9704.00	28.68	16.03	16.94	38.17	42.46	74.00	-31.54	Peak
4	10911.00	28.89	16.97	17.15	39.45	44.68	74.00	-29.32	Peak
5	14022.00	29.40	12.15	19.38	43.40	45.53	74.00	-28.47	Peak
6	15654.00	29.65	15.80	20.42	38.99	45.56	74.00	-28.44	Peak

Test mode: 802.11b 2462MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.27	12.28	33.23	49.22	74.00	-24.78	Peak
2	7386.00	27.98	23.31	16.62	37.36	49.31	74.00	-24.69	Peak
3	8497.00	28.25	18.63	16.76	36.80	43.94	74.00	-30.06	Peak
4	10486.00	28.85	15.66	17.06	39.17	43.04	74.00	-30.96	Peak
5	13053.00	29.21	13.00	18.28	40.94	43.01	74.00	-30.99	Peak
6	15212.00	29.58	16.37	20.13	38.46	45.38	74.00	-28.62	Peak

Test mode: 802.11g 2412MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	32.11	12.01	32.99	49.61	74.00	-24.39	Peak
2	7236.00	27.95	23.17	16.61	37.30	49.13	74.00	-24.87	Peak
3	8463.00	28.24	20.16	16.76	36.77	45.45	74.00	-28.55	Peak
4	10078.00	28.81	19.27	16.98	38.53	45.97	74.00	-28.03	Peak
5	12781.00	29.16	16.50	18.03	40.18	45.55	74.00	-28.45	Peak
6	15144.00	29.57	14.15	20.09	38.47	43.14	74.00	-30.86	Peak

Test mode: 802.11g 2412MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	32.47	12.01	32.99	49.97	74.00	-24.03	Peak
2	7236.00	27.95	22.73	16.61	37.30	48.69	74.00	-25.31	Peak
3	8939.00	28.38	19.91	16.87	37.32	45.72	74.00	-28.28	Peak
4	11387.00	28.94	17.96	17.24	39.81	46.07	74.00	-27.93	Peak
5	13291.00	29.26	14.32	18.54	42.05	45.65	74.00	-28.35	Peak
6	15076.00	29.56	18.59	20.04	38.49	47.56	74.00	-26.44	Peak

Test mode: 802.11g 2437MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.95	12.14	33.11	49.67	74.00	-24.33	Peak
2	7311.00	27.96	23.04	16.62	37.32	49.02	74.00	-24.98	Peak
3	8633.00	28.29	21.63	16.80	36.96	47.10	74.00	-26.90	Peak
4	10486.00	28.85	18.53	17.06	39.17	45.91	74.00	-28.09	Peak
5	12322.00	29.06	18.99	17.64	39.47	47.04	74.00	-26.96	Peak
6	14583.00	29.49	16.79	19.73	40.25	47.28	74.00	-26.72	Peak

Test mode: 802.11g 2437MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	32.25	12.14	33.11	49.97	74.00	-24.03	Peak
2	7311.00	27.96	23.07	16.62	37.32	49.05	74.00	-24.95	Peak
3	9500.00	28.60	19.56	16.92	38.00	45.88	74.00	-28.12	Peak
4	11744.00	28.97	18.59	17.31	39.66	46.59	74.00	-27.41	Peak
5	14192.00	29.43	13.96	19.48	42.40	46.41	74.00	-27.59	Peak
6	15722.00	29.66	15.36	20.45	39.25	45.40	74.00	-28.60	Peak

Test mode: 802.11g 2462MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.68	12.28	33.23	49.63	74.00	-24.37	Peak
2	7386.00	27.98	22.64	16.62	37.36	48.64	74.00	-25.36	Peak
3	8973.00	28.39	21.89	16.87	37.36	47.73	74.00	-26.27	Peak
4	10503.00	28.85	19.79	17.07	39.20	47.21	74.00	-26.79	Peak
5	12764.00	29.15	16.72	18.02	40.14	45.73	74.00	-28.27	Peak
6	15127.00	29.57	16.50	20.08	38.48	45.49	74.00	-28.51	Peak

Test mode: 802.11g 2462MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.02	12.28	33.23	48.97	74.00	-25.03	Peak
2	7386.00	27.98	22.98	16.62	37.36	48.98	74.00	-25.02	Peak
3	9517.00	28.61	16.39	16.92	38.01	42.71	74.00	-31.29	Peak
4	11489.00	28.95	14.40	17.26	39.89	42.60	74.00	-31.40	Peak
5	14141.00	29.42	10.54	19.45	42.70	43.27	74.00	-30.73	Peak
6	16521.00	29.91	9.96	21.00	43.44	44.49	74.00	-29.51	Peak

Test mode: 802.11n(HT20) 2412MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	31.17	12.01	32.99	48.67	74.00	-25.33	Peak
2	7236.00	27.95	23.39	16.61	37.30	49.35	74.00	-24.65	Peak
3	8769.00	28.33	18.50	16.83	37.12	44.12	74.00	-29.88	Peak
4	10894.00	28.89	17.64	17.15	39.44	45.34	74.00	-28.66	Peak
5	13325.00	29.26	13.46	18.59	42.21	45.00	74.00	-29.00	Peak
6	14345.00	29.45	13.91	19.59	41.50	45.55	74.00	-28.45	Peak

Test mode: 802.11n(HT20) 2412MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	31.17	12.01	32.99	48.67	74.00	-25.33	Peak
2	7236.00	27.95	22.63	16.61	37.30	48.59	74.00	-25.41	Peak
3	8497.00	28.25	19.29	16.76	36.80	44.60	74.00	-29.40	Peak
4	10571.00	28.86	17.90	17.08	39.24	45.36	74.00	-28.64	Peak
5	13410.00	29.28	12.35	18.69	42.60	44.36	74.00	-29.64	Peak
6	15348.00	29.60	16.96	20.23	38.43	46.02	74.00	-27.98	Peak

Test mode: 802.11n(HT20) 2437MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.20	12.14	33.11	48.92	74.00	-25.08	Peak
2	7311.00	27.96	22.20	16.62	37.32	48.18	74.00	-25.82	Peak
3	9364.00	28.54	18.09	16.91	37.83	44.29	74.00	-29.71	Peak
4	11319.00	28.93	18.20	17.23	39.75	46.25	74.00	-27.75	Peak
5	12883.00	29.18	12.87	18.11	40.42	42.22	74.00	-31.78	Peak
6	15331.00	29.60	15.95	20.21	38.43	44.99	74.00	-29.01	Peak

Test mode: 802.11n(HT20) 2437MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.40	12.14	33.11	49.12	74.00	-24.88	Peak
2	7311.00	27.96	22.35	16.62	37.32	48.33	74.00	-25.67	Peak
3	8854.00	28.35	16.87	16.85	37.22	42.59	74.00	-31.41	Peak
4	11200.00	28.92	17.13	17.21	39.66	45.08	74.00	-28.92	Peak
5	13121.00	29.22	14.40	18.36	41.26	44.80	74.00	-29.20	Peak
6	14940.00	29.54	16.66	19.96	38.78	45.86	74.00	-28.14	Peak

Test mode: 802.11n(HT20) 2462MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.36	12.28	33.23	49.31	74.00	-24.69	Peak
2	7386.00	27.98	22.05	16.62	37.36	48.05	74.00	-25.95	Peak
3	9534.00	28.61	14.87	16.92	38.03	41.21	74.00	-32.79	Peak
4	11081.00	28.91	15.85	17.18	39.57	43.69	74.00	-30.31	Peak
5	14090.00	29.41	11.99	19.43	43.00	45.01	74.00	-28.99	Peak
6	15416.00	29.61	14.28	20.26	38.42	43.35	74.00	-30.65	Peak

Test mode: 802.11n(HT20) 2462MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	30.17	12.28	33.23	48.12	74.00	-25.88	Peak
2	7386.00	27.98	22.34	16.62	37.36	48.34	74.00	-25.66	Peak
3	9075.00	28.43	15.78	16.88	37.48	41.71	74.00	-32.29	Peak
4	11574.00	28.96	13.68	17.28	39.83	41.83	74.00	-32.17	Peak
5	13818.00	29.36	7.97	19.14	43.32	41.07	74.00	-32.93	Peak
6	14770.00	29.52	11.77	19.85	39.48	41.58	74.00	-32.42	Peak

Test mode: 802.11n(HT40) 2422MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4844.00	27.51	31.10	12.05	33.03	48.67	74.00	-25.33	Peak
2	7266.00	27.95	22.18	16.61	37.31	48.15	74.00	-25.85	Peak
3	9041.00	28.41	16.95	16.88	37.44	42.86	74.00	-31.14	Peak
4	10622.00	28.86	14.03	17.09	39.27	41.53	74.00	-32.47	Peak
5	12645.00	29.13	15.65	17.91	39.86	44.29	74.00	-29.71	Peak
6	14549.00	29.48	12.28	19.71	40.39	42.90	74.00	-31.10	Peak

Test mode: 802.11n(HT40) 2422MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4844.00	27.51	31.12	12.05	33.03	48.69	74.00	-25.31	Peak
2	7266.00	27.95	22.40	16.61	37.31	48.37	74.00	-25.63	Peak
3	9568.00	28.63	15.99	16.93	38.06	42.35	74.00	-31.65	Peak
4	11353.00	28.94	13.27	17.24	39.78	41.35	74.00	-32.65	Peak
5	13087.00	29.22	11.62	18.32	41.10	41.82	74.00	-32.18	Peak
6	15314.00	29.60	12.82	20.20	38.44	41.86	74.00	-32.14	Peak

Test mode: 802.11n(HT40) 2437MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	30.65	12.14	33.11	48.37	74.00	-25.63	Peak
2	7311.00	27.96	21.21	16.62	37.32	47.19	74.00	-26.81	Peak
3	9228.00	28.49	14.98	16.90	37.67	41.06	74.00	-32.94	Peak
4	11863.00	28.99	13.13	17.34	39.54	41.02	74.00	-32.98	Peak
5	14362.00	29.45	10.83	19.60	41.40	42.38	74.00	-31.62	Peak
6	16776.00	30.01	6.33	21.17	44.06	41.55	74.00	-32.45	Peak

Test mode: 802.11n(HT40) 2437MHz

Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.25	12.14	33.11	48.97	74.00	-25.03	Peak
2	7311.00	27.96	22.15	16.62	37.32	48.13	74.00	-25.87	Peak
3	9211.00	28.48	15.35	16.90	37.65	41.42	74.00	-32.58	Peak
4	10656.00	28.87	12.67	17.10	39.29	40.19	74.00	-33.81	Peak
5	12713.00	29.14	12.57	17.97	40.02	41.42	74.00	-32.58	Peak
6	14243.00	29.44	10.71	19.52	42.10	42.89	74.00	-31.11	Peak

Test mode: 802.11n(HT40) 2452MHz

Polarization: HORIZONTAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4904.00	27.55	30.38	12.23	33.19	48.25	74.00	-25.75	Peak
2	7356.00	27.97	21.35	16.62	37.34	47.34	74.00	-26.66	Peak
3	8871.00	28.36	11.99	16.85	37.24	37.72	74.00	-36.28	Peak
4	10418.00	28.84	13.26	17.05	39.07	40.54	74.00	-33.46	Peak
5	12968.00	29.19	12.72	18.18	40.62	42.33	74.00	-31.67	Peak
6	14991.00	29.55	14.24	20.00	38.57	43.26	74.00	-30.74	Peak

Test mode: 802.11n(HT40) 2452MHz



Polarization: VERTICAL

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4904.00	27.55	30.32	12.23	33.19	48.19	74.00	-25.81	Peak
2	7356.00	27.97	22.36	16.62	37.34	48.35	74.00	-25.65	Peak
3	9160.00	28.46	14.88	16.89	37.59	40.90	74.00	-33.10	Peak
4	10826.00	28.88	16.51	17.13	39.40	44.16	74.00	-29.84	Peak
5	13444.00	29.29	10.61	18.73	42.76	42.81	74.00	-31.19	Peak
6	15076.00	29.56	12.26	20.04	38.49	41.23	74.00	-32.77	Peak



For conducted test

All modes for 802.11b/g/n have tested, and the worst result 802.11b recorded as below.



802.11b 2412MHz



802.11b 2437MHz



802.11b 2462MHz



6. 6DB OCCUPY BANDWIDTH

6.1. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz Test data:

6.2. Test setup


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the RBW =100kHz.
3. Set the VBW = 300kHz
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Measure and record the result in the test report.

6.3. Test result


	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
802.11b	2412	10.194	>0.5	Pass
	2437	10.284	>0.5	Pass
	2462	10.218	>0.5	Pass
802.11g	2412	16.143	>0.5	Pass
	2437	16.128	>0.5	Pass
	2462	16.094	>0.5	Pass
802.11n(HT20)	2412	16.142	>0.5	Pass
	2437	16.121	>0.5	Pass
	2462	16.143	>0.5	Pass
802.11n(HT40)	2422	35.297	>0.5	Pass
	2437	35.274	>0.5	Pass
	2452	35.265	>0.5	Pass

Test plot as follows:


802.11b 2412MHz




802.11b 2437MHz




802.11b 2462MHz




802.11g 2412MHz




802.11g 2437MHz




802.11g 2462MHz




802.11n(HT20) 2412MHz




802.11n(HT20) 2437MHz




802.11n(HT20) 2462MHz




802.11n(HT40) 2422MHz



802.11n(HT40) 2437MHz



802.11n(HT40) 2452MHz



7. BAND EDGE COMPLIANCE TEST

7.1. Limits

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

7.2. Test setup

The EUT was placed on a turn table which was 0.8 m above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 m away from the receiving antenna which was mounted on an antenna tower. The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 m to 4 m for both horizontal and vertical polarizations.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure. For all test, used peak detector.

For radiated test as follows:

	Frequency (MHz)	Antenna polarization (H/V)	measuring result (dBuV/m)	Band edge Limit (dBuV/m)	
			PK	PK	AV
802.11b	<2400	H	50.24	74.00	54.00
	<2400	V	51.52	74.00	54.00
	>2483.5	H	52.42	74.00	54.00
	>2483.5	V	51.14	74.00	54.00
802.11g	<2400	H	52.78	74.00	54.00
	<2400	V	51.25	74.00	54.00
	>2483.5	H	52.62	74.00	54.00
	>2483.5	V	51.18	74.00	54.00
802.11n(HT20)	<2400	H	52.41	74.00	54.00
	<2400	V	51.27	74.00	54.00
	>2483.5	H	52.62	74.00	54.00
	>2483.5	V	51.52	74.00	54.00
802.11n(HT40)	<2400	H	52.73	74.00	54.00
	<2400	V	52.16	74.00	54.00
	>2483.5	H	51.58	74.00	54.00
	>2483.5	V	52.27	74.00	54.00

8. OUTPUT POWER TEST

8.1. Limits

For systems using digital modulation in the 2400~2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

8.2. Test setup

1. The Transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

8.3. Test result

	Channel Frequency (MHz)	Peak output Power(dBm)	Limit (dBm)	Result
802.11b	2412	14.90	30	Pass
	2437	14.59	30	Pass
	2462	14.38	30	Pass
802.11g	2412	12.57	30	Pass
	2437	12.40	30	Pass
	2462	12.46	30	Pass
802.11n(HT20)	2412	11.27	30	Pass
	2437	11.16	30	Pass
	2462	11.23	30	Pass
802.11n(HT40)	2422	10.28	30	Pass
	2437	10.19	30	Pass
	2452	10.23	30	Pass

9. POWER SPECTRAL DENSITY TEST

9.1. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.


9.2. Test setup

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW = 3kHz.
4. Set the VBW = 3 times RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.


9.3. Test result

	Channel Frequency (MHz)	Power density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	2412	-16.43	<8	Pass
	2437	-16.93	<8	Pass
	2462	-18.13	<8	Pass
802.11g	2412	-20.98	<8	Pass
	2437	-22.51	<8	Pass
	2462	-23.14	<8	Pass
802.11n (HT20)	2412	-22.94	<8	Pass
	2437	-23.38	<8	Pass
	2462	-22.52	<8	Pass
802.11n (HT40)	2422	-18.54	<8	Pass
	2437	-18.46	<8	Pass
	2452	-17.54	<8	Pass


802.11b 2412MHz




802.11b 2437MHz




802.11b 2462MHz




802.11g 2412MHz




802.11g 2437MHz




802.11g 2462MHz




802.11n(HT20) 2412MHz




802.11n(HT20) 2437MHz




802.11n(HT20) 2462MHz




802.11n(HT40) 2422MHz



802.11n(HT40) 2437MHz



802.11n(HT40) 2452MHz



10. ANTENNA REQUIREMENTS



10.1. Limits

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Result

The antennas used for this product is chip antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.

11. PHOTOGRAPHS OF THE EUT



END