



FCC RF EXPOSURE REPORT

FCC ID: 2AEUPBHASC041

Project No. : 1705154 Equipment : Ring

Model : Spotlight Cam Battery

Series Model: N/A

Applicant: Bot Home Automation, Inc.

Address: 1523 26th St, Santa Monica, CA 90404,USA

According: : FCC Guidelines for Human Exposure IEEE

C95.1

Technical Manager

(Herbort Liu)

BTL INC.

B1, No. 37, Lane 365, Yang-Guang St., Nei-Hu District, Taipei City 114, Taiwan.

TEL: +886-2-2657-3299 FAX: +886-2-2657-3331





MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Manufacture	Model Name	Antenna Type	Connector	Gain (dBi)
1	© INPAQ	CAM V4	PIFA	N/A	2.20





TEST RESULTS

Test Mode: TX B Mode /CH01, CH06, CH11

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.20	1.6596	14.26	26.6686	0.00880948	1	Complies
2.20	1.6596	14.43	27.7332	0.00916116	1	Complies
2.20	1.6596	15.13	32.5837	0.01076342	1	Complies

Test Mode: TX G Mode /CH01, CH06, CH11

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.20	1.6596	18.13	65.0130	0.02147585	1	Complies
2.20	1.6596	18.21	66.2217	0.02187512	1	Complies
2.20	1.6596	17.9	61.6595	0.02036809	1	Complies

Test Mode: TX N-20M Mode_ Total /CH01, CH06, CH11

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2.20	1.6596	18.16	65.4636	0.02162471	1	Complies
2.20	1.6596	18.21	66.2217	0.02187512	1	Complies
2.20	1.6596	17.71	59.0201	0.01949622	1	Complies