



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM150800500102
Page: 1 of 131

FCC REPORT

Application No: SZEM1508005001CR
Applicant: Shenzhen Sunshine Technology Development Co., Ltd
Manufacturer/ Factory: Shenzhen Sunshine Technology Development Co., Ltd
Product Name: IP Camera
Model No.(EUT): D01
Trade Mark: Non
FCC ID: 2AEUS-D013D01788
Standards: 47 CFR Part 15, Subpart C (2014)
Date of Receipt: 2015-08-13
Date of Test: 2015-08-14 to 2015-08-26
Date of Issue: 2015-08-31

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 2 of 131

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-08-31		Original

Authorized for issue by:			
Tested By		Owen Zhou <hr/> (Owen Zhou) /Project Engineer	2015-08-26 <hr/> Date
Prepared By		Vivi Zhou <hr/> (Vivi Zhou) /Clerk	2015-08-31 <hr/> Date
Checked By		Chris Zhong <hr/> (Chris Zhong) /Reviewer	2015-08-31 <hr/> Date



3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2009	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2009	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2009	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS



4 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT AND MODE	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST LOCATION	7
5.6 TEST FACILITY	8
5.7 DEVIATION FROM STANDARDS	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
5.10 EQUIPMENT LIST	9
6 TEST RESULTS AND MEASUREMENT DATA.....	12
6.1 ANTENNA REQUIREMENT.....	12
6.2 CONDUCTED EMISSIONS	13
6.3 CONDUCTED PEAK OUTPUT POWER	17
6.4 6dB OCCUPY BANDWIDTH	26
6.5 POWER SPECTRAL DENSITY	34
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	42
6.7 RF CONDUCTED SPURIOUS EMISSIONS	47
6.8 RADIATED SPURIOUS EMISSIONS.....	84
6.8.1 Radiated emission below 1GHz.....	87
6.8.2 Transmitter emission above 1GHz.....	89
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	96
7 PHOTOGRAPHS - EUT TEST SETUP	130
7.1 RADIATED SPURIOUS EMISSION.....	130
7.2 CONDUCTED EMISSION.....	131
8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	131



5 General Information

5.1 Client Information

Applicant:	Shenzhen Sunshine Technology Development Co., Ltd
Address of Applicant:	4/F, Block 4, HongHuaLing Industrial Park (Zone 2), Taoyuan Str., Xili, Shenzhen, 518055, China.
Manufacturer:	Shenzhen Sunshine Technology Development Co., Ltd
Address of Manufacturer:	4/F, Block 4, HongHuaLing Industrial Park (Zone 2), Taoyuan Str., Xili, Shenzhen, 518055, China.
Factory:	Shenzhen Sunshine Technology Development Co., Ltd
Address of Factory:	4/F, Block 4, HongHuaLing Industrial Park (Zone 2), Taoyuan Str., Xili, Shenzhen, 518055, China.
Supplier:	Shenzhen Sunshine Technology Development Co., Ltd
Country of Origin:	China
Country of Destination:	USA

5.2 General Description of EUT

Product Name:	IP Camera
Model No.:	D01
Trade Mark:	Non
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	Fixed production
Test Power Grade:	11B : 01 ; 11G : 00 ; 11N : 00 (manufacturer declare)
Test Software of EUT:	QA Tool (manufacturer declare)
Antenna Type and Gain:	Type: Integral Gain:3.5dBi
Power Supply:	Adaptor Model:XED-FCC050200C Input:AC100-240V 50/60Hz 0.3A Output:DC5V 2A



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 6 of 131

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2422MHz	4	2437MHz	7	2452MHz
2	2427MHz	5	2442MHz		
3	2432MHz	6	2447MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz



5.3 Test Environment and Mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1015 mbar
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Serial No.
iPhone 6	Apple	MG472ZP/A	C34NHTMFG5MN
Router	NETGEAR	DGN2200	REF. No.SEA2200
TF Card	Kingston	SDC8GB	REF. No.SEA0400

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 9 of 131

5.10 Equipment List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2016-05-13
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2016-05-13
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2015-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2015-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2015-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2016-05-13
8	Coaxial Cable	SGS	N/A	SEL0025	2016-05-13
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2016-05-13



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM150800500102
Page: 10 of 131

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2016-05-13
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2016-05-13
10	Coaxial cable	SGS	N/A	SEL0189	2016-05-13
11	Coaxial cable	SGS	N/A	SEL0121	2016-05-13
12	Coaxial cable	SGS	N/A	SEL0178	2016-05-13
13	Band filter	Amindeon	82346	SEL0094	2016-05-13
14	Barometer	Chang Chun	DYM3	SEL0088	2016-05-13
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
16	Humidity/Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2016-05-13
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2016-05-13

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**


Report No.: SZEM150800500102
Page: 11 of 131

RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0179	2016-05-13
6	Barometer	ChangChun	DYM3	SEL0088	2016-05-13
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2016-04-25
8	Band filter	amideon	82346	SEL0094	2016-05-13
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2016-04-25
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:	 <p>The photograph shows the internal components of the EUT. A main PCB is visible with a red line pointing to an integrated antenna. Other components include a black circular component, a small black module, and a white plastic part. A ruler is positioned next to the EUT for scale, with markings from 1 to 30 cm.</p> <p>The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.5dBi.</p>



6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none">1) The mains terminal disturbance voltage test was conducted in a shielded room.2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.		


Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel. Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line:



Site : Shielding Room
Condition : 47 CFR PART15C AV CE LINE
Job No. : 5001CR
Test Mode : TX

	Freq	Cable	LISN	Read	Limit	Over	Remark	
		MHz	Loss	Factor	Level	Level	Line	Limit
1 @	0.17678	0.02	9.83	36.05	45.90	54.64	-8.74	Peak
2 @	0.19863	0.02	9.83	33.88	43.73	53.67	-9.94	Peak
3	0.92821	0.02	9.89	18.90	28.81	46.00	-17.19	Peak
4	2.779	0.02	10.01	21.41	31.44	46.00	-14.56	Peak
5	4.647	0.01	10.11	20.64	30.76	46.00	-15.24	Peak
6	6.488	0.01	10.14	22.00	32.16	50.00	-17.84	Peak

Neutral Line:



Site : Shielding Room
 Condition : 47 CFR PART15C AV CE NEUTRAL
 Job No. : 5001CR
 Test Mode : TX

	Freq	Cable	LISN	Read	Limit	Over	Remark	
		MHz	Loss	Factor	Level	Level	Line	dB
1 @	0.15485	0.02	9.79	38.14	47.95	55.74	-7.79	Peak
2 @	0.17399	0.02	9.82	35.90	45.74	54.77	-9.03	Peak
3	0.30998	0.01	9.86	27.66	37.54	49.97	-12.43	Peak
4	0.92821	0.02	10.01	19.09	29.12	46.00	-16.88	Peak
5	2.794	0.02	10.12	21.81	31.95	46.00	-14.05	Peak
6	4.647	0.01	10.13	21.65	31.79	46.00	-14.21	Peak

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2009
Test Setup:	<p style="text-align: center;"> Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane </p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	30dBm
Test Results:	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 18 of 131

Measurement Data

802.11b mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	17.79	30.00	Pass
Middle	17.93	30.00	Pass
Highest	18.18	30.00	Pass

802.11g mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	21.99	30.00	Pass
Middle	22.09	30.00	Pass
Highest	22.24	30.00	Pass

802.11n(HT20)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	22.20	30.00	Pass
Middle	22.33	30.00	Pass
Highest	22.53	30.00	Pass


802.11n(HT40)mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	21.66	30.00	Pass
Middle	21.77	30.00	Pass
Highest	21.90	30.00	Pass




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Test plot as follows:


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------



Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------



Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



6.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2009
Test Setup:	
Instruments Used:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	≥ 500 kHz
Test Results:	Pass



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM150800500102
Page: 27 of 131

Measurement Data

802.11b mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	10.140	≥500	Pass
Middle	10.140	≥500	Pass
Highest	10.140	≥500	Pass


802.11g mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	16.650	≥500	Pass
Middle	16.590	≥500	Pass
Highest	16.650	≥500	Pass

802.11n(HT20) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	17.640	≥500	Pass
Middle	17.670	≥500	Pass
Highest	17.700	≥500	Pass


802.11n(HT40)mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	36.300	≥500	Pass
Middle	36.180	≥500	Pass
Highest	36.300	≥500	Pass

Test plot as follows:


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2009
Test Setup:	<p style="text-align: center;"> Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane </p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 5.10 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	$\leq 8.00 \text{ dBm}/3\text{kHz}$
Test Results:	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 35 of 131

Measurement Data

802.11b mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
Lowest	-7.29	≤8.00	Pass
Middle	-7.28	≤8.00	Pass
Highest	-7.10	≤8.00	Pass


802.11g mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
Lowest	-5.11	≤8.00	Pass
Middle	-4.97	≤8.00	Pass
Highest	-4.80	≤8.00	Pass

802.11n(HT20) mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
Lowest	-5.29	≤8.00	Pass
Middle	-5.11	≤8.00	Pass
Highest	-5.11	≤8.00	Pass


802.11n(HT40) mode			
Test channel	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
Lowest	-4.68	≤8.00	Pass
Middle	-4.62	≤8.00	Pass
Highest	-4.48	≤8.00	Pass

Test plot as follows:


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------



Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 38 of 131

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."


Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------




6.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2009
Test Setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------



Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------






6.7 RF Conducted Spurious Emissions



Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2009
Test Setup:	<p style="text-align: center;"> Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane </p>
	<p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:



Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------













Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------













Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------









Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch



Report No.: SZEM150800500102
Page: 58 of 131







This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."





Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------













Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------









Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------











SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch



Report No.: SZEM150800500102
Page: 68 of 131





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------













Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------











Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------













SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch



Report No.: SZEM150800500102
Page: 78 of 131

Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------







This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."







Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------







Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



6.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:	
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**


Report No.: SZEM150800500102

Page: 86 of 131

	method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

6.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical




Condition: FCC PART 15 C 3m 3142C VERTICAL

Job No. : 5001CR

Test Mode: TX

Freq	Cable	Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.07	0.67	17.54	25.69	41.71	34.23	40.00 -5.77
2	33.68	0.72	16.64	25.73	38.48	30.11	40.00 -9.89
3	55.22	0.99	7.92	25.75	40.82	23.98	40.00 -16.02
4	107.13	1.44	8.81	26.14	46.67	30.78	43.50 -12.72
5	696.86	4.63	21.65	25.91	33.51	33.88	46.00 -12.12
6	744.87	4.84	21.60	26.68	33.68	33.44	46.00 -12.56

Test mode:	Transmitting	Horizontal
------------	--------------	------------



Condition: FCC PART 15 C 3m 3142C HORIZONTAL

Job No. : 5001CR

Test Mode: TX

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	112.13	1.51	8.57	25.54	42.06	26.60	43.50	-16.90
2	336.04	2.95	15.11	24.45	30.56	24.17	46.00	-21.83
3	649.66	4.42	20.40	26.26	30.79	29.35	46.00	-16.65
4	696.86	4.63	21.65	25.91	34.69	35.06	46.00	-10.94
5	744.87	4.84	21.60	26.68	34.90	34.66	46.00	-11.34
6	793.40	4.84	21.97	25.91	30.80	31.70	46.00	-14.30





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 89 of 131

6.8.2 Transmitter emission above 1GHz

Test mode:		802.11b		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
3631.354	6.89	33.02	38.80	47.95	49.06	74.00	-24.94		Vertical	
4824.000	6.46	34.72	39.24	48.48	50.42	74.00	-23.58		Vertical	
5913.378	7.95	36.13	39.19	47.62	52.51	74.00	-21.49		Vertical	
7236.000	8.96	35.60	39.06	46.95	52.45	74.00	-21.55		Vertical	
9648.000	9.97	37.45	37.91	43.37	52.88	74.00	-21.12		Vertical	
11622.330	10.44	38.32	38.52	43.20	53.44	74.00	-20.56		Vertical	
3892.524	6.75	33.31	38.91	48.06	49.21	74.00	-24.79		Horizontal	
4824.000	6.46	34.72	39.24	49.42	51.36	74.00	-22.64		Horizontal	
5913.378	7.95	36.13	39.19	48.91	53.80	74.00	-20.20		Horizontal	
7236.000	8.96	35.60	39.06	47.74	53.24	74.00	-20.76		Horizontal	
9648.000	9.97	37.45	37.91	42.04	51.55	74.00	-22.45		Horizontal	
11438.810	10.38	38.18	38.44	42.96	53.08	74.00	-20.92		Horizontal	

Test mode:		802.11b		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)		Polarization	
3716.403	6.84	33.09	38.84	48.68	49.77	74.00	-24.23		Vertical	
4874.000	6.57	34.77	39.26	47.68	49.76	74.00	-24.24		Vertical	
6122.333	8.05	36.16	39.17	47.12	52.16	74.00	-21.84		Vertical	
7311.000	9.06	35.52	39.06	47.98	53.50	74.00	-20.50		Vertical	
9748.000	9.91	37.76	37.85	41.48	51.30	74.00	-22.70		Vertical	
11622.330	10.44	38.32	38.52	42.10	52.34	74.00	-21.66		Vertical	
3892.524	6.75	33.31	38.91	48.38	49.53	74.00	-24.47		Horizontal	
4874.000	6.57	34.77	39.26	49.47	51.55	74.00	-22.45		Horizontal	
5930.516	7.97	36.17	39.19	47.71	52.66	74.00	-21.34		Horizontal	
7311.000	9.06	35.52	39.06	46.80	52.32	74.00	-21.68		Horizontal	
9748.000	9.91	37.76	37.85	41.95	51.77	74.00	-22.23		Horizontal	
11422.280	10.37	38.17	38.43	43.08	53.19	74.00	-20.81		Horizontal	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 90 of 131

Test mode:		802.11b		Test channel:	Highest	Remark:	Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3792.453	6.80	33.14	38.87	47.80	48.87	74.00	-25.13	Vertical
4924.000	6.68	34.82	39.28	48.35	50.57	74.00	-23.43	Vertical
5964.939	8.03	36.23	39.19	48.87	53.94	74.00	-20.06	Vertical
7386.000	9.16	35.44	39.05	47.07	52.62	74.00	-21.38	Vertical
9848.000	9.85	38.06	37.79	41.61	51.73	74.00	-22.27	Vertical
11521.870	10.40	38.24	38.48	42.55	52.71	74.00	-21.29	Vertical
3663.017	6.87	33.05	38.81	47.43	48.54	74.00	-25.46	Horizontal
4924.000	6.68	34.82	39.28	48.02	50.24	74.00	-23.76	Horizontal
5896.291	7.92	36.10	39.19	48.83	53.66	74.00	-20.34	Horizontal
7386.000	9.16	35.44	39.05	48.06	53.61	74.00	-20.39	Horizontal
9848.000	9.85	38.06	37.79	41.88	52.00	74.00	-22.00	Horizontal
11455.380	10.38	38.19	38.45	42.55	52.67	74.00	-21.33	Horizontal

Test mode:		802.11g		Test channel:	Lowest	Remark:	Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3652.432	6.88	33.04	38.81	48.59	49.70	74.00	-24.30	Vertical
4824.000	6.46	34.72	39.24	49.14	51.08	74.00	-22.92	Vertical
5999.562	8.08	36.30	39.18	47.73	52.93	74.00	-21.07	Vertical
7236.000	8.96	35.60	39.06	43.87	49.37	74.00	-24.63	Vertical
9648.000	9.97	37.45	37.91	41.68	51.19	74.00	-22.81	Vertical
11422.280	10.37	38.17	38.43	42.49	52.60	74.00	-21.40	Vertical
3641.878	6.89	33.03	38.80	48.74	49.86	74.00	-24.14	Horizontal
4824.000	6.46	34.72	39.24	50.18	52.12	74.00	-21.88	Horizontal
6016.949	8.08	36.28	39.18	48.04	53.22	74.00	-20.78	Horizontal
7326.000	9.08	35.50	39.06	48.24	53.76	74.00	-20.24	Horizontal
9648.000	9.97	37.45	37.91	42.15	51.66	74.00	-22.34	Horizontal
11323.540	10.35	38.14	38.38	42.82	52.93	74.00	-21.07	Horizontal



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 91 of 131

Test mode:		802.11g		Test channel:		Middle	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3568.847	6.93	32.97	38.77	48.75	49.88	74.00	-24.12	Vertical	
4874.000	6.57	34.77	39.26	49.18	51.26	74.00	-22.74	Vertical	
5828.433	7.81	35.97	39.20	47.76	52.34	74.00	-21.66	Vertical	
7311.000	9.06	35.52	39.06	47.03	52.55	74.00	-21.45	Vertical	
9748.000	9.91	37.76	37.85	42.82	52.64	74.00	-21.36	Vertical	
11757.650	10.50	38.46	38.59	42.53	52.90	74.00	-21.10	Vertical	
3652.432	6.88	33.04	38.81	48.59	49.70	74.00	-24.30	Horizontal	
4874.000	6.57	34.77	39.26	48.51	50.59	74.00	-23.41	Horizontal	
6087.002	8.06	36.20	39.17	47.56	52.65	74.00	-21.35	Horizontal	
7311.000	9.06	35.52	39.06	43.85	49.37	74.00	-24.63	Horizontal	
9748.000	9.91	37.76	37.85	42.09	51.91	74.00	-22.09	Horizontal	
11488.580	10.39	38.22	38.46	43.06	53.21	74.00	-20.79	Horizontal	

Test mode:		802.11g		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3558.534	6.94	32.96	38.77	46.69	47.82	74.00	-26.18	Vertical	
4924.000	6.68	34.82	39.28	47.76	49.98	74.00	-24.02	Vertical	
6087.002	8.06	36.20	39.17	47.33	52.42	74.00	-21.58	Vertical	
7386.000	9.16	35.44	39.05	43.02	48.57	74.00	-25.43	Vertical	
9848.000	9.85	38.06	37.79	40.78	50.90	74.00	-23.10	Vertical	
11757.650	10.50	38.46	38.59	42.06	52.43	74.00	-21.57	Vertical	
3803.444	6.80	33.16	38.87	46.82	47.91	74.00	-26.09	Horizontal	
4924.000	6.68	34.82	39.28	47.37	49.59	74.00	-24.41	Horizontal	
5930.516	7.97	36.17	39.19	47.51	52.46	74.00	-21.54	Horizontal	
7386.000	9.16	35.44	39.05	41.46	47.01	74.00	-26.99	Horizontal	
9848.000	9.85	38.06	37.79	39.17	49.29	74.00	-24.71	Horizontal	
11860.170	10.55	38.56	38.64	43.40	53.87	74.00	-20.13	Horizontal	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 92 of 131

Test mode:		802.11n(HT20)		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3694.956	6.86	33.07	38.83	47.68	48.78	74.00	-25.22	Vertical		
4824.000	6.46	34.72	39.24	49.06	51.00	74.00	-23.00	Vertical		
5811.590	7.79	35.93	39.20	47.65	52.17	74.00	-21.83	Vertical		
7236.000	8.96	35.60	39.06	46.52	52.02	74.00	-21.98	Vertical		
9648.000	9.97	37.45	37.91	42.23	51.74	74.00	-22.26	Vertical		
11521.870	10.40	38.24	38.48	42.95	53.11	74.00	-20.89	Vertical		
3737.975	6.83	33.10	38.84	47.07	48.16	74.00	-25.84	Horizontal		
4824.000	6.46	34.72	39.24	48.20	50.14	74.00	-23.86	Horizontal		
5964.939	8.03	36.23	39.19	46.99	52.06	74.00	-21.94	Horizontal		
7236.000	8.96	35.60	39.06	47.86	53.36	74.00	-20.64	Horizontal		
9648.000	9.97	37.45	37.91	41.92	51.43	74.00	-22.57	Horizontal		
11757.650	10.50	38.46	38.59	42.61	52.98	74.00	-21.02	Horizontal		

Test mode:		802.11n(HT20)		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3716.403	6.84	33.09	38.84	47.79	48.88	74.00	-25.12	Vertical		
4874.000	6.57	34.77	39.26	48.92	51.00	74.00	-23.00	Vertical		
5913.378	7.95	36.13	39.19	47.85	52.74	74.00	-21.26	Vertical		
7311.000	9.06	35.52	39.06	47.11	52.63	74.00	-21.37	Vertical		
9748.000	9.91	37.76	37.85	41.92	51.74	74.00	-22.26	Vertical		
11723.670	10.49	38.43	38.57	42.98	53.33	74.00	-20.67	Vertical		
3652.432	6.88	33.04	38.81	47.55	48.66	74.00	-25.34	Horizontal		
4874.000	6.57	34.77	39.26	47.11	49.19	74.00	-24.81	Horizontal		
5964.939	8.03	36.23	39.19	48.02	53.09	74.00	-20.91	Horizontal		
7311.000	9.06	35.52	39.06	43.74	49.26	74.00	-24.74	Horizontal		
9748.000	9.91	37.76	37.85	41.55	51.37	74.00	-22.63	Horizontal		
11656.010	10.46	38.36	38.54	41.94	52.22	74.00	-21.78	Horizontal		



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 93 of 131

Test mode:		802.11n(HT20)		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3631.354	6.89	33.02	38.80	47.95	49.06	74.00	-24.94	Vertical	
4924.000	6.68	34.82	39.28	49.60	51.82	74.00	-22.18	Vertical	
5947.702	8.00	36.20	39.19	47.71	52.72	74.00	-21.28	Vertical	
7386.000	9.16	35.44	39.05	44.18	49.73	74.00	-24.27	Vertical	
9848.000	9.85	38.06	37.79	40.64	50.76	74.00	-23.24	Vertical	
11323.540	10.35	38.14	38.38	42.30	52.41	74.00	-21.59	Vertical	
3727.173	6.84	33.10	38.84	48.26	49.36	74.00	-24.64	Horizontal	
4924.000	6.68	34.82	39.28	48.35	50.57	74.00	-23.43	Horizontal	
5930.516	7.97	36.17	39.19	47.50	52.45	74.00	-21.55	Horizontal	
7386.000	9.16	35.44	39.05	46.87	52.42	74.00	-21.58	Horizontal	
9848.000	9.85	38.06	37.79	41.90	52.02	74.00	-21.98	Horizontal	
11372.800	10.36	38.15	38.41	42.60	52.70	74.00	-21.30	Horizontal	

Test mode:		802.11n(HT40)		Test channel:		Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3898.160	6.74	33.32	38.91	47.63	48.78	74.00	-25.22	Vertical	
4844.000	6.51	34.74	39.25	48.38	50.38	74.00	-23.62	Vertical	
5990.888	8.07	36.28	39.18	46.90	52.07	74.00	-21.93	Vertical	
7266.000	9.00	35.57	39.06	43.80	49.31	74.00	-24.69	Vertical	
9688.000	9.94	37.57	37.88	42.18	51.81	74.00	-22.19	Vertical	
11488.580	10.39	38.22	38.46	42.53	52.68	74.00	-21.32	Vertical	
3819.990	6.79	33.19	38.88	47.59	48.69	74.00	-25.31	Horizontal	
4844.000	6.51	34.74	39.25	48.59	50.59	74.00	-23.41	Horizontal	
5964.939	8.03	36.23	39.19	47.14	52.21	74.00	-21.79	Horizontal	
7266.000	9.00	35.57	39.06	43.14	48.65	74.00	-25.35	Horizontal	
9688.000	9.94	37.57	37.88	40.50	50.13	74.00	-23.87	Horizontal	
11656.010	10.46	38.36	38.54	42.89	53.17	74.00	-20.83	Horizontal	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 94 of 131

Test mode:		802.11n(HT40)		Test channel:		Middle	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3842.163	6.77	33.23	38.89	46.53	47.64	74.00	-26.36	Vertical	
4874.000	6.57	34.77	39.26	48.49	50.57	74.00	-23.43	Vertical	
5956.314	8.01	36.22	39.19	48.37	53.41	74.00	-20.59	Vertical	
7311.000	9.06	35.52	39.06	47.10	52.62	74.00	-21.38	Vertical	
9748.000	9.91	37.76	37.85	40.59	50.41	74.00	-23.59	Vertical	
11323.540	10.35	38.14	38.38	42.11	52.22	74.00	-21.78	Vertical	
3663.017	6.87	33.05	38.81	46.43	47.54	74.00	-26.46	Horizontal	
4874.000	6.57	34.77	39.26	47.16	49.24	74.00	-24.76	Horizontal	
5896.291	7.92	36.10	39.19	47.83	52.66	74.00	-21.34	Horizontal	
7311.000	9.06	35.52	39.06	47.09	52.61	74.00	-21.39	Horizontal	
9748.000	9.91	37.76	37.85	42.18	52.00	74.00	-22.00	Horizontal	
11455.380	10.38	38.19	38.45	41.55	51.67	74.00	-22.33	Horizontal	

Test mode:		802.11n(HT40)		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3477.098	7.01	32.87	38.73	48.26	49.41	74.00	-24.59	Vertical	
4904.000	6.64	34.81	39.27	48.90	51.08	74.00	-22.92	Vertical	
6034.386	8.07	36.26	39.18	47.06	52.21	74.00	-21.79	Vertical	
7356.000	9.12	35.47	39.05	43.74	49.28	74.00	-24.72	Vertical	
9808.000	9.88	37.94	37.81	42.29	52.30	74.00	-21.70	Vertical	
11438.810	10.38	38.18	38.44	42.26	52.38	74.00	-21.62	Vertical	
3620.861	6.90	33.02	38.79	48.52	49.65	74.00	-24.35	Horizontal	
4904.000	6.64	34.81	39.27	48.88	51.06	74.00	-22.94	Horizontal	
5939.103	7.99	36.18	39.19	47.32	52.30	74.00	-21.70	Horizontal	
7356.000	9.12	35.47	39.05	47.44	52.98	74.00	-21.02	Horizontal	
9808.000	9.88	37.94	37.81	41.42	51.43	74.00	-22.57	Horizontal	
11505.210	10.39	38.23	38.47	42.87	53.02	74.00	-20.98	Horizontal	



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 95 of 131

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205					
Test Method:	ANSI C63.10 2009					
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)					
Limit:	Frequency	Limit (dBuV/m @3m)	Remark			
	30MHz-88MHz	40.0	Quasi-peak Value			
	88MHz-216MHz	43.5	Quasi-peak Value			
	216MHz-960MHz	46.0	Quasi-peak Value			
	960MHz-1GHz	54.0	Quasi-peak Value			
	Above 1GHz	54.0	Average Value			
		74.0	Peak Value			
Test Setup:						

Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM150800500102
Page: 97 of 131

Test Procedure:	<ul style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channelg. Test the EUT in the lowest channel , the Highest channelh. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case.i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 98 of 131

Test plot as follows:

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 5001CR
Mode: : 2412 Band edge B

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	57.54	56.33	74.00	-17.67
2 pp	2412.13	4.93	32.41	38.46	105.99	104.87	74.00	30.87



Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2412 Band edge B

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	71.41	70.20	74.00	-3.80
2 pp	2411.68	4.93	32.41	38.46	110.78	109.66	74.00	35.66

Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------


Data: 34



Site : chamber
 Condition: FCC PART C 247 AV 3m Vertical
 Job No: : 5001CR
 Mode: : 2412 Band edge B

	Cable Freq		Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	47.35	46.14	54.00	-7.86
2 pp	2412.81	4.93	32.41	38.46	84.40	83.28	54.00	29.28


Worse case mode:	802.11b	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2412 Band edge B

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Over Line	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	48.40	47.19	54.00	-6.81
2 pp	2413.26	4.93	32.41	38.46	88.37	87.25	54.00	33.25

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 5001CR
Mode: : 2462 Band edge B

	Cable	Ant	Preamp	Read	Limit	Over
Freq	Loss	Factor	Factor	Level	Level	Line
1 pp	2461.66	5.00	32.43	38.46	104.71	103.68
2	2483.50	5.03	32.44	38.47	59.15	58.15

MHz dB dB/m dB dBuV dBuV/m dBuV/m dB

1 pp 2461.66 5.00 32.43 38.46 104.71 103.68 74.00 29.68
2 2483.50 5.03 32.44 38.47 59.15 58.15 74.00 -15.85


Worse case mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------



Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2462 Band edge B

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2461.66	5.00	32.43	38.46	109.84	108.81	74.00 34.81
2	2483.50	5.03	32.44	38.47	57.69	56.69	74.00 -17.31

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------



Site : chamber


Condition: FCC PART C 247 AV 3m Vertical

Job No: : 5001CR

Mode: : 2462 Band edge B

	Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2459.82	5.00	32.43	38.46	83.87	82.84	54.00	28.84
2	2483.50	5.03	32.44	38.47	36.93	35.93	54.00	-18.07

Worse case mode:	802.11b	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------




Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2462 Band edge B

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2460.07	5.00	32.43	38.46	87.78	86.75	54.00	32.75
2	2483.50	5.03	32.44	38.47	49.45	48.45	54.00	-5.55

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------	---------------	--------	---------	------	----------

Data: 43




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2412 Band edge G

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	68.05	66.84	74.00	-7.16
2 pp	2405.88	4.92	32.41	38.46	95.40	94.27	74.00	20.27

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------	---------------	--------	---------	------	------------

Data: 41



Site : chamber
 Condition: FCC PART C 247 PK 3m Vertical
 Job No: : 5001CR
 Mode: : 2412 Band edge G

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	64.04	62.83	74.00	-11.17
2 pp	2412.47	4.93	32.41	38.46	98.32	97.20	74.00	23.20




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 108 of 131

Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------	---------------	--------	---------	---------	----------

Data: 42




Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 5001CR
Mode: : 2412 Band edge G

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	37.40	36.19	54.00	-17.81
2 pp	2417.97	4.94	32.42	38.46	79.37	78.27	54.00	24.27



Worse case mode:	802.11g	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------	---------------	--------	---------	---------	------------


Data: 44



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2412 Band edge G

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	38.97	37.76	54.00	-16.24
2 pp	2417.97	4.94	32.42	38.46	78.15	77.05	54.00	23.05

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------	---------------	---------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 5001CR
Mode: : 2462 Band edge G

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2455.85	4.99	32.43	38.46	100.02	98.98	74.00	24.98
2	2483.50	5.03	32.44	38.47	60.20	59.20	74.00	-14.80

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------	---------------	---------	---------	------	------------

Data: 47




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2462 Band edge G

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2455.70	4.99	32.43	38.46	99.31	98.27	74.00	24.27
2	2483.50	5.03	32.44	38.47	59.32	58.32	74.00	-15.68

Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------	---------------	---------	---------	---------	----------

Data: 46



Site : chamber


Condition: FCC PART C 247 AV 3m Vertical

Job No: : 5001CR

Mode: : 2462 Band edge G

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit
1 pp	2468.83	5.01	32.43	38.46	76.01	74.99	54.00 20.99
2	2483.50	5.03	32.44	38.47	36.81	35.81	54.00 -18.19


Worse case mode:	802.11g	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------	---------------	---------	---------	---------	------------



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2462 Band edge G

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2456.05	4.99	32.43	38.46	80.58	79.54	54.00	25.54
2	2483.50	5.03	32.44	38.47	35.27	34.27	54.00	-19.73


Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------



Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 5001CR
Mode: : 2412 Band edge N 20

	Cable Freq		Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	68.22	67.01	74.00	-6.99
2 pp	2414.54	4.93	32.42	38.46	100.82	99.71	74.00	25.71

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2412 Band edge N 20

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	68.97	67.76	74.00	-6.24
2 pp	2418.95	4.94	32.42	38.46	99.67	98.57	74.00	24.57

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------


Data: 54



Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 5001CR
Mode: : 2412 Band edge N 20

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	38.54	37.33	54.00	-16.67
2 pp	2417.97	4.94	32.42	38.46	81.25	80.15	54.00	26.15

Worse case mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2412 Band edge N 20


	Cable Freq		Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	38.52	37.31	54.00	-16.69
2 pp	2414.30	4.93	32.42	38.46	81.19	80.08	54.00	26.08



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 118 of 131

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 5001CR
Mode: : 2462 Band edge N 20

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2469.63	5.01	32.44	38.46	99.45	98.44	74.00	24.44
2	2483.50	5.03	32.44	38.47	61.50	60.50	74.00	-13.50



Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------




Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2462 Band edge N 20

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 2459.08	5.00	32.43	38.46	98.77	97.74	74.00	23.74
2 2483.50	5.03	32.44	38.47	59.41	58.41	74.00	-15.59

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------


Data: 52



Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 5001CR
Mode: : 2462 Band edge N 20

	Cable Freq		Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2469.08	5.01	32.43	38.46	82.08	81.06	54.00	27.06
2	2483.50	5.03	32.44	38.47	36.70	35.70	54.00	-18.30

Worse case mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------



Site : chamber


Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 5001CR

Mode: : 2462 Band edge N 20

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2455.00	4.99	32.43	38.46	81.65	80.61	54.00	26.61
2	2483.50	5.03	32.44	38.47	35.23	34.23	54.00	-19.77


Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	---------------	---------------	--------	---------	------	----------



Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2422 Band edge N 40

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	69.34	68.13	74.00	-5.87
2 pp	2408.41	4.93	32.41	38.46	103.37	102.25	74.00	28.25


Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	---------------	---------------	--------	---------	------	------------



Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2422 Band edge N 40

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	69.73	68.52	74.00	-5.48
2 pp	2433.05	4.96	32.42	38.46	96.90	95.82	74.00	21.82


Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	---------------	---------------	--------	---------	---------	----------



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2422 Band edge N 40

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	40.50	39.29	54.00	-14.71
2 pp	2415.50	4.94	32.42	38.46	83.92	82.82	54.00	28.82


Worse case mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	---------------	---------------	--------	---------	---------	------------



Site : chamber
Condition: FCC PART C 247 AV 3m Horizontal
Job No: : 5001CR
Mode: : 2422 Band edge N 40

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	36.82	35.61	54.00	-18.39
2 pp	2418.21	4.94	32.42	38.46	79.97	78.87	54.00	24.87


Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	---------------	---------------	---------	---------	------	----------



Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 5001CR
Mode: : 2452 Band edge N 40

	Cable Freq	Ant Loss	Preamplifier Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2463.00	5.00	32.43	38.46	97.42	96.39	74.00	22.39
2	2483.50	5.03	32.44	38.47	62.80	61.80	74.00	-12.20

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	---------------	---------------	---------	---------	------	------------



Site : chamber
Condition: FCC PART C 247 PK 3m Horizontal
Job No: : 5001CR
Mode: : 2452 Band edge N 40

	Cable	Ant	Preamplifier	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit
1 pp	2446.69	4.98	32.43	38.46	101.84	100.79	74.00
2	2483.50	5.03	32.44	38.47	69.23	68.23	74.00

MHz dB dB/m dB dBuV dBuV/m dBuV/m dB


1 pp 2446.69 4.98 32.43 38.46 101.84 100.79 74.00 26.79
2 2483.50 5.03 32.44 38.47 69.23 68.23 74.00 -5.77



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150800500102
Page: 128 of 131

Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Vertical
------------------	---------------	---------------	---------	---------	---------	----------



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical


Job No: : 5001CR

Mode: : 2452 Band edge N 40

	Cable	Ant	Preamplifier	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit
1 pp	2439.89	4.97	32.42	38.46	77.98	76.91	54.00 22.91
2	2483.50	5.03	32.44	38.47	36.67	35.67	54.00 -18.33



Worse case mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	---------------	---------------	---------	---------	---------	------------



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 5001CR

Mode: : 2452 Band edge N 40

	Cable Loss	Ant Factor	Preampl Factor	Read Level	Limit Level	Limit Line	Over Limit	
Freq	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2448.64	4.98	32.43	38.46	82.86	81.81	54.00	27.81
2	2483.50	5.03	32.44	38.47	39.50	38.50	54.00	-15.50

Note:



The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

7 Photographs - EUT Test Setup

Test model No.: D01

7.1 Radiated Spurious Emission



7.2 Conducted Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1508005001CR.