

A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.08	2.96	3.04	
Middle CH	2.96	3.08	3.00	PASS
Highest CH	3.04	3.04	2.92	

Report No.: FG560818







26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.65	4.64	4.64
Middle CH	4.67	4.64	4.66
Highest CH	4.65	4.62	4.65

Report No.: FG560818

SPORTON INTERNATIONAL INC. Page Number : A2-4 of 18







Occupied Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.09	4.07	4.08
Middle CH	4.08	4.09	4.08
Highest CH	4.09	4.09	4.09

Report No.: FG560818


SPORTON INTERNATIONAL INC. Page Number : A2-7 of 18







Conducted Band Edge

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A2-10 of 18









Conducted Spurious Emission

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Page Number : A2-14 of 18





Frequency Stability

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0012	
40	Normal Voltage	0.0155	
30	Normal Voltage	0.0024	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0096	
0	Normal Voltage	0.0036	
-10	Normal Voltage	0.0000	PASS
-20	Normal Voltage	0.0048	
-30	Normal Voltage	0.0060	
20	Maximum Voltage	0.0120	
20	Normal Voltage	0.0024	
20	Battery End Point	0.0108	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0016	
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0021	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0037	
0	Normal Voltage	0.0106	
-10	Normal Voltage	0.0144	PASS
-20	Normal Voltage	0.0032	
-30	Normal Voltage	0.0011	
20	Maximum Voltage	0.0005	
20	Normal Voltage	0.0101	
20	Battery End Point	0.0027	

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0127	
40	Normal Voltage	0.0006	
30	Normal Voltage	0.0017	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0017	
0	Normal Voltage	0.0139	
-10	Normal Voltage	0.0012	PASS
-20	Normal Voltage	0.0012	
-30	Normal Voltage	0.0023	
20	Maximum Voltage	0.0139	
20	Normal Voltage	0.0133	
20	Battery End Point	0.0121	1

FG560818

Report No.:

Note:

- 1. Normal Voltage = 12V. ; Battery End Point (BEP) = 5 V.; Maximum Voltage =18 V
- **2.** The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

SPORTON INTERNATIONAL INC. Page Number : A2-18 of 18