
FCC Test Report

Report No.: AGC04678170101FE03


FCC ID : 2AEWC-UR881
APPLICATION PURPOSE : Original Equipment
PRODUCT DESIGNATION : Bulova Clock with Bluetooth Speaker
BRAND NAME : N/A
MODEL NAME : UR-881
CLIENT : Uni-rich Technology Limited
DATE OF ISSUE : Mar.11, 2017
STANDARD(S) : FCC Part 15 Rules
TEST PROCEDURE(S)
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar.11, 2017	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
2.2. TABLE OF CARRIER FREQUENCIES	5
3. MEASUREMENT UNCERTAINTY	6
4. DESCRIPTION OF TEST MODES.....	6
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM.....	8
5.2. EQUIPMENT USED IN EUT SYSTEM.....	8
5.3. SUMMARY OF TEST RESULTS.....	8
6. TEST FACILITY	9
TEST METHODOLOGY.....	9
7. ALL TEST EQUIPMENT LIST	9
8. RADIATED EMISSION	11
8.1TEST LIMIT.....	11
8.2. MEASUREMENT PROCEDURE.....	12
8.3. TEST SETUP	14
8.4. TEST RESULT	16
9. BAND EDGE EMISSION	31
9.1. MEASUREMENT PROCEDURE.....	31
9.2 TEST SETUP	31
9.3 RADIATED TEST RESULT	32
10. 20DB BANDWIDTH.....	36
10.1. MEASUREMENT PROCEDURE.....	36
10.2. TEST SET-UP	36
10.3. LIMITS AND MEASUREMENT RESULTS.....	36
11. FCC LINE CONDUCTED EMISSION TEST	43
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST	43
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	43
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	44
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	44
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	45
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	47
APPENDIX B: PHOTOGRAPHS OF EUT	50

1. VERIFICATION OF CONFORMITY

Applicant	Uni-rich Technology Limited
Address	Unit D, 6th Floor, Haribest Industrial Building, 45-47 Au Pui Wan Street, Fotan, Shatin, N.T., HK
Manufacturer	Uni-rich Technology Limited
Address	Unit D, 6th Floor, Haribest Industrial Building, 45-47 Au Pui Wan Street, Fotan, Shatin, N.T., HK
Product Designation	Bulova Clock with Bluetooth Speaker
Brand Name	N/A
Test Model	UR-881
Date of test	Jan.13, 2007 to Jan.17, 2017
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By Strive Liang
Strive Liang(Liang Faqiang) Jan.17, 2017

Reviewed By Forrest Lei
Forrest Lei(Lei Yonggang) Mar.11, 2017

Approved By Solger Zhang
Solger Zhang(Zhang Hongyi)
Authorized Officer Mar.11, 2017

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-2.36dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V 3.0
Modulation	GFSK , π /4-DQPSK, 8DPSK
Number of channels	79 for BR/EDR
Hardware Version	2.0
Software Version	1.0
Antenna Designation	PCB Antenna (Met 15.203 Antenna requirement)
Antenna Gain	1dBi
Power Supply	DC 5V by adapter for Bluetooth function
Note: The USB port only be used for charging and can't be used to transfer data with PC.	

2.2. TABLE OF CARRIER FREQUENCIES

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHz	0	2402MHz
	1	2403MHz
	:	:
	38	2440 MHz
	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	BT Link with charging
11	BT Link

Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. The EUT used fully-charged battery when tested.

Software Setting

AppoTech RF Control Kit V4.0

IC Model: **CW66xx**

COM Port Info: Port: **COM1** Rate: **921600**

DUT MODE: **FCC Mode** **OK**

RF Trim: ☐ Fix_RX_24xx ☐ SingleTone Hopping: **OFF**

☒ Channel **41** (2-80) Tx Modulation: **ON**

☒ Power **6** (0-7) Packet Type: **3DH5**

Test scenario: **3 Transmitter test - 1010 pattern**

Specification

FIX RX mode (1)check FIX_RX_24xx (2)check channel to set channel number

FIX TX mode (1)unchecked FIX_RX_24xx (2)check channel to set channel number (3)check power to set TX signal amplitude (4)Modulation Enable OFF

TX Modulation mode (1)unchecked FIX_RX_24xx (2)check channel to set channel number (3)check power to set TX signal amplitude (4)Modulation Enable ON (5)select Packet Type

Hopping mode (1)unchecked FIX_RX_24xx (2)unchecked channel to enable Hopping ON and TX Modulation OFF (3)check power (4)select Packet Type

RF **R12** **60BD** **Write** **Read** Address **0206** Val **04** **Write_xSFR** **Read_xSFR**

☒ Enable Patch 1 ☒ Enable Patch 2

00C845 **00C0CF** **019E68** **019E69**

048280 **0482AE** **048040** **048073**

PFile **...**


☒ Show HCI **Clear** **Save** **Read MROM** **Send**

01 19 FC 40 0F 40 B2 41 04 06 A0 40 00 81 00 00 80 0
04 0E 04 01 19 FC 00
01 08 FC 03 68 4F 00
04 0E 04 01 08 FC 00
01 0F FC 0A 02 03 00 27 00 06 28 2F FD 03
04 0E 04 01 0F FC 00
01 09 FC 01 0C
04 0E 07 01 09 FC 00 0C BD 60

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Note: Owing to the EUT has own battery, Testing will be performed while PC or adapter remove.

Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Bulova Clock with Bluetooth	Uni-rich	UR-881	EUT
2	Adapter	SWITCHING	HKP06-0501000dU	Accessory
3	PC	Sony	E1412AYCW	A.E
4	Control box	JR	N/A	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a)	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	Bandwidth	Compliant

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013

7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHz)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101417	July 4, 2016	July 3, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2016	July 3, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2016	July 3, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	MAX-FULL	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	SCHWARZBECK	FMZB1519	1519-038	June 6, 2016	June 5, 2017
Spectrum analyzer	AGILENT	E4407B	MY46185649	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

FOR RADIATED EMISSION TEST (1GHz ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101417	July 4, 2016	July 3, 2017
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2016	July 10, 2017
Spectrum Analyzer	AGILENT	E4411B	MY4511453	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2016	July 6, 2017
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2016	July 7, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	MAX-FULL	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101417	July 4, 2016	July 3, 2017
Artificial Mains Network	NARDA	L2-16B	000WX31025	July 8, 2016	July 7, 2017
Artificial Mains Network (AUX)	NARDA	L2-16B	000WX31026	July 8, 2016	July 7, 2017
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2016	July 3, 2017
Shielded Room	CHENGYU	843	PTS-002	June 6, 2016	June 5, 2017
Conduction Cable	MXT	SE1	S003	June 6, 2016	June 5, 2017

8. RADIATED EMISSION

8.1 TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark:

- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE

1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak&AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



8.4. TEST RESULT

(Worst modulation:GFSK)


FOR BR/EDR

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




Site: site #1	Polarization: Horizontal	Temperature: 22.2
Limit: FCC Class B 3M Radiation	Power:	Humidity: 54.3 %
EUT: Bulova Clock with Bluetooth Speaker	Distance:	
M/N: UR-881		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		72.0333	22.64	8.28	30.92	40.00	-9.08	peak			
2	*	96.2833	32.37	6.77	39.14	43.50	-4.36	peak			
3		215.9167	25.18	10.38	35.56	43.50	-7.94	peak			
4		299.9833	22.87	15.41	38.28	46.00	-7.72	peak			
5		348.4833	17.72	18.64	36.36	46.00	-9.64	peak			
6		527.9333	7.39	21.88	29.27	46.00	-16.73	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.2

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.3 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881

Mode: Low Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	96.2833	30.70	0.05	30.75	43.50	-12.75	peak			
2		152.8667	14.44	15.28	29.72	43.50	-13.78	peak			
3		299.9833	14.12	15.41	29.53	46.00	-16.47	peak			
4		460.0333	8.35	20.70	29.05	46.00	-16.95	peak			
5		755.8832	2.41	26.71	29.12	46.00	-16.88	peak			
6		951.5000	2.55	29.99	32.54	46.00	-13.46	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 22.2
Limit: FCC Class B 3M Radiation Power: Humidity: 54.3 %
EUT: Bulova Clock with Bluetooth Speaker Distance:
M/N: UR-881
Mode: Middle Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		72.0333	22.73	8.28	31.01	40.00	-8.99	peak			
2	*	96.2833	31.23	6.77	38.00	43.50	-5.50	peak			
3		211.0667	20.97	10.87	31.84	43.50	-11.66	peak			
4		299.9833	22.70	15.41	38.11	46.00	-7.89	peak			
5		348.4833	13.83	18.64	32.47	46.00	-13.53	peak			
6		503.6833	6.94	21.23	28.17	46.00	-17.83	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.2

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.3 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	72.0333	25.07	3.76	28.83	40.00	-11.17	peak			
2		96.2833	30.12	0.05	30.17	43.50	-13.33	peak			
3		152.8667	13.96	15.28	29.24	43.50	-14.26	peak			
4		299.9833	14.01	15.41	29.42	46.00	-16.58	peak			
5		460.0333	8.66	20.70	29.36	46.00	-16.64	peak			
6		925.6333	1.93	29.32	31.25	46.00	-14.75	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 22.2

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.3 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	96.2833	32.15	6.77	38.92	43.50	-4.58	peak			
2		214.3000	21.08	10.54	31.62	43.50	-11.88	peak			
3		275.7333	22.43	11.28	33.71	46.00	-12.29	peak			
4		299.9833	22.88	15.41	38.29	46.00	-7.71	peak			
5		348.4833	17.95	18.64	36.59	46.00	-9.41	peak			
6		527.9333	8.61	21.88	30.49	46.00	-15.51	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.2

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.3 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	96.2833	30.57	0.05	30.62	43.50	-12.88	peak			
2		152.8667	14.10	15.28	29.38	43.50	-14.12	peak			
3		299.9833	14.18	15.41	29.59	46.00	-16.41	peak			
4		398.6000	8.36	19.06	27.42	46.00	-18.58	peak			
5		460.0333	7.62	20.70	28.32	46.00	-17.68	peak			
6		527.9333	6.55	21.88	28.43	46.00	-17.57	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHz**(Worst modulation: GFSK)****FOR BR/EDR****RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL**

Site: site #1

Polarization: **Horizontal**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	82.24	10.32	92.56	114.00	-21.44	peak			
2	*	2402.000	74.35	10.32	84.67	94.00	-9.33	AVG	100	138	
3		3458.333	34.52	12.07	46.59	74.00	-27.41	peak			
4		5600.000	50.81	-1.76	49.05	74.00	-24.95	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	82.35	10.32	92.67	114.00	-21.33	peak			
2	*	2402.000	74.45	10.32	84.77	94.00	-9.23	AVG	150	125	
3		3575.000	36.16	12.57	48.73	74.00	-25.27	peak			
4		4808.333	42.37	7.70	50.07	74.00	-23.93	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Polarization: **Horizontal**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	82.29	10.36	92.65	114.00	-21.35	peak			
2	*	2441.000	74.37	10.36	84.73	94.00	-9.27	AVG	100	249	
3		4350.000	37.29	9.38	46.67	74.00	-27.33	peak			
4		5583.333	50.17	-1.77	48.40	74.00	-25.60	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	82.48	10.36	92.84	114.00	-21.16	peak			
2	*	2441.000	74.61	10.36	84.97	94.00	-9.03	AVG	150	197	
3		3941.667	33.56	14.83	48.39	74.00	-25.61	peak			
4		5108.333	43.46	6.03	49.49	74.00	-24.51	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: Horizontal

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	82.04	10.41	92.45	114.00	-21.55	peak			
2	*	2480.000	74.22	10.41	84.63	94.00	-9.37	AVG	150	349	
3		3733.333	35.33	13.55	48.88	74.00	-25.12	peak			
4		5441.667	52.07	-0.64	51.43	74.00	-22.57	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 22.7

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 53.6 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:

M/N: UR-881

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	82.23	10.41	92.64	114.00	-21.36	peak			
2	*	2480.000	74.28	10.41	84.69	94.00	-9.31	AVG	150	123	
3		4483.333	41.68	7.17	48.85	74.00	-25.15	peak			
4		5166.667	44.97	4.86	49.83	74.00	-24.17	peak			

RESULT: PASS**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	82.24	10.32	92.56	114	-21.44	Horizontal
2402	82.35	10.32	92.67	114	-21.33	Vertical
2441	82.29	10.36	92.65	114	-21.35	Horizontal
2441	82.48	10.36	92.84	114	-21.16	Vertical
2480	82.04	10.41	92.45	114	-21.55	Horizontal
2480	82.23	10.41	92.64	114	-21.36	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	74.35	10.32	84.67	94	-9.33	Horizontal
2402	74.45	10.32	84.77	94	-9.23	Vertical
2441	74.37	10.36	84.73	94	-9.27	Horizontal
2441	74.61	10.36	84.97	94	-9.03	Vertical
2480	74.22	10.41	84.63	94	-9.37	Horizontal
2480	74.28	10.41	84.69	94	-9.31	Vertical

2Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	81.73	10.32	92.05	114	-21.95	Horizontal
2402	81.76	10.32	92.08	114	-21.92	Vertical
2441	81.77	10.36	92.13	114	-21.87	Horizontal
2441	81.79	10.36	92.15	114	-21.85	Vertical
2480	81.45	10.41	91.86	114	-22.14	Horizontal
2480	81.48	10.41	91.89	114	-22.11	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	73.79	10.32	84.11	94	-9.89	Horizontal
2402	73.80	10.32	84.12	94	-9.88	Vertical
2441	73.85	10.36	84.21	94	-9.79	Horizontal
2441	73.90	10.36	84.26	94	-9.74	Vertical
2480	73.73	10.41	84.14	94	-9.86	Horizontal
2480	73.78	10.41	84.19	94	-9.81	Vertical

3Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	81.22	10.32	91.54	114	-22.46	Horizontal
2402	81.25	10.32	91.57	114	-22.43	Vertical
2441	81.27	10.36	91.63	114	-22.37	Horizontal
2441	81.29	10.36	91.65	114	-22.35	Vertical
2480	80.91	10.41	91.32	114	-22.68	Horizontal
2480	80.93	10.41	91.34	114	-22.66	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	73.32	10.32	83.64	94	-10.36	Horizontal
2402	73.34	10.32	83.66	94	-10.34	Vertical
2441	73.39	10.36	83.75	94	-10.25	Horizontal
2441	73.43	10.36	83.79	94	-10.21	Vertical
2480	73.38	10.41	83.79	94	-10.21	Horizontal
2480	73.41	10.41	83.82	94	-10.18	Vertical


9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE

- 1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




9.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHz(PK)	Power:	Humidity: 60 %
EUT: Bulova Clock with Bluetooth Speaker	Distance:	
M/N: UR-881		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2336.667	33.01	10.25	43.26	74.00	-30.74	peak			
2		2390.000	36.50	10.31	46.81	74.00	-27.19	peak			
3	*	2402.000	82.11	10.32	92.43	74.00	18.43	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHz(PK)

Power:

Humidity: 60 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:


M/N: UR-881

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2335.642	34.08	10.25	44.33	74.00	-29.67	peak			
2		2390.000	36.21	10.31	46.52	74.00	-27.48	peak			
3	*	2402.000	82.09	10.32	92.41	74.00	18.41	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHz(PK)

Power:

Humidity: 60 %

EUT: Bulova Clock with Bluetooth Speaker

Distance:


M/N: UR-881

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	81.58	10.41	91.99	74.00	17.99	peak			
2		2483.500	37.69	10.41	48.10	74.00	-25.90	peak			
3		2492.043	38.14	10.42	48.56	74.00	-25.44	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHz(PK) Power: Humidity: 60 %
EUT: Bulova Clock with Bluetooth Speaker Distance:
M/N: UR-881
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	81.36	10.41	91.77	74.00	17.77	peak			
2		2483.500	35.26	10.41	45.67	74.00	-28.33	peak			
3		2493.253	37.61	10.42	48.03	74.00	-25.97	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.


10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

10.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	0.962	1.120	PASS
	Middle Channel	0.993	1.130	PASS
	High Channel	0.985	1.122	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.181	1.322	PASS
	Middle Channel	1.186	1.326	PASS
	High Channel	1.166	1.310	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.203	1.342	PASS
	Middle Channel	1.190	1.333	PASS
	High Channel	1.200	1.331	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

By adapter(worst case)

FOR BR/EDR

Line Conducted Emission Test Line 1-L



Site: Conduction

Phase: L1

Temperature: 23.1

Limit: FCC Class B Conduction(QP)

Power:

Humidity: 55.4 %

EUT:Bulova Clock with Bluetooth Speaker


M/N:UR-881

Mode: BT Link

Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2816	24.93		6.76	10.28	35.21		17.04	60.77	50.77	-25.56	-33.73	P	
2	0.3980	26.18		11.13	10.33	36.51		21.46	57.89	47.89	-21.38	-26.43	P	
3	0.8417	28.50		9.58	10.33	38.83		19.91	56.00	46.00	-17.17	-26.09	P	
4	1.6377	30.01		10.68	10.34	40.35		21.02	56.00	46.00	-15.65	-24.98	P	
5	2.4380	28.29		9.87	10.40	38.69		20.27	56.00	46.00	-17.31	-25.73	P	
6	4.3338	22.28		3.04	10.28	32.56		13.32	56.00	46.00	-23.44	-32.68	P	

Line Conducted Emission Test Line 2-N




Site: Conduction Phase: **N** Temperature: 23.1
Limit: FCC Class B Conduction(QP) Power: Humidity: 55.4 %
EUT: Bulova Clock with Bluetooth Speaker
M/N: UR-881
Mode: BT Link
Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.4020	28.91		13.61	10.33	39.24		23.94	57.81	47.81	-18.57	-23.87	P	
2	0.7660	29.27		9.99	10.30	39.57		20.29	56.00	46.00	-16.43	-25.71	P	
3	1.2097	29.03		11.91	10.37	39.40		22.28	56.00	46.00	-16.60	-23.72	P	
4	2.3699	26.99		12.26	10.38	37.37		22.64	56.00	46.00	-18.63	-23.36	P	
5	3.8580	25.18		2.50	10.45	35.63		12.95	56.00	46.00	-20.37	-33.05	P	
6	15.4778	12.38		-5.08	10.11	22.49		5.03	60.00	50.00	-37.51	-44.97	P	



APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP







APPENDIX B: PHOTOGRAPHS OF EUT

WHOLE VIEW OF EUT




TOP VIEW OF EUT




BOTTOM VIEW OF EUT




FRONT VIEW OF EUT




BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




VIEW OF EUT (PORT)




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



VIEW OF ADAPTER



----END OF REPORT----