

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	SHENZHEN HUBSAN INTELLIGENT COMPANY LIMITED
Address	:	13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, China. 518054
Equipment under Test	:	FPV Transmitter
Model No	:	FPV1
Trade Mark	:	HUBSAN
FCC ID	:	2AEXYFPV1TX
Manufacturer	:	DONGGUAN TENGSHENG INDUSTRIAL CO., LTD
Address	:	A22# Luyi Street, Tianxin Village, Tangxia Town, Dongguan, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel: +86-0769-22891499 [Http://www.dgddt.com](http://www.dgddt.com)

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	4
2.	General test information.....	5
2.1.	Description of EUT	5
2.2.	Accessories of EUT.....	5
2.3.	Assistant equipment used for test.....	5
2.4.	Block diagram of EUT configuration for test	5
2.5.	Test environment conditions	6
2.6.	Test laboratory.....	6
2.7.	Measurement uncertainty	6
3.	20dB Bandwidth.....	7
3.1.	Test equipment	7
3.2.	Block diagram of test setup	7
3.3.	Limits	7
3.4.	Test Procedure.....	7
3.5.	Test Result.....	8
3.6.	Original test data	8
4.	Radiated emission	10
4.1.	Test equipment	10
4.2.	Block diagram of test setup	10
4.3.	Limit	12
4.4.	Test Procedure.....	13
4.5.	Test result	14
5.	Band Edge Compliance (radiated method)	18
5.1.	Test equipment	18
5.2.	Block diagram of test setup	18
5.3.	Limit	18
5.4.	Test Procedure.....	18
5.5.	Test result	19
6.	Antenna Requirements	23
6.1.	Limit	23
6.2.	Result.....	23
7.	Test setup photograph	24
8.	Photos of the EUT	25

TEST REPORT DECLARE

Applicant	:	SHENZHEN HUBSAN INTELLIGENT COMPANY LIMITED
Address	:	13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen, China. 518054
Equipment under Test	:	FPV Transmitter
Model No	:	FPV1
Trade Mark	:	HUBSAN
FCC ID	:	2AEXYFPV1TX
Manufacturer	:	DONGGUAN TENGSHENG INDUSTRIAL CO., LTD
Address	:	A22# Luyi Street, Tianxin Village, Tangxia Town, Dongguan, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C: 2015

Test procedure used:

ANSI C63.10:2009, ANSI C63.4:2009.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No:	DDT-R15Q0608-3E2		
Date of Test:	June 1, 2015~June 4, 2015	Date of Report:	June 8, 2015

Prepared By:



Leo Liu/Engineer

Approved By:



Kevin Feng/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

1. Summary of test results

Description of Test Item	Standard	Results
20dB Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2009 ANSI C63.4:2009	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.249(d) ANSI C63.10 :2009 ANSI C63.4:2009	PASS
Band Edge Compliance	FCC Part 15: 15.249(d) ANSI C63.10 :2009 ANSI C63.4:2009	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2009 ANSI C63.4:2009	N/A
Note: N/A is an abbreviation for Not Applicable.		

2. General test information

2.1. Description of EUT

EUT* Name	:	FPV Transmitter
Model Number	:	FPV1
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 12V from battery
Operation frequency	:	2410MHz -2465MHz
Modulation	:	GFSK
Data rate	:	N/A
Antenna Type	:	External Dipole Antenna, maximum PK gain: 2dBi
Date of Receipt	:	2015/6/1
Sample Type	:	Series production

Note: EUT is the ab. of equipment under test.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number or Type	Serial No.	Other
/	/	/	/	/

2.3. Assistant equipment used for test

Description of Assistant equipment	Manufacturer	Model number or Type	EMC Compliance	SN
/	/	/	/	/

2.4. Block diagram of EUT configuration for test



Used to control EUT work in Continuous TX mode by key, and select test channel, wireless mode as blow table.

Tested mode, information	
Mode	Frequency (MHz)
Tx Mode	2410
	2435
	2465

2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.6. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808 Tel: +86-0769-22891499 <http://www.dgddt.com>

FCC Registration Number: 270092

2.7. Measurement uncertainty

Test Item	Uncertainty
Occupied Channel Bandwidth	±1%
Temperature	±0.2°C
Humidity	±1%
DC and Low frequency voltage	±0.5%
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.14 dB (Polarize: V)
	3.16 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz to 25GHz)	2.08dB(Polarize: V)
	2.56dB (Polarize: H)
Uncertainty for Conduction emission test	2.44dB
Uncertainty for Radiation Emission test (150KHz-30MHz)	3.21dB


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. 20dB Bandwidth

3.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum analyzer	R&S	FSU	1166.1660.26	2014/10/25	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2014/10/25	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2014/10/25	1 Year

3.2. Block diagram of test setup



3.3. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


3.4. Test Procedure



- (1) Configure EUT and assistant system according clause 2.4 and 4.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

3.5. Test Result

EUT: FPV Transmitter		M/N: FPV1				
Mode	Freq (MHz)	20dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	Limit (MHz)	Margin (MHz)	Conclusion
Tx mode	2410	1.258	/	/	/	PASS
	2435	1.274	/	/	/	PASS
	2465	1.322	/	/	/	PASS
Test Date : 2015/6/2				Test Engineer: Leo		

3.6. Original test data






4. Radiated emission

4.1. Test equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2014/10/25	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2014/10/25	1 Year
3	Loop antenna	TESEQ	HLA6120	20129	2014/11/01	1 Year
4	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2015/04/12	1 Year
5	Double Ridged Horn Antenna	R&S	HF907	100276	2014/11/01	1 Year
6	Horn Antenna	EMCO	3116	00060095	2014/11/01	1 Year
7	Pre-amplifier	A.H.	PAM-1840VH	562	2014/10/25	1 Year
8	RF Cable	R&S	R01	10403	2014/10/25	1 Year
9	RF Cable	R&S	R02	10512	2014/10/25	1 Year
10	Testing software	Audix	E3	6.111111	/	/

4.2. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

4.3. Limit

8.3.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

8.3.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30m}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30m/3m)$$

8.3.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.4. Test Procedure

- (1) EUT height should be 0.8m for below 1GHz at a semi - anechoic chamber while EUT height should be 0.8m for above 1GHz at full chamber or semi - anechoic chamber ground with absorbers.
- (2) Setup EUT and assistant system according clause 2.4 and 8.2
- (3) Test antenna was located 1m/3m from the EUT on an adjustable mast, and the antenna used as below table:

Test frequency range	Test antenna used	Test distance
9KHz-30MHz	Active Loop antenna	3 m
30MHz-1GHz	Trilog Broadband Antenna	3 m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2009 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

- (b) Change work frequency or channel of device if practicable.

- (c) Change modulation type of device if practicable.

- (d) Change power supply range from 85% to 115% of the rated supply voltage

- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9KHz to 18GHz.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to

ANSI C63.10 2009 on Radiated Emission test.

- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 3MHz, VBW is set at 10MHz for Peak measure; RMS detector RBW 3MHz VBW 10MHz for Average measure (according ANSI C63.10:2009 clause 4.2.3.2.3 procedure for average measure).

4.5. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9 KHz to 25GHz were comply with 8.3.2 limit.

Note1: According exploratory test no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.


Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2435MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Radiated Emission test (below 1GHz)**TR-4-E-009 Radiated Emission Test Result**

Test Site : DDT 3m Chamber **E:\2015 Report Data\ID 249 .EM6**
Test Date : 2015-06-02 **Tested By** : Jerry
EUT : FPV Transmitter **Model Number** : FPV1
Power Supply : DC 12V from battery **Test Mode** : TX Mode
Condition : Temp:24.5'C,Humi:55%,
Antenna/Distance : 2014 VULB 9163/3m/VERTICAL
Press:100.1kPa
Memo :

Data: 1



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	162.04	30.05	8.63	1.97	40.65	43.50	-2.85	QP	VERTICAL
2	170.79	24.78	8.83	2.03	35.64	43.50	-7.86	QP	VERTICAL
3	178.13	27.10	9.57	2.07	38.74	43.50	-4.76	QP	VERTICAL
4	216.02	23.98	10.33	2.20	36.51	46.00	-9.49	QP	VERTICAL
5	383.93	25.37	15.58	3.18	44.13	46.00	-1.87	QP	VERTICAL
6	432.55	18.21	15.93	3.33	37.47	46.00	-8.53	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\ID 249 .EM6**
Test Date : 2015-06-02 **Tested By** : Jerry
EUT : FPV Transmitter **Model Number** : FPV1
Power Supply : DC 12V from battery **Test Mode** : TX Mode
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 VULB 9163/3m/HORIZONTAL
Memo :

Data: 2



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	178.13	25.67	9.57	2.07	37.31	43.50	-6.19	QP	HORIZONTAL
2	216.02	30.47	10.33	2.20	43.00	46.00	-3.00	QP	HORIZONTAL
3	270.38	27.97	13.40	2.59	43.96	46.00	-2.04	QP	HORIZONTAL
4	287.99	27.99	14.25	2.67	44.91	46.00	-1.09	QP	HORIZONTAL
5	319.94	20.31	13.78	2.76	36.85	46.00	-9.15	QP	HORIZONTAL
6	383.93	16.13	15.58	3.18	34.89	46.00	-11.11	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Result: Pass.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
Tx mode 2410MHz									
2410.00	94.00	30.04	30.21	5.17	99.00	114.00	-15.00	Peak	HORIZONTAL
2410.00	80.60	30.04	30.21	5.17	85.60	94.00	-8.40	Average	HORIZONTAL
4820.00	44.66	35.42	29.13	8.09	59.04	74.00	-14.96	Peak	HORIZONTAL
4820.00	32.82	35.42	29.13	8.09	47.20	54.00	-6.80	Average	HORIZONTAL
16436.00	36.71	43.62	36.62	13.75	57.46	74.00	-16.54	Peak	HORIZONTAL
16436.00	22.11	43.62	36.62	13.75	42.86	54.00	-11.14	Average	HORIZONTAL
2410.00	101.47	30.04	30.21	5.17	106.47	114.00	-7.53	Peak	VERTICAL
2410.00	86.20	30.04	30.21	5.17	91.20	94.00	-2.80	Average	VERTICAL
4820.00	57.17	35.42	29.13	8.09	71.55	74.00	-2.45	Peak	VERTICAL
4820.00	37.51	35.42	29.13	8.09	51.89	54.00	-2.11	Average	VERTICAL
15943.00	37.31	42.93	36.44	13.68	57.48	74.00	-16.52	Peak	VERTICAL
15943.00	21.61	42.93	36.44	13.68	41.78	54.00	-12.22	Average	VERTICAL
Tx mode 2435MHz									
2435.00	91.90	30.09	30.23	5.24	97.00	114.00	-17.00	Peak	HORIZONTAL
2435.00	76.60	30.09	30.23	5.24	81.70	94.00	-12.30	Average	HORIZONTAL
4870.00	42.93	35.51	29.08	8.14	57.50	74.00	-16.50	Peak	HORIZONTAL
4870.00	30.19	35.51	29.08	8.14	44.76	54.00	-9.24	Average	HORIZONTAL
16419.00	36.20	43.60	36.62	13.75	56.93	74.00	-17.07	Peak	HORIZONTAL
16419.00	21.41	43.60	36.62	13.75	42.14	54.00	-11.86	Average	HORIZONTAL
2435.00	96.74	30.09	30.23	5.24	101.84	114.00	-12.16	Peak	VERTICAL
2435.00	81.10	30.09	30.23	5.24	86.20	94.00	-7.80	Average	VERTICAL
4870.00	49.12	35.51	29.08	8.14	63.69	74.00	-10.31	Peak	VERTICAL
4870.00	35.59	35.51	29.08	8.14	50.16	54.00	-3.84	Average	VERTICAL
16470.00	36.30	43.66	36.63	13.76	57.09	74.00	-16.91	Peak	VERTICAL
16470.00	21.79	43.66	36.63	13.76	42.58	54.00	-11.42	Average	VERTICAL
Tx mode 2465MHz									
2465.00	92.26	30.20	30.25	5.31	97.52	114.00	-16.48	Peak	HORIZONTAL
2465.00	79.50	30.20	30.25	5.31	84.76	94.00	-9.24	Average	HORIZONTAL
4930.00	41.45	35.59	29.06	8.16	56.14	74.00	-17.86	Peak	HORIZONTAL
4930.00	29.10	35.59	29.06	8.16	43.79	54.00	-10.21	Average	HORIZONTAL
16827.00	36.01	43.63	36.85	13.84	56.63	74.00	-17.37	Peak	HORIZONTAL
16827.00	21.51	43.63	36.85	13.84	42.13	54.00	-11.87	Average	HORIZONTAL
2465.00	97.71	30.20	30.25	5.31	102.97	114.00	-11.03	Peak	VERTICAL
2465.00	80.60	30.20	30.25	5.31	85.86	94.00	-8.14	Average	VERTICAL
4930.00	52.27	35.59	29.06	8.16	66.96	74.00	-7.04	Peak	VERTICAL
4930.00	36.10	35.59	29.06	8.16	50.79	54.00	-3.21	Average	VERTICAL
16487.00	35.97	43.68	36.65	13.77	56.77	74.00	-17.23	Peak	VERTICAL
16487.00	21.19	43.68	36.65	13.77	41.99	54.00	-12.01	Average	VERTICAL

Note: Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


Result: Pass.

5. Band Edge Compliance (radiated method)

5.1. Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2014/10/25	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2014/10/25	1 Year
3	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2015/04/12	1 Year
4	Double Ridged Horn Antenna	R&S	HF907	100276	2014/11/01	1 Year
5	Pre-amplifier	A.H.	PAM0-0118	360	2014/10/25	1 Year
6	RF Cable	R&S	R01	10403	2014/10/25	1 Year
7	RF Cable	R&S	R02	10512	2014/10/25	1 Year
8	Testing software	Audix	E3	6.111111	/	/

5.2. Block diagram of test setup



5.3. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

5.4. Test Procedure

Same with clause 4.4 except change investigated frequency range from 2310MHz to 2415MHz and 2475MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.


5.5. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	E:\2015 Report Data\FPV1 249 .EM6
Test Date	: 2015-06-02	Tested By : Jerry
EUT	: FPV Transmitter	Model Number : FPV1
Power Supply	: DC 12V from battery	Test Mode : TX 2410MHz
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	Antenna/Distance : 2014 HF907/3m/HORIZONTAL
Memo	:	

Data: 9



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2400.00	60.79	29.99	30.21	5.17	65.74	74.00	-8.26	Peak	HORIZONTAL
2	2400.00	45.40	29.99	30.21	5.17	50.35	54.00	-3.65	Average	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 3 MHz, VBW: 10 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:** \2015 Report Data\FPV1 249 .EM6
Test Date : 2015-06-02 **Tested By** : Jerry
EUT : FPV Transmitter **Model Number** : FPV1
Power Supply : DC 12V from battery **Test Mode** : TX 2410MHz
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/VERTICAL
Memo :

Data: 10



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2400.00	68.44	29.99	30.21	5.17	73.39	74.00	-0.61	Peak	VERTICAL
2	2400.00	46.90	29.99	30.21	5.17	51.85	54.00	-2.15	Average	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 3 MHz, VBW: 10 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\FPV1 249 .EM6**
Test Date : 2015-06-02 **Tested By** : Jerry
EUT : FPV Transmitter **Model Number** : FPV1
Power Supply : DC 12V from battery **Test Mode** : TX 2465MHz
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/VERTICAL
Memo :

Data: 11



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	59.50	30.25	30.25	5.31	64.81	74.00	-9.19	Peak	VERTICAL
2	2483.50	43.60	30.25	30.25	5.31	48.91	54.00	-5.09	Average	VERTICAL
3	2490.38	57.48	30.30	30.25	5.31	62.84	74.00	-11.16	Peak	VERTICAL
4	2490.38	42.60	30.30	30.25	5.31	47.96	54.00	-6.04	Average	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 3 MHz, VBW: 10 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **E:\2015 Report Data\FPV1 249 .EM6**
Test Date : 2015-06-02 **Tested By** : Jerry
EUT : FPV Transmitter **Model Number** : FPV1
Power Supply : DC 12V from battery **Test Mode** : TX 2465MHz
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2014 HF907/3m/HORIZONTAL
Memo :

Data: 12



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	49.06	30.25	30.25	5.31	54.37	74.00	-19.63	Peak	HORIZONTAL
2	2483.50	33.90	30.25	30.25	5.31	39.21	54.00	-14.79	Average	HORIZONTAL
3	2484.44	49.57	30.25	30.25	5.31	54.88	74.00	-19.12	Peak	HORIZONTAL
4	2484.44	33.60	30.25	30.25	5.31	38.91	54.00	-15.09	Average	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 3 MHz, VBW: 10 MHz, Sweep time: auto.

6. Antenna Requirements

6.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2. Result

The antennas used for this product is External Dipole antenna with SMA-B connector and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 2 dBi.