



RADIO TEST REPORT

Report No: STS1506051F02

Issued for

Jolla Ltd.

Kalevantie 2, Tampere, Finland

Product Name:	Tablet computer
Brand Name:	Jolla
Model No.:	JT-1501
Series Model:	N/A
FCC ID:	2AEZWJT-1501
IC:	20283-JT1501
Test Standard:	FCC Part 15.247 RSS 247 Issue 1

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented test sample.





TEST RESULT CERTIFICATION

Applicant's name..... : Jolla Ltd.
Address..... : Kalevantie 2, Tampere, Finland
Manufacture's Name : Borqs BeiJing Ltd.
Address..... : Tower A, Building B23, Universal Business Park, No. 10
Jiuxianqiao Road, Chaoyang District Beijing, 100015 China

Product description

Product name..... : Tablet computer

Model and/or type reference : JT-1501

Serial Model : N/A

Standards..... : FCC Part 15.247
RSS 247 Issue 1

Test procedure..... : ANSI C63.10-2013

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date (s) of performance of tests..... : 11 June. 2015 ~18 June. 2015

Date of Issue : 19 June. 2015

Test Result : **Pass**

Testing Engineer :

(Jin Ming)

Technical Manager :

(Vita Li)

Authorized Signatory :

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST	11
2.4 DESCRIPTION OF SUPPORT UNITS	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST RESULT	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 TEST SETUP	18
3.2.4 EUT OPERATING CONDITIONS	19
3.2.5 TEST RESULT	20
4. CONDUCTED SPURIOUS EMISSIONS	26
4.1 APPLIED PROCEDURES / LIMIT	26
4.2 TEST PROCEDURE	26
4.3 DEVIATION FROM STANDARD	26
4.4 TEST SETUP	26
4.5 EUT OPERATION CONDITIONS	26
4.6 TEST RESULTS	27
5. POWER SPECTRAL DENSITY TEST	36
5.1 APPLIED PROCEDURES / LIMIT	36
5.2 TEST PROCEDURE	36
5.3 DEVIATION FROM STANDARD	36
5.4 TEST SETUP	36
5.5 EUT OPERATION CONDITIONS	36
5.6 TEST RESULTS	37
6. BANDWIDTH TEST	43



Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	43
6.2 TEST PROCEDURE	43
6.3 DEVIATION FROM STANDARD	43
6.4 TEST SETUP	43
6.5 EUT OPERATION CONDITIONS	43
6.6 TEST RESULTS	44
7. PEAK OUTPUT POWER TEST	50
7.1 APPLIED PROCEDURES / LIMIT	50
7.2 TEST PROCEDURE	50
7.3 DEVIATION FROM STANDARD	50
7.4 TEST SETUP	50
7.5 EUT OPERATION CONDITIONS	50
7.6 TEST RESULTS	51
8. ANTENNA REQUIREMENT	52
8.1 STANDARD REQUIREMENT	52
8.2 EUT ANTENNA	52
APPENDIX - PHOTOS OF TEST SETUP	53

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	19 June. 2015	STS1506051F02	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) RSS 247, Subpart C				
Standard Section		Test Item	Judgment	Remark
15.207	RSS-Gen Issue 3: 7.2.4	Conducted Emission	PASS	
15.247 (a)(2)	RSS-247 Issue 5 (5.2)	6dB&99% Bandwidth	PASS	
15.247 (b) (reference KDB 558074 d05 v02. /9.1.2)	RSS-247 Issue 5 (5.2)	Peak Output Power	PASS	
15.247 (c)	RSS-247 Issue 5 (5.5)	Radiated Spurious Emission	PASS	
15.247 (d)	RSS-247 Issue 5 (5.5)	Conducted Spurious Emission	PASS	
15.247 (e)	RSS-247 Issue 5 (5.2)	Power Spectral Density	PASS	
15.205	RSS-247 Issue 5 (5.5)	Band Edge Emission	PASS	
15.203	RSS-Gen Issue 3: 7.1.2	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
6	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
7	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
8	Temperature	$\pm 0.5^{\circ}\text{C}$
9	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Tablet computer	
Trade Name	Jolla	
Model Name	JT-1501	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Tablet computer	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz):300/150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20: 11CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	0 dBi
Channel List	Please refer to the Note 2.	
Ratings	DC 3.8V from battery	
Adapter	Input: AC100-240V, 200mA, 50/60 Hz Output: DC5V, 1500mA	
Battery	Battery: Rated Voltage:3.8V Charge Limit: 4.35V capacity : 4450mA	
Hardware version number	N/A	
Software versioning number	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	PIFA Antenna	N/A	0	N/A





2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging+ Keeping TX Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Charging+ Keeping TX Mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging+ Keeping TX Mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Tablet computer	Jolla	JT-1501	N/A	EUT
E-2	Adapter	LEAGOO	V50	N/A	Input : AC100-240V, 200mA, 50/60 Hz Output: DC5V, 1500mA
E-3	Earphone	N/A	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	unshielded	NO	100cm	N/A
C-2	unshielded	NO	145cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2014.10.25	2015.10.24
Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2014.11.25	2015.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2015.03.06	2016.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
PreAmplifier	Agilent	8449B	60538	2014.10.25	2015.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2014.10.25	2015.10.24

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2014.11.20	2015.11.19
LISN	R&S	ENV216	101242	2014.10.25	2015.10.24



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver



3.1.2 TEST RESULT


EUT:	Tablet computer	Model Name.:	JT-1501
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	DC 5V from adapter	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1735	32.91	10.00	42.91	64.79	-21.88	QP
0.1735	19.27	10.00	29.27	54.79	-25.52	AVG
0.2960	24.65	9.90	34.55	60.35	-25.80	QP
0.2960	15.13	9.90	25.03	50.35	-25.32	AVG
0.9906	20.46	9.90	30.36	56.00	-25.64	QP
0.9906	12.20	9.90	22.10	46.00	-23.90	AVG
3.9800	27.19	10.19	37.38	56.00	-18.62	QP
3.9800	13.79	10.19	23.98	46.00	-22.02	AVG
11.4998	21.53	10.37	31.90	60.00	-28.10	QP
11.4998	11.77	10.37	22.14	50.00	-27.86	AVG
14.1565	16.73	10.32	27.05	60.00	-32.95	QP
14.1565	8.43	10.32	18.75	50.00	-31.25	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV






EUT:	Tablet computer	Model Name.:	JT-1501
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Voltage:	DC 5V from adapter	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1945	37.14	10.00	47.14	63.84	-16.70	QP
0.1945	22.46	10.00	32.46	53.84	-21.38	AVG
0.2487	32.98	9.95	42.93	61.80	-18.87	QP
0.2487	19.58	9.95	29.53	51.80	-22.27	AVG
0.3384	25.17	9.94	35.11	59.24	-24.13	QP
0.3384	13.30	9.94	23.24	49.24	-26.00	AVG
1.7122	17.51	10.00	27.51	56.00	-28.49	QP
1.7122	9.74	10.00	19.74	46.00	-26.26	AVG
3.8831	22.84	10.20	33.04	56.00	-22.96	QP
3.8831	15.01	10.20	25.21	46.00	-20.79	AVG
11.5473	21.23	10.30	31.53	60.00	-28.47	QP
11.5473	11.82	10.30	22.12	50.00	-27.88	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

6 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&205(a), then the Part 15.247&209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10 th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz / 10Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz




(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.





3.2.5 TEST RESULT

9KHz-30MHz

EUT:	Tablet computer	Model Name. :	JT-1501
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	Link mode	Polarization :	--


Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.





30MHz - 1000MHz

EUT:	Tablet computer	Model Name. :	JT-1501
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	Mode 4	Polarization :	Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
31.9545	5.52	17.68	23.20	40.00	-16.80	QP
61.1315	15.47	5.39	20.86	40.00	-19.14	QP
110.1816	5.95	11.28	17.23	43.50	-26.27	QP
171.3925	12.85	10.45	23.30	43.50	-20.20	QP
253.8367	14.31	14.23	28.54	46.00	-17.46	QP
900.1473	7.79	26.61	34.40	46.00	-11.60	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m






30MHz - 1000MHz

EUT:	Tablet computer	Model Name. :	JT-1501
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	Mode 4	Polarization :	Vertical

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
30.2110	4.78	18.60	23.38	40.00	-16.62	QP
64.8864	12.11	5.66	17.77	40.00	-22.23	QP
136.9391	7.79	12.55	20.34	43.50	-23.16	QP
176.8877	17.92	10.23	28.15	43.50	-15.35	QP
236.6447	16.13	11.41	27.54	46.00	-18.46	QP
472.1760	12.48	19.73	32.21	46.00	-13.79	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.





Above 1000MHz

EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from adapter

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11b/2412 MHz)							
4824.20	66.14	-3.58	62.56	74	-11.44	PK	Vertical
4824.22	46.86	-3.58	43.28	54	-10.72	AV	Vertical
7236.14	61.70	-0.8	60.9	74	-13.1	PK	Vertical
7236.12	41.27	-0.8	40.47	54	-13.53	AV	Vertical
4824.20	61.77	-3.58	58.19	74	-15.81	PK	Horizontal
4824.22	44.16	-3.58	40.58	54	-13.42	AV	Horizontal
Mid Channel (802.11b/2437 MHz)							
4874.08	64.89	-3.56	61.33	74	-12.67	PK	Vertical
4874.07	49.12	-3.56	45.56	54	-8.44	AV	Vertical
7311.21	60.70	-0.78	59.92	74	-14.08	PK	Vertical
7311.21	43.82	-0.78	43.04	54	-10.96	AV	Vertical
4874.18	61.39	-3.56	57.83	74	-16.17	PK	Horizontal
4874.14	44.96	-3.56	41.4	54	-12.6	AV	Horizontal
High Channel (802.11b/2462 MHz)							
4944.26	61.14	-3.54	57.6	74	-16.4	PK	Vertical
4944.30	45.04	-3.54	41.5	54	-12.5	AV	Vertical
7416.33	61.01	-0.75	60.26	74	-13.74	PK	Vertical
7416.30	45.06	-0.75	44.31	54	-9.69	AV	Vertical
4944.26	60.88	-3.54	57.34	74	-16.66	PK	Horizontal
4944.30	45.28	-3.54	41.74	54	-12.26	AV	Horizontal
Remark: 1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. 2. Scan with 802.11b, 802.11g, 802.11n (HT-20), 802.11n (HT-40), the worst case is 802.11b.							



3.2.6 TEST RESULTS (Band edge)

EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from adapter

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11 b							
2399.9	67.91	-12.99	54.92	74	-19.08	PK	Vertical
2399.9	53.86	-12.99	40.87	54	-13.13	AV	Vertical
2399.9	69.09	-12.99	56.1	74	-17.9	PK	Horizontal
2399.9	52.95	-12.99	39.96	54	-14.04	AV	Horizontal
2483.6	70.04	-12.78	57.26	74	-16.74	PK	Vertical
2483.6	52.81	-12.78	40.03	54	-13.97	AV	Vertical
2483.6	70.20	-12.78	57.42	74	-16.58	PK	Horizontal
2483.6	52.69	-12.78	39.91	54	-14.09	AV	Horizontal
802.11 g							
2399.9	67.71	-12.99	54.72	74	-19.28	PK	Vertical
2399.9	53.80	-12.99	40.81	54	-13.19	AV	Vertical
2399.9	68.90	-12.99	55.91	74	-18.09	PK	Horizontal
2399.9	52.89	-12.99	39.9	54	-14.1	AV	Horizontal
2483.6	69.92	-12.78	57.14	74	-16.86	PK	Vertical
2483.6	53.26	-12.78	40.48	54	-13.52	AV	Vertical
2483.6	69.99	-12.78	57.21	74	-16.79	PK	Horizontal
2483.6	53.07	-12.78	40.29	54	-13.71	AV	Horizontal



802.11 n20							
2399.9	67.89	-12.99	54.9	74	-19.1	PK	Vertical
2399.9	53.79	-12.99	40.8	54	-13.2	AV	Vertical
2399.9	68.71	-12.99	55.72	74	-18.28	PK	Horizontal
2399.9	52.83	-12.99	39.84	54	-14.16	AV	Horizontal
2483.6	69.85	-12.78	57.07	74	-16.93	PK	Vertical
2483.6	52.63	-12.78	39.85	54	-14.15	AV	Vertical
2483.6	69.83	-12.78	57.05	74	-16.95	PK	Horizontal
2483.6	53.11	-12.78	40.33	54	-13.67	AV	Horizontal
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							
Low measurement frequencies is range from 2310 to 2400 MHz, high measurement frequencies is range from 2483.5 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.							

4. CONDUCTED SPURIOUS EMISSIONS

4.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



4.6 TEST RESULTS


EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX b Mode /CH01, CH06, CH11		

CH 01






CH 06




CH 11






Band edge

CH 01




CH 11






EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX g Mode /CH01, CH06, CH11		

CH 01




CH06






CH 11






Band edge

CH 01




CH11






EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

CH 01




CH 06






CH 11






Band edge

CH 01



CH 11





5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULTS


EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-6.516	8	PASS
2437 MHz	-6.154	8	PASS
2462 MHz	-5.810	8	PASS






TX CH06



TX CH11






EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-10.09	8	PASS
2437 MHz	-9.906	8	PASS
2462 MHz	-9.485	8	PASS

TX CH01






TX CH06




TX CH11






EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-10.55	8	PASS
2437 MHz	-9.815	8	PASS
2462 MHz	-9.243	8	PASS






TX CH06



TX CH11





6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) &RSS-210 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


6.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




6.6 TEST RESULTS

EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	7.219	12.084	>=500KHz	PASS
2437 MHz	7.219	12.137	>=500KHz	PASS
2462 MHz	7.625	12.237	>=500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	15.924	16.596	>=500KHz	PASS
2437 MHz	15.980	16.567	>=500KHz	PASS
2462 MHz	15.963	16.570	>=500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	17.410	17.559	>=500KHz	PASS
2437 MHz	16.594	17.561	>=500KHz	PASS
2462 MHz	17.322	17.552	>=500KHz	PASS

TX CH 01






TX CH 06



TX CH 11





7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

- The EUT was directly connected to the Power Sensor&Power meter

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULTS

EUT :	Tablet computer	Model Name :	JT-1501
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.8V
Test Mode :	TX b/g/n(20M,40M) Mode /CH01, CH06, CH11		

TX 802.11b Mode			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	18.04	30
CH06	2437	16.90	30
CH11	2462	17.28	30

TX 802.11g Mode			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	17.56	30
CH06	2437	17.67	30
CH11	2462	17.94	30

TX 802.11n20 Mode			
Test Channe	Frequency	Peak Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	15.60	30
CH06	2437	16.05	30
CH11	2462	16.18	30



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


8.2 EUT ANTENNA

The EUT antenna is permanent attach Antenna. It comply with the standard requirement.



APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos



Conducted Measurement Photos



*****END OF THE REPORT*****