

Report Number: F690501/RF-RTL013471

Page:

1

of

6

# **TEST REPORT**

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2AF4X-VRPF1000

Equipment Under Test : VARRAM PET FITNESS

Model Name : VRPF1000

Applicant : VARRAM SYSTEM Co., Ltd.

Manufacturer : VARRAM SYSTEM Co., Ltd.

Date of Receipt : 2019.01.02

Date of Test(s) : 2019.01.15 ~ 2019.01.28

Date of Issue : 2019.01.28

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2019.01.28

Murphy Kim

Hyunchae You

Technical Manager:

Date:

2019.01.28



Report Number: F690501/RF-RTL013471 Page: 2 of 6

## **INDEX**

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL013471 Page: 3 of 6

#### 1. General Information

## 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a>.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

## 1.2. Details of applicant

Applicant : VARRAM SYSTEM Co., Ltd.

Address : 57, Techno 11-ro, Yuseong-gu, Daejeon, Korea

Contact Person : Jung, Ju-yong Phone No. : +82 70 8797 8920

#### 1.3. Details of manufacturer

Company : Same as applicant Address : Same as applicant

### 1.4. Description of EUT

Kind of Product	VARRAM PET FITNESS
Model Name	VRPF1000
Power Supply	DC 3.7 V
Frequency Range	2 402 Mb ~ 2 480 Mb (Bluetooth Low Energy)
Modulation Technique	GFSK
Number of Channels	40 channels (Bluetooth Low Energy)
Antenna Type	DIELECTRIC CHIP Antenna
Antenna Gain	0.50 dB i



Report Number: F690501/RF-RTL013471 Page: 4 of 6

## 1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL013471	2019.01.28	Initial



Report Number: F690501/RF-RTL013471 Page: 5 of 6

## 2. RF Exposure Evaluation

## 2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (⊪W/c㎡)	Average Time	
(A) Limits for Occupational/Controlled Exposure					
0.3 – 3.0	614	1.63	*100	6	
3.0 – 30	1842/f	4.89/f	*900/f <sup>2</sup>	6	
30 – 300	61.4	0.163	1.0	6	
300 – 1 500	-	-	f/300	6	
1 500 – 100 000	-	-	5	6	
(B) Limits for General Population/Uncontrolled Exposure					
0.3 – 1.34	614	1.63	*100	30	
1.34 – 30	824/f	2.19/f	*180/f <sup>2</sup>	30	
30 – 300	27.5	0.073	0.2	30	
300 – 1 500	-	-	f/1500	30	
<u>1 500 – 100 000</u>	-	-	<u>1.0</u>	<u>30</u>	

## 2.1.1. Friis transmission formula: Pd = (Pout\*G)/(4\*pi\*R<sup>2</sup>)

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report Number: F690501/RF-RTL013471 Page: 6 of 6

#### 2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

#### 2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

- Maximum tune up tolerance

Operating Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm²)	Limits (ﷺ)
2 402 ~ 2 480	-7.5	0.5	0.000 040	1

#### Remark:

- The power density Pd (5th column) at a distance of 20  $\,^{\rm cm}$  calculated from the friis transmission formula is far below the limit of 1  $\,^{\rm mW/cm^2}$ .
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20  $\,$  cm  $\,$  between the radiator and your body.
- The antenna gain of this transmitter is less than  $6\,\mathrm{dB}\,i$  and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

## - End of the Test Report -