

Report Number: F690501-RF-RTL000314

Page:

1

of

5

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: 2AF4X-VRTC1000

Equipment Under Test : VARRAM360

Model Name : VRTC1000

FCC Applicant : VARRAM SYSTEM Co., Ltd.

Manufacturer : VARRAM SYSTEM Co., Ltd.

Date of Receipt : 2019.12.23

Date of Test(s) : 2019.12.24 ~ 2020.02.06

Date of Issue : 2020.02.21

In the configuration tested, the EUT complied with the standards specified above

Tested By:

Date:

2020.02.21

Jinhyoung Cho

Jungmin Yang

Technical

Manager:

Date:

2020.02.21

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501-RF-RTL000314 Page: 2 of 5

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	4



Report Number: F690501-RF-RTL000314 Page: 3 of 5

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : VARRAM SYSTEM Co., Ltd.

Address : 57, Techno 11-ro, Yuseong-gu, Daejeon, South Korea, 34036

Contact Person : Jung, Ju-yong Phone No. : +82 10 6342 9876

1.3. Details of Manufacturer

Company : Same as applicant Address : Same as applicant

1.4. Description of EUT

Kind of Product	VARRAM360	
Model Name	VRTC1000	
Power Supply	DC 3.6 V	
Frequency Range	2 412 Mb ~ 2 462 Mb (11b/g/n_HT20) 2 422 Mb ~ 2 452 Mb (11n_HT40)	
Modulation Technique	DSSS, OFDM	
Number of Channels	11 channels (11b/g/n_HT20) 7 channels (11n_HT40)	
Antenna Type	ntenna Type Dielectric Chip Antenna	
Antenna Gain	0.50 dB i	

1.5. Test Report Revision

Revision	Report Number	Date of Issue	Description
0	F690501-RF-RTL000314	2020.02.21	Initial

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501-RF-RTL000314 Page: 4 of 5

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (쌘)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm)	Average Time		
(A) Limits for Occupational/Controlled Exposure						
0.3-3.0	614	1.63	*100	6		
3.0-30	1842/f 4.89/f *		*900/f ²	6		
30-300	30-300 61.4 0.163		1.0 6			
300-1 500	-	-	f/300	6		
1 500-100 000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*100	30		
1.34-30	824/f	2.19/f	*180/f ²	30		
30-300	27.5	0.073	0.2	30		
300-1 500	-	-	f/1500	30		
<u>1 500-100 000</u>	-	-	1.0	<u>30</u>		

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results of this test report are effective only to the items tested. The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501-RF-RTL000314 Page: 5 of 5

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

WLAN (2.4G)

- Maximum tune up tolerance

Frequency Range	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm²)	Limits (ﷺ)
2 412 ~ 2 462	17.82	0.50	0.013 512	1

Remark;

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than $6\,\mathrm{dB}\,\mathrm{i}$ and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.
- According to KDB 447498 D01 RF Exposure Guidance 4.1.d, Output Average Power to Antenna applied Maximum Tune up power considering tolerance.

- End of the Test Report -