Report No.: NTC1702231FV00

FCC ID: 2AF52626



RADIO TEST REPORT

The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

Applicant

: KING PROFIT TRADING LTD.

Address

: Flat 06, 19/F, Laurels Industrial Centre, 32 Tai Yau st., San Po Kong,

Kowloon, Hong Kong

Manufacturer/Factory

: DONG GUAN YUNG FU ELECTRONICS LTD.

Address

: No.3 Lian Sheng Industrial Area, Deng Wu Village, Qiao Tou Town,

DongGuan City, Guangdong, China

E.U.T.

: PORTABLE SOUND SYSTEM

Brand Name

: KING PROFIT, TOSHIBA

Model No.

: KP626BT, TY-ASC40 (For model difference refer to section 1)

FCC ID

: 2AF52626

Measurement Standard : FCC PART 15.247: 2016

Date of Receiver

: February 27, 2017

Date of Test

: February 27, 2017 to March 20, 2017

Date of Report

: March 20, 2017

This Test Report is Issued Under the Authority of :

Prepared by

Alina Guo / Engineer

d Signer Approve

Iori Far Signatory

This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1702231FV00 FCC ID: 2AF52626



Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	
1.3 TEST METHODOLOGY	7
1.4 EQUIPMENT MODIFICATIONS	7
1.5 Support Device	
1.6 TEST FACILITY AND LOCATION	
1.7 SUMMARY OF TEST RESULTS	
2. SYSTEM TEST CONFIGURATION	9
2.1 EUT CONFIGURATION	g
2.2 SPECIAL ACCESSORIES	g
2.3 DESCRIPTION OF TEST MODES	
2.4 EUT EXERCISE	
3. CONDUCTED EMISSIONS TEST	10
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	10
3.2 TEST CONDITION	10
3.3 MEASUREMENT RESULTS	10
4. RADIATED EMISSION TEST	13
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
4.2 MEASUREMENT PROCEDURE	14
4.3 LIMIT	14
4.4 MEASUREMENT RESULTS	15
5. CHANNEL SEPARATION TEST	19
5.1 MEASUREMENT PROCEDURE	19
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
5.3 MEASUREMENT RESULTS	19
6. 20DB BANDWIDTH	25
6.1 MEASUREMENT PROCEDURE	25
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	25
6.3 MEASUREMENT RESULTS	25
7. HOPPING CHANNEL NUMBER	31
7.1 MEASUREMENT PROCEDURE	31
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	31
7.3 Measurement Results	31

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1702231FV00 FCC ID: 2AF52626



8. TIME OF OCCUPANCY (DWELL TIME)	33
8.1 MEASUREMENT PROCEDURE	33
8.2 MEASUREMENT RESULTS	33
9. MAXIMUM PEAK OUTPUT POWER	33
9.1 MEASUREMENT PROCEDURE	39
9.2 MEASUREMENT RESULTS	
10. BAND EDGE	39
10.1 MEASUREMENT PROCEDURE	45
10.2 LIMIT	
10.3 MEASUREMENT RESULTS	45
11. ANTENNA APPLICATION	45
11.1 ANTENNA REQUIREMENT	52
11.2 MEASUREMENT RESULTS	
12. CONDUCTED SPURIOUS EMISSIONS	53
12.1 MEASUREMENT PROCEDURE	53
12.2. MEASUREMENT RESULTS	
13. TEST EQUIPMENT LIST	

Dongguan Nore Testing Center Co., Ltd. Report No.: NTC1702231FV00 FCC ID: 2AF52626



Revision History of This Test Report

Report Number	Description	Issued Date
NTC1702231FV00	Initial Issue	2017-03-20

Report No.: NTC1702231FV00

FCC ID: 2AF52626



1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a Bluetooth speaker, it's powered by AC mains or DC 12V come from internal battery. For more details features, please refer to User's Manual.

Power Supply : AC 100-240V 50/60Hz

DC 12V come from internal battery

Adapter : None

Test voltage : AC 120V 60Hz, AC 240V 50Hz

DC 12V From internal battery

Only the worst case was recorded in the report.

Model name : KP626BT, TY-ASC40

All tests were carried on model KP626BT.

Model difference : Both of models have the same circuit schematic.

construction, PCB Layout and critical components.

Their difference in model number and brand

name due to trading purpose.

Hardware version : V4.0

Software version : V3.0

Serial number : N/A

Note : None

Technical parameters

For BT function

Item	BT Version: BT2.1+EDR
Frequency	2402-2480MHz
Modulation	GFSK, π/4-DQPSK, 8DPSK
Number of Channel	79
Channel space	1MHz
Antenna Type	PCB antenna
Antenna Gain	0 dBi

FCC ID: 2AF52626



BT 2.1+EDR Channel List

Channel	Frequency MHz	Channel	Frequency MHz	Channel	Frequency MHz	Channel	Frequency MHz
1	2402	21	2422	41	2442	61	2462
2	2403	22	2423	42	2443	62	2463
3	2404	23	2424	43	2444	63	2464
4	2405	24	2425	44	2445	64	2465
5	2406	25	2426	45	2446	65	2466
6	2407	26	2427	46	2447	66	2467
7	2408	27	2428	47	2448	67	2468
8	2409	28	2429	48	2449	68	2469
9	2410	29	2430	49	2450	69	2470
10	2411	30	2431	50	2451	70	2471
11	2412	31	2432	51	2452	71	2472
12	2413	32	2433	52	2453	72	2473
13	2414	33	2434	53	2454	73	2474
14	2415	34	2435	54	2455	74	2475
15	2416	35	2436	55	2456	75	2476
16	2417	36	2437	56	2457	76	2477
17	2418	37	2438	57	2458	77	2478
18	2419	38	2439	58	2459	78	2479
19	2420	39	2440	59	2460	79	2480
20	2421	40	2441	60	2461		

Note: According to section 15.31(m), regards to the operating frequency range over 10MHz, the Lowest, middle, and the Highest frequency of channel were selected to perform the test. The selected frequency and test software see below:

Channel	Frequency MHz
1	2402
40	2441
79	2480

Report No.: NTC1702231FV00

FCC ID: 2AF52626



1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AF52626 filing to comply with Section 15.247 of the FCC Part 15 (2016), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

Notebook PC : Manufacturer: IBM Corporation

M/N: R50e

S/N: L3-HZNGO P/N: 1834KDC

Adapter : Manufacturer: IBM Corporation

(For Notebook PC) M/N: 08K8210

Input: AC100-240V 50/60Hz 0.5-1.0A

Output: DC 16V 4.5A

Report No.: NTC1702231FV00

FCC ID: 2AF52626



1.6 Test Facility and Location

Listed by CNAS, August 14, 2015
The certificate is valid until August 13, 2018
The Laboratory has been assessed and proved to be in compliance with CNAS/CL01
The Certificate Registration Number is L5795.

Listed by FCC, July 03, 2014
The Certificate Registration Number is 665078.
Listed by Industry Canada, June 18, 2014
The Certificate Registration Number is 46405-9743.

Dongguan NTC Co., Ltd.

(Full Name: Dongguan Nore Testing Center Co., Ltd.)

Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong, China (Full Name: Building D, Gaosheng Science & Technology Park, Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.

1.7 Summary of Test Results

FCC Rules	Description Of Test	Uncertainty	Result
§15.247(a)(1)	Channel Separation test	±1.42 x10 ⁻⁴ %	Compliant
§15.247(a)(1)	20dB Bandwidth	±1.42 x10 ⁻⁴ %	Compliant
§15.247(a)(1)(iii)	Hopping Channel Number	±1.42 x10 ⁻⁴ %	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	±5%	Compliant
§15.247(b)	Max Peak output Power test	±1.06dB	Compliant
§15.247(d)	Band edge test	±1.70dB	Compliant
§15.207 (a)	AC Power Conducted Emission	±1.06dB	Compliant
§15.247(d),§15.209, §15.205	Radiated Emission	±3.70dB	Compliant
§15.203	Antenna Requirement	±0.60dB	Compliant
§15.247(d)	Conducted Spurious Emission	±2.51dB	Compliant

Report No.: NTC1702231FV00

FCC ID: 2AF52626



2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing, and all packets DH1, DH3 and DH5 mode in all modulation type GFSK, $\pi/4$ -DQPSK, 8DPSK were tested.

2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.


Report No.: NTC1702231FV00

FCC ID: 2AF52626



3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: Charging+BT Link

3.3 Measurement Results

Please refer to following plots of the worst case: GFSK Middle channel.

Report No.: NTC1702231FV00

FCC ID: 2AF52626




Site: Conduction



Dongguan NTC Co., Ltd. Tel: +86-769-22022444 Fax: +86-769-22022799

g Center Web: Http://www.ntc-c.com

Test Time: 2017-2-28 13:30:56



Phase:

Report No.: KP626BT

Test Standard: FCC PART 15C_QP Test item: **Conducted Emission**

Applicant: 25(C) / 50 % King Profit Temp.()/Hum.(%):

PROTABLE SOUND SYSTEM AC 120V/60Hz Product: Power Rating: Model No.: KP626BT Test Engineer: Lueng

Test Mode: Charging+BT Link

Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	10.80	41.00	51.80	65.99	-14.19	QP	Р	
2	0.1500	10.80	26.00	36.80	55.99	-19.19	AVG	Р	
3	0.1740	10.80	37.80	48.60	64.76	-16.16	QP	Р	
4	0.1740	10.80	23.90	34.70	54.76	-20.06	AVG	Р	
5	0.1980	10.80	35.50	46.30	63.69	-17.39	QP	Р	
6	0.1980	10.80	19.20	30.00	53.69	-23.69	AVG	Р	
7	0.2260	10.80	30.40	41.20	62.59	-21.39	QP	Р	
8	0.2260	10.80	15.70	26.50	52.59	-26.09	AVG	Р	
9	0.5299	10.80	31.90	42.70	56.00	-13.30	QP	Р	
10	0.5299	10.80	26.90	37.70	46.00	-8.30	AVG	Р	
11	13.0899	10.80	28.10	38.90	60.00	-21.10	QP	Р	
12	13.0899	10.80	19.40	30.20	50.00	-19.80	AVG	Р	

Report No.: NTC1702231FV00

FCC ID: 2AF52626




Site: Conduction



Dongguan NTC Co., Ltd. Tel: +86-769-22022444 Fax: +86-769-22022799

ting Center Web: Http://www.ntc-c.com

Test Time: 2017-2-28 13:21:17



Report No.: KP626BT

Test Standard: FCC PART 15C_QP Test item: **Conducted Emission**

Applicant: King Profit Temp.()/Hum.(%): 25(C) / 50 %

Phase:

Product: PROTABLE SOUND SYSTEM Power Rating: AC 120V/60Hz Model No.: KP626BT Test Engineer: Lueng

Test Mode: Charging+BT Link

Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	10.80	40.40	51.20	65.78	-14.58	QP	Р	
2	0.1539	10.80	28.80	39.60	55.78	-16.18	AVG	Р	
3	0.1740	10.80	38.10	48.90	64.76	-15.86	QP	Р	
4	0.1740	10.80	24.70	35.50	54.76	-19.26	AVG	Р	
5	0.2100	10.80	33.40	44.20	63.20	-19.00	QP	Р	
6	0.2100	10.80	20.90	31.70	53.20	-21.50	AVG	Р	
7	0.2260	10.80	30.40	41.20	62.59	-21.39	QP	Р	
8	0.2260	10.80	18.10	28.90	52.59	-23.69	AVG	Р	
9	0.5380	10.80	32.50	43.30	56.00	-12.70	QP	Р	
10	0.5380	10.80	27.60	38.40	46.00	-7.60	AVG	Р	
11	13.3178	10.80	28.80	39.60	60.00	-20.40	QP	Р	
12	13.3178	10.80	20.40	31.20	50.00	-18.80	AVG	Ρ	


FCC ID: 2AF52626




4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz






Report No.: NTC1702231FV00

FCC ID: 2AF52626



4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- a. Blow 1GHz, the EUT was placed on the top of a rotating table 0.01 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:
 - The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

Report No.: NTC1702231FV00

FCC ID: 2AF52626



During the radiated emission test, the spectrum analyzer was set with the following configurations:

<u> </u>			
Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
Above 1000	Average	1 MHz	10 Hz

4.3 Limit

Frequency range	Distance Meters	Field Strengths Limit (15.209)
MHz		μV/m
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

Remark : (1) Emission level (dB) μ V = 20 log Emission level μ V/m

- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

4.4 Measurement Results

Please refer to following plots of the worst case: GFSK Middle channel.


Report No.: NTC1702231FV00

FCC ID: 2AF52626





Site: Radiation



Test Distance:

Power Rating:

Test Engineer:

Ant. Polarization:

Temp.(C)/Hum.(%):

3m

Horizontal 22(C) / 54 %

AC 120V/60Hz

Knight

Report No.: KP626BT

Test Standard: FCC Part 15_Class B_3M

Test item: Radiation Emission

Applicant: King Profit

Product: PROTABLE SOUND SYSTEM

Model No.: KP626BT

Test Mode: Charging+BT Link

Remark:

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	319.0600	-9.95	36.45	26.50	46.00	-19.50	QP			Р	
2	358.8299	-9.14	31.94	22.80	46.00	-23.20	QP			Р	
3	438.3700	-8.26	33.36	25.10	46.00	-20.90	QP			Р	
4	598.4200	-5.03	38.83	33.80	46.00	-12.20	QP			Р	
5	677.9600	-4.40	34.70	30.30	46.00	-15.70	QP			Р	
6	837.0398	-1.34	30.44	29.10	46.00	-16.90	QP			Р	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Report No.: NTC1702231FV00


FCC ID: 2AF52626





Genter Web: Http://www.ntc-c.com

Site: Radiation



Test Distance:

Power Rating:

Test Engineer:

Ant. Polarization:

Temp.(C)/Hum.(%):

3m

Vertical

AC 120V/60Hz

Knight

22(C) / 54 %

Report No.: KP626BT

Test Standard: FCC Part 15_Class B_3M

Test item: Radiation Emission

Applicant: King Profit

Product: PROTABLE SOUND SYSTEM

Model No.: KP626BT

Test Mode: Charging+BT Link

Remark:

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	34.8500	-16.17	48.77	32.60	40.00	-7.40	QΡ			Ъ	
2	127.9698	-17.94	46.04	28.10	43.50	-15.40	QP			Р	
3	159.0098	-18.20	44.40	26.20	43.50	-17.30	QP			Р	
4	278.3199	-13.02	40.32	27.30	46.00	-18.70	QP			Р	
5	318.0899	-11.98	39.28	27.30	46.00	-18.70	QΡ			Ъ	
6	596.4800	-7.09	33.89	26.80	46.00	-19.20	QP			Р	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Report No.: NTC1702231FV00

FCC ID: 2AF52626



Modulation: GFSK (the worst case)

Frequency Range: 1-25GHz Test Date: March 02, 2017

Test Result: PASS Temperature: 22 °C Measured Distance: 3m Humidity: 54 %

Test By: Sance

Freq.	Ant.Pol. (H/V)	Rea Level(•	Factor				t 3m V/m)		rgin B)
(MHz)		PK	AV	(dB/m)	PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
4804	V	43.36	32.33	14.05	57.41	46.38	74.00	54.00	-16.59	-7.62
7206	V	43.43	32.18	18.81	62.24	50.99	74.00	54.00	-11.76	-3.01
4804	Н	45.89	34.91	14.05	59.94	48.96	74.00	54.00	-14.06	-5.04
7206	Н	42.87	32.11	18.18	61.05	50.29	74.00	54.00	-12.95	-3.71
			Ope	ration Mo	ode: TX N	lode (Mi	d)			
4882	V	43.71	33.04	14.41	58.12	47.45	74.00	54.00	-15.88	-6.55
7323	V	42.57	32.12	18.36	60.93	50.48	74.00	54.00	-13.07	-3.52
4882	Н	44.32	32.98	14.41	58.73	47.39	74.00	54.00	-15.27	-6.61
7323	Н	41.82	30.54	18.36	60.18	48.90	74.00	54.00	-13.82	-5.10
			Oper	ation Mo	de: TX M	ode (Hig	gh)			
4960	V	44.42	33.15	14.76	59.18	47.91	74.00	54.00	-14.82	5.18
7440	V	42.8	31.41	18.55	61.35	49.96	74.00	54.00	-12.65	7.35
4960	Н	44.33	33.25	14.76	59.09	48.01	74.00	54.00	-14.91	5.09
7440	Н	42.26	31.02	18.55	60.81	49.57	74.00	54.00	-13.19	6.81

Note: (1) All Readings are Peak Value and AV.

- (2) Emission Level= Reading Level + Factor
- (3) Factor= Antenna Gain + Cable Loss Amplifier Gain
- (4) Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
- (5) Measurement uncertainty: ±3.7dB.
- (6) Horn antenna used for the emission over 1000MHz.

Report No.: NTC1702231FV00

FCC ID: 2AF52626




5. Channel Separation test

5.1 Measurement Procedure

Minimum Hopping Channel Carrier Frequency Separation, FCC Rule 15.247(a)(1):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable, and using the MARKER and Max-Hold function to record the separation of two adjacent channels.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Results

Modulation: GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 100KHz VBW: 300KHz Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: March 01, 2017

Temperature: 24 °C Humidity: 50 %

Test Result: PASS

Channel number	Channel frequency (MHz)	Separation Read Value (KHz)	Separation Limit 2/3 20dB Bandwidth (KHz)							
	GFSK									
Lowest	2402	1000	>743.3							
Middle	2441	1000	>743.3							
Highest	2480	1000	>743.3							
	π/	/4-DQPSK								
Lowest	2402	1000	>968.0							
Middle	2441	1000	>958.7							
Highest	2480	1000	>955.3							
	8DPSK									
Lowest	2402	1000	>961.3							
Middle	2441	1000	>961.3							
Highest	2480	1000	>971.3							

FCC ID: 2AF52626




GFSK Lowest Channel



Date: 1.MAR.2017 16:06:53

GFSK Middle Channel



Date: 1.MAR.2017 16:08:31




GFSK Highest Channel



Date: 1.MAR.2017 16:10:11


π/4-DQPSK Lowest Channel



Date: 1.MAR.2017 16:12:25




π/4-DQPSK Middle Channel



Date: 1.MAR.2017 16:14:29


$\pi/4$ -DQPSK Highest Channel



Date: 1.MAR.2017 16:16:48




8DPSK Lowest Channel



Date: 1.MAR.2017 16:21:44

8DPSK Middle Channel




Date: 1.MAR.2017 16:23:31

FCC ID: 2AF52626



8DPSK Highest Channel



Date: 1.MAR.2017 16:24:37

Report No.: NTC1702231FV00

FCC ID: 2AF52626



6. 20dB Bandwidth

6.1 Measurement Procedure

Maximum 20dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Results

Refer to attached data chart.

Modulation: GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 30KHz VBW: 100KHz Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: March 01, 2017

Temperature : 24 $^{\circ}$ C Humidity : 50 $^{\circ}$


Test Result: PASS

Channel frequency (MHz)	20dB Down BW(kHz)						
GFSK							
2402	1115						
2441	1115						
2480	1115						
π/4-D	QPSK						
2402	1452						
2441	1438						
2480	1433						
8DPSK							
2402	1442						
2441	1442						
2480	1457						

FCC ID: 2AF52626




GFSK Lowest Channel



Date: 1.MAR.2017 15:29:56


GFSK Middle Channel



Date: 1.MAR.2017 15:30:52




GFSK Highest Channel




Date: 1.MAR.2017 15:32:01

π/4-DQPSK Lowest Channel






π/4-DQPSK Middle Channel




Date: 1.MAR.2017 15:46:03

$\pi/4$ -DQPSK Highest Channel






8DPSK Lowest Channel



Date: 1.MAR.2017 15:47:18


8DPSK Middle Channel



FCC ID: 2AF52626



8DPSK Highest Channel



Date: 1.MAR.2017 15:49:23

Report No.: NTC1702231FV00

FCC ID: 2AF52626




7. Hopping Channel Number

7.1 Measurement Procedure

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum, and the spectrum analyzer set to MAX HOLD readings were taken for 3-5 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Results

Modulation GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 100KHz VBW: 300KHz

Packet: DH5 Spectrum Detector: PK

Test By: Sance Test Date: March 01, 2017

Temperature : 24 $^{\circ}$ Humidity : 50 $^{\circ}$


Test Result: PASS

Hopping Channel Frequency Range	Number of Hopping Channels	Limit
2402-2480	79	≥15

The worst case: GFSK

FCC ID: 2AF52626





Date: 1.MAR.2017 17:25:24

Report No.: NTC1702231FV00

FCC ID: 2AF52626



8. Time of Occupancy (Dwell Time)

8.1 Measurement Procedure

Average Channel Occupancy Time, FCC Ref:15.247(a)(1)(iii):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable. The spectrum analyzer center frequency was set to one of the known hopping channels. The Sweep was set to 10 ms, the SPAN was set to Zero SPAN. The time duration of the transmissions so captured was measured with the Marker Delta function

8.2 Measurement Results

The maximum number of hopping channels in 31.6s (0.4s/Channel x 79 Channel)

Refer to attached data chart.

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK


RBW: 1MHz VBW: 3MHz Spectrum Detector: PK Test By: Sance Test Date: March 01, 2017 Temperature: 24° C Test Result: PASS Humidity: 50 %

Packet	Frequency		Result						
	(MHz)		(msec)						
GFSK									
DH1	2441	0.417	(ms)*(1600/(2*79))*31.6=	133.4	400				
DH3	2441	1.442	(ms)*(1600/(4*79))*31.6=	230.7	400				
DH5	2441	2.428	(ms)*(1600/(6*79))*31.6=	259.0	400				
	π/4-DQPSK								
2-DH1	2441	0.565	(ms)*(1600/(2*79))*31.6=	180.8	400				
2-DH3	2441	1.410	(ms)*(1600/(4*79))*31.6=	225.6	400				
2-DH5	2441	2.913	(ms)*(1600/(6*79))*31.6=	310.7	400				
	8DPSK								
3-DH1	2441	0.581	(ms)*(1600/(2*79))*31.6=	185.9	400				
3-DH3	2441	1.254	(ms)*(1600/(4*79))*31.6=	200.6	400				
3-DH5	2441	2.672	(ms)*(1600/(6*79))*31.6=	285.0	400				

FCC ID: 2AF52626








Date: 1.MAR.2017 16:27:22

GFSK DH3




Date: 1.MAR.2017 16:27:55

FCC ID: 2AF52626








Date: 1.MAR.2017 16:28:37

π/4-DQPSK 2-DH1




Date: 1.MAR.2017 16:29:38

FCC ID: 2AF52626




$\pi/4$ -DQPSK 2-DH3



Date: 1.MAR.2017 16:40:40

π/4-DQPSK 2-DH5




Date: 1.MAR.2017 16:42:05

FCC ID: 2AF52626




8DPSK 3-DH1



Date: 1.MAR.2017 16:45:32

8DPSK 3-DH3




Date: 1.MAR.2017 16:46:06

FCC ID: 2AF52626



8DPSK 3-DH5



Date: 1.MAR.2017 16:46:38

Report No.: NTC1702231FV00

FCC ID: 2AF52626



9. MAXIMUM PEAK OUTPUT POWER

9.1 Measurement Procedure

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm. Cable loss was considered during this measurement.

9.2 Measurement Results

Refer to attached data chart.

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK

RBW: 3MHz VBW: 3MHz

Spectrum Detector: PK Test Date: March 01, 2017


Test By: Sance Temperature : 24 $^{\circ}$ C Test Result: PASS Humidity : 50 $^{\circ}$

Channel	Cable	Peak Power	Peak Power	Peak Power	Pass/Fail				
Frequency	Loss	output(dBm)	output(mW)	Limit(dBm)					
(MHz)	dB								
GFSK									
2402.00	1.5	0.65	1.16	21	PASS				
2441.00	1.5	0.92	1.24	21	PASS				
2480.00	1.5	0.84	1.21	21	PASS				
π/4-DQPSK									
2402.00	1.5	-0.98	0.80	21	PASS				
2441.00	1.5	-0.73	0.85	21	PASS				
2480.00	1.5	-0.84	0.82	21	PASS				
8DPSK									
2402.00	1.5	-0.48	0.90	21	PASS				
2441.00	1.5	-0.22	0.95	21	PASS				
2480.00	1.5	-0.31	0.93	21	PASS				

FCC ID: 2AF52626



GFSK Lowest Channel



Date: 1.MAR.2017 15:22:47

GFSK Middle Channel




Date: 1.MAR.2017 15:23:35

FCC ID: 2AF52626








Date: 1.MAR.2017 15:23:57

π/4-DQPSK Lowest Channel




Date: 1.MAR.2017 15:24:22

FCC ID: 2AF52626




π/4-DQPSK Middle Channel



Date: 1.MAR.2017 15:24:50

$\pi/4\text{-DQPSK}$ Highest Channel




Date: 1.MAR.2017 15:25:54

FCC ID: 2AF52626




8DPSK Lowest Channel



Date: 1.MAR.2017 15:26:44


8DPSK Middle Channel



Date: 1.MAR.2017 15:27:43

FCC ID: 2AF52626





Date: 1.MAR.2017 15:28:24

Report No.: NTC1702231FV00

FCC ID: 2AF52626



10. Band Edge

10.1 Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz, and the video bandwidth set to 300KHz.

10.2 Limit

15.247(d)In any 100KHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

10.3 Measurement Results

Please see below test table and plots.

For Radiated Emission The worst case: GFSK

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV	(dB/m)	PK	AV	PK	AV	PK	AV
2390.000	Н	41.11	30.52	8.09	49.20	38.61	74.00	54.00	-24.8	-15.39
2390.000	V	42.18	30.91	8.09	50.27	39.00	74.00	54.00	-23.73	-15.00
2483.500	Н	44.97	33.99	8.36	53.33	42.35	74.00	54.00	-20.67	-11.65
2483.500	V	48.32	36.98	8.36	56.68	45.34	74.00	54.00	-17.32	-8.66

Note: (1) Emission Level= Reading Level + Factor

(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain


(3) Horn antenna used for the emission over 1000MHz.

FCC ID: 2AF52626




For RF Conducted

GFSK Lowest Channel



Date: 1.MAR.2017 16:49:27




Date: 1.MAR.2017 16:50:23


FCC ID: 2AF52626



GFSK Highest Channel



Date: 1.MAR.2017 16:52:04




Date: 1.MAR.2017 16:52:25


FCC ID: 2AF52626



π/4-DQPSK Lowest Channel



Date: 1.MAR.2017 16:53:23




Date: 1.MAR.2017 16:54:04


FCC ID: 2AF52626



$\pi/4\text{-DQPSK}$ Highest Channel



Date: 1.MAR.2017 16:58:17




Date: 1.MAR.2017 17:00:27


FCC ID: 2AF52626



8DPSK Lowest Channel



Date: 1.MAR.2017 17:02:34




Date: 1.MAR.2017 17:04:00


FCC ID: 2AF52626



8DPSK Highest Channel



Date: 1.MAR.2017 17:05:06



Date: 1.MAR.2017 17:05:48

Report No.: NTC1702231FV00

FCC ID: 2AF52626



11. Antenna Application

11.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

11.2 Measurement Results

The antenna is PCB antenna and no consideration of replacement, and the best case gain of the antenna is 0dBi. So, the antenna is consider meet the requirement.

Report No.: NTC1702231FV00

FCC ID: 2AF52626



12. Conducted Spurious Emissions

12.1 Measurement Procedure

Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband.


12.2. Measurement Results

Please refer to following plots, the worst case (GFSK) was shown.

FCC ID: 2AF52626




Lowest Channel



Date: 1.MAR.2017 17:09:01


Middle Channel



Date: 1.MAR.2017 17:10:20

FCC ID: 2AF52626





Date: 1.MAR.2017 17:12:35

Note: Sweep points=30001pts

FCC ID: 2AF52626



13. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date		
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 22, 2016	Nov. 21, 2017		
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 25, 2016	Nov. 24, 2017		
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A		
Color Monitor	SUNSPO	SP-140A	N/A	N/A	N/A	N/A		
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A		
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A		
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A		
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 06, 2016	Nov. 05, 2017		
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 06, 2016	Nov. 05, 2017		
RF Cable	Huber+Suhner	SF-104	MY16559/4	9KHz~25GHz	Mar. 05, 2017	Mar. 04, 2018		
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 06, 2016	Nov. 05, 2017		
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.22, 2016	Oct.21, 2017		
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 04, 2016	Nov. 03, 2017		
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.09, 2016	Oct.08, 2017		
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Aug. 31, 2016	Aug. 30, 2017		
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 02, 2016	Nov. 01, 2017		
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 02, 2016	Nov. 01, 2017		
Temporary antenna connector	TESCOM	SS402	N/A	9KHz-25GHz	N/A	N/A		

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.