

FCC RADIO TEST REPORT

FCC ID: 2AF69Z4

Product Name:	TV BOX
Trademark:	N/A
Model Name :	Z4
Prepared For :	Golden Sunshine Technology CO.,LTD
Address :	8thFloor,VIABuilding,9966shennanroad,NanshanDistrict,Shenzhen, China
Prepared By :	DongGuan Precise Testing Service Co., Ltd.
Address :	Building D, Baoding Technology Park, Guangming Road 2, Guangming Community, Dongcheng District, Dongguan, Guangdong, China
Test Date:	Sep.20, 2015 ~Sep.28, 2015
Date of Report :	Sep.28, 2015
Report No.:	PT1509148045F1

TEST RESULT CERTIFICATION

Applicant's name: Golden Sunshine Technology CO.,LTD
Address: 8th Floor ,VIA Building ,9966 shennan road, Nanshan District,Shenzhen,China.

Manufacture's Name: Golden Sunshine Technology CO.,LTD
Address: 8th Floor ,VIA Building ,9966 shennan road, Nanshan District,Shenzhen,China.

Product description

Product name.....: TV BOX

Model and/or type reference: Z4


Serial Model: N/A


Standards: FCC Part15.249

Test procedure ANSI C63.10-2013

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Testing Engineer : _____  _____
(Juan Zeng)

Technical Manager : _____  _____
(Tom Zhang)


Authorized Signatory : _____  _____
(Chris Du)

TABLE OF CONTENTS

2	TEST SUMMARY	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF E.U.T.	5
3.2	DETAILS OF E.U.T.	5
3.3	CHANNEL LIST.....	5
3.4	DESCRIPTION OF SUPPORT UNITS	5
3.5	DESCRIPTION OF TEST MODES.....	6
3.6	TEST FACILITY	6
3.7	MEASUREMENT UNCERTAINTY	6
4	EQUIPMENT USED DURING TEST	7
4.1	EQUIPMENTS LIST.....	7
4.2	MEASUREMENT UNCERTAINTY	8
4.3	TEST EQUIPMENT CALIBRATION.....	8
5	CONDUCTED EMISSION	9
5.1	E.U.T. OPERATION	9
5.2	EUT SETUP	9
5.3	CONDUCTED EMISSION TEST RESULT	10
6	SPURIOUS RADIATED EMISSIONS	12
6.1	EUT OPERATION :	12
6.2	TEST SETUP.....	13
6.3	SPECTRUM ANALYZER SETUP.....	14
6.4	TEST PROCEDURE	15
6.5	CORRECTED AMPLITUDE & MARGIN CALCULATION.....	15
6.6	SUMMARY OF TEST RESULTS.....	15
6.1.1	TEST RESULTS (Between 9KHz – 30 MHz).....	16
6.1.2	TEST RESULTS (Between 30MHz – 1GHz).....	17
7	BAND EDGE MEASUREMENT	21
7.1	TEST PROCEDURE	21
7.2	TEST RESULT:.....	21
8	20 DB BANDWIDTH MEASUREMENT	23
8.1	TEST PROCEDURE:	23
8.2	TEST RESULT:.....	23
9	ANTENNA REQUIREMENT	26
10	EUT TEST PHOTO	27

2 Test Summary

Test Items	Test Requirement	Result
Spurious Radiated Emissions	15.205(a) 15.209 15.249(d)	PASS
Band edge Emissions	15.249(d)	PASS
Conducted Emissions	15.207	PASS
20dB Bandwidth	15.215c 15.249	PASS

3 General Information

3.1 General Description of E.U.T.

Product Name : TV BOX
Model No. : Z4
Serial Model : N/A
Brand Name : N/A
Operation Frequency : 2402MHz ~ 2480MHz, 79 channels in total, separated by 1MHz
Type of Modulation : GFSK, Pi/4DQPSK, 8DPSK
Antenna installation : External antenna
Antenna Gain : 1.25 dBi
Bluetooth version : 3.0+EDR

3.2 Details of E.U.T.

Technical Data : (1) DC 5V from adapter

3.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2403	3	2404	4	2405
5	2406	6	2407	7	2408	8	2409
9	2410	10	2411	11	2412	12	2413
13	2414	14	2415	15	2416	16	2417
17	2418	18	2419	19	2420	20	2421
21	2422	22	2423	23	2424	24	2425
25	2426	26	2427	27	2428	28	2429
29	2430	30	2431	31	2432	32	2433
33	2434	34	2435	35	2436	36	2437
37	2438	38	2439	39	2440	40	2441
41	2442	42	2443	43	2444	44	2445
45	2446	46	2447	47	2448	48	2449
49	2450	50	2451	51	2452	52	2453
53	2454	54	2455	55	2456	56	2457
57	2458	58	2459	59	2460	60	2461
61	2462	62	2463	63	2464	64	2465
65	2466	66	2467	67	2468	68	2469
69	2470	70	2471	71	2472	72	2473
73	2474	74	2475	75	2476	76	2477
77	2478	78	2479	79	2480	-	-

3.4 Description of Support Units

No.	Equipment	Manufacturer	Model No.	Serial No.
1.	N/A	N/A	N/A	N/A

3.5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Conducted & Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Link Mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test

3.6 TEST FACILITY

DongGuan Precise Testing Service Co., Ltd.

Add.: Building D, Baoding Technology Park, Guangming Road 2, Guangming Community, Dongcheng District, Dongguan, Guangdong, China

FCC Registration No.: 371540

3.7 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

4 Equipment Used during Test

4.1 Equipments List

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45109572	2015.08.25	2016.08.24	1 year
2	Test Receiver	R&S	ESPI	101396	2015.08.25	2016.08.24	1 year
3	Bilog Antenna	SCHWARZBECK	VULB9160	VULB9160-3369	2015.08.25	2016.08.24	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	SCHWARZBECK	9120D	9120D-1275	2015.08.25	2016.08.24	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	SCHWARZBECK	BBV9718	9718-270	2015.08.25	2016.08.24	1 year
9	Amplifier	SCHWARZBECK	BBV9743	9743-119	2015.08.25	2016.08.24	1 year
10	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
11	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
12	Power Sensor	R&S	URV5-Z4	0395.1619.05	2015.07.06	2016.07.05	1 year
13	RF cables	R&S	N/A	N/A	2015.07.06	2016.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101421	2015.08.25	2016.08.24	1 year
2	LISN	SCHWARZBECK	NSLK8127	812779	2015.08.25	2016.08.24	1 year
3	LISN	EMCO	Feb-16	42990	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year

4.2 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Temperature	± 1 °C
DC Source	$\pm 0.05\%$
Radiated Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 4.74 dB (Horn antenna 1000M~25000MHz)
Conducted Emissions test	3.64dB (150kHz~30MHz)

4.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No. 110 Dongguan Zhuang RD. Guangzhou, P.R.China.

5 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10-2013
Test Result:	PASS
Frequency Range:	150 kHz to 30 MHz
Class:	Class B
Limit:	66-56 dB μ V between 0.15 MHz & 0.5 MHz 56 dB μ V between 0.5 MHz & 5MHz 60 dB μ V between 5 MHz & 30MHz
Detector:	Peak for pre-scan (9 kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

5.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C
Humidity: 51 % RH
Atmospheric Pressure: 1012 mbar
Voltage: AC 120V/60Hz

EUT Operation:

The pre-test was performed in Bluetooth linking, and the data were shown as follow.

The EUT was tested according to ANSI C63.10-2013. The frequency spectrum from 150 kHz to 30MHz was investigated.


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

The EUT was in transmitting mode, The worst mode was GFSK low channel, the data was recording in the report.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

5.2 EUT Setup

The EUT was placed on the test table in shielding room.




5.3 Conducted Emission Test Result

EUT:	TV BOX	Model Name. :	Z4
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 4

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1 *	0.1539	47.94	10.05	57.99	65.78	-7.79	QP	
2	0.1539	26.11	10.05	36.16	55.78	-19.62	AVG	
3	0.3339	38.16	10.10	48.26	59.35	-11.09	QP	
4	0.3339	21.38	10.10	31.48	49.35	-17.87	AVG	
5	0.5260	33.75	10.12	43.87	56.00	-12.13	QP	
6	0.5260	16.16	10.12	26.28	46.00	-19.72	AVG	
7	0.7700	29.80	10.14	39.94	56.00	-16.06	QP	
8	0.7700	10.73	10.14	20.87	46.00	-25.13	AVG	
9	19.0340	27.98	10.17	38.15	60.00	-21.85	QP	
10	19.0340	17.40	10.17	27.57	50.00	-22.43	AVG	
11	25.0660	20.16	10.20	30.36	60.00	-29.64	QP	
12	25.0660	8.25	10.20	18.45	50.00	-31.55	AVG	

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	TV BOX	Model Name. :	Z4
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	AC120V/60Hz	Test Mode:	Mode 4

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1641	46.60	10.05	56.65	65.25	-8.60	QP	
2	0.1641	27.48	10.05	37.53	55.25	-17.72	AVG	
3	0.3379	37.83	10.10	47.93	59.25	-11.32	QP	
4	0.3379	20.52	10.10	30.62	49.25	-18.63	AVG	
5	0.5299	33.39	10.12	43.51	56.00	-12.49	QP	
6	0.5299	15.73	10.12	25.85	46.00	-20.15	AVG	
7	0.7060	29.57	10.14	39.71	56.00	-16.29	QP	
8	0.7060	11.10	10.14	21.24	46.00	-24.76	AVG	
9	1.0180	23.96	10.17	34.13	56.00	-21.87	QP	
10	1.0180	7.95	10.17	18.12	46.00	-27.88	AVG	
11	19.3300	29.16	10.17	39.33	60.00	-20.67	QP	
12	19.3300	18.09	10.17	28.26	50.00	-21.74	AVG	

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



6 Spurious Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.249

Test Method: DA 00-705

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation :

Operating Environment:

Temperature: 25.5 °C

Humidity: 51 % RH

Atmospheric Pressure: 1010 mbar


Voltage: AC 120V/60Hz

Operation Mode:


The EUT was tested in transmitting mode, and the data were shown as follow.

6.2 Test Setup


The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10-2013.
The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



6.3 Spectrum Analyzer Setup

According to FCC Part15 Rules, the system was tested 9kHz to 25000MHz.

Below 30MHz

Sweep Speed Auto
IF Bandwidth.....10kHz
Video Bandwidth.....10kHz
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....100kHz
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....1MHz
Video Bandwidth.....3MHz
DetectorAve.
Resolution Bandwidth.....1MHz
Video Bandwidth.....10Hz

6.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

6.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

6.6 Summary of Test Results

Test Frequency: Below 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Test mode: transmitting

Test Frequency: 18~25GHz

The measurements were more than 20 dB below the limit and not reported.

All the modulation modes were tested, the data of the worst mode were recorded in the following pages.

6.1.1 TEST RESULTS (Between 9KHz – 30 MHz)

EUT:	TV BOX	Model Name. :	Z4
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

6.1.2 TEST RESULTS (Between 30MHz – 1GHz)

EUT:	TV BOX	Model Name :	Z4
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX		

	Freq.	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.249/209/205	
					Height	Polar			Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
GFSK Lower Channel 2402MHz	45.24	14.06	QP	87	2.5	H	16.24	30.30	40.00	Pass
	76.35	15.24	QP	27	3.3	H	16.76	32.00	40.00	Pass
	112.32	15.29	QP	16	1.8	H	17.02	32.31	43.50	Pass
	353.26	17.74	QP	0	2.0	H	17.34	35.08	43.50	Pass
	431.21	16.29	QP	78	1.0	H	17.62	33.91	46.00	Pass
	532.06	15.42	QP	125	1.6	H	17.68	33.10	46.00	Pass
	32.62	17.62	QP	36	1.2	V	16.45	34.07	40.00	Pass
	94.63	18.02	QP	44	1.5	V	16.38	34.40	43.50	Pass
	196.35	16.48	QP	29	1.4	V	16.74	33.22	43.50	Pass
	312.21	18.08	QP	62	1.0	V	17.08	35.16	43.50	Pass
	521.24	15.74	QP	43	1.1	V	17.33	33.07	46.00	Pass
	758.63	16.06	QP	26	1.5	V	17.26	33.32	46.00	Pass

GFSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	103.61	PK	H	1.31	104.92	114.00	Pass
	2402.00	89.31	Ave	H	1.31	90.62	94.00	Pass
	4804.00	57.96	PK	H	-1.06	56.90	74.00	Pass
	4804.00	48.95	Ave	H	-1.06	47.89	54.00	Pass
	2402.00	102.51	PK	V	1.31	103.82	114.00	Pass
	2402.00	88.54	Ave	V	1.31	89.85	94.00	Pass
	4804.00	58.93	PK	V	-1.06	57.87	74.00	Pass
	4804.00	47.41	Ave	V	-1.06	46.35	54.00	Pass
Middle Channel 2441MHz	2441.00	103.39	PK	H	0.85	104.24	114.00	Pass
	2441.00	88.80	Ave	H	0.85	89.65	94.00	Pass
	4882.00	54.76	PK	H	-0.62	54.14	74.00	Pass
	4882.00	43.87	Ave	H	-0.62	43.25	54.00	Pass
	2441.00	103.30	PK	V	0.85	104.15	114.00	Pass
	2441.00	88.17	Ave	V	0.85	89.02	94.00	Pass
	4882.00	55.67	PK	V	-0.62	55.05	74.00	Pass
	4882.00	44.94	Ave	V	-0.62	44.32	54.00	Pass
Upper Channel 2480MHz	2480.00	103.60	PK	H	0.53	104.13	114.00	Pass
	2480.00	88.88	Ave	H	0.53	89.41	94.00	Pass
	4960.00	52.86	PK	H	-0.24	52.62	74.00	Pass
	4960.00	43.77	Ave	H	-0.24	43.53	54.00	Pass
	2480.00	102.75	PK	V	0.53	103.28	114.00	Pass
	2480.00	88.14	Ave	V	0.53	88.67	94.00	Pass
	4960.00	55.05	PK	V	-0.24	54.81	74.00	Pass
	4960.00	43.99	Ave	V	-0.24	43.75	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.

PI/4 DPSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	102.33	PK	H	1.31	103.64	114.00	Pass
	2402.00	88.24	Ave	H	1.31	89.55	94.00	Pass
	4804.00	57.25	PK	H	-1.06	56.19	74.00	Pass
	4804.00	48.36	Ave	H	-1.06	47.30	54.00	Pass
	2402.00	101.27	PK	V	1.31	102.58	114.00	Pass
	2402.00	87.47	Ave	V	1.31	88.78	94.00	Pass
	4804.00	58.23	PK	V	-1.06	57.17	74.00	Pass
	4804.00	46.83	Ave	V	-1.06	45.77	54.00	Pass
	2441.00	102.14	PK	H	0.85	102.99	114.00	Pass
	2441.00	87.71	Ave	H	0.85	88.56	94.00	Pass
Middle Channel 2441MHz	4882.00	54.10	PK	H	-0.62	53.48	74.00	Pass
	4882.00	43.34	Ave	H	-0.62	42.72	54.00	Pass
	2441.00	102.05	PK	V	0.85	102.90	114.00	Pass
	2441.00	87.10	Ave	V	0.85	87.95	94.00	Pass
	4882.00	54.99	PK	V	-0.62	54.37	74.00	Pass
	4882.00	44.40	Ave	V	-0.62	43.78	54.00	Pass
	2480.00	102.34	PK	H	0.53	102.87	114.00	Pass
	2480.00	87.79	Ave	H	0.53	88.32	94.00	Pass
Upper Channel 2480MHz	4960.00	52.21	PK	H	-0.24	51.97	74.00	Pass
	4960.00	43.24	Ave	H	-0.24	43.00	54.00	Pass
	2480.00	101.49	PK	V	0.53	102.02	114.00	Pass
	2480.00	87.07	Ave	V	0.53	87.60	94.00	Pass
	4960.00	54.39	PK	V	-0.24	54.15	74.00	Pass
	4960.00	43.45	Ave	V	-0.24	43.21	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.

8DPSK

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dBμV)	(PK/QP/Ave)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	
Lower Channel 2402MHz	2402.00	103.17	PK	H	1.31	104.48	114.00	Pass
	2402.00	88.96	Ave	H	1.31	90.27	94.00	Pass
	4804.00	57.72	PK	H	-1.06	56.66	74.00	Pass
	4804.00	48.75	Ave	H	-1.06	47.69	54.00	Pass
	2402.00	102.10	PK	V	1.31	103.41	114.00	Pass
	2402.00	88.18	Ave	V	1.31	89.49	94.00	Pass
	4804.00	58.71	PK	V	-1.06	57.65	74.00	Pass
	4804.00	47.21	Ave	V	-1.06	46.15	54.00	Pass
	2441.00	102.97	PK	H	0.85	103.82	114.00	Pass
	2441.00	88.43	Ave	H	0.85	89.28	94.00	Pass
Middle Channel 2441MHz	4882.00	54.54	PK	H	-0.62	53.92	74.00	Pass
	4882.00	43.69	Ave	H	-0.62	43.07	54.00	Pass
	2441.00	102.88	PK	V	0.85	103.73	114.00	Pass
	2441.00	87.81	Ave	V	0.85	88.66	94.00	Pass
	4882.00	55.44	PK	V	-0.62	54.82	74.00	Pass
	4882.00	44.76	Ave	V	-0.62	44.14	54.00	Pass
	2480.00	103.18	PK	H	0.53	103.71	114.00	Pass
	2480.00	88.51	Ave	H	0.53	89.04	94.00	Pass
Upper Channel 2480MHz	4960.00	52.64	PK	H	-0.24	52.40	74.00	Pass
	4960.00	43.59	Ave	H	-0.24	43.35	54.00	Pass
	2480.00	102.32	PK	V	0.53	102.85	114.00	Pass
	2480.00	87.78	Ave	V	0.53	88.31	94.00	Pass
	4960.00	54.83	PK	V	-0.24	54.59	74.00	Pass
	4960.00	43.80	Ave	V	-0.24	43.56	54.00	Pass

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.

7 Band Edge Measurement

Test Requirement:	Section 15.249(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	DA 00-705
Limit:	40.0 dBuV/m between 30MHz & 88MHz; 43.5 dBuV/m between 88MHz & 216MHz; 46.0 dBuV/m between 216MHz & 960MHz; 54.0 dBuV/m above 960MHz. 74.0 dBuV/m for peak above 1GHz 54.0 dBuV/m for AVG above 1GHz

7.1 Test Procedure

1. The EUT was placed on a turntable which is 0.8m above ground plane
2. Measurement Distance is 3m
3. Detector:

For Peak value:
RBW = 1 MHz for $f \geq 1$ GHz
VBW \geq RBW; Sweep = auto
Detector function = peak
Trace = max hold
For AVG value:
RBW = 1 MHz for $f \geq 1$ GHz
VBW = 10Hz; Sweep = auto
Detector function = AVG
Trace = max hold
4. Continuous transmitting

7.2 Test Result:

Test result shown as follows:

GFSK

	Frequency (MHz)	Antenna polarization (H/V)	Test Frequency (MHz)	Emission (dBuV/m)	Band edge Limit (dBuV/m)		Result
				PK	PK	AV	
Hopping	<2400	H	2386.34	49.18	74.00	54.00	Pass
	<2400	V	2389.41	49.12	74.00	54.00	Pass
	>2483.5	H	2488.27	49.62	74.00	54.00	Pass
	>2483.5	V	2486.51	50.27	74.00	54.00	Pass
Unhopping	<2400	H	2387.28	49.57	74.00	54.00	Pass
	<2400	V	2381.36	49.62	74.00	54.00	Pass
	>2483.5	H	2486.29	50.53	74.00	54.00	Pass
	>2483.5	V	2487.17	49.98	74.00	54.00	Pass

PI/4 DPSK

	Frequency (MHz)	Antenna polarization (H/V)	Test Frequency (MHz)	Emission (dBuV/m)	Band edge Limit (dBuV/m)		Result
				PK	PK	AV	
Hopping	<2400	H	2384.51	50.54	74.00	54.00	Pass
	<2400	V	2386.22	50.69	74.00	54.00	Pass
	>2483.5	H	2487.47	50.13	74.00	54.00	Pass
	>2483.5	V	2486.80	50.38	74.00	54.00	Pass
Unhopping	<2400	H	2393.61	49.93	74.00	54.00	Pass
	<2400	V	2394.53	49.45	74.00	54.00	Pass
	>2483.5	H	2486.84	50.13	74.00	54.00	Pass
	>2483.5	V	2486.25	50.18	74.00	54.00	Pass

8-DPSK

	Frequency (MHz)	Antenna polarization (H/V)	Test Frequency (MHz)	Emission (dBuV/m)	Band edge Limit (dBuV/m)		Result
				PK	PK	AV	
Hopping	<2400	H	2392.42	50.69	74.00	54.00	Pass
	<2400	V	2393.74	50.41	74.00	54.00	Pass
	>2483.5	H	2486.28	50.01	74.00	54.00	Pass
	>2483.5	V	2486.16	50.10	74.00	54.00	Pass
Unhopping	<2400	H	2389.39	50.30	74.00	54.00	Pass
	<2400	V	2391.10	50.44	74.00	54.00	Pass
	>2483.5	H	2486.74	49.93	74.00	54.00	Pass
	>2483.5	V	2488.61	49.91	74.00	54.00	Pass

8 20 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.249
 Test Method: DA 00-705
 Test Mode: Test in fixing operating frequency at low, Middle, high channel.

8.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 15kHz, VBW = 47kHz

8.2 Test Result:


Modulation	Test Channel	Bandwidth(kHz)
GFSK	Lower	928
	Middle	927
	Upper	927
Pi/4DQPSK	Lower	1305
	Middle	1308
	Upper	1305
8DPSK	Lower	1345
	Middle	1342
	Upper	1342

For pretest, the worst mode was 8DPSK, the data only show the 8DPSK mode.


Test result plot as follows:

Modulation: 8DPSK


Lower Channel



Middle Channel



Upper Channel




9 Antenna Requirement


According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has a external antenna, fulfill the requirement of this section.

10 EUT TEST PHOTO

Radiated Measurement Photos



Radiated Measurement Photos



Conducted Measurement Photos



===== End of Test Report =====