# Appendix A

# RF Test Data for Lora-DTS (902-928MHz DTS Mode)


**Product Name: LoRa module** Trade Mark: RAK Test Model: RAK4260(H) FCC ID: 2AF6B-RAK4260H


# **Environmental Conditions**

Temperature:	24.5° C
Relative Humidity:	60%
ATM Pressure:	100.0 kPa
Test Engineer:	Gary Qian
Supervised by:	Eden Hu

#### 1.6dB Bandwidth

Test Mode	Test Channel	Ant	EBW[MHz]	Limit	Verdict
Lora-DTS	LCH	Ant1	0.748	0.5	PASS
Lora-DTS	MCH	Ant1	0.683	0.5	PASS
Lora-DTS	HCH	Ant1	0.686	0.5	PASS







## 2.Occupied Bandwidth

Test Mode Test Channel Ant	OBW[MHz]	Limit[MHz]	Verdict
----------------------------	----------	------------	---------

### 3. Maximum peak conducted output power

Test Mode	Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
Lora-DTS	LCH	Ant1	12.594	30	PASS
Lora-DTS	MCH	Ant1	12.509	30	PASS
Lora-DTS	HCH	Ant1	12.341	30	PASS






### 4. Maximum Peak power spectral density


Test Mode	Test	Ant	PSD[dBm/3KHz]	Limit[dBm/3KHz]	Verdict
Lora-DTS	LCH	Ant1	0.441	8.00	PASS
Lora-DTS	MCH	Ant1	1.096	8.00	PASS
Lora-DTS	HCH	Ant1	0.984	8.00	PASS







**5.Band-edge for RF Conducted Emissions** 

Туре	Carrier Frequency(MHz)	Frequency(MHz)	Carrier Frequency Power [dBm]	Bandedge Peak(dBm)	Upper limit(dBm)	Conclusion
Lora-DTS	903	901.783	12.946	-44.051	-7.054	Pass
Lora-DTS	927	928	12.604	-46.47	-7.396	Pass



#### **6.RF Conducted Spurious Emissions**







#### 8. Duty Cycle

Test Mode	Test Channel	Ant	Duty Cycle[%]	Verdict
BLE	915	Ant1	60.33	PASS

