

FCC TEST REPORT

For

Azlan Logistics Limited

Digital Amplifier

Model No.: AV-1800

Prepared For : Azlan Logistics Limited
Address : Redwood 2, Chineham Business Park, Crockford Lane, Basingstoke,
Hampshire, RG24 8WQ, United Kingdom

Prepared By : Shenzhen Anbotech Compliance Laboratory Limited
Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei
community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong,
China.518102
Tel: (86) 755-26066440 Fax: (86) 755-26014772

Report Number : R0217100052W2
Date of Receipt : Oct. 25, 2017
Date of Test : Oct. 25, 2017~Aug. 22, 2018
Date of Report : Aug. 22, 2018

Contents

1. General Information.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	5
1.4. Description of Test Modes.....	6
1.5. List of channels.....	7
1.6. Description Of Test Setup.....	8
1.7. Test Equipment List.....	9
1.8. Description of Test Facility.....	10
2. Summary of Test Results.....	11
3. Conducted Emission Test.....	12
3.1. Test Standard and Limit.....	12
3.2. Test Setup.....	12
3.3. Test Procedure.....	12
3.4. Test Data.....	12
4. Radiation Spurious Emission and Band Edge.....	17
4.1. Test Standard and Limit.....	17
4.2. Test Setup.....	17
4.3. Test Procedure.....	18
4.4. Test Data.....	19
5. Maximum Peak Output Power Test.....	28
5.1. Test Standard and Limit.....	28
5.2. Test Setup.....	28
5.3. Test Procedure.....	28
5.4. Test Data.....	28
6. 6DB Occupy Bandwidth Test.....	31
6.1. Test Standard and Limit.....	31
6.2. Test Setup.....	31
6.3. Test Procedure.....	31
6.4. Test Data.....	31
7. Power Spectral Density Test.....	34
7.1. Test Standard and Limit.....	34
7.2. Test Setup.....	34
7.3. Test Procedure.....	34
7.4. Test Data.....	34
8. 100kHz Bandwidth of Frequency Band Edge Requirement.....	37
8.1. Test Standard and Limit.....	37
8.2. Test Setup.....	37
8.3. Test Procedure.....	37
8.4. Test Data.....	37
9. Antenna Requirement.....	41
9.1. Test Standard and Requirement.....	41

9.2. Antenna Connected Construction.....	41
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	42
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	44
APPENDIX III -- INTERNAL PHOTOGRAPH.....	48

TEST REPORT

Applicant : Azlan Logistics Limited
Manufacturer : Azlan Logistics Limited
Product Name : Digital Amplifier
Model No. : AV-1800
Trade Mark : VISION
Rating(s) : Input: AC 100-240V, 50/60Hz, 1A Max

Test Standard(s) : FCC Part15 Subpart C 2017, Section 15.247

Test Method(s) : ANSI C63.10: 2013, KDB558074 D01 DTS Meas Guidance v04

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test

Oct. 25, 2017~Aug. 22, 2018

Prepared by



Oliay Yang
(Engineer / Oliay Yang)

Reviewer

Calvin Liss
(Supervisor / Calvin Liu)

Approved & Authorized Signer

Tom Chen
(Manager / Tom Chen)

1. General Information

1.1. Client Information

Applicant	:	Azlan Logistics Limited
Address	:	Redwood 2, Chineham Business Park, Crockford Lane, Basingstoke, Hampshire, RG24 8WQ, United Kingdom
Manufacturer	:	Azlan Logistics Limited
Address	:	Redwood 2, Chineham Business Park, Crockford Lane, Basingstoke, Hampshire, RG24 8WQ, United Kingdom

1.2. Description of Device (EUT)

Product Name	:	Digital Amplifier	
Model No.	:	AV-1800	
Trade Mark	:	VISION	
Test Power Supply	:	AC 240V, 60Hz/ AC 120V, 60Hz	
Product Description	:	Operation Frequency:	2402MHz-2480MHz
		Transfer Rate:	1 Mbits/s
		Number of Channel:	40 Channel
		Modulation Type:	GFSK
		Antenna Type:	Cylindrical Antenna
		Antenna Gain(Peak):	3 dBi
Remark: 1)For a more detailed features description, please refer to the manufacturer’s specifications or the User’s Manual. 2)This report is for BLE.			

1.3. Auxiliary Equipment Used During Test

Mobile Phone	:	Manufacturer: HUAWEI
		M/N: C8650 S/N: L6W7NA11B1013157 CE, FCC, DOC
DVD	:	Manufacturer: SONY
		M/N: BDP-S380 S/N: 4065848 CE, FCC

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Keeping TX+Charging mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX+Charging mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Keeping TX+Charging mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 1Mbps for radiated emission due to the highest RF output power.



1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT built-in battery-powered, fully-charged battery use of the test battery.

1.6. Description Of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 17, 2017	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 17, 2017	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 17, 2017	1 Year
5.	Spectrum Analysis	Agilent	N9038A	MY53227295	Nov. 17, 2017	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 17, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
8.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 20, 2017	1 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 20, 2017	1 Year
10.	Loop Antenna	Schwarzbeck	HFH2-Z2	100047	Nov. 17, 2017	1 Year
11.	Horn Antenna	Schwarzbeck	BBHA9170	9170-375	Nov. 17, 2017	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Nov. 17, 2017	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 18, 2017	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 17, 2017	1 Year
16.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 17, 2017	1 Year
17.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 18, 2017	1 Year
18.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 18, 2017	1 Year
19.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 18, 2017	1 Year
20.	DC Power Supply	LW	TPR-6410D	349315	Nov. 01, 2017	1 Year
21.	Constant Temperature Humidity Chamber	Sertep	ZJ-HWHS80B	ZJ-17042804	Nov. 01, 2017	1 Year

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.


1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: “N/A” is an abbreviation for Not Applicable.		

3.1. Test Standard and Limit

3.2. Test Setup




The frequency range from 150kHz to 30MHz is checked.

Please to see the following pages

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 240V, 60Hz
Comment: Live Line
Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1580	30.75	19.90	50.65	65.56	-14.91	QP	
2	0.4020	24.78	19.94	44.72	57.81	-13.09	QP	
3	0.4020	19.68	19.94	39.62	47.81	-8.19	AVG	
4	0.4980	22.48	19.98	42.46	56.03	-13.57	QP	
5	4.0380	22.24	20.18	42.42	56.00	-13.58	QP	
6	4.4380	26.07	20.19	46.26	56.00	-9.74	QP	
7	4.4380	16.89	20.19	37.08	46.00	-8.92	AVG	
8	4.8420	25.24	20.20	45.44	56.00	-10.56	QP	
9	4.8420	17.48	20.20	37.68	46.00	-8.32	AVG	
10	28.2380	17.34	20.27	37.61	50.00	-12.39	AVG	
11	29.0500	17.22	20.27	37.49	50.00	-12.51	AVG	
12	29.8420	16.76	20.27	37.03	50.00	-12.97	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 240V, 60Hz
Comment: Neutral Line
Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.4020	23.36	19.94	43.30	57.81	-14.51	QP	
2	0.4020	15.44	19.94	35.38	47.81	-12.43	AVG	
3	0.4980	22.67	19.98	42.65	56.03	-13.38	QP	
4	4.0340	19.99	20.18	40.17	56.00	-15.83	QP	
5	4.4380	24.97	20.19	45.16	56.00	-10.84	QP	
6	4.4380	16.17	20.19	36.36	46.00	-9.64	AVG	
7	4.8460	25.37	20.20	45.57	56.00	-10.43	QP	
8	4.8460	16.49	20.20	36.69	46.00	-9.31	AVG	
9	26.6460	17.34	20.28	37.62	50.00	-12.38	AVG	
10	28.2500	17.47	20.27	37.74	50.00	-12.26	AVG	
11	29.8660	24.09	20.27	44.36	60.00	-15.64	QP	
12	29.8660	17.92	20.27	38.19	50.00	-11.81	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 120V, 60Hz
Comment: Live Line
Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1620	30.45	19.90	50.35	65.36	-15.01	QP	
2	0.4060	24.54	19.94	44.48	57.73	-13.25	QP	
3	0.4060	19.94	19.94	39.88	47.73	-7.85	AVG	
4	0.4700	17.16	19.97	37.13	46.51	-9.38	AVG	
5	0.4740	24.25	19.97	44.22	56.44	-12.22	QP	
6	4.0340	21.07	20.18	41.25	56.00	-14.75	QP	
7	4.4380	26.32	20.19	46.51	56.00	-9.49	QP	
8	4.4380	17.74	20.19	37.93	46.00	-8.07	AVG	
9	4.8420	25.43	20.20	45.63	56.00	-10.37	QP	
10	4.8420	18.86	20.20	39.06	46.00	-6.94	AVG	
11	29.0500	16.89	20.27	37.16	50.00	-12.84	AVG	
12	29.8540	16.82	20.27	37.09	50.00	-12.91	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Keeping TX+ Charging Mode
Test Specification: AC 120V, 60Hz
Comment: Neutral Line
Tem.: 22.2°C Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1620	29.72	19.90	49.62	65.36	-15.74	QP	
2	0.4060	23.71	19.94	43.65	57.73	-14.08	QP	
3	0.4060	15.49	19.94	35.43	47.73	-12.30	AVG	
4	0.4660	15.42	19.96	35.38	46.58	-11.20	AVG	
5	0.4740	24.33	19.97	44.30	56.44	-12.14	QP	
6	4.4380	24.42	20.19	44.61	56.00	-11.39	QP	
7	4.4380	15.91	20.19	36.10	46.00	-9.90	AVG	
8	4.8420	23.28	20.20	43.48	56.00	-12.52	QP	
9	4.8420	15.80	20.20	36.00	46.00	-10.00	AVG	
10	28.2460	16.97	20.27	37.24	50.00	-12.76	AVG	
11	29.0580	16.90	20.27	37.17	50.00	-12.83	AVG	
12	29.8580	24.07	20.27	44.34	60.00	-15.66	QP	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying

aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9kHz, VBW = 30kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector = Peak, Trace mode = Max hold, Sweep = auto couple.

RBW = 1MHz, VBW = 10Hz, Detector = Average, Trace mode = Max hold, Sweep = auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Test Results (30~1000MHz)

Job No.: 0217100052W1 Temp.(°C)/Hum.(%RH): 23.2°C/53.4%RH
Standard: FCC PART 15C Power Source: AC 240V, 60Hz
Test Mode: Keeping TX+ Charging Mode Polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	43.6584	33.94	-15.07	18.87	40.00	-21.13	QP	300	62	
2	75.4464	46.03	-21.70	24.33	40.00	-15.67	QP	300	123	
3	112.9196	53.56	-20.83	32.73	43.50	-10.77	QP	300	174	
4	192.4186	47.65	-19.67	27.98	43.50	-15.52	QP	300	256	
5	431.0316	38.31	-12.29	26.02	46.00	-19.98	QP	300	324	
6	560.6928	37.87	-11.13	26.74	46.00	-19.26	QP	300	360	

Test Results (30~1000MHz)


Job No.: 0217100052W1 Temp.(°C)/Hum.(%RH): 23.2°C/53.4%RH
Standard: FCC PART 15C Power Source: AC 240V, 60Hz
Test Mode: Keeping TX+ Charging Mode Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.7455	50.61	-17.33	33.28	40.00	-6.72	QP	300	47	
2	66.4989	50.14	-18.46	31.68	40.00	-8.32	QP	300	99	
3	84.4054	44.37	-18.16	26.21	40.00	-13.79	QP	300	156	
4	108.2667	37.60	-14.65	22.95	43.50	-20.55	QP	300	173	
5	155.9101	39.92	-17.06	22.86	43.50	-20.64	QP	300	264	
6	454.3100	38.96	-11.85	27.11	46.00	-18.89	QP	300	360	

Test Results (30~1000MHz)

Job No.: 0217100052W1 Temp.(°C)/Hum.(%RH): 23.2°C/53.4%RH
Standard: FCC PART 15C Power Source: AC 120V, 60Hz
Test Mode: Keeping TX+ Charging Mode Polarization: Horizontal



Test Results (30~1000MHz)

Job No.: 0217100052W1 Temp.(°C)/Hum.(%RH): 23.2°C/53.4%RH
Standard: FCC PART 15C Power Source: AC 120V, 60Hz
Test Mode: Keeping TX+ Charging Mode Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	38.2120	44.86	-14.34	30.52	40.00	-9.48	QP	300	42	
2	68.5014	48.74	-19.23	29.51	40.00	-10.49	QP	300	87	
3	85.5977	47.58	-17.86	29.72	40.00	-10.28	QP	300	144	
4	104.9033	42.58	-14.70	27.88	43.50	-15.62	QP	300	217	
5	171.3926	38.83	-16.46	22.37	43.50	-21.13	QP	300	263	
6	452.7197	41.42	-11.78	29.64	46.00	-16.36	QP	300	360	

Test Results (1GHz-25GHz)

Test Mode: CH00					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804.00	35.91	34.04	6.58	34.09	42.44	74.00	-31.56	V
7206.00	30.91	37.11	7.73	34.50	41.25	74.00	-32.75	V
9608.00	30.65	39.31	9.23	34.79	44.40	74.00	-29.60	V
12010.00	*					74.00		V
14412.00	*					74.00		V
4804.00	39.91	34.04	6.58	34.09	46.44	74.00	-27.56	H
7206.00	32.54	37.11	7.73	34.50	42.88	74.00	-31.12	H
9608.00	29.94	39.31	9.23	34.79	43.69	74.00	-30.31	H
12010.00	*					74.00		H
14412.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804.00	24.99	34.04	6.58	34.09	31.52	54.00	-22.48	V
7206.00	19.75	37.11	7.73	34.50	30.09	54.00	-23.91	V
9608.00	18.91	39.31	9.23	34.79	32.66	54.00	-21.34	V
12010.00	*					54.00		V
14412.00	*					54.00		V
4804.00	29.06	34.04	6.58	34.09	35.59	54.00	-18.41	H
7206.00	21.83	37.11	7.73	34.50	32.17	54.00	-21.83	H
9608.00	18.53	39.31	9.23	34.79	32.28	54.00	-21.72	H
12010.00	*					54.00		H
14412.00	*					54.00		H

Test Results (1GHz-25GHz)

Test Mode: CH19					Test channel: Middle			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880.00	35.34	34.38	6.69	34.09	42.32	74.00	-31.68	V
7320.00	30.53	37.22	7.78	34.53	41.00	74.00	-33.00	V
9760.00	30.31	39.46	9.35	34.80	44.32	74.00	-29.68	V
12200.00	*					74.00		V
14640.00	*					74.00		V
4880.00	39.23	34.38	6.69	34.09	46.21	74.00	-27.79	H
7320.00	32.11	37.22	7.78	34.53	42.58	74.00	-31.42	H
9760.00	29.55	39.46	9.35	34.80	43.56	74.00	-30.44	H
12200.00	*					74.00		H
14640.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880.00	24.53	34.38	6.69	34.09	31.51	54.00	-22.49	V
7320.00	19.44	37.22	7.78	34.53	29.91	54.00	-24.09	V
9760.00	18.64	39.46	9.35	34.80	32.65	54.00	-21.35	V
12200.00	*					54.00		V
14640.00	*					54.00		V
4880.00	28.54	34.38	6.69	34.09	35.52	54.00	-18.48	H
7320.00	21.48	37.22	7.78	34.53	31.95	54.00	-22.05	H
9760.00	18.21	39.46	9.35	34.80	32.22	54.00	-21.78	H
12200.00	*					54.00		H
14640.00	*					54.00		H

Test Results (1GHz-25GHz)

Test Mode: CH39					Test channel: Highest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	35.20	34.72	6.79	34.09	42.62	74.00	-31.38	V
7440.00	30.43	37.34	7.82	34.57	41.02	74.00	-32.98	V
9920.00	30.22	39.62	9.46	34.81	44.49	74.00	-29.51	V
12400.00	*					74.00		V
14880.00	*					74.00		V
4960.00	39.05	34.72	6.79	34.09	46.47	74.00	-27.53	H
7440.00	32.00	37.34	7.82	34.57	42.59	74.00	-31.41	H
9920.00	29.45	39.62	9.46	34.81	43.72	74.00	-30.28	H
12400.00	*					74.00		H
14880.00	*					74.00		H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960.00	24.43	34.72	6.79	34.09	31.85	54.00	-22.15	V
7440.00	19.37	37.34	7.82	34.57	29.96	54.00	-24.04	V
9920.00	18.58	39.62	9.46	34.81	32.85	54.00	-21.15	V
12400.00	*					54.00		V
14880.00	*					54.00		V
4960.00	28.43	34.72	6.79	34.09	35.85	54.00	-18.15	H
7440.00	21.41	37.34	7.82	34.57	32.00	54.00	-22.00	H
9920.00	18.14	39.62	9.46	34.81	32.41	54.00	-21.59	H
12400.00	*					54.00		H
14880.00	*					54.00		H

Remark:

1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:

Test Mode: CH00					Test channel: Lowest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2390.00	43.94	29.15	3.41	34.01	42.49	74.00	-31.51	H
2400.00	60.88	29.16	3.43	34.01	59.46	74.00	-14.54	H
2390.00	44.59	29.15	3.41	34.01	43.14	74.00	-30.86	V
2400.00	63.03	29.16	3.43	34.01	61.61	74.00	-12.39	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2390.00	34.25	29.15	3.41	34.01	32.80	54.00	-21.20	H
2400.00	45.55	29.16	3.43	34.01	44.13	54.00	-9.87	H
2390.00	34.27	29.15	3.41	34.01	32.82	54.00	-21.18	V
2400.00	42.30	29.16	3.43	34.01	40.88	54.00	-13.12	V

Test Mode: CH39					Test channel: Highest			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2483.50	46.17	29.28	3.53	34.03	44.95	74.00	-29.05	H
2500.00	45.14	29.30	3.56	34.03	43.97	74.00	-30.03	H
2483.50	47.19	29.28	3.53	34.03	45.97	74.00	-28.03	V
2500.00	46.24	29.30	3.56	34.03	45.07	74.00	-28.93	V
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
2483.50	37.09	29.28	3.53	34.03	35.87	54.00	-18.13	H
2500.00	34.94	29.30	3.56	34.03	33.77	54.00	-20.23	H
2483.50	38.39	29.28	3.53	34.03	37.17	54.00	-16.83	V
2500.00	34.95	29.30	3.56	34.03	33.78	54.00	-20.22	V

Remark:


1. Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	30dBm

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.


1. Set the RBW \geq DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data


Test Item : Max. peak output power
Test Voltage : DC 11.1V Battery inside
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 24°C
Humidity : 55%RH


Channel Frequency (MHz)	Peak Power output (dBm)	Limit (dBm)	Results
2402	0.835	30	PASS
2440	2.071	30	PASS
2480	1.444	30	PASS



CH: Low



CH: Middle




CH: High

6. 6DB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	>500kHz

6.2. Test Setup




6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 100kHz, VBW \geq 3*RBW = 300kHz,
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data

Test Item	: 6dB Bandwidth	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 11.1V Battery inside	Temperature	: 24℃
Test Result	: PASS	Humidity	: 55%RH


Channel	Frequency(MHz)	Bandwidth (kHz)	Limit (kHz)	Results
Low	2402	646.5	>500	PASS
Middle	2440	652.9		PASS
High	2480	659.8		PASS



CH: Low



CH: Middle




CH: High

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 1.5xDTS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data


Test Item : Power Spectral Density
Test Voltage : DC 11.1V Battery inside
Test Result : PASS

Test Mode : CH Low ~ CH High
Temperature : 24°C
Humidity : 55%RH

Channel	Frequency (MHz)	PPSD (dBm/KHz)	Limit (dBm/3KHz)	Results
Low	2402	-14.777	8.00	PASS
Middle	2440	-13.547	8.00	PASS
High	2480	-13.878	8.00	PASS



CH: Low



CH: Middle




CH: High

8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2. Test Setup



8.3. Test Procedure


Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Test Item	: Band edge	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 11.1V Battery inside	Temperature	: 24°C
Test Result	: PASS	Humidity	: 55%RH

Frequency Band (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Results
2400	41.630	>20	PASS
2483.5	61.334	>20	PASS



CH: Low



CH: High

Conducted Emission Method



CH: Low



CH: Middle



CH: High


9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

9.2. Antenna Connected Construction

The BT antenna is a Cylindrical Antenna which permanently attached, and the best case gain of the antenna is 3 dBi. It complies with the standard requirement.





APPENDIX I-- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement






Photo of Radiation Emission Test







APPENDIX II -- EXTERNAL PHOTOGRAPH

















APPENDIX III -- INTERNAL PHOTOGRAPH

















----- End of Report -----