

## INTERTEK TESTING SERVICES

---

### RF Exposure report

The Equipment Under Test (EUT) is a Panel PC. The EUT was powered by AC/DC adaptor through AC120V/60Hz. More detailed features description, please refer to the user's manual.

For WiFi function, operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 9 channels with 5MHz channel spacing.

Modulation Type: BPSK, QPSK, 16QAM, 64QAM for OFDM. CCK, DQPSK, DBPSK for DSSS.

Antenna Type: Integral antenna

Antenna Gain: 2.2dBi

The nominal conducted output power specified: 20dBm (Tolerance: +/-3dB)

The maximum conducted output power for the EUT is 21.98 dBm in the frequency 2.462GHz 802.11n-HT20 mode which is within the production variation.

The minimum conducted output power for the EUT is 18.65dBm in the frequency 2.412GHz 802.11b mode which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use.

For Maximum Permissible Exposure (MPE) evaluation of the product, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in FCC Part 1.1310.

The maximum EIRP= 20+3+2.2=25.2dBm=331.1mW

The source-based time averaged maximum radiated power = 331.1 mW x Duty Cycle = 331.1mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET 65 as follow:

$$= PG/4\pi R^2$$

$$= EIRP/4\pi R^2 = 331.1/ 4\pi R^2$$

$$= 0.07 \text{ mW/cm}^2$$

## INTERTEK TESTING SERVICES

---

The MPE limit is  $1.0 \text{ mW/cm}^2$  for general population and uncontrolled exposure in the WiFi frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

### Transmitter Duty Cycle Calculation

The EUT transmit continuously during the test, the duty cycle is 100%.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

**“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”**

## INTERTEK TESTING SERVICES

---

For NFC function operating at 13.56MHz.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi

The nominal conducted output power specified: -15.00dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -17.15dBm (+/- 3dB)

Modulation Type: ASK

The worst-case peak radiated emission for the EUT is 80.1dBμV/m at 3m in the frequency 13.56MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -15.13dBm

The ERP = EIRP - 2.15 = -17.28 dBm

which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use.

For Maximum Permissible Exposure (MPE) evaluation of the product, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in FCC Part 1.1310.

The maximum EIRP = -12.0dBm = 0.063mW

The source-based time averaged maximum radiated power = 0.063mW x Duty Cycle = 0.063mW

From above data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET 65 as follow:

$$= PG/4\pi R^2$$

$$= EIRP/4\pi R^2 = 0.063/ 4\pi R^2$$

$$< 1.0 \text{ mW/cm}^2$$

## INTERTEK TESTING SERVICES

---

The MPE limit is  $1.0 \text{ mW/cm}^2$  for general population and uncontrolled exposure in the WiFi frequency range according to FCC Part 1.1310. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

### Transmitter Duty Cycle Calculation

The EUT transmit continuously during the test, the duty cycle is 100%.

The following RF exposure statement or similar sentence is proposed to be included in the user manual:

**“FCC RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”**


## INTERTEK TESTING SERVICES

### Simultaneous transmissions for both WiFi function and NFC function

According to the KDB 447498:

The information of operating frequency (MHz), power (W), antenna gain (dBi), location (X and Y coordinates showed on below antenna photo) for each antenna are entered in the MPE spreadsheet.

Antenna photo



The power densities of up to 2 antennas located within a 90 cm<sup>2</sup> region at 1cm intervals are estimated first. Then the power densities computed for each antenna are summed.

The plot “% MPE Contour” displays the result in percentages of the frequency-dependent power density limits. As the measured power density at 20cm from the transmitter is lower than the MPE limit (the compliance boundary for simultaneous transmission), the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the radiating structures of the transmitter and body of the user or nearby persons.

# INTERTEK TESTING SERVICES

Antenna No.		Total	1	2	3	4	5	6
Tx Status			On	On	Off	Off	Off	Off
Frequency	MHz		13.56	2450	1900	2450	2450	5800
MPE Limit	mW/cm <sup>2</sup>		0.98	1.00	0.00	0.00	0.00	0.00
Max % MPE	%	6.6	0.0	6.6	0.0	0.0	0.0	0.0
Power	(W)	0.200	0.000	0.200	0.000	0.000	0.000	0.000
Antenna Gain	dBi		0.00	2.20	3.00	1.50	0.50	1.00
EIRP	(W)	0.33	0.000	0.332	0.000	0.000	0.000	0.000
X	(cm)		6.0	0.0	12.0	4.0	-8.0	8.0
Y	(cm)		0.0	14.0	0.0	0.0	0.0	0.0
Sector			FALSE	FALSE	FALSE	FALSE	FALSE	FALSE
Arc			FALSE	FALSE	FALSE	FALSE	FALSE	FALSE
$\theta_1$	degs	input	-120	-120	-120	-120	-120	-120
$\theta_2$			60	60	60	60	60	60
$\theta_1$		actual	-120	-120	-120	-120	-120	-120
$\theta_2$			60	60	60	60	60	60

Note: The 0% contour surrounding the antennas identifies a 20 cm perimeter surrounding all active antennas

