



RADIO TEST REPORT

Report No: STS1509033F01

Issued for

Wuunet Technology Co., Ltd

7F, No. 209, Bldg. B, Sec. 1, Nangang Rd., Nangang Dist.,
Taipei City, Taiwan (11568)

Product Name:	Personal Cloud Box
Brand Name:	N/A
Model No.:	PCX-1000
Series Model:	N/A
FCC ID:	2AF8P-PCX1000
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented test sample.





TEST RESULT CERTIFICATION

Applicant's name.....: Wuunet Technology Co., Ltd
Address.....: 7F, No. 209, Bldg. B, Sec. 1, Nangang Rd., Nangang Dist., Taipei City, Taiwan (11568)
Manufacture's Name: Sunitec Enterprise Co., Ltd
Address.....: No.2,Qilin Road 2, RunTang Ind, Dan-Keng Village Fu Min Community, Guan-Lan Town, BaoAn District,Shenzhen Guangdong China

Product description

Product name: Personal Cloud Box
Model and/or type reference : PCX-1000
Serial Model.....: N/A

Standards: FCC Part15.247

Test procedure..... ANSI C63.10-2013

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test.....:

Date (s) of performance of tests.....: 10 Sep. 2015 ~18 Sep. 2015

Date of Issue: 19 Sep. 2015

Test Result.....: **Pass**

Testing Engineer :

(Jin Ming)

Technical Manager :

(Vita Li)

Authorized Signatory :

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST	12
2.4 DESCRIPTION OF SUPPORT UNITS	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST RESULT	15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	18
3.2.3 TEST SETUP	19
3.2.4 EUT OPERATING CONDITIONS	20
3.2.5 TEST RESULT	21
4. CONDUCTED SPURIOUS EMISSIONS	27
4.1 APPLIED PROCEDURES / LIMIT	27
4.2 TEST PROCEDURE	27
4.3 DEVIATION FROM STANDARD	27
4.4 TEST SETUP	27
4.5 EUT OPERATION CONDITIONS	27
4.6 TEST RESULTS	28
5. POWER SPECTRAL DENSITY TEST	40
5.1 APPLIED PROCEDURES / LIMIT	40
5.2 TEST PROCEDURE	40
5.3 DEVIATION FROM STANDARD	40
5.4 TEST SETUP	40
5.5 EUT OPERATION CONDITIONS	40
5.6 TEST RESULTS	41



Table of Contents	Page
6. BANDWIDTH TEST	49
6.1 APPLIED PROCEDURES / LIMIT	49
6.2 TEST PROCEDURE	49
6.3 DEVIATION FROM STANDARD	49
6.4 TEST SETUP	49
6.5 EUT OPERATION CONDITIONS	49
6.6 TEST RESULTS	49
7. PEAK OUTPUT POWER TEST	58
7.1 APPLIED PROCEDURES / LIMIT	58
7.2 TEST PROCEDURE	58
7.3 DEVIATION FROM STANDARD	58
7.4 TEST SETUP	58
7.5 EUT OPERATION CONDITIONS	58
7.6 TEST RESULTS	59
8. ANTENNA REQUIREMENT	60
8.1 STANDARD REQUIREMENT	60
8.2 EUT ANTENNA	60
APPENDIX - PHOTOS OF TEST SETUP	61

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	19 Sep. 2015	STS1509033F01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b) (reference KDB 558074 d05 v02. /9.1.2)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Conducted Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
6	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
7	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
8	Temperature	$\pm 0.5^{\circ}\text{C}$
9	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Personal Cloud Box	
Trade Name	N/A	
Model Name	PCX-1000	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a Personal Cloud Box	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz 802.11n 40: 2422~2452MHz
	Modulation Type:	CCK/OFDM/DBPSK/DAPSK
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20/40MHz):300/150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20: 11CH 802.11n 40: 7CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	3.7 dbi
Channel List	Please refer to the Note 2.	
Adapter	Input: AC100-240V, 500mA, 47~63 Hz Output: DC 5V, 2100mA	
Hardware version number	--	
Software versioning number	--	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:


- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				



3

Emissions Testing of Transmitters with Multiple Outputs in the Same Band.

For devices having two outputs driving a cross-polarized pair of antennas, see Attachment 662911 D02 of this publication for additional guidance.

d) *Unequal antenna gains, with equal transmit powers.* For antenna gains given by G_1, G_2, \dots, G_N dBi

(i) If transmit signals are *correlated*, then Directional gain = $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / NANT]$ dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

(ii) If all transmit signals are *completely uncorrelated*, then Directional gain = $10 \log[(10^{G_1/10} + 10^{G_2/10} + \dots + 10^{G_N/10}) / NANT]$ dBi

Not: If transmit signals are *correlated*, then Directional gain.

ANT-A=2.8 dBi


ANT-B=2.8 dBi

Total gain= $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / NANT]$ dBi

$10 * \log_{10}((10^{2.8/20} + 10^{2.8/20})^2 / 2) = 3.67936 \approx 3.7$

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	PCX-1000	Ceramic Antenna	N/A	ANT-A=2.8 dBi ANT-B=2.8 dBi	N/A





2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging + Keeping TX mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Charging + Keeping TX mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	Low
Mode 2	Middle
Mode 3	High
Mode 4	Charging + Keeping TX mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported
- (3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TEST



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Personal Cloud Box	N/A	PCX-1000	N/A	EUT
E-2	PC	HP	500-320cx	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	unshielded	NO	101cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2014.10.25	2015.10.24
Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2014.11.25	2015.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2015.03.06	2016.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
PreAmplifier	Agilent	8449B	60538	2014.10.25	2015.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2014.10.25	2015.10.24

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2014.11.20	2015.11.19
LISN	R&S	ENV216	101242	2014.10.25	2015.10.24
LISN	EMCO	3810/2NM	000-23625	2014.10.25	2015.10.24



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver



3.1.2 TEST RESULT


EUT:	Personal Cloud Box	Model Name.:	PCX-1000
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	AC120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1580	48.94	10.24	59.18	65.57	-6.39	QP
0.1580	31.91	10.24	42.15	55.57	-13.42	AVG
0.2660	39.36	9.93	49.29	61.24	-11.95	QP
0.2660	25.19	9.93	35.12	51.24	-16.12	AVG
0.5940	35.86	9.95	45.81	56.00	-10.19	QP
0.5940	22.34	9.95	32.29	46.00	-13.71	AVG
1.0780	34.31	9.91	44.22	56.00	-11.78	QP
1.0780	12.00	9.91	21.91	46.00	-24.09	AVG
3.6820	30.19	10.19	40.38	56.00	-15.62	QP
3.6820	13.65	10.19	23.84	46.00	-22.16	AVG
16.2060	39.81	10.42	50.23	60.00	-9.77	QP
16.2060	23.09	10.42	33.51	50.00	-16.49	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV






EUT:	Personal Cloud Box	Model Name.:	PCX-1000
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Voltage:	AC120V/60Hz	Test Mode:	Mode 4

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.1620	43.49	10.00	53.49	65.36	-11.87	QP
0.1620	27.83	10.00	37.83	55.36	-17.53	AVG
0.5900	41.54	9.94	51.48	56.00	-4.52	QP
0.5900	28.97	9.94	38.91	46.00	-7.09	AVG
1.1980	35.80	10.00	45.80	56.00	-10.20	QP
1.1980	14.38	10.00	24.38	46.00	-21.62	AVG
3.0940	36.42	10.00	46.42	56.00	-9.58	QP
3.0940	17.34	10.00	27.34	46.00	-18.66	AVG
9.8220	31.34	10.19	41.53	60.00	-18.47	QP
9.8220	17.43	10.19	27.62	50.00	-22.38	AVG
16.7260	40.52	10.40	50.92	60.00	-9.08	QP
16.7260	24.47	10.40	34.87	50.00	-15.13	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

6 dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&205(a), then the Part 15.247&209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10 th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.5 TEST RESULT

9KHz-30MHz

EUT:	Personal Cloud Box	Model Name. :	PCX-1000
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Link mode	Polarization :	--


Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.





30MHz - 1000MHz


EUT:	Personal Cloud Box	Model Name. :	PCX-1000
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
32.0667	6.85	17.64	24.49	40.00	-15.51	QP
81.2116	19.25	8.19	27.44	40.00	-12.56	QP
148.4410	23.76	12.05	35.81	43.50	-7.69	QP
174.4241	27.60	10.27	37.87	43.50	-5.63	QP
250.3012	22.32	13.70	36.02	46.00	-9.98	QP
580.7025	16.00	22.32	38.32	46.00	-7.68	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





30MHz - 1000MHz


EUT:	Personal Cloud Box	Model Name. :	PCX-1000
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	Vertical

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
30.8535	15.12	18.27	33.39	40.00	-6.61	QP
58.6126	28.54	5.55	34.09	40.00	-5.91	QP
77.8654	26.93	7.63	34.56	40.00	-5.44	QP
153.2004	27.56	11.89	39.45	43.50	-4.05	QP
250.3011	18.00	13.70	31.70	46.00	-14.30	QP
580.7025	12.87	22.32	35.19	46.00	-10.81	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





Above 1000MHz

EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11b/2412 MHz)							
4824.20	62.07	-3.58	58.49	74	-15.51	PK	Vertical
4824.21	43.35	-3.58	39.77	54	-14.23	AV	Vertical
7236.14	58.65	-0.8	57.85	74	-16.15	PK	Vertical
7236.12	37.82	-0.8	37.02	54	-16.98	AV	Vertical
4824.20	58.56	-3.58	54.98	74	-19.02	PK	Horizontal
4824.21	40.59	-3.58	37.01	54	-16.99	AV	Horizontal
Mid Channel (802.11b/2437 MHz)							
4874.08	63.51	-3.56	59.95	74	-14.05	PK	Vertical
4874.07	47.48	-3.56	43.92	54	-10.08	AV	Vertical
7311.22	59.58	-0.78	58.8	74	-15.2	PK	Vertical
7311.21	43.12	-0.78	42.34	54	-11.66	AV	Vertical
4874.18	59.76	-3.56	56.2	74	-17.8	PK	Horizontal
4874.15	43.82	-3.56	40.26	54	-13.74	AV	Horizontal
High Channel (802.11b/2462 MHz)							
4944.26	59.82	-3.54	56.28	74	-17.72	PK	Vertical
4944.31	43.63	-3.54	40.09	54	-13.91	AV	Vertical
7416.33	60.01	-0.75	59.26	74	-14.74	PK	Vertical
7416.30	44.09	-0.75	43.34	54	-10.66	AV	Vertical
4944.26	59.64	-3.54	56.1	74	-17.9	PK	Horizontal
4944.30	44.02	-3.54	40.48	54	-13.52	AV	Horizontal
Remark: 1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. 2. Scan with 802.11b, 802.11g, 802.11n (HT-20), 802.11n (HT-40), the worst case is 802.11b.							



3.2.6 TEST RESULTS (Band edge)

EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11 b							
2390.0	67.06	-12.99	54.07	74	-19.93	PK	Vertical
2390.0	53.78	-12.99	40.79	54	-13.21	AV	Vertical
2390.0	65.35	-12.99	52.36	74	-21.64	PK	Horizontal
2390.0	51.47	-12.99	38.48	54	-15.52	AV	Horizontal
2483.6	65.54	-12.78	52.76	74	-21.24	PK	Vertical
2483.6	51.87	-12.78	39.09	54	-14.91	AV	Vertical
2483.6	67.02	-12.78	54.24	74	-19.76	PK	Horizontal
2483.6	52.48	-12.78	39.7	54	-14.3	AV	Horizontal
802.11 g							
2399.9	67.10	-12.99	54.11	74	-19.89	PK	Vertical
2399.9	54.11	-12.99	41.12	54	-12.88	AV	Vertical
2399.9	65.76	-12.99	52.77	74	-21.23	PK	Horizontal
2399.9	51.88	-12.99	38.89	54	-15.11	AV	Horizontal
2483.6	65.92	-12.78	53.14	74	-20.86	PK	Vertical
2483.6	52.03	-12.78	39.25	54	-14.75	AV	Vertical
2483.6	67.11	-12.78	54.33	74	-19.67	PK	Horizontal
2483.6	52.59	-12.78	39.81	54	-14.19	AV	Horizontal



802.11 n20							
2399.9	66.72	-12.99	53.73	74	-20.27	PK	Vertical
2399.9	53.91	-12.99	40.92	54	-13.08	AV	Vertical
2399.9	65.82	-12.99	52.83	74	-21.17	PK	Horizontal
2399.9	51.34	-12.99	38.35	54	-15.65	AV	Horizontal
2483.6	65.32	-12.78	52.54	74	-21.46	PK	Vertical
2483.6	52.11	-12.78	39.33	54	-14.67	AV	Vertical
2483.6	66.87	-12.78	54.09	74	-19.91	PK	Horizontal
2483.6	52.74	-12.78	39.96	54	-14.04	AV	Horizontal
802.11 n40							
2399.9	67.07	-12.99	54.08	74	-19.92	PK	Vertical
2399.9	52.56	-12.99	39.57	54	-14.43	AV	Vertical
2399.9	68.00	-12.99	55.01	74	-18.99	PK	Horizontal
2399.9	51.99	-12.99	39	54	-15	AV	Horizontal
2483.6	68.78	-12.78	56	74	-18	PK	Vertical
2483.6	51.93	-12.78	39.15	54	-14.85	AV	Vertical
2483.6	68.60	-12.78	55.82	74	-18.18	PK	Horizontal
2483.6	51.52	-12.78	38.74	54	-15.26	AV	Horizontal
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							
Low measurement frequencies is range from 2310 to 2400 MHz, high measurement frequencies is range from 2483.5 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.							

4. CONDUCTED SPURIOUS EMISSIONS

4.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




4.6 TEST RESULTS

Not: A/B Represent the value of antennaA/B,The worst data is Antenna A ,only shown Antenna A Plot.


EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX b Mode /CH01, CH06, CH11		

TX 802.11b Mode CH 01 (Ant A) worst data






TX 802.11b Mode CH 06 (Ant A) worst data




TX 802.11b Mode CH 11 (Ant A) worst data






Band edge

TX 802.11b Mode CH 01 (Ant A) worst data




TX 802.11b Mode CH 11 (Ant A) worst data






EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX g Mode /CH01, CH06, CH11		

TX 802.11g Mode CH 01 (Ant A) worst data




TX 802.11g Mode CH 06 (Ant A) worst data






TX 802.11g Mode CH11 (Ant A) worst data






Band edge

TX 802.11g Mode CH 01 (Ant A) worst data




TX 802.11g Mode CH 11 (Ant A) worst data






EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

TX 802.11n(HT20) Mode CH 01 (Ant A) worst data




TX 802.11n(HT20) Mode CH 06 (Ant A) worst data






TX 802.11n(HT20) Mode CH 11 (Ant A) worst data






Band edge

TX 802.11n(HT20) Mode CH 01 (Ant A) worst data




TX 802.11n(HT20) Mode CH 11 (Ant A) worst data






EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		

TX 802.11n(HT40) Mode CH 03 (Ant A) worst data






TX 802.11n(HT40) Mode CH 06 (Ant A) worst data




TX 802.11n(HT40) Mode CH 09 (Ant A) worst data






Band edge

TX 802.11n(HT40) Mode CH 03 (Ant A) worst data



TX 802.11n(HT40) Mode CH 09 (Ant A) worst data





5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100\text{ kHz} \geq \text{RBW} \geq 3\text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




5.6 TEST RESULTS

Not: Power density is the sum of the power density(A+B),The worst data is Antenna A ,only shown Antenna A Plot.

EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	Power Density (A/dBm)	Power Density (B/dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-5.967	-6.040	-2.993	8	PASS
2437 MHz	-4.764	-4.830	-1.787	8	PASS
2462 MHz	-4.013	-3.860	-0.926	8	PASS

TX 802.11b Mode CH 01 (Ant A) worst data






TX 802.11b Mode CH 06 (Ant A) worst data



TX 802.11b Mode CH 11 (Ant A) worst data






EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	Power Density (A/dBm)	Power Density (B/dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-11.680	-11.750	-8.705	8	PASS
2437 MHz	-10.510	-10.500	-7.495	8	PASS
2462 MHz	-9.688	-9.690	-6.679	8	PASS

TX 802.11g Mode CH 01 (Ant A) worst data






TX 802.11g Mode CH 06 (Ant A) worst data



TX 802.11g Mode CH 11 (Ant A) worst data






EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	Power Density (A/dBm)	Power Density (B/dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-11.500	-11.490	-8.485	8	PASS
2437 MHz	-10.420	-10.280	-7.339	8	PASS
2462 MHz	-11.500	-11.440	-8.460	8	PASS

TX 802.11n(HT20) Mode CH 01 (Ant A) worst data






TX 802.11n(HT20) Mode CH 06 (Ant A) worst data



TX 802.11n(HT20) Mode CH 11 (Ant A) worst data






EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		


Frequency	Power Density (A/dBm)	Power Density (B/dBm)	Total Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-19.400	-19.250	-16.314	8	PASS
2437 MHz	-18.950	-19.000	-15.965	8	PASS
2452 MHz	-19.230	-19.270	-16.240	8	PASS

TX 802.11n(HT40) Mode CH 03 (Ant A) worst data






TX 802.11n(HT40) Mode CH 06 (Ant A) worst data



TX 802.11n(HT40) Mode CH 09 (Ant A) worst data





6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW \geq 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

Note:A/B Represent the value of antennaA/B,The worst data is A Antenna a ,only shown Antenna A Plot.




EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	6dB /Ant A Bandwidth (MHz)	6dB /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	9.561	9.586	>=500KHz	PASS
2437 MHz	9.578	9.580	>=500KHz	PASS
2462 MHz	10.038	10.058	>=500KHz	PASS

Frequency	99% /Ant A Bandwidth (MHz)	99% /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	12.826	12.887	>=500KHz	PASS
2437 MHz	12.730	12.767	>=500KHz	PASS
2462 MHz	12.343	12.349	>=500KHz	PASS


TX 802.11b Mode CH 01 (Ant A) worst data



TX 802.11b Mode CH 06 (Ant A) worst data



TX 802.11b Mode CH 11 (Ant A) worst data



EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%




Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB /Ant A Bandwidth (MHz)	6dB /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	15.800	15.854	>=500KHz	PASS
2437 MHz	15.800	15.812	>=500KHz	PASS
2462 MHz	15.465	15.453	>=500KHz	PASS

Frequency	99% /Ant A Bandwidth (MHz)	99% /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	16.391	16.358	>=500KHz	PASS
2437 MHz	16.344	16.346	>=500KHz	PASS
2462 MHz	16.336	16.376	>=500KHz	PASS


TX 802.11g Mode CH 01 (Ant A) worst data



TX 802.11g Mode CH 06 (Ant A) worst data



TX 802.11g Mode CH 11 (Ant A) worst data



EUT :

Personal Cloud Box

Model Name :

PCX-1000




Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	6dB /Ant A Bandwidth (MHz)	6dB /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	17.047	17.049	>=500KHz	PASS
2437 MHz	16.648	16.651	>=500KHz	PASS
2462 MHz	15.432	15.445	>=500KHz	PASS

Frequency	99% /Ant A Bandwidth (MHz)	99% /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	17.517	17.556	>=500KHz	PASS
2437 MHz	17.528	17.564	>=500KHz	PASS
2462 MHz	17.518	17.527	>=500KHz	PASS


TX 802.11n(HT20) Mode CH 01 (Ant A) worst data



TX 802.11n(HT20) Mode CH 06 (Ant A) worst data



TX 802.11n(HT20) Mode CH 11 (Ant A) worst data



EUT :

Personal Cloud Box

Model Name :

PCX-1000




Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX n Mode(40M) /CH03, CH06, CH09		



Frequency	6dB /Ant A Bandwidth (MHz)	6dB /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2422 MHz	35.390	35.396	>=500KHz	PASS
2437 MHz	35.342	35.345	>=500KHz	PASS
2452 MHz	34.916	34.920	>=500KHz	PASS

Frequency	99% /Ant A Bandwidth (MHz)	99% /Ant B Bandwidth (MHz)	Channel Separation (KHz)	Result
2422 MHz	35.740	35.745	>=500KHz	PASS
2437 MHz	35.776	35.778	>=500KHz	PASS
2452 MHz	35.801	35.808	>=500KHz	PASS

TX 802.11n(HT40) Mode CH 03 (Ant A) worst data



TX 802.11n(HT40) Mode CH 06 (Ant A) worst data

**TX 802.11n(HT40) Mode CH 09 (Ant A) worst data**



7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor&Power meter

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULTS

Note: Output Power is the sum of the Output power A/B

EUT :	Personal Cloud Box	Model Name :	PCX-1000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V
Test Mode :	TX b/g/n(20M,40M) Mode /CH01, CH06, CH11		

TX 802.11b Mode					
Test Channe	Frequency	Peak Conducted Output Power(dBm)			LIMIT
	(MHz)	Ant A	Ant B	Total power (dBm)	dBm
CH01	2412	16.21	16.32	19.28	30
CH06	2437	16.22	16.13	19.19	30
CH11	2462	16.54	16.58	19.57	30

TX 802.11g Mode					
Test Channe	Frequency	Peak Conducted Output Power(dBm)			LIMIT
	(MHz)	Ant A	Ant B	Total power (dBm)	dBm
CH01	2412	14.82	14.79	17.82	30
CH06	2437	14.74	14.88	17.82	30
CH11	2462	14.85	14.90	17.89	30

TX 802.11n20 Mode					
Test Channe	Frequency	Peak Conducted Output Power(dBm)			LIMIT
	(MHz)	Ant A	Ant B	Total power (dBm)	dBm
CH01	2412	14.86	15.01	17.95	30
CH06	2437	14.73	14.66	17.71	30
CH11	2462	14.84	14.81	17.84	30

TX 802.11n40 Mode					
Test Channe	Frequency	Peak Conducted Output Power(dBm)			LIMIT
	(MHz)	Ant A	Ant B	Total power (dBm)	dBm
CH03	2422	12.95	12.95	15.96	30
CH06	2437	13.28	14.43	16.90	30
CH09	2452	13.13	13.16	16.16	30



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



8.2 EUT ANTENNA

The EUT antenna is Ceramic Antenna. It comply with the standard requirement.



APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos



Conducted Measurement Photos



*****END OF THE REPORT*****