

# **FCC ID: 2AF9Q-ST3007**

## **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

### **11.1 Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi$ =3.1416

$R$ = distance between observation point and center of the radiator in cm(20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

$mW = 10^{(dBm/10)}$

### **11.2 Measurement Result**

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: Ceramic Chip Antenna

Antenna gain: 1.0dBi,

$R$ =20cm

$mW = 10^{(dBm/10)}$

802.11b:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2412	802.11b	18.28	12.62	13±1	14	1.26	0.006294	1
2437	802.11b	18.41	12.65	13±1	14	1.26	0.006294	1
2462	802.11b	19.86	12.98	13±1	14	1.26	0.006294	1
2412	802.11g	15.07	11.78	12.0±1	13	1.26	0.005000	1
2437	802.11g	15.60	11.93	12.0±1	13	1.26	0.005000	1
2462	802.11g	15.96	12.03	12.0±1	13	1.26	0.005000	1
2412	802.11n H20	11.59	10.64	11±1	12	1.26	0.003971	1
2437	802.11n H20	11.43	10.58	11±1	12	1.26	0.003971	1
2462	802.11n H20	11.80	10.72	11±1	12	1.26	0.003971	1

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: Ceramic Chip Antenna

Antenna gain: 1.0dBi,

R=20cm

mW=10<sup>^(dBm/10)</sup>

Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2402	GFSK	4.12	6.15	6.0±1	7	1.26	0.001255	1
2440		4.68	6.7	6.0±1	7	1.26	0.001255	1
2480		4.19	6.22	6.0±1	7	1.26	0.001255	1

#### Conclusion:

For the max result : 0.006294≤ 3.0 for 1g SAR, No SAR is required.

*Brown Lu*

**Signature:**

**Date:** 2016-3-23

**NAME AND TITLE** (Please print or type): Brown Lu/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.