

FCC PART 15.247 TEST REPORT

For

CROSBY LIMITED

Room 201B Floor 2, Lee Wai Commercial Building, 1-3 Hart Avenue, T.S.T., Kowloon, Hong Kong

FCC ID: 2AFBHSP814

Report Type: **Product Type:** Original Report Bluetooth Speaker Wang Emily Test Engineer: Emily Wang **Report Number:** RDG160629802-00 **Report Date:** 2016-08-04)ean. Lau. Dean Liu Reviewed By: RF Engineer Bay Area Compliance Laboratories Corp. (Dongguan) **Test Laboratory:** No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT EXERCISE SOFTWARE	
EQUIPMENT MODIFICATIONS	
EXTERNAL CABLE	
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	7
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	8
Antenna Connector Construction	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
Measurement Uncertainty EUT Setup	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUPEMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
TEST FROCEDORE TEST EQUIPMENT LIST AND DETAILS.	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST DATA	16
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	
APPLICABLE STANDARD	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	28

APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	38
Applicable Standard	
TEST PROCEDURE	
TEST FROCEDURE TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	54
APPLICABLE STANDARD	54
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	
FCC §15.247(d) - BAND EDGES TESTING	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
Trop Data	61

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The CROSBY LIMITED's product, model number: LI-S20254BT (FCC ID: 2AFBHSP814) (the "EUT") in this report was a Bluetooth Speaker, which was measured approximately: 8.5 mm (L) x 8.5 mm (W) x5.3 mm (H), rated input voltage: DC3.7V from battery or DC5V from USB port.

Report No.: RDG160629802-00

Note: The series product, model LI-S20254BT, FA-S141BT, FA-S45BT, CR-S141BT are electrically identical, the difference between them just is the model name, we selected LI-S20254BT for fully testing, the details were explained in the declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 160629802 (Assigned by BACL, Dongguan). The EUT was received on 2016-06-30.

Objective

This report is prepared on behalf of *CROSBY LIMITED* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.247 Page 4 of 64

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The software 'BK3256 RF Test_V1.3.exe' was used during testing, the system configured maxmum output power as default setting. The software is only for changing channel and modes.

Report No.: RDG160629802-00

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Plum	Switching Adapter	PMC43	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
USB Cable	No	No	0.55	Adapter	EUT





FCC Part 15.247 Page 5 of 64

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & \$1.1310 & \$2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

Report No.: RDG160629802-00

FCC Part 15.247 Page 6 of 64

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: RDG160629802-00

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum tune-up power including tolerance is 0 dBm(1mW). [(max. power of channel, mW)/(min. test separation distance, mm)][$\sqrt{f(GHz)}$] = 1.0/5*($\sqrt{2.480}$) = 0.3 < 3.0

So the stand-alone SAR evaluation is not necessary.

FCC Part 15.247 Page 7 of 64

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RDG160629802-00

Antenna Connector Construction

The EUT has one internal antenna arrangement for buletooth and the antenna gain is -3.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 8 of 64

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG160629802-00

If $U_{\rm lab}$ is less than or equal to $U_{\rm cispr}$ of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 − Values of U_{cispr}

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 9 of 64

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

Report No.: RDG160629802-00

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W		
150 kHz – 30 MHz	9 kHz		

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

 V_C : corrected voltage amplitude V_R : reading voltage amplitude A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 10 of 64

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2016-06-09	2017-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2016-05-06	2017-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

Report No.: RDG160629802-00

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	31.6°C
Relative Humidity:	48%
ATM Pressure:	100.3 kPa


The testing was performed by Emily Wang on 2016-07-01.

FCC Part 15.247 Page 11 of 64

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting

AC120 V, 60 Hz, Line:




Report No.: RDG160629802-00

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.406123	27.9	9.000	L1	10.2	29.8	57.7	Compliance
0.541050	26.7	9.000	L1	10.1	29.3	56.0	Compliance
1.039922	22.0	9.000	L1	10.4	34.0	56.0	Compliance
1.289541	26.9	9.000	L1	10.4	29.1	56.0	Compliance
1.407671	26.4	9.000	L1	10.4	29.6	56.0	Compliance
1.787792	17.0	9.000	L1	10.4	39.0	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.241949	17.9	9.000	L1	10.2	34.1	52.0	Compliance
0.255827	17.6	9.000	L1	10.2	34.0	51.6	Compliance
0.415949	20.7	9.000	L1	10.2	26.8	47.5	Compliance
0.511698	20.1	9.000	L1	10.1	25.9	46.0	Compliance
1.239175	19.3	9.000	L1	10.4	26.7	46.0	Compliance
1.289541	20.9	9.000	L1	10.4	25.1	46.0	Compliance

FCC Part 15.247 Page 12 of 64

AC120 V, 60 Hz, Neutral:



Report No.: RDG160629802-00

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.426011	28.5	9.000	N	10.2	28.8	57.3	Compliance
0.439808	29.5	9.000	N	10.1	27.6	57.1	Compliance
0.541050	27.1	9.000	N	10.1	28.9	56.0	Compliance
0.581275	26.2	9.000	N	10.2	29.8	56.0	Compliance
1.219583	25.4	9.000	N	10.4	30.6	56.0	Compliance
1.385415	27.8	9.000	N	10.4	28.2	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.396530	21.4	9.000	N	10.2	26.5	47.9	Compliance
0.443327	20.9	9.000	N	10.1	26.1	47.0	Compliance
0.511698	21.2	9.000	N	10.1	24.8	46.0	Compliance
0.975701	19.4	9.000	N	10.4	26.6	46.0	Compliance
1.239175	20.0	9.000	N	10.4	26.0	46.0	Compliance
1.289541	20.9	9.000	N	10.4	25.1	46.0	Compliance

FCC Part 15.247 Page 13 of 64

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG160629802-00

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of U_{cispr}

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				

EUT Setup

Below 1GHz:



FCC Part 15.247 Page 14 of 64

Above 1GHz:



Report No.: RDG160629802-00

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 15 of 64

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-18
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06

Report No.: RDG160629802-00

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Data

Environmental Conditions

Temperature:	26.1°C
Relative Humidity:	71%
ATM Pressure:	99.7kPa

^{*} The testing was performed by Emily Wang on 2016-07-12.


Test Mode: Transmitting

FCC Part 15.247 Page 16 of 64

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Below 1GHz:

Horizontal:




Report No.: RDG160629802-00

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	21.55	QP	0.95	22.50	40.00	17.50
126.0300	21.68	QP	-5.58	16.10	43.50	27.40
170.6500	25.26	QP	-7.96	17.30	43.50	26.20
286.0800	23.81	QP	-5.91	17.90	46.00	28.10
479.1100	22.34	QP	-1.74	20.60	46.00	25.40
640.1300	22.18	QP	0.62	22.80	46.00	23.20

FCC Part 15.247 Page 17 of 64

Vertical:



Report No.: RDG160629802-00

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.0000	29.15	QP	0.95	30.10	40.00	9.90
46.4900	39.10	QP	-10.60	28.50	40.00	11.50
185.2000	26.33	QP	-8.43	17.90	43.50	25.60
334.5800	21.46	QP	-5.16	16.30	46.00	29.70
440.3100	21.67	QP	-2.77	18.90	46.00	27.10
602.3000	20.88	QP	-0.68	20.20	46.00	25.80

FCC Part 15.247 Page 18 of 64

BDR Mode (GFSK):

Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
	Reading	D	Polar	Factor	loss	Gain	Amplitude	Limit	Margin
(MHz)	(dBµV)	Detector	(H/V)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
				Low Chann	el: 2402 N	MHz	· · ·		, ,
2402	60.50	PK	Н	25.65	3.66	0.00	89.81	N/A	N/A
2402	52.02	AV	Н	25.65	3.66	0.00	81.33	N/A	N/A
2402	56.16	PK	V	25.65	3.66	0.00	85.47	N/A	N/A
2402	46.36	AV	V	25.65	3.66	0.00	75.67	N/A	N/A
2390	29.73	PK	Н	25.61	3.63	0.00	58.97	74.00	15.03
2390	15.70	AV	Н	25.61	3.63	0.00	44.94	54.00	9.06
4804	43.80	PK	Н	30.59	5.06	27.41	52.04	74.00	21.96
4804	36.21	AV	Н	30.59	5.06	27.41	44.45	54.00	9.55
7206	32.58	PK	Н	34.09	6.61	25.91	47.37	74.00	26.63
7206	23.65	AV	Н	34.09	6.61	25.91	38.44	54.00	15.56
3327	49.06	PK	Н	28.25	4.95	27.26	55.00	74.00	19.00
3327	46.99	AV	Н	28.25	4.95	27.26	52.93	54.00	1.07
Middle Channel: 2441 MHz									
2441	60.56	PK	Н	25.75	3.76	0.00	90.07	N/A	N/A
2441	52.01	AV	Н	25.75	3.76	0.00	81.52	N/A	N/A
2441	55.72	PK	V	25.75	3.76	0.00	85.23	N/A	N/A
2441	45.79	AV	V	25.75	3.76	0.00	75.30	N/A	N/A
4882	42.17	PK	Н	30.79	5.19	27.42	50.73	74.00	23.27
4882	34.65	AV	Н	30.79	5.19	27.42	43.21	54.00	10.79
7323	33.19	PK	Н	34.38	6.75	25.88	48.44	74.00	25.56
7323	24.61	AV	Н	34.38	6.75	25.88	39.86	54.00	14.14
3327	49.35	PK	Н	28.25	4.95	27.26	55.29	74.00	18.71
3327	47.19	AV	Н	28.25	4.95	27.26	53.13	54.00	0.87
3723	33.57	PK	Н	29.29	4.59	27.34	40.11	74.00	33.89
3723	21.02	AV	Н	29.29	4.59	27.34	27.56	54.00	26.44
				High Chann		MHz			
2480	60.34	PK	Н	25.85	3.68	0.00	89.87	N/A	N/A
2480	52.72	AV	Н	25.85	3.68	0.00	82.25	N/A	N/A
2480	55.13	PK	V	25.85	3.68	0.00	84.66	N/A	N/A
2480	45.92	AV	V	25.85	3.68	0.00	75.45	N/A	N/A
2483.5	39.86	PK	Н	25.86	3.67	0.00	69.39	74.00	4.61
2483.5	22.44	AV	Н	25.86	3.67	0.00	51.97	54.00	2.03
4960	44.12	PK	Н	31.00	5.34	27.43	53.03	74.00	20.97
4960	36.17	AV	Н	31.00	5.34	27.43	45.08	54.00	8.92
7440	33.21	PK	Н	34.66	6.89	25.97	48.79	74.00	25.21
7440	25.68	AV	Н	34.66	6.89	25.97	41.26	54.00	12.74
3327	49.07	PK	Н	28.25	4.95	27.26	55.01	74.00	18.99
3327	47.11	AV	Н	28.25	4.95	27.26	53.05	54.00	0.95

Report No.: RDG160629802-00

FCC Part 15.247 Page 19 of 64

EDR Mode ($\pi/4$ -DOPSK):

Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
			1	Low Chann	el: 2402 N	МНz			
2402	60.54	PK	Н	25.65	3.66	0.00	89.85	N/A	N/A
2402	48.68	AV	Н	25.65	3.66	0.00	77.99	N/A	N/A
2402	55.82	PK	V	25.65	3.66	0.00	85.13	N/A	N/A
2402	43.41	AV	V	25.65	3.66	0.00	72.72	N/A	N/A
2390	29.35	PK	Н	25.61	3.63	0.00	58.59	74.00	15.41
2390	14.23	AV	Н	25.61	3.63	0.00	43.47	54.00	10.53
4804	42.08	PK	Н	30.59	5.06	27.41	50.32	74.00	23.68
4804	34.58	AV	Н	30.59	5.06	27.41	42.82	54.00	11.18
7206	31.82	PK	Н	34.09	6.61	25.91	46.61	74.00	27.39
7206	22.84	AV	Н	34.09	6.61	25.91	37.63	54.00	16.37
3327	49.33	PK	Н	28.25	4.95	27.26	55.27	74.00	18.73
3327	47.28	AV	Н	28.25	4.95	27.26	53.22	54.00	0.78
Middle Channel: 2441 MHz									
2441	60.12	PK	Н	25.75	3.76	0.00	89.63	N/A	N/A
2441	48.87	AV	Н	25.75	3.76	0.00	78.38	N/A	N/A
2441	55.10	PK	V	25.75	3.76	0.00	84.61	N/A	N/A
2441	43.53	AV	V	25.75	3.76	0.00	73.04	N/A	N/A
4882	41.05	PK	Н	30.79	5.19	27.42	49.61	74.00	24.39
4882	30.89	AV	Н	30.79	5.19	27.42	39.45	54.00	14.55
7323	32.92	PK	Н	34.38	6.75	25.88	48.17	74.00	25.83
7323	20.67	AV	Н	34.38	6.75	25.88	35.92	54.00	18.08
3327	49.30	PK	Н	28.25	4.95	27.26	55.24	74.00	18.76
3327	47.08	AV	Н	28.25	4.95	27.26	53.02	54.00	0.98
3770	33.62	PK	Н	29.39	4.59	27.36	40.24	74.00	33.76
3770	21.41	AV	Н	29.39	4.59	27.36	28.03	54.00	25.97
				High Chann		MHz			
2480	60.43	PK	Н	25.85	3.68	0.00	89.96	N/A	N/A
2480	48.85	AV	Н	25.85	3.68	0.00	78.38	N/A	N/A
2480	54.20	PK	V	25.85	3.68	0.00	83.73	N/A	N/A
2480	42.39	AV	V	25.85	3.68	0.00	71.92	N/A	N/A
2483.5	36.85	PK	Н	25.86	3.67	0.00	66.38	74.00	7.62
2483.5	19.20	AV	Н	25.86	3.67	0.00	48.73	54.00	5.27
4960	41.66	PK	Н	31.00	5.34	27.43	50.57	74.00	23.43
4960	32.56	AV	Н	31.00	5.34	27.43	41.47	54.00	12.53
7440	33.83	PK	Н	34.66	6.89	25.97	49.41	74.00	24.59
7440	24.51	AV	Н	34.66	6.89	25.97	40.09	54.00	13.91
3327	49.43	PK	Н	28.25	4.95	27.26	55.37	74.00	18.63
3327	47.18	AV	Н	28.25	4.95	27.26	53.12	54.00	0.88

Report No.: RDG160629802-00

FCC Part 15.247 Page 20 of 64

EDR Mode (8-DPSK):

Frequency	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
]	Low Chann	el: 2402 N	МНz			
2402	60.56	PK	Н	25.65	3.66	0.00	89.87	N/A	N/A
2402	48.25	AV	Н	25.65	3.66	0.00	77.56	N/A	N/A
2402	55.49	PK	V	25.65	3.66	0.00	84.80	N/A	N/A
2402	43.48	AV	V	25.65	3.66	0.00	72.79	N/A	N/A
2390	29.99	PK	Н	25.61	3.63	0.00	59.23	74.00	14.77
2390	14.58	AV	Н	25.61	3.63	0.00	43.82	54.00	10.18
4804	43.39	PK	Н	30.59	5.06	27.41	51.63	74.00	22.37
4804	31.58	AV	Н	30.59	5.06	27.41	39.82	54.00	14.18
7206	32.16	PK	Н	34.09	6.61	25.91	46.95	74.00	27.05
7206	20.19	AV	Н	34.09	6.61	25.91	34.98	54.00	19.02
3327	49.13	PK	Н	28.25	4.95	27.26	55.07	74.00	18.93
3327	47.32	AV	Н	28.25	4.95	27.26	53.26	54.00	0.74
Middle Channel: 2441 MHz									
2441	60.73	PK	Н	25.75	3.76	0.00	90.24	N/A	N/A
2441	48.14	AV	Н	25.75	3.76	0.00	77.65	N/A	N/A
2441	55.21	PK	V	25.75	3.76	0.00	84.72	N/A	N/A
2441	43.43	AV	V	25.75	3.76	0.00	72.94	N/A	N/A
4882	41.19	PK	Н	30.79	5.19	27.42	49.75	74.00	24.25
4882	31.56	AV	Н	30.79	5.19	27.42	40.12	54.00	13.88
7323	32.15	PK	Н	34.38	6.75	25.88	47.40	74.00	26.60
7323	21.96	AV	Н	34.38	6.75	25.88	37.21	54.00	16.79
3327	49.60	PK	Н	28.25	4.95	27.26	55.54	74.00	18.46
3327	47.13	AV	Н	28.25	4.95	27.26	53.07	54.00	0.93
3765	33.58	PK	Н	29.38	4.58	27.36	40.18	74.00	33.82
3765	20.69	AV	Н	29.38	4.58	27.36	27.29	54.00	26.71
			·	High Chann	el: 2480 l	MHz	_		
2480	60.52	PK	Н	25.85	3.68	0.00	90.05	N/A	N/A
2480	48.88	AV	Н	25.85	3.68	0.00	78.41	N/A	N/A
2480	55.54	PK	V	25.85	3.68	0.00	85.07	N/A	N/A
2480	43.25	AV	V	25.85	3.68	0.00	72.78	N/A	N/A
2483.5	37.56	PK	Н	25.86	3.67	0.00	67.09	74.00	6.91
2483.5	19.54	AV	Н	25.86	3.67	0.00	49.07	54.00	4.93
4960	41.39	PK	Н	31.00	5.34	27.43	50.30	74.00	23.70
4960	32.80	AV	Н	31.00	5.34	27.43	41.71	54.00	12.29
7440	33.10	PK	Н	34.66	6.89	25.97	48.68	74.00	25.32
7440	21.98	AV	Н	34.66	6.89	25.97	37.56	54.00	16.44
3327	49.87	PK	Н	28.25	4.95	27.26	55.81	74.00	18.19
3327	47.34	AV	Н	28.25	4.95	27.26	53.28	54.00	0.72

Report No.: RDG160629802-00

FCC Part 15.247 Page 21 of 64

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Report No.: RDG160629802-00

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA03-5RN	OE01153830	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- 1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
- 2. Set the adjacent channel of the EUT maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	31.4°C
Relative Humidity:	52%
ATM Pressure:	100.3kPa

^{*} The testing was performed by Emily Wang on 2016-08-01.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 22 of 64

Test Mode: Transmitting

Mode	Channel	Frequency	Channel Seperation	Limit
		MHz	MHz	MHz
BDR (GFSK)	Low	2402	1.006	0.57
	Middle	2441	1.002	0.57
	High	2480	1.002	0.57
EDR (π/4-DQPSK)	Low	2402	0.998	0.82
	Middle	2441	1.006	0.81
	High	2480	1.002	0.82
EDR (8DPSK)	Low	2402	0.998	0.844
	Middle	2441	1.002	0.852
	High	2480	1.002	0.844

Report No.: RDG160629802-00

Note: Limit= $(2/3) \times 20dB$ bandwidth

BDR Mode (GFSK):

Low Channel




Date: 01,406,2016 00;49;2

FCC Part 15.247 Page 23 of 64

Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 00:51:26

High Channel




FCC Part 15.247 Page 24 of 64


EDR Mode (\pi/4-DQPSK):

Low Channel

Report No.: RDG160629802-00




Middle Channel



FCC Part 15.247 Page 25 of 64


High Channel

Report No.: RDG160629802-00



EDR Mode (8-DPSK):


Low Channel



FCC Part 15.247 Page 26 of 64


Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:01:28

High Channel



Date: 01.AUG.2016 01:04:06

FCC Part 15.247 Page 27 of 64

FCC $\S15.247(a)$ (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RDG160629802-00

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA03-5RN	OE01153830	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	31.4°C	
Relative Humidity:	52%	
ATM Pressure:	100.3kPa	

^{*} The testing was performed by Emily Wang on 2016-08-01.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 28 of 64


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
DDD 14 1	Low	2402	0.95
BDR Mode (GFSK)	Middle	2441	0.95
(GI SK)	High	2480	0.94
EDR Mode (π/4-DQPSK):	Low	2402	1.26
	Middle	2441	1.26
	High	2480	1.25
EDR Mode (8-DPSK)	Low	2402	1.26
	Middle	2441	1.27
	High	2480	1.26

Report No.: RDG160629802-00

BDR Mode (GFSK):


Low Channel



FCC Part 15.247 Page 29 of 64


Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 00:46:13

High Channel




Date: 01.AUG.2016 00:44:38

FCC Part 15.247 Page 30 of 64

Low Channel

Report No.: RDG160629802-00



Middle Channel



FCC Part 15.247 Page 31 of 64


High Channel

Report No.: RDG160629802-00



EDR Mode (8-DPSK):


Low Channel



FCC Part 15.247 Page 32 of 64


Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 00:36:01

High Channel



FCC Part 15.247 Page 33 of 64

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RDG160629802-00

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA03-5RN	OE01153830	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	31.4°C	
Relative Humidity:	52%	
ATM Pressure:	100.3kPa	

^{*} The testing was performed by Emily Wang on 2016-08-01.

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


FCC Part 15.247 Page 34 of 64

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Report No.: RDG160629802-00

Number of Hopping Channels




FCC Part 15.247 Page 35 of 64

EDR Mode (\pi/4-DQPSK):

Frequency Range Number of (MHz) Hopping Channel		Limit
2400-2483.5	79	≥15

Report No.: RDG160629802-00

Number of Hopping Channels




FCC Part 15.247 Page 36 of 64

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15

Report No.: RDG160629802-00

Number of Hopping Channels



FCC Part 15.247 Page 37 of 64

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RDG160629802-00

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s Hop rate=1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA03-5RN	OE01153830	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	31.4°C
Relative Humidity:	52%
ATM Pressure:	100.3kPa

^{*} The testing was performed by Emily Wang on 2016-08-01.

Test Result: Compliance.

Please refer to following tables and plots

FCC Part 15.247 Page 38 of 64


Test Mode: Transmitting

BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.381	0.122	0.4	Compliance	
DH1	Middle	0.381	0.122	0.4	Compliance	
DIII	High	0.381	0.122	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.641	0.263	0.4	Compliance	
DH3	Middle	1.641	0.263	0.4	Compliance	
DIIS	High	1.647	0.264	0.4	Compliance	
	Note: Dwell tin	ne=Pulse time ($(ms) \times (1600/$	/4/79) ×31.	6 s	
	Low	2.906	0.310	0.4	Compliance	
DH5	Middle	2.906	0.310	0.4	Compliance	
DIIS	High	2.906	0.310	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s					

Report No.: RDG160629802-00


DH1: Low Channel



FCC Part 15.247 Page 39 of 64


DH1: Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:16:19

DH1: High Channel




Date: 01.AUG.2016 01:16:32

FCC Part 15.247 Page 40 of 64


DH3: Low Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:16:58

DH3: Middle Channel




Date: 01.AUG.2016 01:17:08

FCC Part 15.247 Page 41 of 64


DH3: High Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:17:22

DH5: Low Channel




Date: 01.AUG.2016 01:18:40

FCC Part 15.247 Page 42 of 64


DH5: Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:18:50

DH5: High Channel



Date: 01.AUG.2016 01:19:07


FCC Part 15.247 Page 43 of 64

EDR Mode ($\pi/4$ -DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result		
	Low	0.389	0.124	0.4	Compliance		
2DH1	Middle	0.389	0.124	0.4	Compliance		
2D111	High	0.393	0.126	0.4	Compliance		
	Note: Dwell tim	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s					
	Low	1.647	0.264	0.4	Compliance		
2DH3	Middle	1.647	0.264	0.4	Compliance		
2DH3	High	1.647	0.264	0.4	Compliance		
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times				.6 s		
	Low	2.906	0.310	0.4	Compliance		
2DH5	Middle	2.906	0.310	0.4	Compliance		
2DH3	High	2.906	0.310	0.4	Compliance		
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s						

Report No.: RDG160629802-00


2DH1: Low Channel



FCC Part 15.247 Page 44 of 64


2DH1: Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:09:16


2DH1: High Channel



FCC Part 15.247 Page 45 of 64


2DH3: Low Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:09:59


2DH3: Middle Channel



FCC Part 15.247 Page 46 of 64


2DH3: High Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:10:19

2DH5: Low Channel




Date: 01.AUG.2016 01:10:58

FCC Part 15.247 Page 47 of 64


2DH5: Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:11:08

2DH5: High Channel




bate. 01.A08.2010 01.11.10

FCC Part 15.247 Page 48 of 64

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result	
	Low	0.389	0.124	0.4	Compliance	
3DH1	Middle	0.389	0.124	0.4	Compliance	
3DIII	High	0.393	0.126	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) × (1600/2/79) ×31.6 s					
	Low	1.647	0.264	0.4	Compliance	
3DH3	Middle	1.647	0.264	0.4	Compliance	
SDIIS	High	1.647	0.264	0.4	Compliance	
	Note: Dwell tin	ne=Pulse time ($ms) \times (1600/4)$	4/79) ×31.6	S	
	Low	2.906	0.310	0.4	Compliance	
3DH5	Middle	2.906	0.310	0.4	Compliance	
SDIIS	High	2.906	0.310	0.4	Compliance	
	Note: Dwell time=Pulse time (ms) × (1600/6/79) ×31.6 s					

Report No.: RDG160629802-00


3DH1: Low Channel



FCC Part 15.247 Page 49 of 64


3DH1: Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:08:24

3DH1: High Channel




Date: 01.AUG.2016 01:08:34

FCC Part 15.247 Page 50 of 64


3DH3: Low Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:14:20


3DH3: Middle Channel



FCC Part 15.247 Page 51 of 64


3DH3: High Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:14:39


3DH5: Low Channel



FCC Part 15.247 Page 52 of 64


3DH5: Middle Channel

Report No.: RDG160629802-00



Date: 01.AUG.2016 01:13:29

3DH5: High Channel



Date: 01.AUG.2016 01:13:39

FCC Part 15.247 Page 53 of 64

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Report No.: RDG160629802-00

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA03-5RN	OE01153830	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	31.4°C
Relative Humidity:	52%
ATM Pressure:	100.3kPa

^{*} The testing was performed by Emily Wang on 2016-08-01.

Test Result: Compliance.

FCC Part 15.247 Page 54 of 64

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
22216	Low	2402	-2.01	30
BDR Mode (GFSK)	Middle	2441	-2.13	30
(GI SK)	High	2480	-2.01	30
EDD 14 1	Low	2402	-2.13	30
EDR Mode (π/4-DQPSK)	Middle	2441	-2.26	30
(M4-DQI SIC)	High	2480	-2.26	30
	Low	2402	-2.01	30
EDR Mode (8-DPSK)	Middle	2441	-2.26	30
(o Di bit)	High	2480	-2.01	30

Report No.: RDG160629802-00

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):

Output Power, Low Channel




FCC Part 15.247 Page 55 of 64

Output Power, Middle Channel



Date: 01.AUG.2016 00:46:43

Output Power, High Channel




Date: 01.AUG.2016 00:45:07


FCC Part 15.247 Page 56 of 64

Output Power, Low Channel

Report No.: RDG160629802-00




Output Power, Middle Channel



FCC Part 15.247 Page 57 of 64

Report No.: RDG160629802-00






Date: 01.AUG.2016 00:43:06

EDR Mode (8-DPSK):


Output Power, Low Channel



Date: 01.AUG.2016 00:37:35


FCC Part 15.247 Page 58 of 64

Output Power, Middle Channel



Date: 01.AUG.2016 00:36:30

Output Power, High Channel



FCC Part 15.247 Page 59 of 64

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RDG160629802-00

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2016-05-09	2017-05-09
N/A	Coaxial Cable	0.1m	N/A	2016-05-06	2017-05-06
E-Microwave	Attenuator	EMCA03-5RN	OE01153830	2016-05-08	2017-05-08
E-Microwave	DC Blocking	EMDCB- 00036	0E01201047	2016-05-06	2017-05-06

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 60 of 64

Test Data

Environmental Conditions

Temperature:	31.4°C
Relative Humidity:	52%
ATM Pressure:	100.3kPa


^{*} The testing was performed by Emily Wang on 2016-08-01.

Test Result: Compliance

BDR Mode (GFSK):

Band Edge, Left Side


Report No.: RDG160629802-00



FCC Part 15.247 Page 61 of 64


Band Edge, Right Side

Report No.: RDG160629802-00



EDR Mode ($\pi/4$ -DQPSK):


Band Edge, Left Side



FCC Part 15.247 Page 62 of 64


Band Edge, Right Side

Report No.: RDG160629802-00



EDR Mode (8-DPSK):


Band Edge, Left Side



FCC Part 15.247 Page 63 of 64

Band Edge, Right Side

Report No.: RDG160629802-00



*****END OF REPORT****

FCC Part 15.247 Page 64 of 64