






Add: 2/F., Building 2,Sanwei Chaxi Industrial Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China














Add: 2/F., Building 2,Sanwei Chaxi Industrial Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China











Add: 2/F., Building 2,Sanwei Chaxi Industrial Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China



## 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

## **10.1 MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD-1 in the ANSI C63.10 (2013) item 11.10 was used in this testing.

## 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.

## **10.3 MEASUREMENT EQUIPMENT USED**

Refer To Section 6.



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,





# **10.4 LIMITS AND MEASUREMENT RESULT**


Mode	Channel	PSD [dBm/20kHz]	Limit[dBm/3kHz]	Verdict
11b	LCH	-3.607	8	PASS
	MCH	-3.699	8	PASS
	HCH	-4.045	8	PASS
11g	LCH	-8.578	8	PASS
	MCH	-7.295	8	PASS
	HCH	-7.121	8	PASS
11nHT20	LCH	-9.238	8	PASS
	MCH	-6.686	8	PASS
	HCH	-7.787	8	PASS
11NHT40	LCH	-13.702	8	PASS
	MCH	-14.259	8	PASS
	HCH	-14.240	8	PASS



**Test Graph** 












 $Attestation\ of\ Global\ Compliance (Shenzhen) Co., Ltd.$ 

Add: 2/F., Building 2,Sanwei Chaxi Industrial Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China











Add: 2/F., Building 2,Sanwei Chaxi Industrial Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China