SGS

SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM1507003390CR

Page: 1 of 1

FCC ID: 2AFEC-UNTANGLEDPRO

RF Exposure Compliance Requirement

The product belongs to **standalone portable device** base the FCC rule part 2.1091&2.1093. The transmission frequencies of the device are between 100 MHz and 6 GHz. The worst case test separation distance is **5mm.**

The Max Conducted Output Power and SAR Test Exclusion Threshold (mW) are listed below:

Normal mode

Transmit frequency (GHz)	Max Radiated Output Power (dBm)	Max Radiated Output Power (mW)	SAR Test Exclusion Threshold (mW)
2.402	2.39	1.734	9.7
2.441	4.39	2.748	9.6
2.480	2.91	1.954	9.5

EDR mode

Transmit frequency (GHz)	Max Radiated Output Power (dBm)	Max Radiated Output Power (mW)	SAR Test Exclusion Threshold (mW)
2.402	3.69	2.339	9.7
2.442	5.47	3.524	9.6
2.480	4.12	2.582	9.5

The SAR Test Exclusion Threshold for 100 MHz to 6 GHz is calculated from:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances

$\leqslant$ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] ·

[$\sqrt{f(GHz)}$] $\leqslant$ 3.0 for 1-g SAR   and $\leqslant$ 7.5 for 10-g extremity SAR,   where

  f(GHz) is the RF channel transmit frequency in GHz

  Power and distance are rounded to the nearest mW and mm before calculation

  The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is $\leqslant$ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.   When the minimum test separation *distance is* < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

According to SAR Exclusion Threshold in KDB 447498 (D01) General RF Exposure Guidance v05r02, the SAR report is not required.