
FCC Test Report

Report No.: AGC04844170602FE05

FCC ID : 2AFHPKM-W8

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : 2.4GHz Wireless Mouse

BRAND NAME : AUKEY

MODEL NAME : KM-W8, KM-W9, KM-W10, KM-W11, KM-W12, KM-W13,
KM-W14, KM-W15, KM-W16, KM-W17, KM-W18,
KM-W19, KM-W20

CLIENT : SHENZHEN AUKEY E BUSINESS CO., LTD.

DATE OF ISSUE : July 11, 2017

STANDARD(S) : FCC Part 15 Rules

TEST PROCEDURE(S)

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

| Report Version | Revise Time | Issued Date | Valid Version | Notes |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0 | / | July 11, 2017 | Valid | Original Report |

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY 4

2. GENERAL INFORMATION..... 5

 2.1. PRODUCT DESCRIPTION 5

 2.2. TABLE OF CARRIER FREQUENCY 5

3. MEASUREMENT UNCERTAINTY..... 6

4. DESCRIPTION OF TEST MODES..... 6

5. SYSTEM TEST CONFIGURATION 7

 5.1. CONFIGURATION OF EUT SYSTEM..... 7

 5.2. EQUIPMENT USED IN EUT SYSTEM..... 7

 5.3. SUMMARY OF TEST RESULTS 7

6. TEST FACILITY..... 8

7. RADIATED EMISSION..... 9

 7.1TEST LIMIT 9

 7.2. MEASUREMENT PROCEDURE..... 10

 7.3. TEST SETUP 12

 7.4. TEST RESULT 13

8. BAND EDGE EMISSION..... 18

 8.1. MEASUREMENT PROCEDURE..... 18

 8.2 TEST SETUP 18

 8.3 RADIATED TEST RESULT 18

9. 20DB BANDWIDTH 23

 9.1. MEASUREMENT PROCEDURE..... 23

 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 23

 9.3. MEASUREMENT RESULTS 23

APPENDIX A: PHOTOGRAPHS OF TEST SETUP..... 26

APPENDIX B: PHOTOGRAPHS OF EUT 27


1. VERIFICATION OF CONFORMITY

| | |
|---------------------------------|---|
| Applicant | SHENZHEN AUKEY E BUSINESS CO., LTD. |
| Address | Room 102, Bld P09, Huanan International Zone, No.1 Huanan Rd, PinghuTown Longgang District, Shenzhen, China |
| Manufacturer | Eastemtimes Technology Co., Ltd. |
| Address | Fengrun Industrial Park, Youganpu Village Fenggang Town, Donggang, Guangdong, China |
| Product Designation | 2.4GHz Wireless Mouse |
| Brand Name | AUKEY |
| Test Model | KM-W8 |
| Series Model | KM-W9, KM-W10, KM-W11, KM-W12, KM-W13, KM-W14, KM-W15, KM-W16, KM-W17, KM-W18, KM-W19, KM-W20 |
| Model Difference | All the same except appearance color. |
| Date of test | July 10, 2017 to July 11, 2017 |
| Deviation | None |
| Condition of Test Sample | Normal |
| Test Result | Pass |
| Report Template | AGCRT-US-BR/RF |

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested by




Max Zhang(Zhang Yi) July 11, 2017

Reviewed by



Bart Xie(Xie Xiaobin)) July 11, 2017

Approved by



Solger Zhang(Zhang Hongyi)
Authorized Officer July 11, 2017

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

| | |
|-------------------------------|---|
| Operation Frequency | 2.408 GHz to 2.474GHz |
| Maximum field strength | 85.52dBuV/m@3m(AV) |
| Modulation | FSK |
| Number of channels | 34 |
| Antenna Gain | 0.11dBi |
| Antenna Designation | Integrated Antenna (Met 15.203 Antenna requirement) |
| Hardware Version | CHeck Sum: 79D4 |
| Software Version | V01T9-1 |
| Power Supply | DC 1.5V by battery |

2.2. TABLE OF CARRIER FREQUENCY

| Channel Number | Frequency | Channel Number | Frequency |
|----------------|-----------|----------------|-----------|
| 1 | 2408MHz | 18 | 2442MHz |
| 2 | 2410MHz | 19 | 2444MHz |
| 3 | 2412MHz | 20 | 2446MHz |
| 4 | 2414MHz | 21 | 2448MHz |
| 5 | 2416MHz | 22 | 2450MHz |
| 6 | 2418MHz | 23 | 2452MHz |
| 7 | 2420MHz | 24 | 2454MHz |
| 8 | 2422MHz | 25 | 2456MHz |
| 9 | 2424MHz | 26 | 2458MHz |
| 10 | 2426MHz | 27 | 2460MHz |
| 11 | 2428MHz | 28 | 2462MHz |
| 12 | 2430MHz | 29 | 2464MHz |
| 13 | 2432MHz | 30 | 2466MHz |
| 14 | 2434MHz | 31 | 2468MHz |
| 15 | 2436MHz | 32 | 2470MHz |
| 16 | 2438MHz | 33 | 2472MHz |
| 17 | 2440MHz | 34 | 2474MHz |

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|-------------------------|-------------------------|
| 1 | Conducted Emission Test | $\pm 3.18\text{dB}$ |
| 2 | All emissions, radiated | $\pm 3.91\text{dB}$ |
| 3 | Temperature | $\pm 0.5^\circ\text{C}$ |
| 4 | Humidity | $\pm 2\%$ |


4. DESCRIPTION OF TEST MODES

| NO. | TEST MODE DESCRIPTION |
|---|--------------------------------------|
| 1 | Low channel TX in GFSK modulation |
| 2 | Middle channel TX in GFSK modulation |
| 3 | High channel TX in GFSK modulation |
| Note: 1. Only the result of the worst case was recorded in the report, if no other cases. 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode. 3. The EUT had been programmed in continuous transmission conditions for the test modes. | |

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1:



5.2. EQUIPMENT USED IN EUT SYSTEM

| Item | Equipment | Model No. | ID or Specification | Remark |
|------|-----------------------|-----------|---------------------|--------|
| 1 | 2.4GHz Wireless Mouse | KM-W8 | 2AFHPKM-W8 | EUT |

5.3. SUMMARY OF TEST RESULTS

| FCC RULES | DESCRIPTION OF TEST | RESULT |
|-----------|---------------------|-----------|
| §15.249 | Radiated Emission | Compliant |
| §15.249 | Band Edges | Compliant |
| §15.215 | 20dB bandwidth | Compliant |

6. TEST FACILITY

| | |
|-----------------------------|--|
| Site | Dongguan Precise Testing Service Co., Ltd. |
| Location | Building D, Baoding Technology Park, Guangming Road2, Dongcheng District, Dongguan, Guangdong, China. |
| FCC Registration No. | 371540 |
| Description | The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014. |

ALL TEST EQUIPMENT LIST

| Radiated Emission Test Site | | | | | |
|-------------------------------------|-----------------|--------------|---------------|------------------|-----------------|
| Name of Equipment | Manufacturer | Model Number | Serial Number | Last Calibration | Due Calibration |
| EMI Test Receiver | Rohde & Schwarz | ESCI | 101417 | July 2, 2017 | July 1, 2018 |
| Trilog Broadband Antenna (25M-1GHz) | SCHWARZBECK | VULB9160 | 9160-3355 | July 2, 2017 | July 1, 2018 |
| Signal Amplifier | SCHWARZBECK | BBV 9475 | 9745-0013 | July 2, 2017 | July 1, 2018 |
| RF Cable | SCHWARZBECK | AK9515E | 96221 | July 2, 2017 | July 1, 2018 |
| 3m Anechoic Chamber | CHENGYU | 966 | PTS-001 | July 2, 2017 | July 1, 2018 |
| MULTI-DEVICE Positioning Controller | Max-Full | MF-7802 | MF780208339 | N/A | N/A |
| Active loop antenna (9K-30MHz) | Schwarzbeck | FMZB1519 | 1519-038 | June 2, 2017 | June 1, 2018 |
| Spectrum analyzer | Agilent | E4407B | MY46185649 | June 2, 2017 | June 1, 2018 |
| Horn Antenna (1G-18GHz) | SCHWARZBECK | BBHA9120D | 9120D-1246 | June 2, 2017 | June 1, 2018 |
| Horn Ant (18G-40GHz) | Schwarzbeck | BBHA 9170 | 9170-181 | June 2, 2017 | June 1, 2018 |

| Conducted Emission Test Site | | | | | |
|--------------------------------|-----------------|--------------|---------------|------------------|-----------------|
| Name of Equipment | Manufacturer | Model Number | Serial Number | Last Calibration | Due Calibration |
| EMI Test Receiver | Rohde & Schwarz | ESCI | 101417 | June 2, 2017 | June 1, 2018 |
| Artificial Mains Network | Narda | L2-16B | 000WX31025 | June 2, 2017 | June 1, 2018 |
| Artificial Mains Network (AUX) | Narda | L2-16B | 000WX31026 | June 2, 2017 | June 1, 2018 |
| RF Cable | SCHWARZBECK | AK9515E | 96222 | June 2, 2017 | June 1, 2018 |
| Shielded Room | CHENGYU | 843 | PTS-002 | June 2, 2017 | June 1, 2018 |

7. RADIATED EMISSION

7.1 TEST LIMIT

Standard FCC15.249

| Fundamental Frequency | Field Strength of Fundamental (millivolts/meter) | Field Strength of Harmonics (microvolts/meter) |
|-----------------------|---|---|
| 900-928MHz | 50 | 500 |
| 2400-2483.5MHz | 50 | 500 |
| 5725-5875MHz | 50 | 500 |
| 24.0-24.25GHz | 250 | 2500 |

Standard FCC 15.209

| Frequency (MHz) | Distance Meters | Field Strengths Limit | |
|--------------------|--------------------|---|----------------|
| | | μ V/m | dB(μ V)/m |
| 0.009 ~ 0.490 | 300 | 2400/F(kHz) | --- |
| 0.490 ~ 1.705 | 30 | 24000/F(kHz) | --- |
| 1.705 ~ 30 | 30 | 30 | --- |
| 30 ~ 88 | 3 | 100 | 40.0 |
| 88 ~ 216 | 3 | 150 | 43.5 |
| 216 ~ 960 | 3 | 200 | 46.0 |
| 960 ~ 1000 | 3 | 500 | 54.0 |
| Above 1000 | 3 | Other: 74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average) | |

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

7.2. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use minimum resolution bandwidth of 1 MHz. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|-----------------------|---|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |
| Start ~Stop Frequency | 1GHz~26.5GHz RBW 3MHz/VBW 10MHz for Peak, RBW 3MHz/VBW 10Hz for Average |


| Receiver Parameter | Setting |
|-----------------------|--------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RB 200Hz for QP |
| Start ~Stop Frequency | 150KHz~30MHz/RB 9KHz for QP |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120KHz for QP |

7.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz




7.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION 30MHz- 1GHZ


| | | | |
|---------------|-----------------------|---------------------|------------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 1 | Polarization : | Horizontal |



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 76.8833 | 7.28 | 3.54 | 10.82 | 40.00 | -29.18 | peak | | | |
| 2 | | 149.6332 | 2.15 | 12.85 | 15.00 | 43.50 | -28.50 | peak | | | |
| 3 | | 503.6832 | 3.38 | 21.23 | 24.61 | 46.00 | -21.39 | peak | | | |
| 4 | | 576.4333 | 1.82 | 23.14 | 24.96 | 46.00 | -21.04 | peak | | | |
| 5 | | 814.0833 | 0.71 | 27.32 | 28.03 | 46.00 | -17.97 | peak | | | |
| 6 | * | 951.5000 | 0.15 | 29.99 | 30.14 | 46.00 | -15.86 | peak | | | |

RESULT: PASS

| | | | |
|---------------|-----------------------|---------------------|----------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 1 | Polarization : | Vertical |



| No. | Mk | Freq. | Reading | Factor | Measurement | Limit | Over | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | cm | degree | |
| 1 | | 38.0833 | 5.34 | 6.39 | 11.73 | 40.00 | -28.27 | peak | | | |
| 2 | | 148.0166 | 2.71 | 15.25 | 17.96 | 43.50 | -25.54 | peak | | | |
| 3 | | 245.0166 | 3.33 | 13.41 | 16.74 | 46.00 | -29.26 | peak | | | |
| 4 | | 448.7167 | 2.59 | 20.55 | 23.14 | 46.00 | -22.86 | peak | | | |
| 5 | | 807.6167 | 1.46 | 27.32 | 28.78 | 46.00 | -17.22 | peak | | | |
| 6 | * | 948.2667 | 0.30 | 29.95 | 30.25 | 46.00 | -15.75 | peak | | | |

RESULT: PASS

Note:

Factor=Antenna Factor + Cable loss, Margin=Result-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

The mode 1 is the worst case, and only the data of the worst case recorded in this test report.

RADIATED EMISSION ABOVE 1GHZ

| | | | |
|---------------|-----------------------|---------------------|------------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 1 | Polarization : | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2408.013 | 99.71 | -9.37 | 90.34 | 114 | -23.66 | peak |
| 2408.013 | 94.54 | -9.37 | 85.17 | 94 | -8.83 | AVG |
| 4816.026 | 42.36 | 3.74 | 46.1 | 74 | -27.9 | peak |
| 4816.026 | 37.74 | 3.74 | 41.48 | 54 | -12.52 | AVG |
| 7224.039 | 39.42 | 8.14 | 47.56 | 74 | -26.44 | peak |
| 7224.039 | 34.11 | 8.14 | 42.25 | 54 | -11.75 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---------------|-----------------------|---------------------|----------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 ℃ | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 1 | Polarization : | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2408.013 | 97.21 | -9.37 | 87.84 | 114 | -26.16 | peak |
| 2408.013 | 92.74 | -9.37 | 83.37 | 94 | -10.63 | AVG |
| 4816.026 | 41.55 | 3.74 | 45.29 | 74 | -28.71 | peak |
| 4816.026 | 37.08 | 3.74 | 40.82 | 54 | -13.18 | AVG |
| 7224.039 | 39.42 | 8.14 | 47.56 | 74 | -26.44 | peak |
| 7224.039 | 34.81 | 8.14 | 42.95 | 54 | -11.05 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---------------|-----------------------|---------------------|------------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 2 | Polarization : | Horizontal |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 2440.016 | 99.35 | -9.63 | 89.72 | 114 | -24.28 | |
| 2440.016 | 94.02 | -9.63 | 84.39 | 94 | -9.61 | AVG |
| 4880.032 | 41.75 | 3.76 | 45.51 | 74 | -28.49 | peak |
| 4880.032 | 37.27 | 3.76 | 41.03 | 54 | -12.97 | AVG |
| 7320.048 | 39.18 | 8.17 | 47.35 | 74 | -26.65 | peak |
| 7320.048 | 34.57 | 8.17 | 42.74 | 54 | -11.26 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---------------|-----------------------|---------------------|----------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 2 | Polarization : | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|---|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | |
| 2440.016 | 97.53 | -9.63 | 87.9 | 114 | -26.1 | peak |
| 2440.016 | 92.18 | -9.63 | 82.55 | 94 | -11.45 | AVG |
| 4880.032 | 41.64 | 3.76 | 45.4 | 74 | -28.6 | peak |
| 4880.032 | 37.12 | 3.76 | 40.88 | 54 | -13.12 | AVG |
| 7320.048 | 38.54 | 8.17 | 46.71 | 74 | -27.29 | peak |
| 7320.048 | 34.02 | 8.17 | 42.19 | 54 | -11.81 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---------------|-----------------------|---------------------|------------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 3 | Polarization : | Horizontal |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 2474.021 | 101.09 | -9.61 | 91.48 | 114 | -22.52 | peak |
| 2474.021 | 95.13 | -9.61 | 85.52 | 94 | -8.48 | AVG |
| 4948.042 | 41.85 | 3.83 | 45.68 | 74 | -28.32 | peak |
| 4948.042 | 36.24 | 3.83 | 40.07 | 54 | -13.93 | AVG |
| 7422.063 | 40.54 | 8.21 | 48.75 | 74 | -25.25 | peak |
| 7422.063 | 35.18 | 8.21 | 43.39 | 54 | -10.61 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

| | | | |
|---------------|-----------------------|---------------------|----------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 3 | Polarization : | Vertical |

| Frequency (MHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Value Type |
|---|-------------------------|----------------|----------------------------|--------------------|----------------|------------|
| 2474.021 | 99.12 | -9.61 | 89.51 | 114 | -24.49 | peak |
| 2474.021 | 93.18 | -9.61 | 83.57 | 94 | -10.43 | AVG |
| 4948.042 | 41.66 | 3.83 | 45.49 | 74 | -28.51 | peak |
| 4948.042 | 36.02 | 3.83 | 39.85 | 54 | -14.15 | AVG |
| 7422.063 | 39.85 | 8.21 | 48.06 | 74 | -25.94 | peak |
| 7422.063 | 34.71 | 8.21 | 42.92 | 54 | -11.08 | AVG |
| Remark: | | | | | | |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. | | | | | | |

Note: Other emissions from 8G to 25 GHz are considered as ambient noise. No recording in the test report.
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
The “Factor” value can be calculated automatically by software of measurement system.


8. BAND EDGE EMISSION

8.1. MEASUREMENT PROCEDURE

1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO
3. Other procedures refer to clause 7.2.

8.2 TEST SETUP

RADIATED EMISSION TEST SETUP



8.3 RADIATED TEST RESULT

Note:

1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level
2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.

| | | | |
|---------------|-----------------------|---------------------|------------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 1 | Polarization : | Horizontal |

PK Value



AV Value



| | | | |
|---------------|-----------------------|---------------------|----------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 1 | Polarization : | Vertical |

PK Value




AV Value



| | | | |
|---------------|-----------------------|-------------------------|------------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humiditytity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 3 | Polarization : | Horizontal |

PK Value



AV Value



| | | | |
|---------------|-----------------------|-------------------------|----------|
| EUT : | 2.4GHz Wireless Mouse | Model Name. : | KM-W8 |
| Temperature : | 20 °C | Relative Humiditytity : | 48% |
| Pressure : | 1010 hPa | Test Voltage : | DC1.5V |
| Test Mode : | Mode 3 | Polarization : | Vertical |

PK Value



AV Value




9. 20DB BANDWIDTH

9.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel
The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)




9.3. MEASUREMENT RESULTS


| | |
|-----------|-------------------|
| TEST ITEM | 20DB BANDWIDTH |
| TEST MODE | Mode1;Mode2;Mode3 |

| Test Data (MHz) | | Criteria |
|-----------------|-------|----------|
| Low Channel | 1.598 | PASS |
| Middle Channel | 1.574 | PASS |
| High Channel | 1.735 | PASS |


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL





TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP



APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT




LEFT VIEW OF EUT




RIGHT VIEW OF EUT




OPEN VIEW OF EUT



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----