



# FCC RF Test Report


APPLICANT : Solnik S.A.  
EQUIPMENT : Mobile Phone  
BRAND NAME : HYUNDAI  
MODEL NAME : HY1-7372  
FCC ID : 2AFRUHY1-7372  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Oct. 09, 2016 and testing was completed on Oct. 19, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Ken Chen / Manager

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,  
Nanshan District, Shenzhen, Guangdong, P. R. China



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test .....	6
1.5 Modification of EUT .....	6
1.6 Testing Location .....	7
1.7 Applicable Standards .....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Carrier Frequency and Channel .....	8
2.2 Test Mode .....	9
2.3 Connection Diagram of Test System .....	10
2.4 Support Unit used in test configuration and system .....	11
2.5 EUT Operation Test Setup .....	11
2.6 Measurement Results Explanation Example .....	12
<b>3 TEST RESULT .....</b>	<b>13</b>
3.1 6dB Bandwidth Measurement .....	13
3.2 Output Power Measurement .....	15
3.3 Power Spectral Density Measurement .....	16
3.4 Conducted Band Edges and Spurious Emission Measurement .....	18
3.5 Radiated Band Edges and Spurious Emission Measurement .....	31
3.6 AC Conducted Emission Measurement .....	35
3.7 Antenna Requirements .....	39
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>40</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>41</b>
<b>APPENDIX A. CONDUCTED TEST RESULTS</b>	
<b>APPENDIX B. RADIATED SPURIOUS EMISSION</b>	
<b>APPENDIX C. DUTY CYCLE PLOTS</b>	
<b>APPENDIX D. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR6O0902C	Rev. 01	Initial issue of report	Oct. 27, 2016



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.09 dB at 30.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.56 dB at 0.150 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**Solnik S.A.**

Dr. Emilio Ravignani 1724 Ciudad Autonoma de Buenos Aires Zip Code 1414 Argentina

## 1.2 Manufacturer

**Gionee Communication Equipment Co., Ltd.**

21/F, Times Technology Building, No. 7028, Shennan Avenue, Futian District, Shenzhen, China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile Phone
<b>Brand Name</b>	HYUNDAI
<b>Model Name</b>	HY1-7372
<b>FCC ID</b>	2AFRUHY1-7372
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
<b>IMEI Code</b>	Conduction: 354147042119900/354147043119909 Radiation: 354147042119991/354147043119990 Conducted: 354147042119918/354147042119917
<b>HW Version</b>	Ultra Shadow_Mainboard_P2
<b>SW Version</b>	Ultra Shadow_0205_V5353
<b>EUT Stage</b>	Pre-Production

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Channel Frequency Range</b>	2412 MHz ~ 2462 MHz
<b>Maximum (Peak) Output Power to antenna</b>	802.11b : 17.80 dBm (0.0603 W) 802.11g : 21.55 dBm (0.1429 W) 802.11n HT20 : 21.87 dBm (0.1538 W) 802.11n HT40 : 22.68 dBm (0.1854 W)
<b>Antenna Type / Gain</b>	FPC Antenna with gain 0.71 dBi
<b>Type of Modulation</b>	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH01-SZ	CO01-SZ

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH02-SZ	566869

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



## 2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM1900 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone
<b>Remark:</b> 1. For Radiated TCs, The tests were performance with Adapter, Earphone and USB Cable.	

## 2.3 Connection Diagram of Test System

### <WLAN Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

## 2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)}\end{aligned}$$

### **3 Test Result**

#### **3.1 6dB Bandwidth Measurement**

##### **3.1.1 Limit of 6dB Bandwidth**

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### **3.1.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

##### **3.1.3 Test Procedures**

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


##### **3.1.4 Test Setup**





### 3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## **3.2 Output Power Measurement**

### **3.2.1 Limit of Output Power**

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### **3.2.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

### **3.2.3 Test Procedures**

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### **3.2.4 Test Setup**



### **3.2.5 Test Result of Peak Output Power**

Please refer to Appendix A.

### **3.2.6 Test Result of Average output Power (Reporting Only)**

Please refer to Appendix A.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup








### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



### **3.4 Conducted Band Edges and Spurious Emission Measurement**

#### **3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement**

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

#### **3.4.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

#### **3.4.3 Test Procedures**

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### **3.4.4 Test Setup**






## 3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Bruce Huang


## WLAN 802.11b Channel 01

## 100kHz PSD reference Level




Date: 10.OCT.2016 17:22:50

## Low Channel Plot




Date: 10.OCT.2016 17:23:01

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 17:23:16

## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 17:23:25



Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang

## WLAN 802.11b Channel 06


## 100kHz PSD reference Level



Date: 10.OCT.2016 17:28:27


## Mid Channel Plot

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 17:28:42

## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 17:28:50



Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Bruce Huang


## WLAN 802.11b Channel 11

## 100kHz PSD reference Level




Date: 10.OCT.2016 17:34:40

## High Channel Plot




Date: 10.OCT.2016 17:34:55

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 17:35:11


## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 17:35:19




Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Bruce Huang

**WLAN 802.11g Channel 01****100kHz PSD reference Level**


Date: 10.OCT.2016 17:48:20

**Low Channel Plot**

Date: 10.OCT.2016 17:48:33

**Spurious Emission 30MHz~3GHz**

Date: 10.OCT.2016 17:48:47

**Spurious Emission 2GHz~25GHz**


Date: 10.OCT.2016 17:48:56



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang

## WLAN 802.11g Channel 06


## 100kHz PSD reference Level



Date: 10.OCT.2016 17:54:28


## Mid Channel Plot

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 17:56:08

## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 17:56:16



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Bruce Huang


## WLAN 802.11g Channel 11

## 100kHz PSD reference Level




Date: 10.OCT.2016 18:01:24

## High Channel Plot




Date: 10.OCT.2016 18:01:48

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 18:02:02

## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 18:02:10







Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Bruce Huang

**WLAN 802.11n HT20 Channel 01****100kHz PSD reference Level**


Date: 10.OCT.2016 18:07:15

**Low Channel Plot**

Date: 10.OCT.2016 18:07:48

**Spurious Emission 30MHz~3GHz**


Date: 10.OCT.2016 18:08:34

**Spurious Emission 2GHz~25GHz**


Date: 10.OCT.2016 18:08:50




Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang

**WLAN 802.11n HT20 Channel 06****100kHz PSD reference Level**

Date: 10.OCT.2016 18:12:29

**Mid Channel Plot****Spurious Emission 30MHz~3GHz**

Date: 10.OCT.2016 18:13:24

**Spurious Emission 2GHz~25GHz**


Date: 10.OCT.2016 18:13:32



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Bruce Huang


## WLAN 802.11n HT20 Channel 11

## 100kHz PSD reference Level




Date: 10.OCT.2016 18:20:09

## High Channel Plot




Date: 10.OCT.2016 18:20:40

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 18:21:53

## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 18:22:01

<b>Test Mode :</b>	802.11n HT40	<b>Temperature :</b>	24~26℃
<b>Test Band :</b>	2.4GHz Low	<b>Relative Humidity :</b>	50~53%
<b>Test Channel :</b>	03	<b>Test Engineer :</b>	Bruce Huang


## WLAN 802.11n HT40 Channel 03

### 100kHz PSD reference Level




Date: 10.OCT.2016 18:26:08

### Low Channel Plot




Date: 10.OCT.2016 18:26:25

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 18:35:59

## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 18:33:00



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Bruce Huang

## WLAN 802.11n HT40 Channel 06


## 100kHz PSD reference Level



Date: 10.OCT.2016 18:42:31


## Mid Channel Plot

## Spurious Emission 30MHz~3GHz



Date: 10.OCT.2016 18:45:52


## Spurious Emission 2GHz~25GHz




Date: 10.OCT.2016 18:46:24




Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	09	Test Engineer :	Bruce Huang

**WLAN 802.11n HT40 Channel 09****100kHz PSD reference Level**


Date: 10.OCT.2016 18:52:10

**High Channel Plot**

Date: 10.OCT.2016 18:53:26

**Spurious Emission 30MHz~3GHz**

Date: 10.OCT.2016 18:53:38

**Spurious Emission 2GHz~25GHz**

Date: 10.OCT.2016 18:53:47

### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.


For average measurement:

    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

### 3.5.7 Duty Cycle

Please refer to Appendix C.

### 3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

Please refer to Appendix B.

### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


### 3.6.4 Test Setup





## 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		




Site : C001-SZ  
Condition: FCC 15C\_QP LISN\_20160509 LINE  
Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	43.44	-12.56	56.00	32.70	0.14	10.60	Average
2	0.15	47.04	-18.96	66.00	36.30	0.14	10.60	QP
3	0.20	31.81	-21.90	53.71	21.20	0.11	10.50	Average
4	0.20	36.41	-27.30	63.71	25.80	0.11	10.50	QP
5	0.71	26.57	-19.43	46.00	16.30	0.11	10.16	Average
6	0.71	32.57	-23.43	56.00	22.30	0.11	10.16	QP
7	1.27	17.27	-28.73	46.00	7.00	0.11	10.16	Average
8	1.27	26.87	-29.13	56.00	16.60	0.11	10.16	QP
9	1.69	16.58	-29.42	46.00	6.30	0.11	10.17	Average
10	1.69	25.08	-30.92	56.00	14.80	0.11	10.17	QP
11	22.54	17.74	-32.26	50.00	6.70	0.45	10.59	Average
12	22.54	37.94	-22.06	60.00	26.90	0.45	10.59	QP



Test Mode :	Mode 1	Temperature :	21~23
Test Engineer :	Tao Cheng	Relative Humidity :	41~43
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		



Site : CO01-SZ  
Condition: FCC 15C\_QP LISN\_20160509 NEUTRAL  
Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	41.84	-14.16	56.00	31.10	0.14	10.60	Average
2	0.15	46.24	-19.76	66.00	35.50	0.14	10.60	QP
3	0.20	32.21	-21.46	53.67	21.60	0.11	10.50	Average
4	0.20	37.21	-26.46	63.67	26.60	0.11	10.50	QP
5	0.70	30.97	-15.03	46.00	20.70	0.11	10.16	Average
6	0.70	35.57	-20.43	56.00	25.30	0.11	10.16	QP
7	0.80	24.27	-21.73	46.00	14.00	0.11	10.16	Average
8	0.80	31.97	-24.03	56.00	21.70	0.11	10.16	QP
9	1.31	24.47	-21.53	46.00	14.20	0.11	10.16	Average
10	1.31	35.07	-20.93	56.00	24.80	0.11	10.16	QP
11	3.33	24.43	-21.57	46.00	14.10	0.12	10.21	Average
12	3.33	39.13	-16.87	56.00	28.80	0.12	10.21	QP
13	22.42	24.04	-25.96	50.00	13.00	0.45	10.59	Average
14	22.42	41.34	-18.66	60.00	30.30	0.45	10.59	QP



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~40GHz	Jan. 12, 2016	Oct. 10, 2016	Jan. 11, 2017	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 12, 2016	Oct. 10, 2016	Jan. 11, 2017	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 12, 2016	Oct. 10, 2016	Jan. 11, 2017	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz; Max 30dBm	Oct. 20, 2015	Oct. 10, 2016~ Oct. 19, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz; Max 30dBm	Sep. 11, 2016	Oct. 10, 2016~ Oct. 19, 2016	Sep. 10, 2017	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 07, 2016	Oct. 10, 2016~ Oct. 19, 2016	May 06, 2017	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	May 21, 2016	Oct. 10, 2016~ Oct. 19, 2016	May 20, 2017	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 11, 2016	Oct. 10, 2016~ Oct. 19, 2016	Jan. 10, 2017	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	Oct. 10, 2016~ Oct. 19, 2016	Aug. 09, 2017	Radiation (03CH02-SZ)
Amplifier	HP	8447F	3113A04622	9kHz~1300MHz / 30 dB	Jul. 16, 2016	Oct. 10, 2016~ Oct. 19, 2016	Jul. 15, 2017	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1707137	1GHz~18GHz	Sep. 11, 2016	Oct. 10, 2016~ Oct. 19, 2016	Sep. 10, 2017	Radiation (03CH02-SZ)
Amplifier	Agilent	8449B	3008A01023	1GHz~26.5GHz	Oct. 20, 2015	Oct. 10, 2016~ Oct. 19, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Oct. 10, 2016~ Oct. 19, 2016	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Oct. 10, 2016~ Oct. 19, 2016	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Oct. 10, 2016~ Oct. 19, 2016	NCR	Radiation (03CH02-SZ)
EMI Receiver	R&S	ESCI7	100724	9kHz~3GHz;	Nov. 23, 2015	Oct. 13, 2016	Nov. 22, 2016	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103892	9kHz~30MHz	Jan. 12, 2016	Oct. 13, 2016	Jan. 11, 2017	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103912	9kHz~30MHz	Jan. 12, 2016	Oct. 13, 2016	Jan. 11, 2017	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 16, 2016	Oct. 13, 2016	Jul. 15, 2017	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 11, 2016	Oct. 13, 2016	Oct. 10, 2017	Conduction (CO01-SZ)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.5dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
---	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1dB
---	-------



## **Appendix A. Conducted Test Results**

A1 - DTS Part

Test Engineer:	Bruce Huang	Temperature:	24~26	°C
Test Date:	2016/10/10	Relative Humidity:	50~53	%

**TEST RESULTS DATA**  
**6dB and 99% Occupied Bandwidth**

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.05	8.56	0.50	Pass
11b	1Mbps	1	6	2437	12.50	9.56	0.50	Pass
11b	1Mbps	1	11	2462	12.35	9.56	0.50	Pass
11g	6Mbps	1	1	2412	17.40	15.68	0.50	Pass
11g	6Mbps	1	6	2437	17.75	16.36	0.50	Pass
11g	6Mbps	1	11	2462	17.75	15.76	0.50	Pass
HT20	MCS0	1	1	2412	18.15	16.28	0.50	Pass
HT20	MCS0	1	6	2437	18.65	17.56	0.50	Pass
HT20	MCS0	1	11	2462	18.40	16.36	0.50	Pass
HT40	MCS0	1	3	2422	36.30	35.12	0.50	Pass
HT40	MCS0	1	6	2437	37.00	36.32	0.50	Pass
HT40	MCS0	1	9	2452	36.10	35.04	0.50	Pass

**TEST RESULTS DATA**  
**Peak Power Table**

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.21	30.00	0.71	17.92	36.00	Pass
11b	1Mbps	1	6	2437	17.80	30.00	0.71	18.51	36.00	Pass
11b	1Mbps	1	11	2462	17.67	30.00	0.71	18.38	36.00	Pass
11g	6Mbps	1	1	2412	21.19	30.00	0.71	21.90	36.00	Pass
11g	6Mbps	1	6	2437	21.55	30.00	0.71	22.26	36.00	Pass
11g	6Mbps	1	11	2462	21.51	30.00	0.71	22.22	36.00	Pass
HT20	MCS0	1	1	2412	21.51	30.00	0.71	22.22	36.00	Pass
HT20	MCS0	1	6	2437	21.87	30.00	0.71	22.58	36.00	Pass
HT20	MCS0	1	11	2462	21.64	30.00	0.71	22.35	36.00	Pass
HT40	MCS0	1	3	2422	22.40	30.00	0.71	23.11	36.00	Pass
HT40	MCS0	1	6	2437	22.68	30.00	0.71	23.39	36.00	Pass
HT40	MCS0	1	9	2452	22.27	30.00	0.71	22.98	36.00	Pass

**TEST RESULTS DATA**  
**Average Power Table**  
**(Reporting Only)**

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	14.01
11b	1Mbps	1	6	2437	0.00	14.72
11b	1Mbps	1	11	2462	0.00	14.44
11g	6Mbps	1	1	2412	0.10	11.24
11g	6Mbps	1	6	2437	0.10	11.86
11g	6Mbps	1	11	2462	0.10	11.67
HT20	MCS0	1	1	2412	0.12	11.16
HT20	MCS0	1	6	2437	0.12	11.90
HT20	MCS0	1	11	2462	0.12	11.67
HT40	MCS0	1	3	2422	0.25	11.52
HT40	MCS0	1	6	2437	0.25	11.70
HT40	MCS0	1	9	2452	0.25	11.87

**TEST RESULTS DATA**  
**Peak Power Density**

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-9.19	0.71	8.00	Pass
11b	1Mbps	1	6	2437	-8.94	0.71	8.00	Pass
11b	1Mbps	1	11	2462	-9.34	0.71	8.00	Pass
11g	6Mbps	1	1	2412	-13.70	0.71	8.00	Pass
11g	6Mbps	1	6	2437	-14.02	0.71	8.00	Pass
11g	6Mbps	1	11	2462	-13.03	0.71	8.00	Pass
HT20	MCS0	1	1	2412	-14.30	0.71	8.00	Pass
HT20	MCS0	1	6	2437	-13.64	0.71	8.00	Pass
HT20	MCS0	1	11	2462	-13.40	0.71	8.00	Pass
HT40	MCS0	1	3	2422	-15.16	0.71	8.00	Pass
HT40	MCS0	1	6	2437	-14.79	0.71	8.00	Pass
HT40	MCS0	1	9	2452	-15.98	0.71	8.00	Pass



## Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b CH 01 2412MHz		2389.275	43.41	-30.59	74	46.94	25.99	3.81	33.33	172	277	P	H
		2390	33.55	-20.45	54	37.07	25.99	3.81	33.32	172	277	A	H
	*	2412	101.3	-	-	104.75	26.03	3.84	33.32	172	277	P	H
	*	2412	98.33	-	-	101.78	26.03	3.84	33.32	172	277	A	H
		2389.695	40.53	-33.47	74	44.06	25.99	3.81	33.33	243	215	P	V
		2390	30.34	-23.66	54	33.86	25.99	3.81	33.32	243	215	A	V
	*	2412	96.55	-	-	100	26.03	3.84	33.32	243	215	P	V
	*	2412	93.61	-	-	97.06	26.03	3.84	33.32	243	215	A	V
802.11b CH 06 2437MHz		2389.66	45.39	-28.61	74	48.92	25.99	3.81	33.33	166	283	P	H
		2389.94	36.07	-17.93	54	39.59	25.99	3.81	33.32	166	283	A	H
	*	2437	102.78	-	-	106.15	26.1	3.84	33.31	166	283	P	H
	*	2437	99.67	-	-	103.04	26.1	3.84	33.31	166	283	A	H
		2484.81	44.77	-29.23	74	48.03	26.17	3.88	33.31	166	283	P	H
		2484.32	35.12	-18.88	54	38.38	26.17	3.88	33.31	166	283	A	H
		2378.88	38.89	-35.11	74	42.45	25.96	3.81	33.33	150	138	P	V
		2389.94	28.33	-25.67	54	31.85	25.99	3.81	33.32	150	138	A	V
	*	2437	90.51	-	-	93.88	26.1	3.84	33.31	150	138	P	V
	*	2437	87.45	-	-	90.82	26.1	3.84	33.31	150	138	A	V
		2485.16	39.15	-34.85	74	42.41	26.17	3.88	33.31	150	138	P	V
		2483.9	28.8	-25.2	54	32.06	26.17	3.88	33.31	150	138	A	V





<b>802.11b CH 11 2462MHz</b>	*	2462	103.14	-	-	106.44	26.13	3.88	33.31	150	273	P	H
	*	2462	100.01	-	-	103.31	26.13	3.88	33.31	150	273	A	H
		2483.88	45.45	-28.55	74	48.71	26.17	3.88	33.31	150	273	P	H
		2483.84	36.56	-17.44	54	39.82	26.17	3.88	33.31	150	273	A	H
	*	2462	96.14	-	-	99.44	26.13	3.88	33.31	228	226	P	V
	*	2462	93.08	-	-	96.38	26.13	3.88	33.31	228	226	A	V
		2483.96	42.32	-31.68	74	45.58	26.17	3.88	33.31	228	226	P	V
		2483.88	33.13	-20.87	54	36.39	26.17	3.88	33.31	228	226	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11b		4824	51.59	-22.41	74	71.78	30.49	5.92	56.6	150	98	P	H
CH 01		4824	47.67	-6.33	54	67.86	30.49	5.92	56.6	150	98	A	H
2412MHz		4824	45.96	-28.04	74	66.15	30.49	5.92	56.6	150	360	P	V
802.11b		4874	44.95	-29.05	74	65.3	30.58	5.98	56.91	150	360	P	H
CH 06		7311	43.54	-30.46	74	60.22	34.4	6.92	58	174	100	P	H
2437MHz		4874	43.58	-30.42	74	63.93	30.58	5.98	56.91	150	360	P	V
		7311	43.75	-30.25	74	60.43	34.4	6.92	58	174	100	P	V
802.11b		4924	44.73	-29.27	74	64.1	30.68	6.03	56.08	150	347	P	H
CH 11		7386	43.93	-30.07	74	60.22	34.79	6.93	58.01	150	274	P	H
2462MHz		4924	44.25	-29.75	74	63.62	30.68	6.03	56.08	150	347	P	V
		7386	43.12	-30.88	74	59.41	34.79	6.93	58.01	150	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11g (Band Edge @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11g CH 01 2412MHz		2389.8	50.81	-23.19	74	54.33	25.99	3.81	33.32	150	304	P	H
		2390	40.46	-13.54	54	43.98	25.99	3.81	33.32	150	304	A	H
	*	2412	102.28	-	-	105.73	26.03	3.84	33.32	150	304	P	H
	*	2412	94.53	-	-	97.98	26.03	3.84	33.32	150	304	A	H
		2389.59	41.17	-32.83	74	44.7	25.99	3.81	33.33	234	179	P	V
		2390	31.41	-22.59	54	34.93	25.99	3.81	33.32	234	179	A	V
	*	2412	92.33	-	-	95.78	26.03	3.84	33.32	234	179	P	V
	*	2412	84.73	-	-	88.18	26.03	3.84	33.32	234	179	A	V
802.11g CH 06 2437MHz		2389.52	48.43	-25.57	74	51.96	25.99	3.81	33.33	228	274	P	H
		2389.94	40.11	-13.89	54	43.63	25.99	3.81	33.32	228	274	A	H
	*	2437	101.49	-	-	104.86	26.1	3.84	33.31	228	274	P	H
	*	2437	93.89	-	-	97.26	26.1	3.84	33.31	228	274	A	H
		2483.76	49.7	-24.3	74	52.96	26.17	3.88	33.31	228	274	P	H
		2483.55	40.29	-13.71	54	43.55	26.17	3.88	33.31	228	274	A	H
		2389.8	38.98	-35.02	74	42.5	25.99	3.81	33.32	209	75	P	V
		2389.52	29.98	-24.02	54	33.51	25.99	3.81	33.33	209	75	A	V
	*	2437	90.16	-	-	93.53	26.1	3.84	33.31	209	75	P	V
	*	2437	82.48	-	-	85.85	26.1	3.84	33.31	209	75	A	V
		2488.52	40.03	-33.97	74	43.23	26.2	3.91	33.31	209	75	P	V
		2484.04	30.02	-23.98	54	33.28	26.17	3.88	33.31	209	75	A	V



<b>802.11g CH 11 2462MHz</b>	*	2462	101.83	-	-	105.13	26.13	3.88	33.31	199	267	P	H
	*	2462	94.4	-	-	97.7	26.13	3.88	33.31	199	267	A	H
		2483.92	54.68	-19.32	74	57.94	26.17	3.88	33.31	199	267	P	H
		2483.6	41.46	-12.54	54	44.72	26.17	3.88	33.31	199	267	A	H
	*	2462	94.9	-	-	98.2	26.13	3.88	33.31	250	213	P	V
	*	2462	87.09	-	-	90.39	26.13	3.88	33.31	250	213	A	V
		2483.52	48.38	-25.62	74	51.64	26.17	3.88	33.31	250	213	P	V
		2483.56	35.98	-18.02	54	39.24	26.17	3.88	33.31	250	213	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11g CH 01 2412MHz		4824	45.07	-28.93	74	65.26	30.49	5.92	56.6	150	360	P	H
		4824	41.08	-32.92	74	61.27	30.49	5.92	56.6	150	360	P	V
802.11g CH 06 2437MHz		4874	41.8	-32.2	74	62.15	30.58	5.98	56.91	150	360	P	H
		7311	43.78	-30.22	74	60.46	34.4	6.92	58	174	100	P	H
		4874	42.84	-31.16	74	63.19	30.58	5.98	56.91	150	360	P	V
		7311	45.27	-28.73	74	61.95	34.4	6.92	58	174	100	P	V
802.11g CH 11 2462MHz		4924	42.35	-31.65	74	61.72	30.68	6.03	56.08	150	347	P	H
		7386	44.05	-29.95	74	60.34	34.79	6.93	58.01	150	274	P	H
		4924	40.64	-33.36	74	60.01	30.68	6.03	56.08	150	347	P	V
		7386	44.2	-29.8	74	60.49	34.79	6.93	58.01	150	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



## 2.4GHz 2400~2483.5MHz

## WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT20 CH 01 2412MHz		2389.38	60.24	-13.76	74	63.77	25.99	3.81	33.33	150	289	P	H
		2390	47.04	-6.96	54	50.56	25.99	3.81	33.32	150	289	A	H
	*	2412	108.25	-	-	111.7	26.03	3.84	33.32	150	289	P	H
	*	2412	100.49	-	-	103.94	26.03	3.84	33.32	150	289	A	H
		2389.905	45.38	-28.62	74	48.9	25.99	3.81	33.32	231	289	P	V
		2389.695	32.19	-21.81	54	35.72	25.99	3.81	33.33	231	289	A	V
	*	2412	91.57	-	-	95.02	26.03	3.84	33.32	231	289	P	V
	*	2412	83.89	-	-	87.34	26.03	3.84	33.32	231	289	A	V
802.11n HT20 CH 06 2437MHz		2389.52	55.63	-18.37	74	59.16	25.99	3.81	33.33	150	291	P	H
		2389.8	47.12	-6.88	54	50.64	25.99	3.81	33.32	150	291	A	H
	*	2437	108.11	-	-	111.48	26.1	3.84	33.31	150	291	P	H
	*	2437	100.54	-	-	103.91	26.1	3.84	33.31	150	291	A	H
		2483.62	54.38	-19.62	74	57.64	26.17	3.88	33.31	150	291	P	H
		2483.83	45.68	-8.32	54	48.94	26.17	3.88	33.31	150	291	A	H
		2389.8	50.3	-23.7	74	53.82	25.99	3.81	33.32	227	190	P	V
		2389.8	41.78	-12.22	54	45.3	25.99	3.81	33.32	227	190	A	V
	*	2437	101.7	-	-	105.07	26.1	3.84	33.31	227	190	P	V
	*	2437	93.9	-	-	97.27	26.1	3.84	33.31	227	190	A	V
		2483.69	49.42	-24.58	74	52.68	26.17	3.88	33.31	227	190	P	V
		2483.5	39.7	-14.3	54	42.96	26.17	3.88	33.31	227	190	A	V



<b>802.11n</b> <b>HT20</b> <b>CH 11</b> <b>2462MHz</b>	*	2462	106.45	-	-	109.75	26.13	3.88	33.31	166	304	P	H
	*	2462	98.6	-	-	101.9	26.13	3.88	33.31	166	304	A	H
		2483.56	65.39	-8.61	74	68.65	26.17	3.88	33.31	166	304	P	H
		2483.84	47.78	-6.22	54	51.04	26.17	3.88	33.31	166	304	A	H
	*	2462	104.1	-	-	107.4	26.13	3.88	33.31	250	224	P	V
	*	2462	96.41	-	-	99.71	26.13	3.88	33.31	250	224	A	V
		2484.76	60.44	-13.56	74	63.7	26.17	3.88	33.31	250	224	P	V
		2483.52	46.22	-7.78	54	49.48	26.17	3.88	33.31	250	224	A	V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT20 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	43.13	-30.87	74	63.32	30.49	5.92	56.6	150	360	P	H
		4824	41.46	-32.54	74	61.65	30.49	5.92	56.6	150	360	P	V
802.11n HT20 CH 06 2437MHz		4874	41.11	-32.89	74	61.46	30.58	5.98	56.91	150	360	P	H
		7311	44.59	-29.41	74	61.27	34.4	6.92	58	174	100	P	H
		4874	42.32	-31.68	74	62.67	30.58	5.98	56.91	150	360	P	V
		7311	44.24	-29.76	74	60.92	34.4	6.92	58	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	41.41	-32.59	74	60.78	30.68	6.03	56.08	150	347	P	H
		7386	43.06	-30.94	74	59.35	34.79	6.93	58.01	150	274	P	H
		4924	41.3	-32.7	74	60.67	30.68	6.03	56.08	150	347	P	V
		7386	44.03	-29.97	74	60.32	34.79	6.93	58.01	150	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





## 2.4GHz 2400~2483.5MHz

## WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		2389.52	58.47	-15.53	74	62	25.99	3.81	33.33	150	302	P	H
		2389.8	43.84	-10.16	54	47.36	25.99	3.81	33.32	150	302	A	H
	*	2422	98.49	-	-	101.9	26.06	3.84	33.31	150	302	P	H
	*	2422	90.91	-	-	94.32	26.06	3.84	33.31	150	302	A	H
		2484.04	44.74	-29.26	74	48	26.17	3.88	33.31	150	302	P	H
		2483.97	35.41	-18.59	54	38.67	26.17	3.88	33.31	150	302	A	H
		2389.66	48.65	-25.35	74	52.18	25.99	3.81	33.33	232	291	P	V
		2389.66	34.75	-19.25	54	38.28	25.99	3.81	33.33	232	291	A	V
	*	2422	90.18	-	-	93.59	26.06	3.84	33.31	232	291	P	V
	*	2422	82.63	-	-	86.04	26.06	3.84	33.31	232	291	A	V
		2485.58	39.48	-34.52	74	42.74	26.17	3.88	33.31	232	291	P	V
		2484.32	30.77	-23.23	54	34.03	26.17	3.88	33.31	232	291	A	V
802.11n HT40 CH 06 2437MHz		2389.8	55.82	-18.18	74	59.34	25.99	3.81	33.32	150	292	P	H
		2389.94	41.54	-12.46	54	45.06	25.99	3.81	33.32	150	292	A	H
	*	2437	98.39	-	-	101.76	26.1	3.84	33.31	150	292	P	H
	*	2437	90.95	-	-	94.32	26.1	3.84	33.31	150	292	A	H
		2483.83	50.44	-23.56	74	53.7	26.17	3.88	33.31	150	292	P	H
		2483.69	38.88	-15.12	54	42.14	26.17	3.88	33.31	150	292	A	H
		2389.8	52.35	-21.65	74	55.87	25.99	3.81	33.32	248	230	P	V
		2389.8	41.05	-12.95	54	44.57	25.99	3.81	33.32	248	230	A	V
	*	2437	95.12	-	-	98.49	26.1	3.84	33.31	248	230	P	V
	*	2437	87.78	-	-	91.15	26.1	3.84	33.31	248	230	A	V
		2483.62	49.04	-24.96	74	52.3	26.17	3.88	33.31	248	230	P	V
		2483.55	38.45	-15.55	54	41.71	26.17	3.88	33.31	248	230	A	V



802.11n HT40 CH 09 2452MHz		2389.38	45.15	-28.85	74	48.68	25.99	3.81	33.33	150	336	P	H
		2389.8	37	-17	54	40.52	25.99	3.81	33.32	150	336	A	H
	*	2452	98.72	-	-	102.05	26.1	3.88	33.31	150	336	P	H
	*	2452	91.08	-	-	94.41	26.1	3.88	33.31	150	336	A	H
		2483.55	62.93	-11.07	74	66.19	26.17	3.88	33.31	150	336	P	H
		2484.39	46.2	-7.8	54	49.46	26.17	3.88	33.31	150	336	A	H
		2389.66	42.78	-31.22	74	46.31	25.99	3.81	33.33	250	223	P	V
		2389.66	34.62	-19.38	54	38.15	25.99	3.81	33.33	250	223	A	V
	*	2452	94.78	-	-	98.11	26.1	3.88	33.31	250	223	P	V
	*	2452	87.25	-	-	90.58	26.1	3.88	33.31	250	223	A	V
		2483.5	59.27	-14.73	74	62.53	26.17	3.88	33.31	250	223	P	V
		2483.5	43.28	-10.72	54	46.54	26.17	3.88	33.31	250	223	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz**  
**WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
802.11n HT40 CH 03 2422MHz		4844	41.82	-32.18	74	61.96	30.52	5.92	56.58	150	360	P	H
		7266	43.05	-30.95	74	60.16	34.25	6.91	58.27	200	360	P	H
		4844	41.07	-32.93	74	61.21	30.52	5.92	56.58	150	360	P	V
		7266	43.73	-30.27	74	60.84	34.25	6.91	58.27	200	360	P	V
802.11n HT40 CH 06 2437MHz		4874	42.58	-31.42	74	62.93	30.58	5.98	56.91	150	163	P	H
		7311	44.18	-29.82	74	60.86	34.4	6.92	58	150	360	P	H
		4874	41.76	-32.24	74	62.11	30.58	5.98	56.91	150	163	P	V
		7311	43.78	-30.22	74	60.46	34.4	6.92	58	150	360	P	V
802.11n HT40 CH 09 2452MHz		4904	41.39	-32.61	74	61.07	30.64	6.03	56.35	150	360	P	H
		7356	44.1	-29.9	74	60.5	34.64	6.92	57.96	150	320	P	H
		4904	40.82	-33.18	74	60.5	30.64	6.03	56.35	150	360	P	V
		7356	43.21	-30.79	74	59.61	34.64	6.92	57.96	150	320	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



## Emission below 1GHz

## 2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
2.4GHz 802.11n HT20 LF		30	35.91	-4.09	40	44.05	17.28	0.65	26.07	100	0	P	H
		153.19	28.64	-14.86	43.5	41.93	11.13	1.08	25.5	-	-	P	H
		195.87	30.23	-13.27	43.5	43.81	10.52	1.17	25.27	-	-	P	H
		751.68	30.67	-15.33	46	34.67	20.12	2.15	26.27	-	-	P	H
		907.85	31.83	-14.17	46	33.83	21.46	2.35	25.81	-	-	P	H
		988.36	32.04	-21.96	54	32.5	22.27	2.47	25.2	-	-	P	H
		30	32.8	-7.2	40	40.94	17.28	0.65	26.07	100	0	P	V
		104.69	25.6	-17.9	43.5	38.2	12.19	0.96	25.75	-	-	P	V
		194.9	23.2	-20.3	43.5	36.83	10.48	1.17	25.28	-	-	P	V
		432.55	26.98	-19.02	46	34.33	16.96	1.67	25.98	-	-	P	V
		895.24	33.24	-12.76	46	35.43	21.34	2.35	25.88	-	-	P	V
		958.29	32.31	-13.69	46	33.36	21.97	2.41	25.43	-	-	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												

**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>P</b> eak or <b>A</b> verage
H/V	<b>H</b> orizontal or <b>V</b> ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**




## Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100.000	-	-	10Hz
802.11g	97.765	1.400	0.714	1kHz
2.4GHz 802.11n HT20	97.168	1.304	0.767	1kHz
2.4GHz 802.11n HT40	94.461	0.648	1.543	3kHz




802.11b



Date: 10.OCT.2016 11:57:24

802.11g




Date: 10.OCT.2016 12:06:19






802.11n HT20



Date: 10.OCT.2016 12:08:56

802.11n HT40



Date: 10.OCT.2016 12:13:15