



REPORT No.: SZ15080165W02

# FCC RF TEST REPORT

APPLICANT : Solnik S.A.  
PRODUCT NAME : TBW9612C8  
MODEL NAME : HY2-2169NE  
TRADE NAME : N.A  
BRAND NAME : HYUNDAI  
FCC ID : 2AFRUHY22169NE  
STANDARD(S) : 47 CFR Part 15 Subpart C  
ISSUE DATE : 2015-10-12



**SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.**

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB GROUP**

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Http://www.morlab.com

Fax: 86-755-36698525  
E-mail: service@morlab.cn



## DIRECTORY

<b>TEST REPORT DECLARATION</b>	<b>4</b>
<b>1. TECHNICAL INFORMATION</b>	<b>5</b>
1.1 APPLICANT INFORMATION	5
1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION	5
1.2.1 IDENTIFICATION OF ALL USED EUTS	5
1.3 TEST STANDARDS AND RESULTS	6
1.3.1 TEST ENVIRONMENT CONDITIONS	6
<b>2. 47 CFR PART 15C REQUIREMENTS</b>	<b>7</b>
2.1 ANTENNA REQUIREMENT	7
2.1.1 APPLICABLE STANDARD	7
2.1.2 RESULT: COMPLIANT	7
2.2 NUMBER OF HOPPING FREQUENCY	7
2.2.1 REQUIREMENT	7
2.2.2 TEST DESCRIPTION	7
2.2.3 TEST PROCEDURE	8
2.2.4 TEST RESULT	8
2.3 PEAK OUTPUT POWER	12
2.3.1 REQUIREMENT	12
2.3.2 TEST DESCRIPTION	12
2.3.3 TEST RESULT	12
2.4 20DB BANDWIDTH	14
2.4.1 DEFINITION	14
2.4.2 TEST DESCRIPTION	14
2.4.3 TEST PROCEDURE	14
2.4.4 TEST RESULT	14
2.5 CARRIED FREQUENCY SEPARATION	21
2.5.1 DEFINITION	21
2.5.2 TEST DESCRIPTION	21
2.5.3 TEST PROCEDURE	21
2.5.4 TEST RESULT	22
2.6 TIME OF OCCUPANCY (DWELL TIME)	24





2.6.1	REQUIREMENT	24
2.6.2	TEST DESCRIPTION	24
2.6.3	TEST PROCEDURE	24
2.6.4	TEST RESULT	25
<b>2.7</b>	<b>CONDUCTED SPURIOUS EMISSIONS</b>	<b>36</b>
2.7.1	REQUIREMENT	36
2.7.2	TEST DESCRIPTION	36
2.7.3	TEST PROCEDURE	36
2.7.4	TEST RESULT	37
<b>2.8</b>	<b>RESTRICTED FREQUENCY BANDS</b>	<b>49</b>
2.8.1	REQUIREMENT	49
2.8.2	TEST DESCRIPTION	49
2.8.3	TEST PROCEDURE	50
2.8.4	TEST RESULT	50
<b>2.9</b>	<b>CONDUCTED EMISSION</b>	<b>58</b>
2.9.1	REQUIREMENT	58
2.9.2	TEST DESCRIPTION	58
2.9.3	TEST RESULT	59
<b>2.10</b>	<b>RADIATED EMISSION</b>	<b>61</b>
2.10.1	REQUIREMENT	61
2.10.2	TEST DESCRIPTION	62
2.10.3	TEST PROCEDURE	64
2.10.4	TEST RESULT	64
<b>2.11</b>	<b>RF EXPOSURE EVALUATION</b>	<b>74</b>
2.11.1	REQUIREMENT	74
2.11.2	RESULT	74
<b>ANNEX A GENERAL INFORMATION</b>		<b>75</b>

Change History		
Issue	Date	Reason for change
1.0	2015-10-12	First edition



REPORT No.: SZ15080165W02

**TEST REPORT DECLARATION**

Applicant	Solnik S.A.
Applicant Address	Dr Emilio Ravignani 1724 - C.A.B.A. - República Argentina
Manufacturer	Beijing Benywave Wireless Communication Co. Ltd.,
Manufacturer Address	No 55, Jiachuang second road, Zhongguancun science Park OPTO—Mechatronics Industrial Park, Tongzhou District, Beijing, China 101111
Product Name	TBW9612C8
Model Name	HY2-2169NE
Brand Name	HYUNDAI
HW Version	TBW9612_P2_001
SW Version	961221_9716_VXXX
Test Standards	47 CFR Part 15 Subpart C
Test Date	2015-8-20 to 2015-9-21
Test Result	PASS

Tested by : Zou Jian  
Zou Jian(Test Engineer)

Reviewed by : Qiu Xiaojun  
Qiu Xiaojun(RF Manager)

Approved by : Zeng Dexin  
Zeng Dexin(Chief Engineer)

**MORLAB GROUP**

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Http://www.morlab.com

Fax: 86-755-36698525  
E-mail: service@morlab.cn





## 1. TECHNICAL INFORMATION

Note: Provide by applicant.

### 1.1 Applicant Information

Company:	Solnik S.A.
Address:	Dr Emilio Ravignani 1724 - C.A.B.A. - República Argentina

### 1.2 Equipment under Test (EUT) Description

Brand Name:	HYUNDAI
Trade Name:	N.A
Model Name:	HY2-2169NE
Frequency Range:	The frequency range used is 2402MHz – 2480MHz (79 channels, at intervals of 1MHz); The frequency block is 2400MHz to 2483.5MHz.
Modulation Type:	Bluetooth: FHSS (GFSK(1Mbps), $\pi/4$ -DQPSK(EDR 2Mbps), 8-DPSK(EDR 3Mbps))
Bluetooth Version:	2.1+EDR
Antenna Type:	PIFAAntenna
Antenna Gain:	1.1dBi

#### NOTE:

The EUT is a TBW9612C8, it contains Bluetooth Module operating at 2.4GHz ISM band; the frequencies allocated for the Bluetooth Module is  $F(\text{MHz})=2402+1*n$  ( $0 \leq n \leq 78$ ). The lowest, middle, highest channel numbers of the Bluetooth Module used and tested in this report are separately 0 (2402MHz), 39 (2441MHz) and 78 (2480MHz).

For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

#### 1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	TBW9612_P2_001	961221_9716_VXXX



### 1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-13 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Test Date	Result
1	15.203	Antenna Requirement	N.A	<u>PASS</u>
2	15.247(a)	Number of Hopping Frequency	Aug 31, 2015	<u>PASS</u>
3	15.247(b)	Peak Output Power	Aug 31, 2015	<u>PASS</u>
4	15.247(a)	20dB Bandwidth	Aug 28, 2015	<u>PASS</u>
5	15.247(a)	Carrier Frequency Separation	Aug 31, 2015	<u>PASS</u>
6	15.247(a)	Time of Occupancy (Dwell time)	Aug 31, 2015	<u>PASS</u>
7	15.247(d)	Conducted Spurious Emission	Aug 31, 2015	<u>PASS</u>
8	15.247(d)	Restricted Frequency Bands	Sep 21, 2015	<u>PASS</u>
9	15.207	Conducted Emission	Aug 31, 2015	<u>PASS</u>
10	15.209 15.247(d)	Radiated Emission	Sep 16, 2015	<u>PASS</u>
11	15.247(i), 1.1307 & 2.1093	RF exposure evaluation	NA	<u>PASS</u>

**NOTE:** The tests were performed according to the method of measurements prescribed in DA-00-705, ANSI C63.4-2009 and ANSI C63.4: 2009 and ANSI C63.10: 2013.

#### 1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

## 2. 47 CFR PART 15C REQUIREMENTS

### 2.1 Antenna requirement

#### 2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

### 2.2 Number of Hopping Frequency

#### 2.2.1 Requirement

According to FCC §15.247(a)(1)(iii), frequency hopping systems operating in the 2400MHz to 2483.5MHz bands shall use at least 15 hopping frequencies.

#### 2.2.2 Test Description

##### A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

##### B. Equipments List:

Please reference ANNEX A(1.4).





### 2.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize


### 2.2.4 Test Result

The Bluetooth Module operates at hopping-on test mode; the frequencies number employed is counted to verify the Module's using the number of hopping frequency.

#### A. Test Verdict:

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Refer to Plot	Verdict
GFSK	2400 - 2483.5	79	15	Plot A	PASS
$\pi/4$ -DQPSK	2400 - 2483.5	79	15	Plot B	PASS
8-DPSK	2400 - 2483.5	79	15	Plot C	PASS


#### B. Test Plots:








REPORT No.: SZ15080165W02




(Plot A: GFSK)





REPORT No.: SZ15080165W02




(Plot B:  $\pi/4$ -DQPSK)





REPORT No.: SZ15080165W02



(Plot C: 8- DPSK)


## 2.3 Peak Output Power

### 2.3.1 Requirement

According to FCC §15.247(b)(1), for frequency hopping systems that operates in the 2400MHz to 2483.5MHz band employing at least 75 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt. For all other frequency hopping systems in the 2400MHz to 2483.5MHz band, it is 0.125Watts.

### 2.3.2 Test Description

#### A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Power meter and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.3.3 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the module. The lowest, middle and highest channel were tested by power meter.



**2.3.3.1 GFSK Mode****A. Test Verdict:**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	10.71	0.01177606	20.97	0.125	PASS
39	2441	8.14	0.006516284			PASS
78	2480	7.09	0.005116818			PASS

**2.3.3.2  $\pi/4$ -DQPSK Mode****B. Test Verdict:**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	12.17	0.01648162	20.97	0.125	PASS
39	2441	9.45	0.00881049			PASS
78	2480	8.33	0.00680769			PASS

**2.3.3.3 8-DPSK Mode****C. Test Verdict:**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	12.47	0.01766038	20.97	0.125	PASS
39	2441	9.45	0.00881049			PASS
78	2480	8.64	0.00731139			PASS


## 2.4 20dB Bandwidth

### 2.4.1 Definition

According to FCC §15.247(a)(1), the 20dB bandwidth is known as the 99% emission bandwidth, or 20dB bandwidth ( $10 \cdot \log 1\% = 20\text{dB}$ ) taking the total RF output power.

### 2.4.2 Test Description

#### A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 2.4.4 Test Result

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to record the 20dB bandwidth of the Module.






#### 2.4.4.1 GFSK Mode

##### A. Test Verdict:

The maximum 20dB bandwidth measured is 0.9300MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	0.9300	Plot A
39	2441	0.8711	Plot B
78	2480	0.9261	Plot C


##### B. Test Plots:




(Plot A: Channel = 2402 @ GFSK)



REPORT No.: SZ15080165W02



(Plot B: Channel = 2441 @ GFSK)



(Plot C: Channel = 2480 @ GFSK)






#### 2.4.4.2 $\pi/4$ -DQPSK Mode

##### A. Test Verdict:

The maximum 20dB bandwidth measured is 1.272MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.268	Plot D
39	2441	1.272	Plot E
78	2480	1.263	Plot F


##### B. Test Plots:




(Plot D: Channel = 2402 @  $\pi/4$ -DQPSK)



REPORT No.: SZ15080165W02



(Plot E: Channel = 2441 @  $\pi/4$ -DQPSK)



(Plot F: Channel = 2480 @  $\pi/4$ -DQPSK)




#### 2.4.4.3 8-DPSK Mode

##### A. Test Verdict:

The maximum 20dB bandwidth measured is 1.281MHz according to the table below.

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Refer to Plot
0	2402	1.274	Plot G
39	2441	1.273	Plot H
78	2480	1.281	Plot I

##### B. Test Plots:




(Plot G: Channel = 2402 @ 8-DPSK)






REPORT No.: SZ15080165W02



(Plot H: Channel = 2441 @ 8-DPSK)



(Plot I: Channel = 2480 @ 8-DPSK)


## 2.5 Carried Frequency Separation

### 2.5.1 Definition

According to FCC §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 2.5.2 Test Description

#### A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq 1\%$  of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak


Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.



## 2.5.4 Test Result

The Bluetooth Module operates at hopping-on test mode. For any adjacent channels (e.g. the channel 39 and 40 as showed in the Plot A), the Module does have hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel (refer to section 0), whichever is greater. So, the verdict is PASSING




(Plot A: GFSK)






REPORT No.: SZ15080165W02



(Plot B:  $\pi/4$ -DQPSK)



(Plot C: 8-DPSK)


## 2.6 Time of Occupancy (Dwell time)

### 2.6.1 Requirement

According to FCC §15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 2.6.2 Test Description

#### A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.6.3 Test Procedure

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 31.6 second period (79 channel \* 0.4 s) is equal to  $10 * (\# \text{ of pulses in 3.16 s}) * \text{pulse width}$ .



REPORT No.: SZ15080165W02


## 2.6.4 Test Result

### 2.6.4.1 GFSK Mode

#### A. Test Verdict:

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
DH1	0.4	32	0.01280	0.1280	0.4	PASS
DH3	1.65	13	0.02145	0.2145		PASS
DH5	2.85	14	0.03990	0.3990		PASS


#### B. Test Plots:








REPORT No.: SZ15080165W02




(Plot A: DH1 @ GFSK)







REPORT No.: SZ15080165W02



(Plot B: DH3 @ GFSK)





(Plot C: DH5 @ GFSK)

#### 2.6.4.2 $\pi/4$ -DQPSK Mode

##### A. Test Verdict:


DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
DH1	0.4	32	0.01280	0.1280	0.4	PASS
DH3	1.6	16	0.02560	0.2560		PASS
DH5	2.8	16	0.04480	0.4480		PASS

##### B. Test Plots:






REPORT No.: SZ15080165W02



(Plot D: DH1 @  $\pi/4$ -DQPSK)




REPORT No.: SZ15080165W02



(Plot E: DH3 @  $\pi/4$ -DQPSK)



REPORT No.: SZ15080165W02



(Plot F: DH5 @  $\pi/4$ -DQPSK)






REPORT No.: SZ15080165W02


**2.6.4.3 8-DPSK mode****A. Test Verdict:**

DH Packet	Pulse Width (msec)	Number of pulse in 3.16 seconds	Average Time of Occupancy in 3.16 seconds (sec)	Average Time of Occupancy in 31.6 seconds (sec)	Limit (sec)	Verdict
DH1	0.45	31	0.01395	0.1395	0.4	PASS
DH3	1.5	15	0.02250	0.2250		PASS
DH5	2.85	7	0.01995	0.1995		PASS


**B. Test Plots:**



REPORT No.: SZ15080165W02




(Plot G: DH1 @ 8-DPSK)






REPORT No.: SZ15080165W02




(Plot H: DH3 @ 8-DPSK)







REPORT No.: SZ15080165W02



(Plot I: DH5 @ 8-DPSK)


## 2.7 Conducted Spurious Emissions

### 2.7.1 Requirement

According to FCC §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.7.2 Test Description

#### A. Test Setup:



The Bluetooth Module of the EUT is coupled to the Spectrum Analyzer (SA) and the Bluetooth Service Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the Bluetooth Module of the EUT is activated and controlled by the SS, and is set to operate under test mode transmitting 339 bytes DH5 packages at maximum power.

#### B. Equipments List:

Please reference ANNEX A(1.4).

### 2.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.



## 2.7.4 Test Result

The Bluetooth Module operates at hopping-off test mode. The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.


### 2.7.4.1 GFSK Mode

#### A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-41.03	Plot A.1	9.806	-10.194	PASS
39	2441	-41.51	Plot B.1	7.249	-12.751	PASS
78	2480	-42.4	Plot C.1	5.892	-14.108	PASS

#### B. Test Plots:


**Note:** the power of the Module transmitting frequency should be ignored.




(Plot A.1: Channel = 0, 30MHz to 25GHz @ GFSK Mode)



REPORT No.: SZ15080165W02




(Channel = 0, Band edge @ GFSK Mode)




(Channel = 0, Band edge with hopping on @ GFSK Mode)






(Plot B.1: Channel = 39, 30MHz to 25GHz @ GFSK Mode)




(Plot C.1: Channel = 78, 30MHz to 25GHz @ GFSK Mode)



REPORT No.: SZ15080165W02



(Channel = 78, Band edge @ GFSK Mode)



(Channel = 78, Band edge with hopping on @ GFSK Mode)




REPORT No.: SZ15080165W02

**2.7.4.2  $\pi/4$ -DQPSK Mode****A. Test Verdict:**



Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-45.58	Plot D.1	9.265	-10.735	PASS
39	2441	-42.44	Plot E.1	4.165	-15.835	PASS
78	2480	-42.33	Plot F.1	3.937	-16.063	PASS

**B. Test Plots:**

**Note:** the power of the Module transmitting frequency should be ignored.





(Plot D.1: Channel = 0, 30MHz to 25GHz @  $\pi/4$ -DQPSK)

(Channel = 0, Band edge @ $\pi/4$ -DQPSK)(Channel = 0, Band edge with hopping on @ $\pi/4$ -DQPSK)







REPORT No.: SZ15080165W02

(Plot E.1: Channel = 39, 30MHz to 25GHz @  $\pi/4$ -DQPSK)(Plot F.1: Channel = 78, 30MHz to 25GHz @  $\pi/4$ -DQPSK)



REPORT No.: SZ15080165W02

(Channel = 78, Band edge @  $\pi/4$ -DQPSK)(Channel = 78, Band edge with hopping on @  $\pi/4$ -DQPSK)




REPORT No.: SZ15080165W02

**2.7.4.3 8-DPSK Mode****A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Refer to Plot	Limit (dBm)		Verdict
				Carrier Level	Calculated -20dBc Limit	
0	2402	-43.16	Plot G.1	6.699	-13.301	PASS
39	2441	-42.65	Plot H.1	7.951	-12.049	PASS
78	2480	-42.42	Plot I.1	4.65	-15.35	PASS

**B. Test Plots:**


**Note:** the power of the Module transmitting frequency should be ignored.




(Plot G.1: Channel = 0, 30MHz to 25GHz @ 8-DPSK)



REPORT No.: SZ15080165W02



(Channel = 0, Band edge @ 8-DPSK)




(Channel = 0, Band edge with hopping on @ 8-DPSK)






REPORT No.: SZ15080165W02




(Plot H.1: Channel = 39, 30MHz to 25GHz @ 8-DPSK)




(Plot I.1: Channel = 78, 30MHz to 25GHz @ 8-DPSK)



REPORT No.: SZ15080165W02



(Plot I.1: Channel = 78, Band edge @ 8-DPSK)



(Plot I.1: Channel = 78, Band edge with hopping on @ 8-DPSK)


## 2.8 Restricted Frequency Bands

### 2.8.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 2.8.2 Test Description

#### A. Test Setup:



The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna, and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

For the Test Antenna:

Horn Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

**B. Equipments List:**

Please reference ANNEX A(1.4).

**2.8.3 Test Procedure**

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 KHz for  $f < 1\text{GHz}$

VBW = 3 MHz for peak and 10Hz for average

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

**2.8.4 Test Result**

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

AT: Total correction Factor except Antenna

UR: Receiver Reading

Gpreamp: Preamplifier Gain

AFactor: Antenna Factor at 3m

**Note:** Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


**2.8.4.1 GFSK Mode****A. Test Verdict:**

Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBuV)	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission $E$ (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
		PK/ AV						
0	2386.63	PK	54.55	-33.63	32.56	53.48	74	Pass
0	2389.02	AV	44.32	-33.63	32.56	43.25	54	Pass
78	2483.70	PK	66.63	-33.18	32.5	65.95	74	Pass
78	2492.87	AV	44.87	-33.18	32.5	44.19	54	Pass







## B. Test Plots:




(Plot A1:Channel = 0 PEAK @ GFSK)



(Plot A2:Channel = 0 AVERAGE @ GFSK)



(Plot B1: Channel = 78 PEAK @ GFSK)



(Plot B2: Channel = 78 AVERAGE @ GFSK)




## 2.8.4.2 $\pi/4$ -DQPSK Mode

### A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBuV)	$A_T$ (dB)	$A_{Factor}$ (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
0	2389.34	PK	56.76	-33.63	32.56	55.69	74	Pass
0	2389.13	AV	47.96	-33.63	32.56	46.89	54	Pass
78	2483.74	PK	67.60	-33.18	32.5	66.52	74	Pass
78	2492.63	AV	46.08	-33.18	32.5	45.40	54	Pass


### B. Test Plots:




(Plot C1: Channel = 0 PEAK @  $\pi/4$ -DQPSK)



REPORT No.: SZ15080165W02

(Plot C2: Channel = 0 AVERAGE @  $\pi/4$ -DQPSK)(Plot D1: Channel = 78 PEAK @  $\pi/4$ -DQPSK)





(Plot D2: Channel = 78 AVERAGE @  $\pi/4$ -DQPSK)

### 2.8.4.3 8-DPSK Mode


#### A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading $U_R$ (dBμV)	$A_T$ (dB)	$A_{Factor}$ (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2389.34	PK	57.78	-33.63	32.56	56.71	74	Pass
0	2388.82	AV	47.52	-33.63	32.56	46.45	54	Pass
78	2483.72	PK	65.57	-33.18	32.5	64.89	74	Pass
78	2492.61	AV	44.15	-33.18	32.5	43.47	54	Pass


#### B. Test Plots:



REPORT No.: SZ15080165W02



(Plot E1: Channel = 0 PEAK @ 8-DPSK Mode)



(Plot E2: Channel = 0 AVERAGE @ 8-DPSK Mode)



REPORT No.: SZ15080165W02



(Plot F1:Channel = 78 PEAK @ 8-DPSK Mode)



(Plot F2:Channel = 78 AVERAGE @ 8-DPSK Mode)

## 2.9 Conducted Emission

### 2.9.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5- 30	60	50

#### NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.9.2 Test Description

#### A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.4:2009

The factors of the site are calibrated to correct the reading. During the measurement, the Bluetooth Module is activated and controlled by the Bluetooth Service Supplier (SS) via a Common Antenna,





and is set to operate under hopping-on test mode transmitting 339 bytes DH5 packages at maximum power.

## B. Equipments List:

Please reference ANNEX A(1.4).


### 2.9.3 Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

#### A. Test setup:

The EUT configuration of the emission tests is EUT + Link.


#### B. Test Plots:



(Plot A: L Phase)



REPORT No.: SZ15080165W02



(Plot B: N Phase)



## 2.10 Radiated Emission

### 2.10.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

**Note:**

1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)


In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)




## 2.10.2 Test Description

### A. Test Setup:

- 1) For radiated emissions from 9kHz to 30MHz




- 2) For radiated emissions from 30MHz to 1GHz





### 3) For radiated emissions above 1GHz



The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.4 (2009). The EUT was set-up on insulator 80cm above the Ground Plane. The set-up and test methods were according to ANSI C63.4.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

**B. Equipments List:**

Please reference ANNEX A(1.4).

**2.10.3 Test Procedure**

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

**2.10.4 Test Result**

According to ANSI C63.4 selection 4.2.2, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.

**Note:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.




#### 2.10.4.1 GFSK Mode:

##### A. Test Plots for the Whole Measurement Frequency Range:

Plots for Channel = 0



(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 0)




(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 0)






Plot for Channel = 39



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
44.550	18.52	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
55.220	19.48	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
141.550	15.04	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2448.900	44.53	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5162.211	46.71	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
10335.516	48.04	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 39)




Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
43.580	21.46	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
59.100	23.24	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
187.140	14.73	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
3023.641	45.58	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5858.774	47.41	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12559.629	49.26	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 39)






## Plot for Channel = 78




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
55.220	20.06	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
139.610	15.07	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
586.780	20.10	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2213.285	44.22	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5752.864	49.39	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12547.409	49.09	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @ GFSK, channel 78)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
41.640	25.09	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
60.070	22.95	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
86.260	20.59	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
2836.261	45.66	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5752.864	47.53	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12596.290	49.22	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @ GFSK, channel 78)

**2.10.4.2  $\pi/4$ -DQPSK Mode:****B. Test Plots for the Whole Measurement Frequency Range:**Plots for Channel = 0

Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
43.580	18.45	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
55.220	18.82	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
137.670	14.79	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
1674.830	40.01	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4718.203	46.28	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
11753.082	48.66	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS


(30MHz to 25GHz, Antenna Horizontal @  $\pi/4$ -DQPSK, channel 0)

Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
42.610	28.37	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
83.350	19.64	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
184.230	14.98	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2197.919	43.11	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5369.958	47.34	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12152.282	49.72	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @  $\pi/4$ -DQPSK, channel 0)




Plot for Channel = 39



Fre. (MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
44.550	18.23	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
56.190	19.51	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
138.640	14.07	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2803.673	45.51	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5642.881	46.25	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
10335.516	47.68	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @  $\pi/4$ -DQPSK, channel 39)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
41.640	24.02	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
86.260	19.53	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
186.170	15.08	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2224.170	43.27	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5406.619	46.73	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
9109.402	48.22	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(30MHz to 25GHz, Antenna Vertical @  $\pi/4$ -DQPSK, channel 39)






Plot for Channel = 78




(30MHz to 25GHz, Antenna Horizontal @  $\pi/4$ -DQPSK, channel 78)




(30MHz to 25GHz, Antenna Vertical @  $\pi/4$ -DQPSK, channel 78)



**2.10.4.3 8-DPSK Mode:****C. Test Plots for the Whole Measurement Frequency Range:**Plots for Channel = 0

Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
55.220	20.28	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
138.640	14.22	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
445.160	19.18	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2219.048	43.35	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4787.452	45.32	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
14425.277	49.68	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 0)




Fre.(MHz)	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	Antenna	Verdict
43.580	25.48	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
86.260	19.26	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
183.260	15.20	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2304.842	43.47	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5166.285	46.93	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
14885.579	48.50	N.A	N.A	74.0	N.A	54.0	Vertical	PASS


(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 0)



Plot for Channel = 39




(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 39)




(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 39)



Plot for Channel = 78



(30MHz to 25GHz, Antenna Horizontal @8-DPSK, channel 78)



(30MHz to 25GHz, Antenna Vertical @8-DPSK, channel 78)





## **2.11 RF exposure evaluation**

### **2.11.1 Requirement**

According to § 1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of Commission's guideline.

### **2.11.2 Result**

Please refer to SAR report.





## ANNEX A GENERAL INFORMATION

### 1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10: 2013, ANSI C63.4 2009 and CISPR Publication 22; the FCC registration number is 695796.



REPORT No.: SZ15080165W02

**1.4 Test Equipments Utilized****1.4.1 Conducted Test Equipments****Conducted Test Equipment**

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	System Simulator	6K00006210	MT8852B	Anritsu	2015.02.26	2016.02.25
2	Spectrum Analyzer	MY45101810	E4407B	Agilent	2015.02.26	2016.02.25
3	Power Splitter	NW521	1506A	Weinschel	2015.02.26	2016.02.25
4	Attenuator 1	(n.a.)	10dB	Resnet	2015.02.26	2016.02.25
5	Attenuator 2	(n.a.)	3dB	Resnet	2015.02.26	2016.02.25
6	EXA Signal Analyzer	MY51440152	N9010A	Agilent	2015.02.26	2016.02.25
7	RF cable	CB01	RF01	Morlab	N/A	N/A
8	Coaxial cable	CB02	RF02	Morlab	N/A	N/A
9	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

**1.4.2 Conducted Emission Test Equipments****Conducted Emission Test Equipments**

No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	US44210471	E7405A	Agilent	2015.02.26	2016.02.25
2	LISN	812744	NSLK 8127	Schwarzbeck	2015.02.26	2016.02.25
3	Service Supplier	100448	CMU200	R&S	2015.02.26	2016.02.25
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2015.02.26	2016.02.25
5	Coaxial cable(BNC)	CB01	EMC01	Morlab	N/A	N/A



REPORT No.: SZ15080165W02

### 1.4.3 Radiated Test Equipments

Radiated Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	100448	CMU200	R&S	2015.02.26	2016.02.25
2	Receiver	US44210471	E7405A	Agilent	2015.02.26	2016.02.25
3	Test Antenna - Bi-Log	9163-274	9m*6m*6m	Albatross	2015.02.26	2016.02.25
4	Test Antenna - Horn	9120D-963	VULB 9163	Schwarzbeck	2015.02.26	2016.02.25
5	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2015.02.26	2016.02.25
6	Test Antenna - Loop	1519-022	HL050S7	R&S	2015.02.26	2016.02.25
7	Reject Filter	(n.a.)	BRM50702	Micro-Tronics	2015.02.26	2016.02.25
8	Coaxial cable (N male)	CB02	EMC02	Morlab	N/A	N/A
9	Coaxial cable (N male)	CB03	EMC03	Morlab	N/A	N/A

### 1.4.4 Climate Chamber

Climate Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2015.02.26	2016.02.25

### 1.4.5 Vibration Table

Vibration Table						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2015.02.26	2016.02.25

### 1.4.6 Anechoic Chamber

Anechoic Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Albatross	2015.02.26	2016.02.25

\*\*\*\*\* END OF REPORT \*\*\*\*\*