

# FCC Test Report


APPLICANT : Solnik S.A.  
EQUIPMENT : mobile phone  
BRAND NAME : HYUNDAI  
MODEL NAME : HY1-7558  
FCC ID : 2AFRUHY1-7558  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification

The product was received on Nov. 29, 2016 and testing was completed on Jan. 06, 2017. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Prepared by: Eric Shih / Manager



Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (SHENZHEN) INC.**

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,  
Nanshan District, Shenzhen, Guangdong, P. R. China**



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Product Feature of Equipment Under Test .....	5
1.4. Product Specification of Equipment Under Test .....	6
1.5. Modification of EUT .....	6
1.6. Test Location .....	7
1.7. Applicable Standards .....	7
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1. Test Mode .....	8
2.2. Connection Diagram of Test System .....	10
2.3. Support Unit used in test configuration and system .....	12
2.4. EUT Operation Test Setup .....	13
<b>3. TEST RESULT .....</b>	<b>14</b>
3.1. Test of AC Conducted Emission Measurement .....	14
3.2. Test of Radiated Emission Measurement .....	20
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>27</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>28</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC6N2906	Rev. 01	Initial issue of report	Jan. 23, 2017

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 10.96 dB at 0.150 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 4.13 dB at 30.000 MHz

## 1. General Description

### 1.1. Applicant

**Solnik S.A.**

Dr. Emilio Ravignani 1724 Ciudad Autonoma de Buenos Aires Zip Code 1414 Argentina

### 1.2. Manufacturer

**Gionee Communication Equipment Co.,Ltd.**

21/F, Times Technology Building, No. 7028, Shennan Avenue, Futian District, Shenzhen, China

### 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	mobile phone
Brand Name	HYUNDAI
Model Name	HY1-7558
FCC ID	2AFRUHY1-7558
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
IMEI Code	Conduction: 354147042349663/354147042399668 Radiation: 351417042348061/351417042398066
HW Version	Ultra Live II_Mainboard_P2.2
SW Version	Ultra Live II_0202_V5443
EUT Stage	Pre-Production

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass: 1602 MHz + $n \times 0.5625\text{MHz}$ ( $n=-7,-6,-5,...,0,...,6$ )
<b>Antenna Type</b>	WWAN: PIFA Antenna WLAN: SLOT Antenna Bluetooth: SLOT Antenna GPS/Glonass: SLOT Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth v4.0 LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/Glonass : BPSK

## 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6. Test Location

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	CO01-SZ	

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH03-SZ	565805

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## **2. Test Configuration of Equipment Under Test**

### **2.1. Test Mode**


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).




Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera(Rear) + SIM1 <Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera(Front) + SIM2 <Fig.1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM1 <Fig.1> Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx + SIM2 <Fig.2> Mode 5: LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 <Fig.3>
Radiated Emissions < 1GHz	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera(Rear) + SIM1 <Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera(Front) + SIM2 <Fig.1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM1 <Fig.1> Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx + SIM2 <Fig.2> Mode 5: LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 <Fig.3>
Radiated Emissions ≥ 1GHz	Mode 1: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx + SIM2 <Fig.2> Mode 2: LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 <Fig.3>
<b>Remark:</b> <ol style="list-style-type: none"> <li>The worst case of AC is mode 1; and the USB Link mode of AC is mode 5, the test data of these modes are reported.</li> <li>The worst case of RE &lt; 1G is mode 4; and the USB Link mode of RE is mode 5, the test data of these modes are reported.</li> <li>Data Link with Notebook means data application transferred mode between EUT and Notebook.</li> </ol>	


## 2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



**<Fig.3>**

## 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
3.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
4.	Glonass Station	RACELOGIC	RLLS03-2P	Fcc DoC	N/A	N/A
5.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8m
6.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 2.7m with Core
7.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
8.	Bluetooth Earphone	Samsung	HS3000	A3LHS3000	N/A	N/A
9.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
10.	iPod nano 8GB	Apple	MC690ZP/A	FCC DoC	Shielded, 1.2m	N/A
11.	IPod	Apple	MC525 ZP/A	N/A	Shielded, 1.0m	N/A



## **2.4. EUT Operation Test Setup**

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GPS/Glonass function to make the EUT receive continuous signals from GPS/Glonass station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





## 3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	21~23℃
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera(Rear) + SIM1		




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_20160509 LINE  
Project : (FC) 6N2906  
Mode : Mode 1  
IMEI : 354147042349663/354147042399668

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	45.04	-10.96	56.00	34.30	0.14	10.60	Average
2	0.15	48.44	-17.56	66.00	37.70	0.14	10.60	QP
3	0.20	35.01	-18.61	53.62	24.40	0.11	10.50	Average
4	0.20	36.91	-26.71	63.62	26.30	0.11	10.50	QP
5	0.33	15.58	-33.99	49.57	5.10	0.11	10.37	Average
6	0.33	26.88	-32.69	59.57	16.40	0.11	10.37	QP
7	0.59	14.30	-31.70	46.00	4.00	0.11	10.19	Average
8	0.59	26.30	-29.70	56.00	16.00	0.11	10.19	QP
9	0.70	24.07	-21.93	46.00	13.80	0.11	10.16	Average
10	0.70	32.67	-23.33	56.00	22.40	0.11	10.16	QP
11	3.36	16.13	-29.87	46.00	5.80	0.12	10.21	Average
12	3.36	26.33	-29.67	56.00	16.00	0.12	10.21	QP
13	23.51	21.44	-28.56	50.00	10.40	0.48	10.56	Average
14	23.51	40.74	-19.26	60.00	29.70	0.48	10.56	QP





Test Mode :	Mode 1	Temperature :	21~23℃
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera(Rear) + SIM1		




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_20160509 NEUTRAL  
Project : (FC)6N2906  
Mode : Mode 1  
IMEI : 354147042349663/354147042399668

	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark	
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1 *	0.15	43.34	-12.66	56.00	32.60	0.14	10.60	Average	
2	0.15	46.84	-19.16	66.00	36.10	0.14	10.60	QP	
3	0.20	33.21	-20.41	53.62	22.60	0.11	10.50	Average	
4	0.20	35.51	-28.11	63.62	24.90	0.11	10.50	QP	
5	0.59	28.40	-17.60	46.00	18.10	0.11	10.19	Average	
6	0.59	34.50	-21.50	56.00	24.20	0.11	10.19	QP	
7	0.70	28.67	-17.33	46.00	18.40	0.11	10.16	Average	
8	0.70	36.27	-19.73	56.00	26.00	0.11	10.16	QP	
9	1.46	19.58	-26.42	46.00	9.30	0.11	10.17	Average	
10	1.46	33.08	-22.92	56.00	22.80	0.11	10.17	QP	
11	3.40	21.93	-24.07	46.00	11.59	0.13	10.21	Average	
12	3.40	36.23	-19.77	56.00	25.89	0.13	10.21	QP	
13	20.92	22.24	-27.76	50.00	11.20	0.42	10.62	Average	
14	20.92	40.24	-19.76	60.00	29.20	0.42	10.62	QP	
15	23.26	23.44	-26.56	50.00	12.40	0.47	10.57	Average	
16	23.26	42.34	-17.66	60.00	31.30	0.47	10.57	QP	



Test Mode :	Mode 5	Temperature :	21~23℃
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_20160509 LINE  
Project : (FC) 6N2906  
Mode : Mode 5  
IMEI : 354147042349663/354147042399668

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	37.72	-17.97	55.69	26.99	0.14	10.59	Average
2	0.16	43.12	-22.57	65.69	32.39	0.14	10.59	QP
3	0.19	27.53	-26.40	53.93	16.91	0.11	10.51	Average
4	0.19	42.73	-21.20	63.93	32.11	0.11	10.51	QP
5	0.22	27.19	-25.69	52.88	16.60	0.11	10.48	Average
6	0.22	42.69	-20.19	62.88	32.10	0.11	10.48	QP
7	0.29	24.14	-26.49	50.63	13.60	0.11	10.43	Average
8	0.29	38.24	-22.39	60.63	27.70	0.11	10.43	QP
9	0.54	23.52	-22.48	46.00	13.20	0.11	10.21	Average
10	0.54	31.22	-24.78	56.00	20.90	0.11	10.21	QP
11	1.05	23.77	-22.23	46.00	13.50	0.11	10.16	Average
12	1.05	30.47	-25.53	56.00	20.20	0.11	10.16	QP
13 *	15.97	34.27	-15.73	50.00	23.50	0.31	10.46	Average
14	15.97	41.27	-18.73	60.00	30.50	0.31	10.46	QP



Test Mode :	Mode 5	Temperature :	21~23℃
Test Engineer :	Tao Cheng	Relative Humidity :	41~43%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		



Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_20160509 NEUTRAL  
Project : (FC)6N2906  
Mode : Mode 5  
IMEI : 354147042349663/354147042399668

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	44.33	-11.49	55.82	33.60	0.14	10.59	Average
2	0.15	48.03	-17.79	65.82	37.30	0.14	10.59	QP
3	0.20	35.82	-17.94	53.76	25.20	0.11	10.51	Average
4	0.20	42.82	-20.94	63.76	32.20	0.11	10.51	QP
5	0.27	25.55	-25.52	51.07	15.00	0.11	10.44	Average
6	0.27	37.85	-23.22	61.07	27.30	0.11	10.44	QP
7	0.50	24.63	-21.37	46.00	14.30	0.11	10.22	Average
8	0.50	39.13	-16.87	56.00	28.80	0.11	10.22	QP
9	1.08	19.87	-26.13	46.00	9.60	0.11	10.16	Average
10	1.08	38.47	-17.53	56.00	28.20	0.11	10.16	QP
11	15.97	35.47	-14.53	50.00	24.70	0.31	10.46	Average
12	15.97	42.47	-17.53	60.00	31.70	0.31	10.46	QP

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





## 3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 4	Temperature :	23~25°C
Test Engineer :	Jason Zeng	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx + SIM2		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-SZ  
Condition : FCC CLASS-B 3m LF\_ANT(23188)\_6 HORIZONTAL  
Project : 6N2906  
Mode : Mode 4  
IMEI : 354147042348061/354147042398066  
Plane : Y

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	cm	deg
			dB	dBuV/m	dBuV	dB/m	dB	dB		
1	96.42	29.52	-13.98	43.50	41.42	17.96	1.74	31.60	---	Peak
2	137.73	32.98	-10.52	43.50	44.69	17.85	1.89	31.45	200	284 Peak
3	274.08	23.14	-22.86	46.00	34.41	17.48	2.44	31.19	---	Peak
4	320.30	25.08	-20.92	46.00	34.59	19.23	2.56	31.30	---	Peak
5	655.60	29.92	-16.08	46.00	32.55	25.44	3.43	31.50	---	Peak
6	896.40	32.57	-13.43	46.00	31.74	28.38	3.95	31.50	---	Peak
7	1960.00	50.01			72.62	28.56	6.12	57.29	---	Peak
8	2688.00	43.28	-30.72	74.00	60.58	32.47	6.96	56.73	---	Peak
9	4344.00	45.41	-28.59	74.00	61.06	32.83	8.95	57.43	---	Peak
10	6582.00	49.64	-24.36	74.00	59.74	35.99	11.28	57.37	---	Peak
11	8550.00	49.12	-24.88	74.00	55.33	36.32	12.29	54.82	---	Peak
12	9912.00	50.07	-23.93	74.00	54.74	37.62	13.91	56.20	152	178 Peak
13	12812.00	50.02	-23.98	74.00	52.75	39.05	15.50	57.28	---	Peak



Test Mode :	Mode 4	Temperature :	23~25°C
Test Engineer :	Jason Zeng	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Glonass Rx + SIM2		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-SZ  
Condition : FCC CLASS-B 3m LF\_ANT(23188)\_6 VERTICAL  
Project : 6N2906  
Mode : Mode 4  
IMEI : 354147042348061/354147042398066  
Plane : Y

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor			
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.00	35.87	-4.13	40.00	39.75	26.60	1.22	31.70	150	182 Peak
2	138.81	34.91	-8.59	43.50	46.63	17.83	1.89	31.44	---	---
3	273.27	21.83	-24.17	46.00	33.14	17.44	2.44	31.19	---	---
4	428.80	26.48	-19.52	46.00	30.97	23.91	2.90	31.30	---	---
5	690.60	29.63	-16.37	46.00	31.37	26.27	3.49	31.50	---	---
6	954.50	33.04	-12.96	46.00	31.49	28.95	4.10	31.50	---	---
7	1960.00	48.36			70.97	28.56	6.12	57.29	---	---
8	2594.00	43.36	-30.64	74.00	60.91	32.30	6.85	56.70	---	---
9	4666.00	46.16	-27.84	74.00	60.60	33.20	9.33	56.97	---	---
10	6798.00	50.25	-23.75	74.00	60.59	35.94	11.44	57.72	100	154 Peak
11	7084.00	49.72	-24.28	74.00	60.42	35.76	11.60	58.06	---	---
12	9888.00	49.42	-24.58	74.00	54.13	37.64	13.86	56.21	---	---
13	11910.00	49.43	-24.57	74.00	52.58	38.77	14.58	56.50	---	---





Test Mode :	Mode 5	Temperature :	23~25°C
Test Engineer :	Jason Zeng	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-SZ  
Condition : FCC CLASS-B 3m LF\_ANT(23188)\_6 HORIZONTAL  
Project : 6N2906  
Mode : Mode 5  
IMEI : 354147042348061/354147042398066  
Plane : Y

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	99.93	29.75	-13.75	43.50	41.01	18.60	1.74	31.60	---	---	Peak
2	199.29	32.39	-11.11	43.50	46.11	15.30	2.18	31.20	182	178	Peak
3	299.73	33.56	-12.44	46.00	43.85	18.50	2.51	31.30	---	---	Peak
4	300.00	32.67	-13.33	46.00	42.96	18.50	2.51	31.30	---	---	Peak
5	686.40	30.19	-15.81	46.00	32.02	26.18	3.49	31.50	---	---	Peak
6	949.60	32.38	-13.62	46.00	30.88	28.90	4.10	31.50	---	---	Peak
7	2132.00	48.62			70.01	29.57	6.14	57.10	---	---	Peak
8	2994.00	44.96	-29.04	74.00	61.27	33.07	7.45	56.83	---	---	Peak
9	4664.00	46.28	-27.72	74.00	60.72	33.20	9.33	56.97	---	---	Peak
10	6308.00	50.04	-23.96	74.00	59.75	36.08	11.14	56.93	---	---	Peak
11	8936.00	50.08	-23.92	74.00	55.90	36.47	12.73	55.02	---	---	Peak
12	10986.00	50.63	-23.37	74.00	53.59	38.00	14.67	55.63	158	174	Peak
13	12042.00	50.59	-23.41	74.00	53.85	38.80	14.65	56.71	---	---	Peak



Test Mode :	Mode 5	Temperature :	23~25°C
Test Engineer :	Jason Zeng	Relative Humidity :	48~52%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1		
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH03-SZ  
 Condition : FCC CLASS-B 3m LF\_ANT(23188)\_6 VERTICAL  
 Project : 6N2906  
 Mode : Mode 5  
 IMEI : 354147042348061/354147042398066  
 Plane : Y

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	cm	deg	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	99.66	30.09	-13.41	43.50	41.35	18.60	1.74	31.60	---	Peak
2	179.58	26.50	-17.00	43.50	39.44	16.25	2.09	31.28	---	Peak
3	298.65	32.42	-13.58	46.00	42.74	18.46	2.51	31.29	---	Peak
4	300.00	32.62	-13.38	46.00	42.91	18.50	2.51	31.30	100	245 Peak
5	699.70	31.62	-14.38	46.00	33.10	26.48	3.54	31.50	---	Peak
6	966.40	32.76	-21.24	54.00	31.05	29.06	4.15	31.50	---	Peak
7	2132.00	48.20			69.59	29.57	6.14	57.10	---	Peak
8	2510.00	43.68	-30.32	74.00	61.53	32.13	6.70	56.68	---	Peak
9	4456.00	46.31	-27.69	74.00	61.63	33.01	9.07	57.40	---	Peak
10	6486.00	50.34	-23.66	74.00	60.33	36.01	11.23	57.23	100	285 Peak
11	7022.00	49.74	-24.26	74.00	60.33	35.87	11.59	58.05	---	Peak
12	10950.00	49.80	-24.20	74.00	52.93	37.99	14.58	55.70	---	Peak
13	12732.00	50.32	-23.68	74.00	53.26	38.99	15.45	57.38	---	Peak



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	May 07, 2016	Jan. 06, 2017	May 06, 2017	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz	May 07, 2016	Jan. 06, 2017	May 06, 2017	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 21, 2016	Jan. 06, 2017	May 20, 2017	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	May 07, 2016	Jan. 06, 2017	May 06, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 11, 2016	Jan. 06, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 11, 2016	Jan. 06, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jan. 06, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 06, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 06, 2017	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2016	Nov. 30, 2016	Jan. 05, 2017	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2016	Nov. 30, 2016	Jan. 04, 2017	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2016	Nov. 30, 2016	Jan. 04, 2017	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 16, 2016	Nov. 30, 2016	Jul. 15, 2017	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 11, 2016	Nov. 30, 2016	Oct. 10, 2017	Conduction (CO01-SZ)

NCR: No Calibration Required

## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.5dB
--	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	5.1dB
--	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	5.0dB
--	-------