

FCC Test Report

APPLICANT : Solnik S.A.
EQUIPMENT : Mobile phone
BRAND NAME : HYUNDAI
MODEL NAME : HY1-1157
FCC ID : 2AFRUHY1-1157
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product testing was completed on Mar. 08, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2009 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Prepared by: Andy Yeh / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

| | |
|--|-----------|
| REVISION HISTORY | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1. GENERAL DESCRIPTION | 5 |
| 1.1. Applicant..... | 5 |
| 1.2. Manufacturer | 5 |
| 1.3. Product Feature of Equipment Under Test | 5 |
| 1.4. Product Specification subjective to this standard..... | 6 |
| 1.5. Modification of EUT | 7 |
| 1.6. Test Location | 7 |
| 1.7. Applicable Standards | 7 |
| 2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST | 8 |
| 2.1. Test Mode | 8 |
| 2.2. Connection Diagram of Test System | 10 |
| 2.3. Support Unit used in test configuration and system..... | 11 |
| 2.4. EUT Operation Test Setup | 11 |
| 3. TEST RESULT | 12 |
| 3.1. Test of AC Conducted Emission Measurement | 12 |
| 3.2. Test of Radiated Emission Measurement | 18 |
| 4. LIST OF MEASURING EQUIPMENT | 24 |
| 5. UNCERTAINTY OF EVALUATION | 25 |
| APPENDIX A. SETUP PHOTOGRAPHS | |



REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|-------------|---------|--|---------------|
| FC5D1804-02 | Rev. 01 | This project is FCC change ID application, Solnik S.A. market their product under their own identification. Based on the similarity between two products, the test result is not affected; all test cases were leveraged on original report (Sporton Report Number FC5D1804A). | Mar. 21, 2016 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|----------|-----------------------|-----------------|--------|---|
| 3.1 | 15.107 | AC Conducted Emission | < 15.107 limits | PASS | Under limit 4.35 dB at 0.150 MHz |
| 3.2 | 15.109 | Radiated Emission | < 15.109 limits | PASS | Under limit 3.66 dB at 41.340 MHz for Quasi-Peak |

1. General Description

1.1. Applicant

Solnik S.A.

Dr. Emilio Ravignani 1724 Ciudad Autonoma de Buenos Aires Zip Code 1414 Argentina

1.2. Manufacturer

Gionee Communication Equipment Co., Ltd.

21/F, Times Technology Building, No. 7028, Shennan Avenue, Futian District, Shenzhen, China

1.3. Product Feature of Equipment Under Test

| Product Feature | |
|--|---|
| Equipment | Mobile phone |
| Brand Name | HYUNDAI |
| Model Name | HY1-1157 |
| FCC ID | 2AFRUHY1-1157 |
| EUT supports Radios application | GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE |
| IMEI Code | Conduction: 354147042005794/354147042040791 Radiation: 354147042005794/354147042040791 |
| HW Version | WBL7511BA_Mainboard_P2 |
| SW Version | Ultra Charm_0206_V6241 |
| EUT Stage | Pre-Production |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification subjective to this standard

| Product Specification subjective to this standard | |
|---|--|
| Tx Frequency | GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz |
| Rx Frequency | GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV: 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 7 : 2622.5 MHz~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz |
| Antenna Type | WWAN : Fixed Internal Antenna WLAN : Fixed Internal Antenna Bluetooth : Fixed Internal Antenna GPS : Fixed Internal Antenna |
| Type of Modulation | GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : QPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS : BPSK |

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

| | | |
|---------------------------|---|--|
| Test Site | SPORTON INTERNATIONAL (SHENZHEN) INC. | |
| Test Site Location | 1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595 | |
| Test Site No. | Sporton Site No. | |
| | CO01-SZ | |

| | | |
|---------------------------|---|-----------------------------|
| Test Site | SPORTON INTERNATIONAL (SHENZHEN) INC. | |
| Test Site Location | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398 | |
| Test Site No. | Sporton Site No. | FCC Registration No. |
| | 03CH02-SZ | 566869 |

| | | |
|---------------------------|---|-----------------------------|
| Test Site | SPORTON INTERNATIONAL (SHENZHEN) INC. | |
| Test Site Location | No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398 | |
| Test Site No. | Sporton Site No. | FCC Registration No. |
| | 03CH01-SZ | 831040 |

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2009

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.


| Item | EUT Configuration | Test Condition | | |
|------|--|----------------|-----------|-----------|
| | | EMI AC | EMI RE<1G | EMI RE≥1G |
| 1. | Charging Mode (EUT with adapter) | ☒ | ☒ | ☒ |
| 2. | Data application transferred mode (EUT connected with notebook) | ☒ | ☒ | ☒ |

Abbreviations:


- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

| Test Items | EUT Configure Mode | Function Type |
|--|--------------------|---|
| AC Conducted Emission | 1/2 | <p>Mode 1: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1<Fig.1></p> <p>Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Front) + SIM1<Fig.1></p> <p>Mode 3: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM2<Fig.1></p> <p>Mode 4: LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1<Fig.2></p> |
| Radiated Emissions < 1GHz | 1/2 | <p>Mode 1: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1<Fig.1></p> <p>Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Front) + SIM1<Fig.1></p> <p>Mode 3: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM2<Fig.1></p> <p>Mode 4: LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1<Fig.2></p> |
| Radiated Emissions \geq 1GHz | 2 | <p>Mode 1: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1<Fig.2></p> <p>Mode 2: LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1</p> |
| Remark: <ol style="list-style-type: none"> The worst case of AC is mode 1; and the USB Link mode of AC is mode 4, the test data of these modes were reported. The worst case of RE < 1G is mode 1, and the USB Link mode of RE is mode 4, the test data of these modes were reported. Data Link with Notebook means data application transferred mode between EUT and Notebook. | | |

2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>

2.3. Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model Name | FCC ID | Data Cable | Power Cord |
|------|--------------------|------------|------------|-------------|-----------------|--|
| 1. | System Simulator | R&S | CMU 200 | N/A | N/A | Unshielded, 1.8 m |
| 2. | LTE Base Station | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 3. | GPS Station | ADIVIC | MP9000 | N/A | N/A | Unshielded, 1.8 m |
| 4. | WLAN AP | D-Link | DIR-628 | KA2DIR628A2 | N/A | Unshielded, 1.8 m |
| 5. | WLAN AP | ASUSTek | RT-AC66U | MSQ-RTAC66U | N/A | Unshielded, 2.7 m with Core |
| 6. | Notebook | Lenovo | E540 | FCC DoC | N/A | AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m |
| 7. | Bluetooth Earphone | Nokia | BH-108 | PYAHS-107W | N/A | N/A |
| 8. | Bluetooth Earphone | Samsung | HS3000 | A3LHS3000 | N/A | N/A |
| 9. | iPod nano 8GB | Apple | MC690ZP/A | FCC DoC | Shielded, 1.2 m | N/A |
| 10. | iPod | Apple | MC525 ZP/A | FCC DoC | Shielded, 1.0 m | N/A |
| 11. | SD Card | SanDisk | 4G class 4 | FCC DoC | N/A | N/A |

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GPS function to make the EUT receive continuous signals from GPS station.
3. Execute "Video Player" to play MPEG4 files.
4. Turn on camera to capture images.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dBuV) | |
|--------------------------------|------------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

| | | | |
|------------------------|---|----------------------------|--------|
| Test Mode : | Mode 1 | Temperature : | 21~23℃ |
| Test Engineer : | Jacky Yang | Relative Humidity : | 41~43% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Line |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1 | | |




Site : C001-SZ
 Condition: FCC 15B_QP LISN_L_20160112 LINE
 Project : (FC)5D1804-02
 Mode : Mode 1
 IMEI : 354147042005794/354147042040791

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.15 | 39.69 | -16.22 | 55.91 | 28.90 | 0.43 | 10.36 | Average |
| 2 * | 0.15 | 52.59 | -13.32 | 65.91 | 41.80 | 0.43 | 10.36 | QP |
| 3 | 0.23 | 34.50 | -18.02 | 52.52 | 23.70 | 0.54 | 10.26 | Average |
| 4 | 0.23 | 48.00 | -14.52 | 62.52 | 37.20 | 0.54 | 10.26 | QP |
| 5 | 0.37 | 27.93 | -20.50 | 48.43 | 17.20 | 0.55 | 10.18 | Average |
| 6 | 0.37 | 41.13 | -17.30 | 58.43 | 30.40 | 0.55 | 10.18 | QP |
| 7 | 0.45 | 28.07 | -18.73 | 46.80 | 17.30 | 0.61 | 10.16 | Average |
| 8 | 0.45 | 40.97 | -15.83 | 56.80 | 30.20 | 0.61 | 10.16 | QP |
| 9 | 0.53 | 30.60 | -15.40 | 46.00 | 19.81 | 0.64 | 10.15 | Average |
| 10 | 0.53 | 42.40 | -13.60 | 56.00 | 31.61 | 0.64 | 10.15 | QP |
| 11 | 0.68 | 27.80 | -18.20 | 46.00 | 17.10 | 0.55 | 10.15 | Average |
| 12 | 0.68 | 39.70 | -16.30 | 56.00 | 29.00 | 0.55 | 10.15 | QP |



| | | | |
|-----------------|---|---------------------|---------|
| Test Mode : | Mode 1 | Temperature : | 21~23℃ |
| Test Engineer : | Jacky Yang | Relative Humidity : | 41~43% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Neutral |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1 | | |




Site : CO01-SZ
Condition: FCC 15B_QP LISN_N_20160112 NEUTRAL
Project : (FC)5D1804-02
Mode : Mode 1
IMEI : 354147042005794/354147042040791

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.15 | 47.51 | -8.45 | 55.96 | 36.70 | 0.45 | 10.36 | Average |
| 2 * | 0.15 | 61.61 | -4.35 | 65.96 | 50.80 | 0.45 | 10.36 | QP |
| 3 | 0.23 | 41.00 | -11.52 | 52.52 | 30.20 | 0.54 | 10.26 | Average |
| 4 | 0.23 | 55.20 | -7.32 | 62.52 | 44.40 | 0.54 | 10.26 | QP |
| 5 | 0.30 | 35.89 | -14.35 | 50.24 | 25.10 | 0.59 | 10.20 | Average |
| 6 | 0.30 | 51.29 | -8.95 | 60.24 | 40.50 | 0.59 | 10.20 | QP |
| 7 | 0.38 | 31.23 | -17.02 | 48.25 | 20.49 | 0.56 | 10.18 | Average |
| 8 | 0.38 | 44.63 | -13.62 | 58.25 | 33.89 | 0.56 | 10.18 | QP |
| 9 | 0.45 | 28.14 | -18.66 | 46.80 | 17.40 | 0.58 | 10.16 | Average |
| 10 | 0.45 | 43.04 | -13.76 | 56.80 | 32.30 | 0.58 | 10.16 | QP |
| 11 | 0.55 | 26.85 | -19.15 | 46.00 | 16.11 | 0.59 | 10.15 | Average |
| 12 | 0.55 | 42.45 | -13.55 | 56.00 | 31.71 | 0.59 | 10.15 | QP |



| | | | |
|-----------------|---|---------------------|--------|
| Test Mode : | Mode 4 | Temperature : | 21~23℃ |
| Test Engineer : | Jacky Yang | Relative Humidity : | 41~43% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Line |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 | | |




Site : C001-SZ
Condition: FCC 15B_QP LISN_L_20150304 LINE

Mode : Mode 4
IMEI : 354147042004169/354147042039165

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|-----|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.16 | 35.99 | -19.57 | 55.56 | 25.19 | 0.45 | 10.35 | Average |
| 2 | 0.16 | 42.69 | -22.87 | 65.56 | 31.89 | 0.45 | 10.35 | QP |
| 3 | 0.23 | 32.80 | -19.55 | 52.35 | 22.00 | 0.54 | 10.26 | Average |
| 4 | 0.23 | 44.80 | -17.55 | 62.35 | 34.00 | 0.54 | 10.26 | QP |
| 5 | 0.27 | 32.48 | -18.77 | 51.25 | 21.69 | 0.56 | 10.23 | Average |
| 6 * | 0.27 | 44.58 | -16.67 | 61.25 | 33.79 | 0.56 | 10.23 | QP |
| 7 | 0.39 | 20.72 | -27.45 | 48.17 | 10.00 | 0.54 | 10.18 | Average |
| 8 | 0.39 | 36.92 | -21.25 | 58.17 | 26.20 | 0.54 | 10.18 | QP |
| 9 | 0.57 | 21.97 | -24.03 | 46.00 | 11.20 | 0.62 | 10.15 | Average |
| 10 | 0.57 | 37.37 | -18.63 | 56.00 | 26.60 | 0.62 | 10.15 | QP |
| 11 | 0.65 | 19.82 | -26.18 | 46.00 | 9.10 | 0.57 | 10.15 | Average |
| 12 | 0.65 | 34.82 | -21.18 | 56.00 | 24.10 | 0.57 | 10.15 | QP |



| | | | |
|-----------------|---|---------------------|---------|
| Test Mode : | Mode 4 | Temperature : | 21~23°C |
| Test Engineer : | Jacky Yang | Relative Humidity : | 41~43% |
| Test Voltage : | 120Vac / 60Hz | Phase : | Neutral |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 | | |



Site : CO01-SZ
Condition: FCC 15B_QP LISN_N_20150304 NEUTRAL

Mode : Mode 4
IMEI : 354147042004169/354147042039165

| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|------|------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.19 | 34.91 | -19.29 | 54.20 | 24.10 | 0.50 | 10.31 | Average |
| 2 | 0.19 | 40.01 | -24.19 | 64.20 | 29.20 | 0.50 | 10.31 | QP |
| 3 | 0.26 | 25.89 | -25.49 | 51.38 | 15.10 | 0.56 | 10.23 | Average |
| 4 | 0.26 | 40.19 | -21.19 | 61.38 | 29.40 | 0.56 | 10.23 | QP |
| 5 | 0.35 | 26.45 | -22.42 | 48.87 | 15.70 | 0.57 | 10.18 | Average |
| 6 | 0.35 | 38.35 | -20.52 | 58.87 | 27.60 | 0.57 | 10.18 | QP |
| 7 | 0.41 | 21.13 | -26.51 | 47.64 | 10.40 | 0.56 | 10.17 | Average |
| 8 | 0.41 | 36.23 | -21.41 | 57.64 | 25.50 | 0.56 | 10.17 | QP |
| 9 | 0.59 | 26.23 | -19.77 | 46.00 | 15.50 | 0.58 | 10.15 | Average |
| 10 * | 0.59 | 39.63 | -16.37 | 56.00 | 28.90 | 0.58 | 10.15 | QP |
| 11 | 0.69 | 23.40 | -22.60 | 46.00 | 12.70 | 0.55 | 10.15 | Average |
| 12 | 0.69 | 37.60 | -18.40 | 56.00 | 26.90 | 0.55 | 10.15 | QP |

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|----------------------------|--|--|
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

| | | | |
|-----------------|---|---------------------|------------|
| Test Mode : | Mode 1 | Temperature : | 23~25°C |
| Test Engineer : | Jeff Yao | Relative Humidity : | 48~52% |
| Test Distance : | 3m | Polarization : | Horizontal |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1 | | |
| Remark : | #7 is system simulator signal which can be ignored. | | |




Site : 03CH01-SZ
Condition : FCC CLASS-B 3m LF35407CBL6112D_6DB HORIZONTAL
Project : (FC) 5D1804-02
Mode : Mode 1
IMEI : 354147042005794/354147042040791
Plane : X

| | Freq | Level | Over | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark |
|----|----------|--------|--------|--------|-------------|-------|--------|-------|-------|--------|
| | MHz | dBuV/m | Limit | Line | Level | Loss | Factor | cm | deg | |
| | | | dB | dBuV/m | dBuV | dB/m | dB | dB | | |
| 1 | 30.27 | 26.74 | -13.26 | 40.00 | 28.26 | 23.80 | 0.75 | 26.07 | --- | Peak |
| 2 | 160.14 | 27.29 | -16.21 | 43.50 | 34.37 | 17.18 | 1.20 | 25.46 | --- | Peak |
| 3 | 200.37 | 27.50 | -16.00 | 43.50 | 34.92 | 16.33 | 1.50 | 25.25 | --- | Peak |
| 4 | 573.00 | 29.67 | -16.33 | 46.00 | 29.30 | 24.26 | 2.52 | 26.41 | --- | Peak |
| 5 | 719.30 | 32.75 | -13.25 | 46.00 | 30.59 | 25.84 | 2.65 | 26.33 | --- | Peak |
| 6 | 927.20 | 33.95 | -12.05 | 46.00 | 28.96 | 27.57 | 3.08 | 25.66 | 100 | 0 Peak |
| 7 | 1960.00 | 49.00 | | | 71.31 | 31.74 | 4.59 | 58.64 | --- | Peak |
| 8 | 2454.00 | 42.36 | -31.64 | 74.00 | 63.27 | 32.67 | 5.16 | 58.74 | --- | Peak |
| 9 | 4938.00 | 44.47 | -29.53 | 74.00 | 60.85 | 34.47 | 7.56 | 58.41 | --- | Peak |
| 10 | 5652.00 | 44.00 | -30.00 | 74.00 | 59.55 | 35.32 | 8.15 | 59.02 | --- | Peak |
| 11 | 8034.00 | 45.01 | -28.99 | 74.00 | 55.27 | 36.48 | 11.09 | 57.83 | --- | Peak |
| 12 | 10366.00 | 45.27 | -28.73 | 74.00 | 53.65 | 38.39 | 12.23 | 59.00 | --- | Peak |
| 13 | 11710.00 | 45.73 | -28.27 | 74.00 | 53.77 | 39.32 | 12.61 | 59.97 | 100 | 0 Peak |



| | | | |
|-----------------|---|---------------------|----------|
| Test Mode : | Mode 1 | Temperature : | 23~25°C |
| Test Engineer : | Jeff Yao | Relative Humidity : | 48~52% |
| Test Distance : | 3m | Polarization : | Vertical |
| Function Type : | WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera (Back) + SIM1 | | |
| Remark : | #7 is system simulator signal which can be ignored. | | |




Site : 03CH01-SZ
 Condition : FCC CLASS-B 3m LF35407CBL6112D_6DB VERTICAL
 Project : (FC) 5D1804-02
 Mode : Mode 1
 IMEI : 354147042005794/354147042040791
 Plane : X

| | Freq | Level | Over | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark |
|----|----------|--------|--------|-------|-------------|--------|--------|--------|-------|--------|
| | MHz | dBuV/m | Limit | Line | Level | Factor | Loss | Factor | cm | deg |
| 1 | 41.34 | 36.34 | -3.66 | 40.00 | 43.70 | 17.89 | 0.75 | 26.00 | 100 | 14 QP |
| 2 | 101.55 | 25.84 | -17.66 | 43.50 | 32.01 | 18.46 | 1.14 | 25.77 | --- | --- |
| 3 | 203.34 | 27.56 | -15.94 | 43.50 | 34.86 | 16.44 | 1.50 | 25.24 | --- | --- |
| 4 | 691.30 | 31.62 | -14.38 | 46.00 | 29.75 | 25.60 | 2.65 | 26.38 | --- | --- |
| 5 | 771.80 | 33.22 | -12.78 | 46.00 | 30.37 | 26.20 | 2.88 | 26.23 | --- | --- |
| 6 | 943.30 | 34.31 | -11.69 | 46.00 | 28.96 | 27.74 | 3.15 | 25.54 | --- | --- |
| 7 | 1960.00 | 49.81 | | | 72.12 | 31.74 | 4.59 | 58.64 | --- | --- |
| 8 | 2462.00 | 42.79 | -31.21 | 74.00 | 63.70 | 32.67 | 5.16 | 58.74 | --- | --- |
| 9 | 4970.00 | 44.93 | -29.07 | 74.00 | 61.03 | 34.49 | 7.59 | 58.18 | --- | --- |
| 10 | 6994.00 | 43.76 | -30.24 | 74.00 | 55.38 | 36.10 | 9.30 | 57.02 | --- | --- |
| 11 | 8094.00 | 44.44 | -29.56 | 74.00 | 54.69 | 36.45 | 11.08 | 57.78 | --- | --- |
| 12 | 10966.00 | 45.15 | -28.85 | 74.00 | 53.32 | 38.78 | 12.57 | 59.52 | --- | --- |
| 13 | 11698.00 | 45.76 | -28.24 | 74.00 | 53.79 | 39.31 | 12.61 | 59.95 | 100 | 0 Peak |



| | | | |
|-----------------|---|---------------------|------------|
| Test Mode : | Mode 4 | Temperature : | 23~25°C |
| Test Engineer : | Jeff Yao | Relative Humidity : | 48~52% |
| Test Distance : | 3m | Polarization : | Horizontal |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 | | |
| Remark : | #8 is system simulator signal which can be ignored. | | |




Site : 03CH02-SZ
Condition : FCC CLASS-B 3m LF_ANT(23188)_151017 HORIZONTAL

Mode : Mode 4
IMEI : 354147042005794/354147042040791

| | Freq | Level | Over Limit | Limit Line | ReadAntenna Level | Cable Preamp A/Pos T/Pos | Loss Factor | Factor | Pos | Pos | Remark |
|----|----------|--------|------------|------------|-------------------|--------------------------|-------------|--------|-----|-----|--------|
| | MHz | dBuV/m | dB | dBuV/m | dBuV | dB/m | dB | dB | cm | deg | |
| 1 | 85.08 | 33.40 | -6.60 | 40.00 | 47.85 | 10.35 | 1.04 | 25.84 | --- | --- | Peak |
| 2 | 167.16 | 37.49 | -6.01 | 43.50 | 49.56 | 11.97 | 1.38 | 25.42 | --- | --- | Peak |
| 3 | 240.60 | 40.30 | -5.70 | 46.00 | 51.64 | 12.25 | 1.57 | 25.16 | 100 | 125 | QP |
| 4 | 300.00 | 37.28 | -8.72 | 46.00 | 46.51 | 14.10 | 1.71 | 25.04 | --- | --- | Peak |
| 5 | 399.40 | 31.99 | -14.01 | 46.00 | 40.37 | 15.40 | 2.03 | 25.81 | --- | --- | Peak |
| 6 | 722.10 | 39.22 | -6.78 | 46.00 | 42.05 | 20.79 | 2.71 | 26.33 | --- | --- | Peak |
| 7 | 2268.00 | 42.30 | -31.70 | 74.00 | 63.46 | 32.48 | 4.95 | 58.59 | --- | --- | Peak |
| 8 | 2656.00 | 50.87 | | | 71.56 | 32.82 | 5.43 | 58.94 | --- | --- | Peak |
| 9 | 4624.00 | 44.98 | -29.02 | 74.00 | 62.85 | 34.27 | 7.29 | 59.43 | --- | --- | Peak |
| 10 | 5140.00 | 44.26 | -29.74 | 74.00 | 59.58 | 34.68 | 7.72 | 57.72 | --- | --- | Peak |
| 11 | 8892.00 | 45.48 | -28.52 | 74.00 | 55.98 | 36.66 | 10.84 | 58.00 | --- | --- | Peak |
| 12 | 10310.00 | 45.52 | -28.48 | 74.00 | 53.98 | 38.35 | 12.18 | 58.99 | --- | --- | Peak |
| 13 | 11266.00 | 46.28 | -27.72 | 74.00 | 54.36 | 39.01 | 12.58 | 59.67 | 100 | 0 | Peak |



| | | | |
|-----------------|---|---------------------|----------|
| Test Mode : | Mode 4 | Temperature : | 23~25°C |
| Test Engineer : | Jeff Yao | Relative Humidity : | 48~52% |
| Test Distance : | 3m | Polarization : | Vertical |
| Function Type : | LTE Band 7 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx + SIM1 | | |
| Remark : | #8 is system simulator signal which can be ignored. | | |



Site : 03CH02-SZ
Condition : FCC CLASS-B 3m LF_ANT(23188)_151017 VERTICAL

Mode : Mode 4
IMEI : 354147042005794/354147042040791

| | Freq | Level | Over | Limit | ReadAntenna | Cable | Preamp | A/Pos | T/Pos | Remark |
|----|----------|--------|--------|--------|-------------|-------|--------|-------|-------|----------|
| | MHz | dBuV/m | Limit | Line | Level | Loss | Factor | cm | deg | |
| | | | dB | dBuV/m | dBuV | dB/m | dB | dB | | |
| 1 | 42.96 | 32.05 | -7.95 | 40.00 | 43.10 | 14.25 | 0.70 | 26.00 | --- | Peak |
| 2 | 168.24 | 36.39 | -7.11 | 43.50 | 48.52 | 11.90 | 1.38 | 25.41 | --- | Peak |
| 3 | 257.88 | 39.67 | -6.33 | 46.00 | 50.49 | 12.67 | 1.64 | 25.13 | 150 | 200 Peak |
| 4 | 300.00 | 34.90 | -11.10 | 46.00 | 44.13 | 14.10 | 1.71 | 25.04 | --- | Peak |
| 5 | 499.50 | 30.49 | -15.51 | 46.00 | 35.29 | 19.36 | 2.17 | 26.33 | --- | Peak |
| 6 | 715.10 | 35.39 | -10.61 | 46.00 | 38.40 | 20.62 | 2.71 | 26.34 | --- | Peak |
| 7 | 2510.00 | 42.51 | -31.49 | 74.00 | 63.36 | 32.71 | 5.25 | 58.81 | --- | Peak |
| 8 | 2656.00 | 50.26 | | | 70.95 | 32.82 | 5.43 | 58.94 | --- | Peak |
| 9 | 4554.00 | 44.51 | -29.49 | 74.00 | 62.70 | 34.23 | 7.25 | 59.67 | --- | Peak |
| 10 | 6850.00 | 44.13 | -29.87 | 74.00 | 56.79 | 36.16 | 9.14 | 57.96 | --- | Peak |
| 11 | 8488.00 | 44.65 | -29.35 | 74.00 | 54.76 | 36.21 | 11.06 | 57.38 | --- | Peak |
| 12 | 10366.00 | 45.03 | -28.97 | 74.00 | 53.43 | 38.39 | 12.21 | 59.00 | 100 | 0 Peak |
| 13 | 11190.00 | 44.90 | -29.10 | 74.00 | 53.00 | 38.95 | 12.58 | 59.63 | --- | Peak |



4. List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|-----------------------------------|----------------------|---------------------------|--------------|------------------------|-------------------------------|---------------------------------|--------------------------------|-----------------------|
| EMI Test Receiver | R&S | ESR7 | 101404 | 9kHz~7GHz;Max 30dBm | Oct. 20, 2015 | Dec. 28, 2015~ Dec. 29, 2015 | Oct. 19, 2016 | Radiation (03CH02-SZ) |
| Spectrum Analyzer | R&S | FSV40 | 101041 | 10kHz~40GHz; Max 30dBm | Oct. 20, 2015 | Dec. 28, 2015~ Dec. 29, 2015 | Oct. 19, 2016 | Radiation (03CH02-SZ) |
| Bilog Antenna | TeseQ | CBL6112D | 35407 | 30MHz~2GHz | May 06, 2015 | Dec. 28, 2015~ Dec. 29, 2015 | May 05, 2016 | Radiation (03CH02-SZ) |
| Double Ridge Horn Antenna | SCHWARZBECK | BBHA 9120D | 9120D-1285 | 1GHz~18GHz | Jan. 20, 2015 | Dec. 28, 2015~ Dec. 29, 2015 | Jan. 19, 2016 | Radiation (03CH02-SZ) |
| Amplifier | ADVANTEST | BB525C | E9007003 | 9kHz~3000MHz / 30 dB | Jan. 28, 2015 | Dec. 28, 2015~ Dec. 29, 2015 | Jan. 27, 2016 | Radiation (03CH02-SZ) |
| Amplifier | Agilent | 8449B | 3008A01023 | 1GHz~26.5GHz | Oct. 20, 2015 | Dec. 28, 2015~ Dec. 29, 2015 | Oct. 19, 2016 | Radiation (03CH02-SZ) |
| AC Power Source | Chroma | 61601 | 616010002470 | N/A | NCR | Dec. 28, 2015~ Dec. 29, 2015 | NCR | Radiation (03CH02-SZ) |
| Turn Table | Chaintek | T-200 | N/A | 0~360 degree | NCR | Dec. 28, 2015~ Dec. 29, 2015 | NCR | Radiation (03CH02-SZ) |
| Antenna Mast | Chaintek | MBS-400 | N/A | 1 m~4 m | NCR | Dec. 28, 2015~ Dec. 29, 2015 | NCR | Radiation (03CH02-SZ) |
| EMI Test Receiver&SA | Agilent Technologies | N9038A | MY52260185 | 20Hz~26.5GHz | May 26, 2015 | Mar. 08, 2016 | May 25, 2016 | Radiation (03CH01-SZ) |
| Spectrum Analyzer | KEYSIGHT | N9010A | MY55150213 | 10Hz~44GHz;Max 30dBm | Jun. 07, 2015 | Mar. 08, 2016 | Jun. 06, 2016 | Radiation (03CH01-SZ) |
| Bilog Antenna | TeseQ | CBL6112D | 23188 | 30MHz~2GHz | Oct. 17, 2015 | Mar. 08, 2016 | Oct. 16, 2016 | Radiation (03CH01-SZ) |
| Double Ridge Horn Antenna | ETS Lindgren | 3117 | 00119436 | 1GHz~18GHz | Oct. 17, 2015 | Mar. 08, 2016 | Oct. 16, 2016 | Radiation (03CH01-SZ) |
| Amplifier | HP | 8447F | 3113A04622 | 9kHz ~1300MHz / 30 dB | Aug. 07, 2015 | Mar. 08, 2016 | Aug. 06, 2016 | Radiation (03CH01-SZ) |
| Amplifier | Yiai | AV3860B | 04030 | 2GHz~26.5GHz | May 05, 2015 | Mar. 08, 2016 | May 04, 2016 | Radiation (03CH01-SZ) |
| HF Amplifier | MITEQ | TTA1840-35-HG | 1871923 | 18GHz~40GHz | Jul. 18, 2015 | Mar. 08, 2016 | Jul. 17, 2016 | Radiation (03CH01-SZ) |
| AC Power Source | Chroma | 61601 | 616010001985 | N/A | NCR | Mar. 08, 2016 | NCR | Radiation (03CH01-SZ) |
| Turn Table | EM | EM1000 | N/A | 0~360 degree | NCR | Mar. 08, 2016 | NCR | Radiation (03CH01-SZ) |
| Antenna Mast | EM | EM1000 | N/A | 1 m~4 m | NCR | Mar. 08, 2016 | NCR | Radiation (03CH01-SZ) |
| EMI Receiver | R&S | ESCI7 | 100724 | 9kHz~3GHz; | Nov 23, 2015 | Dec. 22, 2015~ Feb. 26, 2016 | Nov 22, 2016 | Conduction (CO01-SZ) |
| AC LISN | EMCO | 3816/2SH | 103892 | 9kHz~30MHz | Feb. 02, 2015 Jan.12, 2016 | Dec. 22, 2015~ Feb. 26, 2016 | Feb. 01, 2016 Jan. 11, 2017 | Conduction (CO01-SZ) |
| AC LISN (for auxiliary equipment) | MessTec | AN3016 | 16850 | 9kHz~30MHz | Feb. 02, 2015 | Dec. 22, 2015 | Feb. 01, 2016 | Conduction (CO01-SZ) |
| AC LISN (for auxiliary equipment) | MessTec | 3816/2SH | 00103912 | 9kHz~30MHz | Jan.12, 2016 | Feb. 26, 2016 | Jan. 11, 2017 | Conduction (CO01-SZ) |
| AC Power Source | Chroma | 61602 | 616020000891 | 100Vac~250Vac | Aug. 07, 2015 | Dec. 22, 2015~ Feb. 26, 2016 | Aug. 06, 2016 | Conduction (CO01-SZ) |
| Pulse Limiter | COM-POWER | LIT-153 Transient Limiter | 53139 | 150kHz~30MHz | Oct. 20, 2015 | Dec. 22, 2015~ Feb. 26, 2016 | Oct. 19, 2016 | Conduction (CO01-SZ) |

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 2.3dB |
|---|-------|

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) (03CH02-SZ)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 5.0dB |
|---|-------|

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) (03CH01-SZ)

| | |
|---|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 4.8dB |
|---|-------|