



FCC PART 15.247 TEST REPORT

For

Dongguan Jin wen hua digital technology Co., LTD.

NO.1 Hua Da Road, Long Bei Ling Village, Tangxia Town, Dongguan City, Guangdong, China

FCC ID: 2AFSGS1

Report Type: **Product Type:** Original Report POPCHOSE SURROUND SOUNDBAR **Report Number:** RSZ180912801-00A **Report Date:** 2018-09-26 Rocky Kang Rocky Kang RF Engineer Reviewed By: Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*".

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTYTEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL I/O CABLEBLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	9
FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	11
APPLICABLE STANDARD	11
Result	11
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	
APPLICABLE STANDARD	
TEST PROCEDURE	20

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH	33
APPLICABLE STANDARD	33
TEST PROCEDURE	
Test Data	
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	39
APPLICABLE STANDARD	39
TEST PROCEDURE	
Test Data	
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	42
APPLICABLE STANDARD	42
Test Procedure	
Test Data	
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	58
APPLICABLE STANDARD	58
TEST PROCEDURE	
Test Data	58
FCC §15.247(d) - BAND EDGES TESTING	59
APPLICABLE STANDARD	59
Test Procedure	
Test Data	50

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Dongguan Jin wen hua digital technology Co., LTD.* 's product, model number: *POPCHOSE-S1* (FCC ID: 2AFSGS1) or the "EUT" in this report was a *POPCHOSE SURROUND SOUNDBAR*, which was measured approximately: 81 cm (L) * 6.6 cm (W) * 6.2 cm (H), rated with input voltage: DC 14V from adapter.

Report No.: RSZ180912801-00A

Adapter Information:

Model: BX18W-1401200G Input: AC 100-240V, 50/60Hz

Output: DC 14V, 1.2A

Objective

This test report is prepared on behalf of *Dongguan Jin wen hua digital technology Co., LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 65

^{*}All measurement and test data in this report was gathered from production sample serial number: 180912801 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-09-12.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Cha	nnel Bandwidth	±5%
RF Output Power	with Power meter	±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions,	Below 1GHz	±4.75dB
Radiated	Above 1GHz	±4.88dB
Temperature		±3℃
Humidity		±6%
Supply	voltages	±0.4%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15.247 Page 5 of 65

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

"Blue Test3" software was used. And the power level is 255.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
BULL	Socket	GN-415K	5503290068073
Jin wen hua	REMOTE CONTROL	POPCHOSE-S1	180912801
Comtrade Distribution	4G Smart Phone	Aeon6750-65-n	17PLPGF00AB0

Report No.: RSZ180912801-00A


External I/O Cable

Cable Description	Length (m)	From Port	То
Un-shielding Detachable DC Cable	1.25	EUT	Adapter
Un-shielding Un-detachable AC Cable	1.0	LISN	Socket

FCC Part 15.247 Page 6 of 65

Block Diagram of Test Setup

For conducted emission:



FCC Part 15.247 Page 7 of 65

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

Report No.: RSZ180912801-00A

FCC Part 15.247 Page 8 of 65

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	Condu	cted Emissions	Test		
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2017-12-21	2018-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-05-21	2018-11-19
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
/	Conducted Emission Cable	N/A	UF A210B-1- 0720-504504	2018-05-12	2018-11-12
	Radia	ated Emission T	est		
A.H.System	Horn Antenna	SAS-200/571	135	2018-08-18	2021-08-17
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
COM-POWER	Pre-amplifier	PA-122	181919	2018-08-01	2019-02-01
Sonoma Instrument	Amplifier	310N	186238	2018-05-12	2018-11-12
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
Ducommun technologies	RF Cable	UFA147A- 2362-100100	MFR64639 231029-003	2018-08-01	2019-02-01
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-21
Ducommun technologies	RF Cable	RG-214	1	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-05-22	2018-11-22
Ducommun Technologies	Horn Antenna	ARH-4223- 02	1007726-04	2017-12-29	2020-12-28
Heatsink Required	Amplifier	QLW- 18405536-J0	15964001002	2018-08-01	2019-02-01
Sinoscite	Notch Filter	BSF2402- 2480MN- 0898-001	N/A	2018-05-21	2018-11-21
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

FCC Part 15.247 Page 9 of 65

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
	RF	Conducted Tes	t		
Agilent	P-Series Power Meter	N1912A	MY5000448	2018-01-02	2019-01-02
Agilent	Wideband Power Sensor	N1921A	MY54210016	2018-01-02	2019-01-02
WEINSCHEL	3dB Attenuator	N/A	N/A	Each Time	
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26		2017-12-24	2018-12-24
Ducommun technologies	RF Cable	RG-214	3	Each	Time

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 10 of 65

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

	Limits for General Population/Uncontrolled Exposure					
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)		
0.3-1.34	614	1.63	*(100)	30		
1.34-30	824/f	2.19/f	$*(180/f^2)$	30		
30-300	27.5	0.073	0.2	30		
300-1500	/	/	f/1500	30		
1500-100,000	/	/	1.0	30		

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency	Antenna Gain		Turn up conducted power		Evaluation Distance	Power Density	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
2402-2480	0	1	-2.0	0.63	20	0.0001	1

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC Part 15.247 Page 11 of 65

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RSZ180912801-00A

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC Part 15.247 Page 12 of 65

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.247 Page 13 of 65

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Report No.: RSZ180912801-00A

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-09-21.

EUT operation mode: Transmitting (the worst case is GFSK Mode, Middle channel)

FCC Part 15.247 Page 14 of 65


AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.173500	48.7	19.8	64.8	16.1	QP
0.209500	52.2	19.7	63.2	11.0	QP
0.225500	51.6	19.7	62.6	11.0	QP
0.229500	51.3	19.7	62.5	11.2	QP
0.257500	47.6	19.7	61.5	13.9	QP
0.289500	45.0	19.8	60.5	15.5	QP
0.173500	43.7	19.8	54.8	11.1	Ave.
0.209500	47.1	19.7	53.2	6.1	Ave.
0.225500	46.2	19.7	52.6	6.4	Ave.
0.229500	45.0	19.7	52.5	7.5	Ave.
0.257500	39.9	19.7	51.5	11.6	Ave.
0.289500	39.2	19.8	50.5	11.3	Ave.

FCC Part 15.247 Page 15 of 65

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.209500	52.3	19.7	63.2	10.9	QP
0.213500	51.7	19.7	63.1	11.4	QP
0.241500	48.7	19.7	62.0	13.3	QP
0.253500	48.2	19.7	61.6	13.4	QP
0.293500	43.5	19.8	60.4	16.9	QP
0.321110	42.6	19.7	59.7	17.1	QP
0.209500	47.2	19.7	53.2	6.0	Ave.
0.213500	46.4	19.7	53.1	6.7	Ave.
0.241500	41.7	19.7	52.0	10.3	Ave.
0.253500	40.1	19.7	51.6	11.5	Ave.
0.293500	38.0	19.8	50.4	12.4	Ave.
0.321110	36.5	19.7	49.7	13.2	Ave.

Note:

- 1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
 3) Margin = Limit Corrected Amplitude

FCC Part 15.247 Page 16 of 65

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

FCC Part 15.247 Page 17 of 65

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 CHa	1 MHz	3 MHz	/	PK
Above 1 GHz	1 MHz	10 Hz	/	Average

Report No.: RSZ180912801-00A

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.</u>

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \le L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

FCC Part 15.247 Page 18 of 65

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa


The testing was performed by Kiki Kong on 2018-09-21.

EUT operation mode: Transmitting (Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK mode, the worst case is GFSK Mode)

Report No.: RSZ180912801-00A

FCC Part 15.247 Page 19 of 65

30 MHz~1 GHz: (the worst case is GFSK Mode, Middle channel)



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
50.143250	22.72	170.0	V	103.0	-19.6	40.00	17.28
50.975125	23.38	147.0	V	99.0	-19.7	40.00	16.62
86.000375	26.08	188.0	Н	337.0	-19.4	40.00	13.92
86.831625	29.21	203.0	Н	0.0	-19.3	40.00	10.79
370.533000	32.85	108.0	Н	50.0	-10.6	46.00	13.15
955.407625	31.31	245.0	V	198.0	9.5	46.00	14.69

FCC Part 15.247 Page 20 of 65

1 GHz - 25 GHz:

	Receive		T 4 11	Rx An	tenna	Corrected	Corrected	T,	M :
Frequency (MHz)	Reading (dBµV)	PK/QP/Ave.	Turntable Degree	Height (m)		Factor (dB/m)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			Low Ch	annel (2	402 MI	Hz)			
2402.00	62.54	PK	2	1.0	Н	33.00	95.54	/	/
2402.00	51.16	Ave.	2	1.0	Н	33.00	84.16	/	/
2402.00	58.57	PK	84	2.4	V	33.00	91.57	/	/
2402.00	47.82	Ave.	84	2.4	V	33.00	80.82	/	/
2322.83	27.42	PK	319	1.0	Н	32.97	60.39	74	13.61
2322.83	13.92	Ave.	319	1.0	Н	32.97	46.89	54	7.11
2484.53	27.64	PK	24	2.0	Н	33.20	60.84	74	13.16
2484.53	13.34	Ave.	24	2.0	Н	33.20	46.54	54	7.46
4804.00	44.77	PK	245	1.2	Н	7.88	52.65	74	21.35
4804.00	33.01	Ave.	245	1.2	Н	7.88	40.89	54	13.11
			Middle C	hannel ((2441 M	ſHz)			
2441.00	64.03	PK	163	2.3	Н	33.10	97.13	/	/
2441.00	52.88	Ave.	163	2.3	Н	33.10	85.98	/	/
2441.00	59.23	PK	349	1.8	V	33.10	92.33	/	/
2441.00	48.78	Ave.	349	1.8	V	33.10	81.88	/	/
4882.00	45.45	PK	35	2.1	Н	9.21	54.66	74	19.34
4882.00	36.38	Ave.	35	2.1	Н	9.21	45.59	54	8.41
			High Ch	nannel (2	2480 M	Hz)			
2480.00	63.92	PK	332	1.9	Н	33.20	97.12	/	/
2480.00	51.82	Ave.	332	1.9	Н	33.20	85.02	/	/
2480.00	59.36	PK	312	1.9	V	33.20	92.56	/	/
2480.00	48.93	Ave.	312	1.9	V	33.20	82.13	/	/
2336.77	28.14	PK	10	2.3	Н	32.97	61.11	74	12.89
2336.77	13.87	Ave.	10	2.3	Н	32.97	46.84	54	7.16
2483.50	31.05	PK	331	2.2	Н	33.20	64.25	74	9.75
2483.50	17.80	Ave.	289	1.1	Н	33.20	51.00	54	3.00
4960.00	45.24	PK	226	1.0	Н	9.07	54.31	74	19.69
4960.00	35.22	Ave.	226	1.0	Н	9.07	44.29	54	9.71


Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded. And for the pre-scan is performed with the 2400-2483.5MHz band filter.

FCC Part 15.247 Page 21 of 65

Pre-scan with Middle channel Peak Horizontal




21.SEP.2018 7:54:10 Date:




FCC Part 15.247 Page 22 of 65

Vertical




Date: 21.SEP.2018 7:58:37




FCC Part 15.247 Page 23 of 65

Pre-scan for Average Horizontal




Date: 21.SEP.2018 7:56:10




FCC Part 15.247 Page 24 of 65

Vertical







FCC Part 15.247 Page 25 of 65

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Report No.: RSZ180912801-00A

Test Procedure

- Set the EUT in transmitting mode, maxhold the channel. Set the adjacent channel of the EUT and maxhold another trace.
- 3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Kiki Kong on 2018-09-20.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.


FCC Part 15.247 Page 26 of 65

Channel	Channel Separation (MHz)	20 dBc BW (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Channel Separation Limit	Result			
			BDR(GFSK)					
Low	1.005	0.918	0.612	> two-thirds of the 20 dB bandwidth	Compliance			
Middle	1.001	0.899	0.599	> two-thirds of the 20 dB bandwidth	Compliance			
High	1.008	0.891	0.594	> two-thirds of the 20 dB bandwidth	Compliance			
	EDR(π/4-DQPSK)							
Low	1.003	1.207	0.805	> two-thirds of the 20 dB bandwidth	Compliance			
Middle	1.001	1.236	0.824	> two-thirds of the 20 dB bandwidth	Compliance			
High	1.006	1.226	0.817	> two-thirds of the 20 dB bandwidth	Compliance			
			EDR(8-DPSK)					
Low	1.000	1.220	0.813	> two-thirds of the 20 dB bandwidth	Compliance			
Middle	1.010	1.221	0.814	> two-thirds of the 20 dB bandwidth	Compliance			
High	1.000	1.216	0.811	> two-thirds of the 20 dB bandwidth	Compliance			

Please refer to the following plots.


FCC Part 15.247 Page 27 of 65

BDR (GFSK): Low Channel



Date: 20.SEP.2018 20:52:01


BDR (GFSK): Middle Channel



Date: 20.SEP.2018 20:55:13


FCC Part 15.247 Page 28 of 65

BDR (GFSK): High Channel



Date: 20.SEP.2018 20:58:24


EDR ($\pi/4$ -DQPSK): Low Channel



Date: 20.SEP.2018 21:06:54


FCC Part 15.247 Page 29 of 65

EDR ($\pi/4$ -DQPSK): Middle Channel



Date: 20.SEP.2018 21:04:45


EDR ($\pi/4$ -DQPSK): High Channel



Date: 20.SEP.2018 21:01:50

FCC Part 15.247 Page 30 of 65

EDR (8-DPSK): Low Channel



Date: 20.SEP.2018 21:10:05


EDR (8-DPSK): Middle Channel



Date: 20.SEP.2018 21:12:08

FCC Part 15.247 Page 31 of 65

EDR (8-DPSK): High Channel



Date: 20.SEP.2018 21:14:20

FCC Part 15.247 Page 32 of 65

FCC $\S15.247(a)$ (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Report No.: RSZ180912801-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃	
Relative Humidity:	52 %	
ATM Pressure:	101.0 kPa	

The testing was performed by Kiki Kong on 2018-09-20.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

FCC Part 15.247 Page 33 of 65


Mode	Mode Channel		20 dB Emission Bandwidth (MHz)	
	Low	2402	0.918	
BDR (GFSK)	Middle	2441	0.899	
(01312)	High	2480	0.891	
	Low	2402	1.207	
EDR (π/4-DQPSK)	Middle	2441	1.236	
(, 1 2 (1 2 12)	High	2480	1.226	
	Low	2402	1.220	
EDR (8-DPSK)	Middle	2441	1.221	
(0- D1 5 IX)	High	2480	1.216	

BDR (GFSK): Low Channel




Date: 20.SEP.2018 20:41:05

FCC Part 15.247 Page 34 of 65



Date: 20.SEP.2018 20:42:56


BDR (GFSK): High Channel



Date: 20.SEP.2018 20:43:43


FCC Part 15.247 Page 35 of 65

EDR ($\pi/4$ -DQPSK): Low Channel



Date: 20.SEP.2018 20:39:05


EDR ($\pi/4$ -DQPSK): Middle Channel



Date: 20.SEP.2018 20:37:43


FCC Part 15.247 Page 36 of 65

EDR ($\pi/4$ -DQPSK): High Channel



Date: 20.SEP.2018 20:35:59


EDR (8-DPSK): Low Channel



Date: 20.SEP.2018 20:31:07


FCC Part 15.247 Page 37 of 65

EDR (8-DPSK): Middle Channel



Date: 20.SEP.2018 20:33:39

EDR (8-DPSK): High Channel



Date: 20.SEP.2018 20:34:35

FCC Part 15.247 Page 38 of 65

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ180912801-00A

Test Procedure

- 1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- 2. Set the EUT in hopping mode from first channel to last.
- 3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-09-20.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots.

Mode	Frequency Range (MHz) Number of Hopping Channel (CH)		Limit (CH)	
BDR (GFSK)	2400-2483.5	79	≥15	
EDR (π/4-DQPSK)	2400-2483.5	79	≥15	
EDR (8-DPSK)	2400-2483.5	79	≥15	


FCC Part 15.247 Page 39 of 65

BDR (GFSK): Number of Hopping Channels



Date: 20.SEP.2018 20:14:30


EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date: 20.SEP.2018 20:19:16

FCC Part 15.247 Page 40 of 65

EDR (8-DPSK): Number of Hopping Channels



Date: 20.SEP.2018 20:28:05

FCC Part 15.247 Page 41 of 65

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Report No.: RSZ180912801-00A

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test or each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period pecified in the requirements. The sweep time shall be equal to, or less than, the period specified in the equirements. Determine the number of hops over the sweep time and calculate the total number of hops in he period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) =

(number of hops on spectrum analyzer) \times (period specified in the requirements / analyzer sweep time) The average time of occupancy is calculated from the transmit time per hop multiplied by the number of ops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-09-20.

EUT operation mode: Transmitting

FCC Part 15.247 Page 42 of 65

Test Result: Compliance. Please refer to following table and plots

Mod	le	Pulse Time (ms)	Hopping Number	Period Time (s)	Total of Dwell (ms)	Limit (ms)	Result
BDR (GFSK)	DH 1	0.439	330	31.6	144.87	400	Pass
	DH 3	1.707	160	31.6	273.12	400	Pass
	DH 5	2.975	110	31.6	327.25	400	Pass
EDR	2DH 1	0.451	320	31.6	144.32	400	Pass
$(\pi/4-$	2DH 3	1.717	160	31.6	274.72	400	Pass
DQPSK)	2DH 5	2.975	110	31.6	327.25	400	Pass
EDR (8-DPSK)	3DH 1	0.451	320	31.6	144.32	400	Pass
	3DH 3	1.717	160	31.6	274.72	400	Pass
	3DH 5	2.975	110	31.6	327.25	400	Pass


Note 1: A period time=0.4*79=31.6(s), Total of Dwell=Pluse Time*Hopping Number

Note 2: Hopping Number= Hopping number in 3.16s *10

Note 3: Hopping number in 3.16s= Total of highest signals in 3.16s. (Second high signals were other channel)


FCC Part 15.247 Page 43 of 65

BDR (GFSK):



Date: 20.SEP.2018 21:19:51


Hopping number in 3.16S, DH1



Date: 20.SEP.2018 21:31:24


FCC Part 15.247 Page 44 of 65

Hopping number in 31.6S, DH1



Date: 20.SEP.2018 21:31:08


Pulse time, DH3



Date: 20.SEP.2018 21:21:55


FCC Part 15.247 Page 45 of 65

Hopping number in 3.16S, DH3



Date: 20.SEP.2018 21:28:36


Hopping number in 31.6S, DH3



Date: 20.SEP.2018 21:29:47


FCC Part 15.247 Page 46 of 65

Pulse time, DH5



Date: 20.SEP.2018 21:25:38


Hopping number in 3.16S, DH5



Date: 20.SEP.2018 21:27:50

FCC Part 15.247 Page 47 of 65


Hopping number in 31.6S, DH5



Date: 20.SEP.2018 21:27:22

EDR ($\pi/4$ -DQPSK):

Pulse time, 2DH1




Date: 20.SEP.2018 21:18:51

FCC Part 15.247 Page 48 of 65


Hopping number in 3.16S, 2DH1

Report No.: RSZ180912801-00A



Date: 20.SEP.2018 21:32:16


Hopping number in 31.6S, 2DH1



Date: 20.SEP.2018 21:33:20


FCC Part 15.247 Page 49 of 65

Pulse time, 2DH3



Date: 20.SEP.2018 21:22:59


Hopping number in 3.16S, 2DH3



Date: 20.SEP.2018 21:34:44


FCC Part 15.247 Page 50 of 65

Hopping number in 31.6S, 2DH3




Date: 20.SEP.2018 21:34:29

Pulse time, 2DH5




Date: 20.SEP.2018 21:25:06

FCC Part 15.247 Page 51 of 65



Date: 20.SEP.2018 21:35:19

Hopping number in 31.6S, 2DH5




Date: 20.SEP.2018 21:36:03

FCC Part 15.247 Page 52 of 65


EDR (8-DPSK):

Pulse time, 3DH1



Date: 20.SEP.2018 21:17:02


Hopping number in 3.16S, 3DH1



Date: 20.SEP.2018 21:37:40


FCC Part 15.247 Page 53 of 65

Hopping number in 31.6S, 3DH1



Date: 20.SEP.2018 21:37:23


Pulse time, 3DH3



Date: 20.SEP.2018 21:23:29


FCC Part 15.247 Page 54 of 65

Hopping number in 3.16S, 3DH3



Date: 20.SEP.2018 21:38:13


Hopping number in 31.6S, 3DH3



Date: 20.SEP.2018 21:39:01


FCC Part 15.247 Page 55 of 65

Pulse time, 3DH5



Date: 20.SEP.2018 21:24:29


Hopping number in 3.16S, 3DH5



Date: 20.SEP.2018 21:40:17

FCC Part 15.247 Page 56 of 65

Hopping number in 31.6S, 3DH5



Date: 20.SEP.2018 21:40:01

FCC Part 15.247 Page 57 of 65

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Report No.: RSZ180912801-00A

Test Procedure

- 1. Place the EUT on a bench and set in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- 3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-09-20.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	nnel Frequency (MHz)	Peak Outp	Limit	
Widae	Chamer		(dBm)	(mW)	(mW)
	Low	2402	-4.20	0.380	125
BDR (GFSK)	Middle	2441	-2.94	0.508	125
(GI SIK)	High	2480	-3.22	0.476	125
	Low	2402	-5.85	0.260	125
EDR (π/4-DQPSK)	Middle	2441	-3.95	0.403	125
(MIDQISIL)	High	2480	-4.19	0.381	125
	Low	2402	-5.52	0.281	125
EDR (8-DPSK)	Middle	2441	-3.89	0.408	125
(0 21 011)	High	2480	-4.08	0.391	125

FCC Part 15.247 Page 58 of 65

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Report No.: RSZ180912801-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Kiki Kong on 2018-09-20 and 2018-09-24.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.

FCC Part 15.247 Page 59 of 65


BDR (GFSK): Band Edge-Left Side

Hopping



Date: 20.SEP.2018 20:05:23

Single




Date: 20.SEP.2018 19:59:45

FCC Part 15.247 Page 60 of 65


BDR (GFSK): Band Edge-Right Side

Hopping



Date: 20.SEP.2018 20:09:01

Single




Date: 20.SEP.2018 19:58:12

FCC Part 15.247 Page 61 of 65


EDR (π /4-DQPSK): Band Edge-Left Side

Hopping



Date: 20.SEP.2018 19:52:44

Single




Date: 20.SEP.2018 19:54:48

FCC Part 15.247 Page 62 of 65


EDR (π/4-DQPSK): Band Edge-Right Side

Hopping



Date: 24.SEP.2018 18:59:24

Single




Date: 20.SEP.2018 19:56:35

FCC Part 15.247 Page 63 of 65


EDR (8-DPSK): Band Edge-Left Side

Hopping



Date: 20.SEP.2018 19:44:15

Single




Date: 20.SEP.2018 19:40:51

FCC Part 15.247 Page 64 of 65


EDR (8-DPSK): Band Edge-Right Side

Hopping



Date: 20.SEP.2018 19:47:16

Single



Date: 24.SEP.2018 19:02:30

***** END OF REPORT *****

FCC Part 15.247 Page 65 of 65