

FCC Test Report

FCC ID : 2AFVRCM-DONGLE01

Equipment : Bluetooth transmitter-receiver

Model No. : CM-DONGLE01

Brand Name : Cooler Master

Applicant : Cooler Master Technology Inc.

Address : 8F., No. 788-1, Zhongzheng Rd., Zhonghe

Dist., New Taipei City 23586, Taiwan (R.O.C.)

Manufacturer : Cooler Master Technology Inc.

Address : 8F., No. 788-1, Zhongzheng Rd., Zhonghe

Dist., New Taipei City 23586, Taiwan (R.O.C.)

Standard : 47 CFR FCC Part 15.247

Received Date : Sep. 17, 2015

Tested Date : Oct. 08 ~ Oct. 28, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

lac MRA



Report No.: FR591701AE Page: 1 of 32



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	
1.4	Test Equipment List and Calibration Data	
1.5	Test Standards	8
1.6	Measurement Uncertainty	8
2	TEST CONFIGURATION	9
2.1	Testing Condition	9
2.2	The Worst Test Modes and Channel Details	9
3	TRANSMITTER TEST RESULTS	10
3.1	Conducted Emissions	10
3.2	6dB and Occupied Bandwidth	13
3.3	RF Output Power	
3.4	Power Spectral Density	17
3.5	Emissions in Restricted Frequency Bands	
3.6	Emissions in non-restricted Frequency Bands	29
4	TEST LABORATORY INFORMATION	32



Release Record

Report No.	Version	Description	Issued Date
FR591701AE	Rev. 01	Initial issue	Nov. 30, 2015

Report No.: FR591701AE Page : 3 of 32



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.165MHz 48.06 (Margin -17.15dB) - QP	Pass
15.247(d)	Radiated Emissions	[dBuV/m at 3m]:4804.00MHz	Pass
15.209	Radiated Effissions	51.99 (Margin -2.01dB) - AV	F a 3 3
15.247(b)(3)	Maximum Output Power	Power [dBm]: 4.46	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR591701AE Page: 4 of 32



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz) Bluetooth Ch. Freq. (MHz) Channel Number Data Rate							
2400-2483.5 V4.0 LE 2402-2480 0-39 [40] 1 Mbps							
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.							

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remark
1	Chip	N/A	0	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from host
-------------------	----------------

1.1.4 Accessories

N/A

1.1.5 Channel List

	Frequency band (MHz)				2400~2	2483.5	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

Report No.: FR591701AE Page: 5 of 32



1.1.6 Test Tool and Duty Cycle

Test tool ISRT, Ver. 2.1.25.4149		
Duty cycle of test signal (%)	66.67%	
Duty Factor (dB)	1.76	

1.1.7 Power Setting


Modulation Mode	Test Frequency (MHz)			
Wodulation Wode	2402	2440	2480	
GFSK/1Mbps	0x4D	0x4D	0x4F	

1.2 Local Support Equipment List

	Support Equipment List							
No.	No. Equipment Brand Model FCC ID Signal cable / Length (r							
1	Notebook	DELL	Latitude E6430	DoC	USB, 0.15m shielded w/o core			
2	Fixture							

Note: No.2 and USB cable were provided by applicant.

1.3 Test Setup Chart



Note: The fixture is disconnected from EUT and removed from test table when EUT is set to transmit/receive continuously

Report No.: FR591701AE Page: 6 of 32



1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission	Conducted Emission							
Test Site	Conduction room 1 / (Conduction room 1 / (CO01-WS)							
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Until								
Receiver	R&S	ESR3	101657	Jan. 15, 2015	Jan. 14, 2016				
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 17, 2014	Nov. 16, 2015				
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Nov. 26, 2014	Nov. 25, 2015				
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 31, 2014	Dec. 30, 2015				
50 ohm terminal (Support Unit)	NA	50	04	Apr. 15, 2015	Apr. 14, 2016				
Measurement Software	AUDIX	e3	6.120210k	NA	NA				
Note: Calibration Interval of instruments listed above is one year.									

Test Item	Radiated Emission	Radiated Emission						
Test Site	966 chamber 2 / (03C	966 chamber 2 / (03CH02-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101499	Dec. 31, 2014	Dec. 30, 2015			
Receiver	R&S	ESR3	101657	Jan. 15, 2015	Jan. 14, 2016			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Oct. 05, 2015	Oct. 04, 2016			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 07, 2015	Oct. 06, 2016			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 10, 2014	Nov. 09, 2015			
Loop Antenna	R&S	HFH2-Z2	11900	Nov. 10, 2014	Nov. 09, 2015			
Preamplifier	Burgeon	BPA-530	100218	Nov. 10, 2014	Nov. 09, 2015			
Preamplifier	Agilent	83017A	MY39501309	Sep. 22, 2015	Sep. 21, 2016			
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 16, 2014	Dec. 15, 2015			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 16, 2014	Dec. 15, 2015			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 16, 2014	Dec. 15, 2015			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 16, 2014	Dec. 15, 2015			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-004	Dec. 16, 2014	Dec. 15, 2015			
Measurement Software	AUDIX	e3	6.120210g	NA	NA			
Note: Calibration Inter	rval of instruments listed	d above is one year.						

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 03, 2015	Feb. 02, 2016
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Inte	rval of instruments liste	d above is one year.			

Report No.: FR591701AE Page: 7 of 32



1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 ANSI C63.10-2013 FCC KDB 558074 D01 DTS Meas Guidance v03r03

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Power density	±0.463 dB
Conducted emission	±2.670 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.62 dB
Radiated emission > 1GHz	±5.6 dB

Report No.: FR591701AE Page: 8 of 32



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 59%	Peter Lin
Radiated Emissions	03CH02-WS	22°C / 66%	Mark Liao
RF Conducted	TH01-WS	22°C / 63%	Alex Huang

FCC site registration No.: 657002IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	BT LE	2440	1Mbps	
Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	
Maximum Output Power				
6dB bandwidth	BT LE	2402, 2440, 2480	1Mbps	
Power spectral density				

NOTE: The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.

Report No.: FR591701AE Page: 9 of 32



3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarith	m of the frequency.	

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR591701AE Page: 10 of 32




3.1.4 Test Result of Conducted Emissions



Report No.: FR591701AE Page: 11 of 32





Report No.: FR591701AE Page: 12 of 32



3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- 1. Set resolution bandwidth (RBW) = 30 kHz, Video bandwidth = 100 kHz.
- 2. Detector = Sample, Trace mode = max hold.
- 3 Sweep = auto couple, Allow the trace to stabilize.
- 4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup




Report No.: FR591701AE Page: 13 of 32



3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.704	1.06	500
BT LE	2440	0.704	1.06	500
BT LE	2480	0.709	1.05	500



Report No.: FR591701AE Page: 14 of 32



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.

Antenna gain > 6dBi

Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations, no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

Maximum Peak Conducted Output Power

- 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
- 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
- 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.


Nower meter

- A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Average Output Power (For reference only)

Nower meter

 A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



Report No.: FR591701AE Page: 15 of 32



3.3.4 Test Result of Maximum Output Power

	Mode Freq. (MHz) Power Po		Peak Power		Antenna	EIRP	EIRP
Mode	Freq. (MHz)		Power (dBm)	Limit (dBm)	gain (dBi)	(dBm)	Limit (dBm)
BT LE	, ,		4.42	30	0	4.42	36
BT LE	2440	2.793	4.46	30	0	4.46	36
BT LE	2480	2.748	4.39	30	0	4.39	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	2.48	3.95	
BT LE	2440	2.51	3.99	
BT LE	2480	2.48	3.94	

Note: Average power is for reference only

Report No.: FR591701AE Page: 16 of 32



3.4 Power Spectral Density

3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - Set the RBW = 3kHz, VBW = 10kHz.
 - 2. Detector = Peak, Sweep time = auto couple.
 - 3. Trace mode = max hold, allow trace to fully stabilize.
 - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - 1. Set the RBW = 100kHz, VBW = 300 kHz.
 - 2. Detector = RMS, Sweep time = auto couple.
 - 3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
 - 4. Perform the measurement over a single sweep.
 - 5. Use the peak marker function to determine the maximum amplitude level.\

3.4.3 Test Setup




Report No.: FR591701AE Page: 17 of 32



3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-10.07	8
BT LE	2440	-10.15	8
BT LE	2480	-11.28	8



Report No.: FR591701AE Page: 18 of 32



3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

	Restricted Band	Emissions Limit	
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR591701AE Page: 19 of 32




3.5.3 Test Setup



Report No.: FR591701AE Page: 20 of 32



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR591701AE Page: 21 of 32



Modulation			GFSK Test Freq. (MHz) 2440								
Polarization			Verti	cal		1					
	90 Le	evel (dB	uV/m)								
	80										
	70										
	60										
	00									FCC CLAS	SS-B
	50										
	40								2 3	4	
	1										ξ
	30										
	20										
	10										
	030	100.	20	0. 30	0. 40	00. 50 Freque	0. 600 ncy (MHz)	0. 700.	800.	900.	1000
		F	rea. E	mission	Limit	Margin	SA	Factor	Remark	ANT	Turn
				level			reading	3		High	Table
			MHz	dBuV/m	dBuV/r	n dB	dBuV	dB		CM	deg
	1	_	35.82	31.58	40.00	-8.42	49.12	-17.54	Peak		
	2		746.83	39.81	46.00		47.06	-7.25	Peak		
	3	7	799.21	41.61	46.00	-4.39	48.43	-6.82	QP	144	88
	4		342.86	39.12	46.00		45.36	-6.24	Peak		
	5		399.12			-10.15	41.27	-5.42	Peak		
•	6	9	998.06	33.87	54.00	-20.13	38.30	-4.43	Peak		

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR591701AE Page: 22 of 32



3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR591701AE Page: 23 of 32



Modulation			GFSK			Test	Test Freq. (MHz)				2402		
Polarization			Vertica	ıl									
	Leve	l (dBuV	//m)										
9													
•	U										E/	CLIVE	C D




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1008.00	38.02	54.00	-15.98	47.20	-9.18	Average	255	59
2	1008.00	44.73	74.00	-29.27	53.91	-9.18	Peak	255	59
3	2390.00	38.82	54.00	-15.18	41.52	-2.70	Average	255	59
4	2390.00	49.95	74.00	-24.05	52.65	-2.70	Peak	255	59
5	4804.00	48.40	54.00	-5.60	43.47	4.93	Average	285	8
6	4804.00	54.18	74.00	-19.82	49.25	4.93	Peak	285	8

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR591701AE Page: 24 of 32






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR591701AE Page: 25 of 32



Modulation	GFSK	Test Freq. (MHz)	2440		
Polarization	Vertical				
90 Level (dB	uV/m)				



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1008.00	39.29	54.00	-14.71	48.47	-9.18	Average	275	62
2	1008.00	45.06	74.00	-28.94	54.24	-9.18	Peak	275	62
3	4880.00	47.89	54.00	-6.11	42.79	5.10	Average	294	41
4	4880.00	54.00	74.00	-20.00	48.90	5.10	Peak	294	41
5	7320.00	39.61	54.00	-14.39	29.71	9.90	Average	255	342
6	7320.00	52.27	74.00	-21.73	42.37	9.90	Peak	255	342

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Page: 26 of 32 Report No.: FR591701AE



4

5

	2480						
Polarization Horizontal	Horizontal						
90 Level (dBuV/m)							
80							
FCC	CLASS-B						
70							
60 4 6	2 0 (4) (2)						
50 FCC CLASS	S-B (AVG)						
50 5							
40							
30							
20							
20							
10							
0 1000 4000. 6000. 8000. 10000. 12000. 14000. 16000. 18000. 20000. 22000). 25000						
Frequency (MHz)	J. 25000						
Freq. Emission Limit Margin SA Factor Remark A	NT Turn						
level reading H:	igh Tabl						
MHz dBuV/m dB dBuV dB cr	m deg						
1 2483.50 38.89 54.00 -15.11 41.26 -2.37 Average	305 95						
-	305 95						
3 4960.00 51.20 54.00 -2.80 45.93 5.27 Average	333 91						

51.27

5.27

10.14

10.14

Peak

Peak

Average

333

353

353

91

63

63

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

4960.00 56.54 74.00 -17.46

7440.00 44.46 54.00 -9.54 34.32 7440.00 55.31 74.00 -18.69 45.17


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR591701AE Page: 27 of 32



Modulation GI	GFSK	Test Freq. (MHz)	2480	
Polarization Ve	/ertical			



	Freq.	Emission level dBuV/m	Limit dBuV/m	Ü	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
4	2402 50	30.50	<u></u> -	14 42	44 05		A	260	
1	2483.50	39.58	54.00	-14.42	41.95	-2.37	Average	268	62
2	2483.50	52.17	74.00	-21.83	54.54	-2.37	Peak	268	62
3	4960.00	48.24	54.00	-5.76	42.97	5.27	Average	285	53
4	4960.00	54.41	74.00	-19.59	49.14	5.27	Peak	285	53
5	7440.00	39.89	54.00	-14.11	29.75	10.14	Average	312	39
6	7440.00	52.66	74.00	-21.34	42.52	10.14	Peak	312	39

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR591701AE Page: 28 of 32



3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference Level Measurement

- 1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


3.6.3 Test Setup




Report No.: FR591701AE Page: 29 of 32



3.6.4 Test Result of Emissions in non-restricted Frequency Bands



Report No.: FR591701AE Page: 30 of 32



Report No.: FR591701AE Page: 31 of 32



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan

Hsien 333, Taiwan, R.O.C.

Tel: 886-3-271-8640

Kwei Shan Site II

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR591701AE Page : 32 of 32